

# Comparisons of Several Mean Vectors

Blake Pappas

December 19, 2023

## Swiss Bank Notes Example

### Read the Data

```
dat = read.csv("swiss3.csv", header = FALSE, skip = 1)
```

### Calculate Summary Statistics

```
real <- which(dat$V1 == "real") # Creates a sample for real bank notes
fake <- which(dat$V1 == "fake") # Creates a sample for fake bank notes
(xbar1 <- colMeans(dat[real, -1])) # Computes the mean for the real bank note sample. # The minus 1 excludes V1
```

```
##      V2      V3      V4      V5      V6      V7
## 214.969 129.943 129.720   8.305  10.168 141.517
```

```
(xbar2 <- colMeans(dat[fake, -1])) # Computes the mean for the fake bank note sample
```

```
##      V2      V3      V4      V5      V6      V7
## 214.823 130.300 130.193  10.530  11.133 139.450
```

```
(Sigma1 <- cov(dat[real, -1])) # Calculates the covariance matrix for the real bank note sample
```

```
##      V2      V3      V4      V5      V6      V7
## V2 0.150241414 0.05801313 0.05729293 0.0571262626 0.01445253 0.0054818182
## V3 0.058013131 0.13257677 0.08589899 0.0566515152 0.04906667 -0.0430616162
## V4 0.057292929 0.08589899 0.12626263 0.0581818182 0.03064646 -0.0237777778
## V5 0.057126263 0.05665152 0.05818182 0.4132070707 -0.26347475 -0.0001868687
## V6 0.014452525 0.04906667 0.03064646 -0.26347475 0.42118788 -0.0753090909
## V7 0.005481818 -0.04306162 -0.02377778 -0.0001868687 -0.07530909 0.1998090909
```

```
(Sigma2 <- cov(dat[fake, -1])) # Calculates the covariance matrix for the fake bank note sample
```

```
##      V2      V3      V4      V5      V6
## V2 0.12401111 0.031515152 0.0240010101 -0.10059596 0.0194353535
## V3 0.03151515 0.065050505 0.0467676768 -0.02404040 -0.0119191919
```

```
## V4 0.02400101 0.046767677 0.088940404 -0.01857576 0.0001323232
## V5 -0.10059596 -0.024040404 -0.0185757576 1.28131313 -0.4901919192
## V6 0.01943535 -0.011919192 0.0001323232 -0.49019192 0.4044555556
## V7 0.01156566 -0.005050505 0.0341919192 0.23848485 -0.0220707071
##
## V2 0.011565657
## V3 -0.005050505
## V4 0.034191919
## V5 0.238484848
## V6 -0.022070707
## V7 0.311212121
```

```
n1 <- length(real) # Calculates the size of the real bank note sample
n2 <- length(fake) # Calculates the size for the fake bank note sample
p <- dim(dat[, -1])[2] # Calculates the number of variables
Sp <- ((n1 - 1) * Sigma1 + (n2 - 1) * Sigma2) / (n1 + n2 - 2) # Calculates the pooled version of the co
```

## Perform a Two-Sample Hotelling's T-Square Test

```
# Test Statistic
T.squared <- as.numeric(t(xbar1 - xbar2) %*% solve(Sp * (1 / n1 + 1 / n2)) %*% (xbar1 - xbar2))
Fobs <- T.squared * ((n1 + n2 - p - 1) / ((n1 + n2 - 2) * p))

# p-Value
pf(Fobs, p, n1 + n2 - p - 1, lower.tail = F)
```

```
## [1] 3.378887e-105
```

## Simultaneous Confidence Intervals

```
# Confidence Intervals
s1 <- diag(Sigma1); s2 <- diag(Sigma2)

xbar_diff <- xbar1 - xbar2
sp_diff <- ((n1 - 1) * s1 + (n2 - 1) * s2) / (n1 + n2 - 2)

multiplier <- sqrt((p * (n1 + n2 - 2) / (n1 + n2 - p - 1)) * qf(0.95, p, n1 + n2 - p - 1))

sp <- sqrt((1 / n1 + 1 / n2) * sp_diff)

CIs <- cbind(xbar_diff + -1 * multiplier * sp, xbar_diff + 1 * multiplier * sp)
CIs
```

```
##           [,1]           [,2]
## V2 -0.04432667 0.3363267
## V3 -0.51856518 -0.1954348
## V4 -0.64159649 -0.3044035
## V5 -2.69809429 -1.7519057
## V6 -1.29523310 -0.6347669
## V7 1.80719722 2.3268028
```

## MANOVA: Romano-British Pottery Example

```
dat <- read.table("pottery.txt", header = F) # Reads in the table
out <- manova(cbind(V2, V3, V4, V5, V6) ~ V1, data = dat) # Creates the MANOVA table
summary(out) # MANOVA Hypothesis Test
```

```
##              Df Pillai approx F num Df den Df      Pr(>F)
## V1              3 1.5539   4.2984      15    60 2.413e-05 ***
## Residuals 22
## ---
## Signif. codes:  0 '***' 0.001 '**' 0.01 '*' 0.05 '.' 0.1 ' ' 1
```

```
summary(out, test = "Wilks") # Wilks Lambda Hypothesis Test
```

```
##              Df      Wilks approx F num Df den Df      Pr(>F)
## V1              3 0.012301   13.088      15 50.091 1.84e-12 ***
## Residuals 22
## ---
## Signif. codes:  0 '***' 0.001 '**' 0.01 '*' 0.05 '.' 0.1 ' ' 1
```