

Scientific Python Cheatsheet

- [Scientific Python Cheatsheet](#)
 - [Pure Python](#)
 - [Types](#)
 - [Lists](#)
 - [Dictionaries](#)
 - [Sets](#)
 - [Strings](#)
 - [Operators](#)
 - [Control Flow](#)
 - [Functions, Classes, Generators, Decorators](#)
 - [IPython](#)
 - [console](#)
 - [debugger](#)
 - [command line](#)
 - [NumPy](#)
 - [array initialization](#)
 - [indexing](#)
 - [array properties and operations](#)
 - [boolean arrays](#)
 - [elementwise operations and math functions](#)
 - [inner/ outer products](#)
 - [linear algebra/ matrix math](#)
 - [reading/ writing files](#)
 - [interpolation, integration, optimization](#)
 - [fft](#)
 - [rounding](#)
 - [random variables](#)
 - [Matplotlib](#)
 - [figures and axes](#)
 - [figures and axes properties](#)
 - [plotting routines](#)
 - [Scipy](#)
 - [interpolation](#)
 - [linear algebra](#)
 - [integration](#)
 - [Pandas](#)
 - [data structures](#)
 - [DataFrame](#)

Pure Python

Types

```
a = 2          # integer
b = 5.0        # float
c = 8.3e5      # exponential
d = 1.5 + 0.5j # complex
e = 4 > 5      # boolean
f = 'word'     # string
```

Lists

```
a = ['red', 'blue', 'green'] # manually initialization
b = list(range(5))           # initialize from iterable
c = [nu**2 for nu in b]      # list comprehension
d = [nu**2 for nu in b if nu < 3] # conditioned list comprehension
e = c[0]                     # access element
f = c[1:2]                   # access a slice of the list
g = c[-1]                    # access last element
h = ['re', 'bl'] + ['gr']    # list concatenation
i = ['re'] * 5                # repeat a list
['re', 'bl'].index('re')     # returns index of 're'
a.append('yellow')            # add new element to end of list
a.extend(b)                   # add elements from list 'b' to end of list 'a'
a.insert(1, 'yellow')         # insert element in specified position
're' in ['re', 'bl']          # true if 're' in list
'fi' not in ['re', 'bl']      # true if 'fi' not in list
sorted([3, 2, 1])             # returns sorted list
a.pop(2)                       # remove and return item at index (default last)
```

Dictionaries

```
a = {'red': 'rouge', 'blue': 'bleu'} # dictionary
b = a['red']                          # translate item
'red' in a                            # true if dictionary a contains key 'red'
c = [value for key, value in a.items()] # loop through contents
d = a.get('yellow', 'no translation found') # return default
a.setdefault('extra', []).append('cyan') # init key with default
a.update({'green': 'vert', 'brown': 'brun'}) # update dictionary by data from another one
a.keys()                             # get list of keys
a.values()                           # get list of values
a.items()                             # get list of key-value pairs
del a['red']                           # delete key and associated with it value
a.pop('blue')                          # remove specified key and return the corresponding value
```

Sets

```

a = {1, 2, 3}
b = set(range(5))
a.add(13)
a.discard(13)
a.update([21, 22, 23])
a.pop()
2 in {1, 2, 3}
5 not in {1, 2, 3}
a.issubset(b)
a <= b
a.issuperset(b)
a >= b
a.intersection(b)
a.difference(b)
a - b
a.symmetric_difference(b)
a.union(b)
c = frozenset()

# initialize manually
# initialize from iterable
# add new element to set
# discard element from set
# update set with elements from iterable
# remove and return an arbitrary set element
# true if 2 in set
# true if 5 not in set
# test whether every element in a is in b
# issubset in operator form
# test whether every element in b is in a
# issuperset in operator form
# return the intersection of two sets as a new set
# return the difference of two or more sets as a new set
# difference in operator form
# return the symmetric difference of two sets as a new set
# return the union of sets as a new set
# the same as set but immutable

```

Strings

```

a = 'red'
char = a[2]
'red' + 'blue'
'1, 2, three'.split(',')
'.'.join(['1', '2', 'three'])

# assignment
# access individual characters
# string concatenation
# split string into list
# concatenate list into string

```

Operators

```

a = 2
a += 1 (*=, /=)
3 + 2
3 / 2
3 // 2
3 * 2
3 ** 2
3 % 2
abs(a)
1 == 1
2 > 1
2 < 1
1 != 2
1 != 2 and 2 < 3
1 != 2 or 2 < 3
not 1 == 2
'a' in b
a is b

# assignment
# change and assign
# addition
# integer (python2) or float (python3) division
# integer division
# multiplication
# exponent
# remainder
# absolute value
# equal
# larger
# smaller
# not equal
# logical AND
# logical OR
# logical NOT
# test if a is in b
# test if objects point to the same memory (id)

```

Control Flow

```

# if/elif/else
a, b = 1, 2
if a + b == 3:
    print('True')
elif a + b == 1:
    print('False')
else:
    print('?')

# for
a = ['red', 'blue', 'green']
for color in a:
    print(color)

# while
number = 1
while number < 10:
    print(number)
    number += 1

# break
number = 1
while True:
    print(number)
    number += 1
    if number > 10:
        break

# continue
for i in range(20):
    if i % 2 == 0:
        continue
    print(i)

```

Functions, Classes, Generators, Decorators

```

# Function groups code statements and possibly
# returns a derived value
def myfunc(a1, a2):
    return a1 + a2

x = myfunc(a1, a2)

# Class groups attributes (data)
# and associated methods (functions)
class Point(object):
    def __init__(self, x):
        self.x = x
    def __call__(self):

```

```

    print(self.x)

x = Point(3)

# Generator iterates without
# creating all values at once
def firstn(n):
    num = 0
    while num < n:
        yield num
        num += 1

x = [i for i in firstn(10)]

# Decorator can be used to modify
# the behaviour of a function
class myDecorator(object):
    def __init__(self, f):
        self.f = f
    def __call__(self):
        print("call")
        self.f()

@myDecorator
def my_func():
    print('func')

my_func()

```

IPython

console

```

<object>?          # Information about the object
<object>.<TAB>      # tab completion

# run scripts / profile / debug
%run myscript.py

%timeit range(1000) # measure runtime of statement
%run -t myscript.py # measure script execution time

%prun <statement>   # run statement with profiler
%prun -s <key> <statement> # sort by key, e.g. "cumulative" or "calls"
%run -p myfile.py   # profile script

%run -d myscript.py # run script in debug mode
%debug              # jumps to the debugger after an exception
%pdb                # run debugger automatically on exception

# examine history
%history
%history ~1/1-5 # lines 1-5 of last session

# run shell commands
!make # prefix command with "!"

# clean namespace
%reset

# run code from clipboard
%paste

```

debugger

```

n          # execute next line
b 42       # set breakpoint in the main file at line 42
b myfile.py:42 # set breakpoint in 'myfile.py' at line 42
c          # continue execution
l          # show current position in the code
p data     # print the 'data' variable
pp data    # pretty print the 'data' variable
s          # step into subroutine
a          # print arguments that a function received
pp locals() # show all variables in local scope
pp globals() # show all variables in global scope

```

command line

```

ipython --pdb -- myscript.py argument1 --option1 # debug after exception
ipython -i -- myscript.py argument1 --option1    # console after finish

```

NumPy (import numpy as np)

array initialization

```

np.array([2, 3, 4]) # direct initialization
np.empty(20, dtype=np.float32) # single precision array of size 20
np.zeros(200) # initialize 200 zeros
np.ones((3,3), dtype=np.int32) # 3 x 3 integer matrix with ones
np.eye(200) # ones on the diagonal
np.zeros_like(a) # array with zeros and the shape of a
np.linspace(0., 10., 100) # 100 points from 0 to 10
np.arange(0, 100, 2) # points from 0 to <100 with step 2
np.logspace(-5, 2, 100) # 100 log-spaced from 1e-5 -> 1e2
np.copy(a) # copy array to new memory

```

indexing

```

a = np.arange(100)          # initialization with 0 - 99
a[:3] = 0                   # set the first three indices to zero
a[2:5] = 1                   # set indices 2-4 to 1
a[:-3] = 2                   # set all but last three elements to 2
a[start:stop:step]          # general form of indexing/slicing
a[None, :]                  # transform to column vector
a[[1, 1, 3, 8]]             # return array with values of the indices
a = a.reshape(10, 10)       # transform to 10 x 10 matrix
a.T                          # return transposed view
b = np.transpose(a, (1, 0)) # transpose array to new axis order
a[a < 2]                     # values with elementwise condition

```

array properties and operations

```

a.shape                      # a tuple with the lengths of each axis
len(a)                       # length of axis 0
a.ndim                       # number of dimensions (axes)
a.sort(axis=1)               # sort array along axis
a.flatten()                  # collapse array to one dimension
a.conj()                     # return complex conjugate
a.astype(np.int16)           # cast to integer
a.tolist()                   # convert (possibly multidimensional) array to list
np.argmax(a, axis=1)         # return index of maximum along a given axis
np.cumsum(a)                 # return cumulative sum
np.any(a)                    # True if any element is True
np.all(a)                    # True if all elements are True
np.argsort(a, axis=1)        # return sorted index array along axis
np.where(cond)                # return indices where cond is True
np.where(cond, x, y)         # return elements from x or y depending on cond

```

boolean arrays

```

a < 2                        # returns array with boolean values
(a < 2) & (b > 10)           # elementwise logical and
(a < 2) | (b > 10)           # elementwise logical or
~a                           # invert boolean array

```

elementwise operations and math functions

```

a * 5                        # multiplication with scalar
a + 5                        # addition with scalar
a + b                        # addition with array b
a / b                        # division with b (np.NaN for division by zero)
np.exp(a)                    # exponential (complex and real)
np.power(a, b)               # a to the power b
np.sin(a)                    # sine
np.cos(a)                    # cosine
np.arctan2(a, b)             # arctan(a/b)
np.arcsin(a)                 # arcsin
np.radians(a)                # degrees to radians
np.degrees(a)                # radians to degrees
np.var(a)                    # variance of array
np.std(a, axis=1)            # standard deviation

```

inner/ outer products

```

np.dot(a, b)                 # inner product: a_mi b_in
np.einsum('ij,kj->ik', a, b) # einstein summation convention
np.sum(a, axis=1)            # sum over axis 1
np.abs(a)                    # return absolute values
a[None, :] + b[:, None]      # outer sum
a[None, :] * b[:, None]      # outer product
np.outer(a, b)               # outer product
np.sum(a * a.T)              # matrix norm

```

linear algebra/ matrix math

```

evals, evecs = np.linalg.eig(a) # Find eigenvalues and eigenvectors
evals, evecs = np.linalg.eigh(a) # np.linalg.eig for hermitian matrix

```

reading/ writing files

```

np.loadtxt(fname/fobject, skiprows=2, delimiter=',') # ascii data from file
np.savetxt(fname/fobject, array, fmt='%.5f')         # write ascii data
np.fromfile(fname/fobject, dtype=np.float32, count=5) # binary data from file
np.tofile(fname/fobject)                             # write (C) binary data
np.save(fname/fobject, array)                         # save as numpy binary (.npy)
np.load(fname/fobject, mmap_mode='c')                 # load .npy file (memory mapped)

```

interpolation, integration, optimization

```

np.trapz(a, x=x, axis=1)    # integrate along axis 1
np.interp(x, xp, yp)        # interpolate function xp, yp at points x
np.linalg.lstsq(a, b)       # solve a x = b in least square sense

```

fft

```

np.fft.fft(a)                # complex fourier transform of a
f = np.fft.fftfreq(len(a))   # fft frequencies
np.fft.fftshift(f)           # shifts zero frequency to the middle
np.fft.rfft(a)               # real fourier transform of a
np.fft.rfftfreq(len(a))      # real fft frequencies

```

rounding

```
np.ceil(a)    # rounds to nearest upper int
np.floor(a)   # rounds to nearest lower int
np.round(a)   # rounds to nearest int
```

random variables

```
from np.random import normal, seed, rand, uniform, randint
normal(loc=0, scale=2, size=100) # 100 normal distributed
seed(23032)                      # resets the seed value
rand(200)                       # 200 random numbers in [0, 1)
uniform(1, 30, 200)             # 200 random numbers in [1, 30)
randint(1, 16, 300)             # 300 random integers in [1, 16)
```

Matplotlib (import matplotlib.pyplot as plt)**figures and axes**

```
fig = plt.figure(figsize=(5, 2)) # initialize figure
fig.savefig('out.png')           # save png image
fig, axes = plt.subplots(5, 2, figsize=(5, 5)) # fig and 5 x 2 ndarray of axes
ax = fig.add_subplot(3, 2, 2)     # add second subplot in a 3 x 2 grid
ax = plt.subplot2grid((2, 2), (0, 0), colspan=2) # multi column/row axis
ax = fig.add_axes([left, bottom, width, height]) # add custom axis
```

figures and axes properties

```
fig.suptitle('title')           # big figure title
fig.subplots_adjust(bottom=0.1, right=0.8, top=0.9, wspace=0.2,
                    hspace=0.5) # adjust subplot positions
fig.tight_layout(pad=0.1, h_pad=0.5, w_pad=0.5,
                rect=None)      # adjust subplots to fit into fig
ax.set_xlabel('xbla')          # set xlabel
ax.set_ylabel('ybla')          # set ylabel
ax.set_xlim(1, 2)              # sets x limits
ax.set_ylim(3, 4)              # sets y limits
ax.set_title('blabla')         # sets the axis title
ax.set(xlabel='bla')           # set multiple parameters at once
ax.legend(loc='upper center')  # activate legend
ax.grid(True, which='both')    # activate grid
bbox = ax.get_position()       # returns the axes bounding box
bbox.x0 + bbox.width           # bounding box parameters
```

plotting routines

```
ax.plot(x,y, '-o', c='red', lw=2, label='bla') # plots a line
ax.scatter(x,y, s=20, c=color)                 # scatter plot
ax.pcolormesh(xx, yy, zz, shading='gouraud')    # fast colormesh
ax.colormesh(xx, yy, zz, norm=norm)            # slower colormesh
ax.contour(xx, yy, zz, cmap='jet')             # contour lines
ax.contourf(xx, yy, zz, vmin=2, vmax=4)        # filled contours
n, bins, patch = ax.hist(x, 50)               # histogram
ax.imshow(matrix, origin='lower',
           extent=(x1, x2, y1, y2))           # show image
ax.specgram(y, FS=0.1, noverlap=128,
            scale='linear')                   # plot a spectrogram
ax.text(x, y, string, fontsize=12, color='m') # write text
```

Scipy (import scipy as sci)**interpolation**

```
# interpolate data at index positions:
from scipy.ndimage import map_coordinates
pts_new = map_coordinates(data, float_indices, order=3)

# simple 1d interpolator with axis argument:
from scipy.interpolate import interp1d
interpolator = interp1d(x, y, axis=2, fill_value=0., bounds_error=False)
y_new = interpolator(x_new)
```

Integration

```
from scipy.integrate import quad # definite integral of python
value = quad(func, low_lim, up_lim) # function/method
```

linear algebra

```
from scipy import linalg
evals, evecs = linalg.eig(a) # Find eigenvalues and eigenvectors
evals, evecs = linalg.eigh(a) # linalg.eig for hermitian matrix
b = linalg.expm(a)           # Matrix exponential
c = linalg.logm(a)           # Matrix logarithm
```

Pandas (import pandas as pd)**Data structures**

```
s = pd.Series(np.random.rand(1000), index=range(1000)) # series
index = pd.date_range("13/06/2016", periods=1000)    # time index
```

```
df = pd.DataFrame(np.zeros((1000, 3)), index=index,
                  columns=["A", "B", "C"]) # DataFrame
```

DataFrame

```
df = pd.read_csv("filename.csv") # read and load CSV file in a DataFrame
raw = df.values                  # get raw data out of DataFrame object
cols = df.columns                # get list of columns headers
df.dtypes                       # get data types of all columns
df.head(5)                      # get first 5 rows
df.describe()                   # get basic statistics for all columns
df.index                        # get index column range

#column slicin
# (.loc[] and .ix[] are inclusive of the range of values selected)
df.col_name                     # select column values as a series by column name (not optimized)
df[['col_name']]                # select column values as a dataframe by column name (not optimized)
df.loc[:, 'col_name']           # select column values as a series by column name
df.loc[:, ['col_name']]         # select column values as a dataframe by column name
df.iloc[:, 0]                   # select by column index
df.iloc[:, [0]]                 # select by column index, but as a dataframe
df.ix[:, 'col_name']            # hybrid approach with column name
df.ix[:, 0]                     # hybrid approach with column index

# row slicin
print(df[:2])                  # print first 2 rows of the dataframe
df.iloc[0:2, :]                # select first 2 rows of the dataframe
df.loc[0:2, 'col_name']         # select first 3 rows of the dataframe
df.loc[0:2, ['col_name1', 'col_name3', 'col_name6']] # select first 3 rows of the 3 different columns
df.iloc[0:2, 0:2]              # select first 3 rows and first 3 columns
# Again, .loc[] and .ix[] are inclusive

# Dicin
df[ df.col_name < 7 ]           # select all rows where col_name < 7
df[ (df.col_name1 < 7) & (df.col_name2 == 0) ] # combine multiple boolean indexing conditionals using bit-wise logical operators.
                                           # Regular Python boolean operators (and, or) cannot be used here.
                                           # Be sure to encapsulate each conditional in parenthesis to make this work.

df[df.reccency < 7] = -100      # writing to slice
```

[Scientific python cheat sheet](#) is maintained by [IPGP](#). This page was generated by [GitHub Pages](#) using the [Cayman theme](#) by [Jason Long](#).