

SAG11200 Gateway

HIGHT LIGHT

- ◆ *112 FXS*
- ◆ *Open Architecture*
- ◆ *WAN failover routing*
- ◆ *Voice/FAX support*
- ◆ *SIP Standard*
- ◆ *Flexible Routing plan*



SAG11200 is a perfect product for the telecom carriers to provide the residential telephony, radio over IP and fax services through the IP networks such as MPLS, HFC, and ADSL. It can be connected to the traditional Radio system, PBXs to provide the voice solutions for Large enterprises, Government, and SME. It can also serve as a hotline service for remote terminal (peer-peer).

Main Feature

Easy to operate and maintain

SAG11200 supports both web-based and text-based configuration set up. Users can remotely upgrade the software, Capture Voice streaming/SIP message, change the configuration parameters, download log files.

High Interoperability

SAG11200 has passed the interoperability tests with many softswitch and gateway suppliers worldwide, such as Huawei, ZTE, Cisco, Alcatel, Lucent, Panasonic, NEC, Harris, Nortel, and open source hosted IPPBX asterisk.

FAX over IP (T.38/Pass-through)

SAG11200 support FAX T.38 as default. FAX T.38 is the preferred method for FAX over TCP/IP because it is more reliable and works well in most network conditions. Anyway, If the service provider does not support T.38, FAX pass-through mode may be applied.

Investment Protection

One main challenge of purchasing new IP-based voice equipment's is how to protect your investment. SAG11200 not only offers the best cost effectiveness but also supports the latest VoIP technologies and of the standards. Users can take advantage newest VoIP technologies by upgrading SAG11200 software.

SAG11200 Gateway

Specification

TECHNICAL SPECIFICATIONS	
Physical Interfaces • 112 FXS • 1 x port Ethernet TCP/IP 10/100 Base-T with RJ45	Network • Static IP, PPPoE,DHCP • DHCP Client • Ping, Tracert • Data and Voice VLAN • NAT traversal: STUN, Static, Dynamic • IPV4,IPV6,SIP-TCP, SIP-UDP,TFTP, FTP, TCP,ARP,RARP, Ping, NTP, SNTP, Http, DNS, Tran cert,IPV4,IMS/NGN network • Static/dynamic ARP
VoIP Specifications • G.711A/U law, G.723.1, G.729A/B • Comfort Noise Generation (CNG) • Voice Activity Detection (VAD) • Echo Cancellation(G.168) • Adaptive (Dynamic) Jitter Buffer • Hook flash test • Programmable Gain Control (TX/RX gain adjust) • T.38/Pass-through/Modem FAX mode,Up to 14.4kbps • Long line mode (max 4.5 km with 0.64 mm twisted pair cable – 22AWG) • DTMF mode: Signal/RFC2833/INBAND • DTMF Interval and Cadence adjustment • Polarity reversal mode	Call Features • Call waiting • Call transfer (Blind transfer, Attend Transfer ,Half blind transfer) • Quick pick • Call forwarding • Hotline • Call hold • DND • 3-way conference • Voice mail • Direct IP address call
SIP Protocol • SIP V2.0 RFC(3261,3262,3264) ,SIP REFER (RFC 3515) • RTP/RTCP (RFC 1889,1890) • STUN (RFC 3489) • ARP/RARP (RFC 826/903) • SNTP (RFC 2030) • DHCP/PPPoE • TFTP/HTTP/HTTPS • DNS/DNS SRV (RFC 1706/RFC 2782) • VLAN 802.1P/802.1Q	

SAG11200 Gateway

Specification

TECHNICAL SPECIFICATIONS	
Call Routing • Port group • IP trunk • Primary and secondary SIP account • 112inbound/outbound routing • Number manipulation • Dial plan set • Failover to local routing when WAN link down	Compatibility • Fully compatible with mainstream vendors, such as HUAWEI softX3000, elastix, trixbox, voipswitch, asterisk etc. • Compatible with other standard Soft Switch and SIP server
Management • Web based configuration, Port monitor (GUI) • Telnet configuration • Data backup/restore • Support English and Chinese language • Firmware upgrade by TFTP • Sys log and CDR • Web & telnet login password modify • Factory reset • Automatic time synchronization • QoS • SNMP/TR069 • Support NMS software for monitoring devices • LED Indicator status display • IVR local maintenance management (Restart/ Port/ IP address)	Environment • Power: input:100-240V,50-60Hz : • Power consumption (w): 124W • Temperature(operator): 0 °C~ 45 °C(storage): -20 °C ~80 °C • Humidity: 10%-90% no condensation
	Dimension • 440(L)*320(W)*135(H)mm 7.0kg

For more information

Please visit: www.suncti.co.th or call 66-2-9610991-94 or email : kit@suncti.co.th

Distributor : Thailand – 66 :

SunCTI Technology Innovation Co.,Ltd.

218/63 Geneva Bldg, room 4/16 Floor 4th,Bangpood, Pakkred Nonthabur 11120 ,Thailand