

Assignment 6

Computational Intelligence SEW, SS2017

Team Members		
Last name	First name	Matriculation Number
Papst	Stefan	1430868
Guggi	Simon	1430534
Perkonigg	Michelle	1430153

Hidden Markov Models

Viterbi Algorithm and optimal State Sequence

Table 1: Optimal State Sequence

	X1	X2
HMM1	['r', 'r', 's', 's', 's', 's']	['r', 'r', 'f', 'f', 'f', 'r', 'r']
HMM2	['r', 'r', 'f', 'f', 'f', 'r']	['r', 'r', 'f', 'f', 'f', 'r', 'r']

When working with probabilities, for example in the iteration phase of the Viterbi algorithm, a lot of multiplication of probabilities is involved. The problem is that these probabilities sometimes are very close to zero. Computers only have a finite amount of storage to store numbers and therefore cannot distinguish very small numbers from zero. This problem can be bypassed by using the log function and the rule that:

$$\log(a) + \log(b) = \log(ab)$$

Sequence Classification

The formula for $P(X|\Theta_i)$ is:

$$P(X|\Theta) = \sum_{Q \in \mathcal{Q}^N} P(X, Q|\Theta) = \sum_{Q \in \mathcal{Q}^N} \left(\pi_{q_1} \cdot b_{q_1}(x_1) \cdot \prod_{n=2}^N a_{q_{n-1}, q_n} \cdot b_{q_n, x_n} \right)$$

The reason why this formula is so computationally expensive to solve is because there are a lot of multiplications which aren't necessary. With recursion and the product rule it is possible to reuse calculations and reduce the computation time.

Markov Model

Graphical representation

