

an ISO 9001-2008 certified company Regd. Off.: Unit No. 1, Riddhi Siddhi, Corporate Park, V. N. Purav Marg, (SionTrombay Road), Chembur, Mumbai - 400 071. MH, India.

Tel.: +91 - 22 - 4232 4121, 2529 9990,

Email: office@easternpetroleum.in, Web:www.easternpetroleum.in CIN NO: U24100MH1964PTC012931

MATERIAL SAFETY DATA SHEET

1. **Product name and Company identification**

> **Product Name EASTTO APPLE SPRAY OIL**

Product Use Apple spray oil

Eastern Petroleum Pvt. Ltd Supplier

235-239, Jawahar industrial Estate, Kamothe, Panvel,

Dist-Raigad, Maharashtra: 410209

Telephone No. 91-22-2743 1694, 91-22-2743 3819.

Email sales@easternpetroleum.in

2. **Composition / Information of Ingredients**

> Ingredient name **CAS Number** % by wt

85 - 90Mineral base oil 64742-65-0 Proprietary additives 10 - 15

3. **Hazards identification** Non dangerous substance

> Physical state Liquid

Human Health Effects

Eyes Not expected to cause irritation

Skin May cause mild skin irritation if prolonged used.

Inhalation Not expected to cause any side effect while inhalation

4. **First Aid Measures**

> Inhalation If inhaled, remove to fresh air. Get medical attention if symptoms occur.

Skin contact Immediately wash affected area with soap and water. Remove contaminated

clothing and shoes. Get medical attentions if a symptom occurs.

Eye contacts In case of contact immediately wash eyes with plenty of water.

Ingestion Do not induce vomiting unless directed to do so by medical personnel. Never

give anything by mouth to an unconscious person. If potentially dangerous quantities of this material have been swallowed, call a physician immediately.

Get medical attention if symptoms occur.

5. **Fire-fighting Measures**

> Flammability of product Not combustible liquid

Extinguishing Media

Suitable Use dry chemical, carbon dioxide (CO₂), or foam

Not suitable Do not use water.

6. **Accidental Release Measures**

> Wear suitable protection clothing and equipment. Remove contaminated clothes Personal precautions

as soon as possible.

Environmental precautions Prevent from spreading or entering into drains, ditches or rivers by using sand, earth or other appropriate barriers. Inform local authorities if this cannot be

prevented. Pick up free liquid for recycling or disposal. The residual oil can be

transferred to another container.

EASTTO APPLE SPRAY OIL

Revision No. 3

Date of issue: 10.11.2014 Date of revision: 22.08.2016



an ISO 9001-2008 certified company

Regd. Off.: Unit No. 1, Riddhi Siddhi, Corporate Park, V. N. Purav Marg, (SionTrombay Road), Chembur, Mumbai - 400 071. MH, India.

Tel.: +91 - 22 - 4232 4121, 2529 9990,

Email: office@easternpetroleum.in, Web:www.easternpetroleum.in CIN NO:U24100MH1964PTC012931

Clean up method- small spillage

Clean up methods - large spillage

Absorb liquid with sand or earth, sweep up and remove to a suitable, clearly

marked container for disposal in accordance with local regulation.

Prevent from spreading by making a barrier with sand, earth or other containment material. Reclaim liquid directly or in an absorbent. Dispose of as for

small spills.

7. Handling and Storage

Storage

Handling Handle in accordance with good industrial hygiene and safety practices. If

handled at elevated temperatures or with high speed mechanical equipment, vapors or mists might be released and require a well ventilated workplace. Store at ambient temperature or with lowest necessary heating as required for

ease of handling.

8. Exposure Controls / Personal Protection

Control parameters Use under well ventilated areas

Personal protection equipment

Respiratory protection Avoid inhalation use suitable mask with filter if necessary.

Hand protection Wear oil-resistant protective gloves if there is a risk of skin contact.

Eye protection For eyes protection wear safety goggles.

Skin and body protectionUse protective cloths and gloves.

Hygienic measures Act in accordance with good industrial Hygiene and safetypractice.

9. Physical and Chemical Properties

CHARCTERISTICS	EASTTO APPLE SPRAY OIL
Physical state	Liquid
Odour	Mild
Kinematic viscosity @ 40°C, cst	15
Solubility in water	soluble
pH(5% Emulsion in DM water)	8

10. Stability and Reactivity

Reactivity and stability Stable at normal conditions and decomposes at higher temperature.

Conditions to avoid Excessive heating and highly oxidizing agents

Hazardous decomposition products Hazardous decomposition products are not expected to form during normal

storage.

Hazardous polymerization Under normal conditions of storage and use, polymerization will not occur.

11. Toxicological Information

Potential chronic health effects

Carcinogenicity No known significant effects or critical hazards.

12. Ecological Information

Environment effect:

Will not have chronic effect on aquatic environment

13. Disposal considerations

Waste disposal procedure:

Place contaminated materials in a disposable container and dispose of in accordance with Local, State environmental regulations and contact local environment and health authorities to get the permission for waste disposal.

Transport Information Not classified as hazardous for transport (DOT, TDG, IMO/IMDG, IATA/ICAO)

EASTTO APPLE SPRAY OIL

Revision No. 3

Date of issue: 10.11.2014

Date of revision: 22.08.2016



an ISO 9001-2008 certified company Regd. Off.: Unit No. 1, Riddhi Siddhi, Corporate Park, V. N. Purav Marg, (SionTrombay Road), Chembur, Mumbai - 400 071. MH, India.

Date of issue: 10.11.2014

Date of revision: 22.08.2016

Tel.: +91 - 22 - 4232 4121, 2529 9990,

Email: office@easternpetroleum.in, Web:www.easternpetroleum.in CIN NO:U24100MH1964PTC012931

15. Regulatory Information Not classified as hazardous.

16. Other Information

The information provided in this Safety Data Sheet is correct to the best of our knowledge, information, and belief at the date of its publication. The information given is designed as a guide for safe handling, use, processing, storage, transportation, disposal and release and is not to be considered as a warranty or quality specification. The information relates only to the specific material designated and may not be valid for such material in combination with any other materials or in any process, unless specified in the text.