



MySQL BIT Data Type

백엔드 개발자 이력서 만들기

0원으로 대기업 백엔드 취업하기

선착순 모집 중. Spring 백엔드 확실하게 배우고 취업하고 싶다면, 지금 소수 정예로 합류해요.

코드잇 스프린트

열기 >

Summary: in this tutorial, you will learn about MySQL `BIT` data type and how to store `BIT` data in a column of a table.

Introduction to MySQL BIT data type

The `BIT` data type that allows you to store bit values, which are 0 and 1.

Here's the syntax for defining `BIT` type of a column:

```
column_name BIT(n)
```

The `BIT(n)` can store up to n-bit values. The `n` can range from 1 to 64. The default value of `n` is 1 if you skip it.

So the following syntaxes are equivalent:

```
column_name BIT(1);
```

and

```
column_name BIT;
```

BIT literals

To specify a bit value literal, you use `b'val'` or `0bval` notation, which `val` is a binary value that contains only 0 and 1.

The leading `b` can be written as `B`, for example, the following are valid bit literals:

```
b01
B11
```

However, the leading `0b` is case-sensitive. Therefore, you cannot use `0B`. For example, the following is an invalid bit literal value:

```
0B'1000'
```

By default the [character set](#) of a bit-value literal is the binary string as follows:

```
SELECT CHARSET(B'); -- binary
```

MySQL BIT data type examples

The following statement [creates a new table](#) named `working_calendars` that has the days column is `BIT(7)` :

```
CREATE TABLE working_calendars(
  year INT,
  week INT,
  days BIT(7),
  PRIMARY KEY(year,week)
);
```

The values in the column `days` indicate whether the day is a working day or day off i.e., 1: working day and 0: day off.

Suppose that Saturday and Friday of the first week of 2017 are not working days, you can [insert a](#)

[row](#) into the `working_calendars` table:

```
INSERT INTO working_calendars(year,week,days)
VALUES(2017,1,B'1111100');
```

The following query retrieves data from the `working_calendar` table:

```
SELECT
    year, week, days
FROM
    working_calendars;
```

Output:

```
+-----+-----+-----+
| year | week | days      |
+-----+-----+-----+
| 2017 |    1 | 0x7C      |
+-----+-----+-----+
1 row in set (0.00 sec)
```

The output indicates that the bit value in the `days` column is converted into an integer. To represent it as bit values, you use the [BIN](#) function:

```
SELECT
    year, week, bin(days)
FROM
    working_calendars;
```

Output:

```
+-----+-----+-----+
| year | week | bin(days) |
+-----+-----+-----+
| 2017 |    1 | 1111100   |
+-----+-----+-----+
1 row in set (0.00 sec)
```

If you insert a value into a `BIT(n)` column that is less than `n` bits long, MySQL will pad zeros on the left of the bit value.

Suppose the first day of the second week is off, you can insert `01111100` into the `days` column. However, the `111100` value will also work because MySQL will pad one zero to the left.

```
INSERT INTO working_calendars(year,week,days)
VALUES(2017,2,B'111100');
```

To view the data you use the same query as above:

```
SELECT
    year, week , bin(days)
FROM
    working_calendars;
```

Output:

```
+-----+-----+-----+
| year | week | bin(days) |
+-----+-----+-----+
| 2017 |    1 | 1111100   |
| 2017 |    2 | 111100    |
+-----+-----+-----+
2 rows in set (0.00 sec)
```

The output shows that MySQL removed the leading zeros before returning the result. To display it correctly, you can use the `LPAD()` function:

```
SELECT
    year, week, lpad(bin(days),7,'0')
FROM
    working_calendars;
```

Output:

```

+-----+-----+-----+
| year | week | lpad(bin(days),7,'0') |
+-----+-----+-----+
| 2017 | 1 | 1111100 |
| 2017 | 2 | 0111100 |
+-----+-----+-----+
2 rows in set (0.00 sec)

```

The output shows the expected format.

Summary

- Use MySQL `BIT` data type to store `BIT` data in a table.

Was this tutorial helpful?



ADVERTISEMENTS

PREVIOUSLY

[MySQL Table Locking](#)

UP NEXT

[MySQL INT Data Type](#)

ADVERTISEMENTS

Search ...

GETTING STARTED

[What Is MySQL?](#)

[Install MySQL Database Server](#)

[Connect to MySQL Server](#)

[Download MySQL Sample Database](#)

[Load Sample Database](#)

QUERYING DATA

[SELECT FROM](#)

[SELECT](#)

[ORDER BY](#)

[WHERE](#)

[SELECT DISTINCT](#)

[AND](#)

[OR](#)

[IN](#)

[NOT IN](#)

[BETWEEN](#)

[LIKE](#)

[LIMIT](#)

[IS NULL](#)

[Table & Column Aliases](#)

[Joins](#)

[INNER JOIN](#)

[LEFT JOIN](#)

[RIGHT JOIN](#)

[Self Join](#)

[CROSS JOIN](#)

[GROUP BY](#)

[HAVING](#)

[HAVING COUNT](#)

[ROLLUP](#)

[Subquery](#)

[Derived Tables](#)

[EXISTS](#)

[EXCEPT](#)

[INTERSECT](#)

ADVERTISEMENT

MANAGING DATABASES

[Select a Database](#)

[Create Databases](#)

[Drop Databases](#)

MANAGING TABLES

[Create Tables](#)

[AUTO_INCREMENT](#)

[Rename Tables](#)

[Add Columns](#)

[Drop Columns](#)

[Drop Tables](#)

[Temporary Tables](#)

[Generated Columns](#)

MYSQL CONSTRAINTS

[Primary Key](#)

[Foreign Key](#)

[Disable Foreign Key Checks](#)

[UNIQUE Constraint](#)

[NOT NULL Constraint](#)

[DEFAULT Constraint](#)

[CHECK Constraint](#)

ADVERTISEMENTS

INSERT DATA

[Insert Into](#)

[Insert Multiple Rows](#)

[INSERT INTO SELECT](#)

[Insert On Duplicate Key Update](#)

[INSERT IGNORE](#)

[Insert DateTimes](#)

[Insert Dates](#)

UPDATE DATA

[UPDATE](#)

[UPDATE JOIN](#)

DELETE DATA

[DELETE JOIN](#)

ON DELETE CASCADE

TRUNCATE TABLE

MYSQL TRANSACTIONS

Table Locking

MYSQL DATA TYPES

BIT

INT

BOOLEAN

DECIMAL

DATETIME

TIMESTAMP

DATE

TIME

CHAR

VARCHAR

TEXT

BINARY

VARBINARY

ENUM

BLOB

MYSQL GLOBALIZATION

MySQL Character Sets

MySQL Collation

MYSQL IMPORT & EXPORT

[Import a CSV File Into a Table](#)

[Export a Table to a CSV File](#)

ADVERTISEMENTS

ABOUT MYSQL TUTORIAL WEBSITE

MySQLTutorial.org helps you master MySQL quickly, easily, and with enjoyment. Our tutorials make learning MySQL a breeze.

All MySQL tutorials are clear, practical and easy-to-follow.
[More About Us](#)

LATEST TUTORIALS

[MySQL Port](#)

[MySQL Commands](#)

[innodb_dedicated_server:
Configure InnoDB Dedicated
Server](#)

[innodb_flush_method:
Configure InnoDB Flush
Method](#)

[innodb_log_buffer_size:
Configure InnoDB Log Buffer
Size](#)

[innodb_buffer_pool_chunk_size:
Configure Buffer Pool Chunk
Size](#)

[innodb_buffer_pool_instances:
Configuring Multiple Buffer
Pool Instances for Improved
Concurrency in MySQL](#)

[innodb_buffer_pool_size:
Configure InnoDB Buffer Pool
Size](#)

[MySQL InnoDB Architecture](#)

SITE LINKS

[Donation](#) 

[Contact Us](#)

[About](#)

[Privacy Policy](#)

OTHERS

[MySQL Cheat Sheet](#)

[MySQL Resources](#)

[MySQL Books](#)

How to Kill a Process in MySQL

Copyright © 2008 - Present by www.mysqltutorial.org. All Rights Reserved.