

MySQL CHECK Constraint



Summary: in this tutorial, you will learn how to use MySQL `CHECK` constraint to ensure that values stored in a column or group of columns satisfy a Boolean expression.

MySQL 8.0.16 implemented the SQL check constraint. If you use MySQL with the earlier versions, you can [emulate a `CHECK` constraint](#) using a [view](#) `WITH CHECK OPTION` or a [trigger](#).

Introduction to the MySQL CHECK constraint

Before MySQL 8.0.16, the `CREATE TABLE` allows you to include a table `CHECK` constraint. However, MySQL ignores all the `CHECK` constraints:

```
CHECK(expression)
```

As of MySQL 8.0.16, the `CREATE TABLE` supported essential features of table and column `CHECK` constraints for all [storage engines](#).

Here is the basic syntax:

```
CONSTRAINT constraint_name  
CHECK (expression)  
[ENFORCED | NOT ENFORCED]
```

In this syntax:

First, specify the name for the check constraint that you want to create after the `CONSTRAINT` keyword. If you omit the constraint name, MySQL automatically generates a name with the following convention:

```
table_name_chk_n
```

In this convention, `n` is an ordinal number such as 1,2, and 3. For example, the automatically generated names of `CHECK` constraints of the `parts` table will be `parts_chk_1` , `parts_chk_2` , and so on.

Second, specify a Boolean `expression` which must be evaluated to `TRUE` or `UNKNOWN` for each row of the table inside the parentheses after the `CHECK` keyword.

If the expression evaluates to `FALSE` , the values violate the constraint or a constraint violation occurs.

Note that MySQL treats 1 as true and 0 as false.

Third, optionally specify the enforcement clause to indicate whether the check constraint is enforced:

- Use `ENFORCED` or omit the `ENFORCED` clause to create and enforce the constraint.
- Use `NOT ENFORCED` to create the constraint but not enforce it.

As mentioned earlier, you can define a `CHECK` constraint as a table constraint or column constraint.

A table `CHECK` constraint can reference multiple columns whereas the column `CHECK` constraint can refer to the only column where it is defined.

MySQL CHECK constraint examples

Let's take some examples of using the `CHECK` constraints.

1) Creating CHECK constraints as column constraints

The following [CREATE TABLE](#) statement creates a new table called `parts` :

```
CREATE TABLE parts (  
    part_no VARCHAR(18) PRIMARY KEY,  
    description VARCHAR(40),  
    cost DECIMAL(10,2) NOT NULL CHECK (cost >= 0),  
    price DECIMAL(10,2) NOT NULL CHECK (price >= 0)  
);
```

The parts table has two column `CHECK` constraints: one for the `cost` column and the other for the `price` column.

Because we did not explicitly specify the names of the `CHECK` constraints, MySQL automatically generated names for them.

To view the table definition with the `CHECK` constraint name, you use the `SHOW CREATE TABLE` statement:

```
SHOW CREATE TABLE parts;
```

Output:

Table	Create Table
parts	<pre>CREATE TABLE `parts` (`part_no` varchar(18) NOT NULL, `description` varchar(40) DEFAULT NULL, `cost` decimal(10,2) NOT NULL, `price` decimal(10,2) NOT NULL, PRIMARY KEY (`part_no`), CONSTRAINT `parts_chk_1` CHECK ((`cost` >= 0)), CONSTRAINT `parts_chk_2` CHECK ((`price` >= 0))) ENGINE=InnoDB DEFAULT CHARSET=utf8</pre>

The output indicates that MySQL generated the names (`parts_chk_1` and `parts_chk_2`) for the check constraints.

After creating `CHECK` constraints, if you [insert](#) or [update](#) a value that causes the Boolean expression to be false, MySQL rejects the change and issues an error.

This statement inserts a new row into the `parts` table:

```
INSERT INTO parts(part_no, description,cost,price)
VALUES('A-001','Cooler',0,-100);
```

MySQL issued an error:

```
Error Code: 3819. Check constraint 'parts_chk_2' is violated.
```

Because the value of the `price` column is negative which causes the expression `price > 0` evaluates to `FALSE` that results in a constraint violation.

2) Creating CHECK constraints as a table constraints

First, drop the `parts` table:

```
DROP TABLE IF EXISTS parts;
```

Then, create a new `parts` table with one more table `CHECK` constraint:

```
CREATE TABLE parts (
  part_no VARCHAR(18) PRIMARY KEY,
  description VARCHAR(40),
  cost DECIMAL(10,2 ) NOT NULL CHECK (cost >= 0),
  price DECIMAL(10,2) NOT NULL CHECK (price >= 0),
  CONSTRAINT parts_chk_price_gt_cost
    CHECK(price >= cost)
);
```

The following new clause defines a table `CHECK` constraint that ensures the price is always greater than or equal to the cost:

```
CONSTRAINT parts_chk_price_gt_cost CHECK(price >= cost)
```

Because we explicitly specify the name of the `CHECK` constraint, MySQL creates the new constraint with the specified name.

Here is the definition of the `parts` table:

```
SHOW CREATE TABLE parts;
```

The table `CHECK` constraint appears at the end of the table definition after the column list.

This statement attempts to [insert](#) a new part whose price is less than the cost:

```
INSERT INTO parts(part_no, description,cost,price)
VALUES('A-001','Cooler',200,100);
```

Here is the error due to the constraint violation:

```
Error Code: 3819. Check constraint 'parts_chk_price_gt_cost' is violated.
```

Adding a check constraint to a table

To add a check constraint to an existing table, you use the `ALTER TABLE ... ADD CHECK` statement:

```
ALTER TABLE table_name
ADD CHECK (expression);
```

If you want to explicitly specify the name of the `CHECK` constraint, you can use the `ALTER TABLE ... ADD CONSTRAINT ... CHECK` statement:

```
ALTER TABLE table_name
ADD CONSTRAINT constraint_name
CHECK (expression);
```

For example, the following statement adds a `CHECK` constraint to the `parts` table:

```
ALTER TABLE parts
ADD CHECK (part_no <> description);
```

This `CHECK` constraint prevents you from having the `part_no` identical to the `description`.

For example, the following `INSERT` statement will be rejected:

```
INSERT INTO parts
VALUES('A', 'A', 100, 120);
```

Output:

```
ERROR 3819 (HY000): Check constraint 'parts_chk_3' is violated.
```

Removing a check constraint from a table

To remove a `CHECK` constraint from a table, you use the `ALTER TABLE ... DROP CHECK` statement:

```
ALTER TABLE table_name
DROP CHECK constraint_name;
```

For example, the following statement removes the `CHECK` constraint `parts_chk_3` from the `parts` table:

```
ALTER TABLE parts
DROP CHECK parts_chk_3;
```

Summary

- Use `CHECK` constraints to ensure values stored in a column satisfy a Boolean condition.
- Use the `CHECK(expression)` to define a `CHECK` constraint.
- Use the `ALTER TABLE ... ADD CHECK` to add a `CHECK` constraint to a table.

- Use the `ALTER TABLE ... DROP CHECK` to remove a `CHECK` constraint from a table.

Was this tutorial helpful?



ADVERTISEMENTS

PREVIOUSLY

[MySQL DEFAULT](#)

UP NEXT

[MySQL INSERT](#)

ADVERTISEMENTS

Search ...

GETTING STARTED

[What Is MySQL?](#)

[Install MySQL Database Server](#)

[Connect to MySQL Server](#)

[Download MySQL Sample Database](#)

[Load Sample Database](#)

QUERYING DATA

SELECT FROM

SELECT

ORDER BY

WHERE

SELECT DISTINCT

AND

OR

IN

NOT IN

BETWEEN

LIKE

LIMIT

IS NULL

Table & Column Aliases

Joins

INNER JOIN

LEFT JOIN

RIGHT JOIN

Self Join

CROSS JOIN

GROUP BY

HAVING

HAVING COUNT

ROLLUP

[Subquery](#)

[Derived Tables](#)

[EXISTS](#)

[EXCEPT](#)

[INTERSECT](#)

ADVERTISEMENT

MANAGING DATABASES

[Select a Database](#)

[Create Databases](#)

[Drop Databases](#)

MANAGING TABLES

[Create Tables](#)

[AUTO_INCREMENT](#)

[Rename Tables](#)

[Add Columns](#)

[Drop Columns](#)

[Drop Tables](#)

[Temporary Tables](#)

[Generated Columns](#)

MYSQL CONSTRAINTS

[Primary Key](#)

[Foreign Key](#)

[Disable Foreign Key Checks](#)

[UNIQUE Constraint](#)

[NOT NULL Constraint](#)

[DEFAULT Constraint](#)

[CHECK Constraint](#)

ADVERTISEMENTS

INSERT DATA

[Insert Into](#)

[Insert Multiple Rows](#)

[INSERT INTO SELECT](#)

[Insert On Duplicate Key Update](#)

[INSERT IGNORE](#)

[Insert DateTime](#)

[Insert Dates](#)

UPDATE DATA

[UPDATE](#)

[UPDATE JOIN](#)

DELETE DATA

[DELETE JOIN](#)

[ON DELETE CASCADE](#)

[TRUNCATE TABLE](#)

MYSQL TRANSACTIONS

[Table Locking](#)

MYSQL DATA TYPES

[BIT](#)

[INT](#)

[BOOLEAN](#)

[DECIMAL](#)

[DATETIME](#)

[TIMESTAMP](#)

[DATE](#)

[TIME](#)

[CHAR](#)

[VARCHAR](#)

[TEXT](#)

[BINARY](#)

[VARBINARY](#)

[ENUM](#)

[BLOB](#)

MYSQL GLOBALIZATION

[MySQL Character Sets](#)

[MySQL Collation](#)

MYSQL IMPORT & EXPORT

[Import a CSV File Into a Table](#)

[Export a Table to a CSV File](#)

ADVERTISEMENTS

**ABOUT MYSQL TUTORIAL
WEBSITE**

LATEST TUTORIALS

[MySQL Port](#)

SITE LINKS

[Donation](#) 

MySQLTutorial.org helps you master MySQL quickly, easily, and with enjoyment. Our tutorials make learning MySQL a breeze.

All MySQL tutorials are clear, practical and easy-to-follow.
[More About Us](#)

[MySQL Commands](#)

[innodb_dedicated_server:
Configure InnoDB Dedicated Server](#)

[innodb_flush_method:
Configure InnoDB Flush Method](#)

[innodb_log_buffer_size:
Configure InnoDB Log Buffer Size](#)

[innodb_buffer_pool_chunk_size:
Configure Buffer Pool Chunk Size](#)

[innodb_buffer_pool_instances:
Configuring Multiple Buffer Pool Instances for Improved Concurrency in MySQL](#)

[innodb_buffer_pool_size:
Configure InnoDB Buffer Pool Size](#)

[MySQL InnoDB Architecture](#)

[How to Kill a Process in MySQL](#)

[Contact Us](#)

[About](#)

[Privacy Policy](#)

OTHERS

[MySQL Cheat Sheet](#)

[MySQL Resources](#)

[MySQL Books](#)