

# MySQL DEFAULT



**Summary:** in this tutorial, you'll learn about MySQL DEFAULT constraint and how to use it effectively.

## Introduction to the MySQL DEFAULT constraint

MySQL `DEFAULT` constraint allows you to specify a default value for a column. Here's the syntax of the `DEFAULT` constraint:

```
column_name data_type DEFAULT default_value;
```

In this syntax, you specify the `DEFAULT` keyword followed by the default value for the column. The type of the default value matches the data type of the column.

The `default_value` must be a literal constant, e.g., a number or a string. It cannot be a function or an expression. However, MySQL allows you to set the current date and time (`CURRENT_TIMESTAMP`) to the `TIMESTAMP` and `DATETIME` columns.

When you define a column without the `NOT NULL` constraint, the column will implicitly take `NULL` as the default value.

If a column has a `DEFAULT` constraint and the `INSERT` or `UPDATE` statement doesn't provide

the value for that column, MySQL will use the default value specified in the `DEFAULT` constraint.

Typically, you set the `DEFAULT` constraints for columns when you [create the table](#). MySQL also allows you to add default constraints to the columns of existing tables. If you don't want to use default values for columns, you can remove the default constraints.

## MySQL DEFAULT constraint example

The following example creates a new table named `cart_items` with four columns `item_id`, `name`, `quantity`, and `sales_tax`:

```
CREATE TABLE cart_items
(
    item_id INT AUTO_INCREMENT PRIMARY KEY,
    name VARCHAR(255) NOT NULL,
    quantity INT NOT NULL,
    price DEC(5,2) NOT NULL,
    sales_tax DEC(5,2) NOT NULL DEFAULT 0.1,
    CHECK(quantity > 0),
    CHECK(sales_tax >= 0)
);
```

The `sales_tax` column has a default value 0.1 (10%). The following statement shows the `cart_items` table:

```
DESC cart_items;
```

Output:

Field	Type	Null	Key	Default	Extra
item_id	int	NO	PRI	NULL	auto_increment
name	varchar(255)	NO		NULL	
quantity	int	NO		NULL	
price	decimal(5,2)	NO		NULL	
sales_tax	decimal(5,2)	NO		0.10	

```
5 rows in set (0.01 sec)
```

The following `INSERT` statement adds a new item to the `cart_items` table:

```
INSERT INTO cart_items(name, quantity, price)
VALUES('Keyboard', 1, 50);
```

In this example, the `INSERT` statement doesn't provide a value for the `sales_tax` column. The `sales_tax` column uses the default value specified in the `DEFAULT` constraint:

```
SELECT * FROM cart_items;
```

Output:

```
+-----+-----+-----+-----+-----+
| item_id | name      | quantity | price | sales_tax |
+-----+-----+-----+-----+-----+
|         1 | Keyboard |         1 | 50.00 |         0.10 |
+-----+-----+-----+-----+-----+
1 row in set (0.00 sec)
```

Also, you can explicitly use the `DEFAULT` keyword when you insert a new row into the `cart_items` table:

```
INSERT INTO cart_items(name, quantity, price, sales_tax)
VALUES('Battery', 4, 0.25, DEFAULT);
```

In this case, the `sales_tax` column takes the default value:

```
SELECT * FROM cart_items;
```

Output:

```
+-----+-----+-----+-----+-----+
| item_id | name      | quantity | price | sales_tax |
+-----+-----+-----+-----+-----+
```

```

|      1 | Keyboard |      1 | 50.00 |      0.10 |
|      2 | Battery  |      4 |  0.25 |      0.10 |
+-----+-----+-----+-----+-----+
2 rows in set (0.01 sec)

```

## Adding a DEFAULT constraint to a column

To add a default constraint to a column of an existing table, you use the `ALTER TABLE` statement:

```

ALTER TABLE table_name
ALTER COLUMN column_name SET DEFAULT default_value;

```

The following example adds a `DEFAULT` constraint to the `quantity` column of the `cart_items` table:

```

ALTER TABLE cart_items
ALTER COLUMN quantity SET DEFAULT 1;

```

If you describe the `cart_items` table, you'll see the changes:

```
DESC cart_items;
```

Output:

```

+-----+-----+-----+-----+-----+-----+
| Field      | Type          | Null | Key | Default | Extra          |
+-----+-----+-----+-----+-----+-----+
| item_id    | int           | NO   | PRI | NULL    | auto_increment |
| name       | varchar(255) | NO   |     | NULL    |                |
| quantity   | int           | NO   |     | 1        |                |
| price      | decimal(5,2) | NO   |     | NULL    |                |
| sales_tax  | decimal(5,2) | NO   |     | 0.10     |                |
+-----+-----+-----+-----+-----+-----+
5 rows in set (0.00 sec)

```

The following statement inserts a new row into the `cart_items` table without specifying a value for the `quantity` column:

```
INSERT INTO cart_items(name, price, sales_tax)
VALUES('Maintenance services',25.99, 0)
```

The value of the `quantity` column will default to 1:

```
SELECT * FROM cart_items;
```

Output:

```
+-----+-----+-----+-----+-----+
| item_id | name                | quantity | price | sales_tax |
+-----+-----+-----+-----+-----+
|      1 | Keyboard            |      1 | 50.00 |      0.10 |
|      2 | Battery             |      4 |  0.25 |      0.10 |
|      3 | Maintenance services |      1 | 25.99 |      0.00 |
+-----+-----+-----+-----+-----+
3 rows in set (0.00 sec)
```

## Removing a DEFAULT constraint from a column

To remove a `DEFAULT` constraint from a column, you use the `ALTER TABLE` statement:

```
ALTER TABLE table_name
ALTER column_name DROP DEFAULT;
```

The following example removes the `DEFAULT` constraint from the `quantity` column of the `cart_items` table:

```
ALTER TABLE cart_items
ALTER COLUMN quantity DROP DEFAULT;
```

And here's the new `cart_items` structure:

```
DESC cart_items;
```

Output:

```
+-----+-----+-----+-----+-----+-----+
| Field      | Type           | Null | Key | Default | Extra           |
+-----+-----+-----+-----+-----+-----+
| item_id    | int            | NO   | PRI | NULL    | auto_increment |
| name       | varchar(255)   | NO   |     | NULL    |                 |
| quantity   | int            | NO   |     | NULL    |                 |
| price      | decimal(5,2)   | NO   |     | NULL    |                 |
| sales_tax  | decimal(5,2)   | NO   |     | 0.10    |                 |
+-----+-----+-----+-----+-----+-----+
5 rows in set (0.00 sec)
```

## Summary

- MySQL `DEFAULT` constraints set default values for columns.
- Use `DEFAULT default_value` to set a default constraint to a column.
- Use `ALTER TABLE ... ALTER COLUMN ... SET DEFAULT` to add a `DEFAULT` constraint to a column of an existing table.
- Use `ALTER TABLE ... ALTER COLUMN ... DROP DEFAULT` to drop a `DEFAULT` constraint from a column of an existing table.

Was this tutorial helpful?



ADVERTISEMENTS

PREVIOUSLY

[MySQL NOT NULL Constraint](#)

UP NEXT

[MySQL CHECK Constraint](#)

ADVERTISEMENTS



Search ...

## GETTING STARTED

[What Is MySQL?](#)

[Install MySQL Database Server](#)

[Connect to MySQL Server](#)

[Download MySQL Sample Database](#)

[Load Sample Database](#)

## QUERYING DATA

[SELECT FROM](#)

[SELECT](#)

[ORDER BY](#)

WHERE

SELECT DISTINCT

AND

OR

IN

NOT IN

BETWEEN

LIKE

LIMIT

IS NULL

Table & Column Aliases

Joins

INNER JOIN

LEFT JOIN

RIGHT JOIN

Self Join

CROSS JOIN

GROUP BY

HAVING

HAVING COUNT

ROLLUP

Subquery

Derived Tables

EXISTS

EXCEPT



## INTERSECT

ADVERTISEMENTS

### MANAGING DATABASES

[Select a Database](#)

[Create Databases](#)

[Drop Databases](#)

### MANAGING TABLES

[Create Tables](#)

[AUTO\\_INCREMENT](#)

[Rename Tables](#)

[Add Columns](#)

[Drop Columns](#)

[Drop Tables](#)

[Temporary Tables](#)

[Generated Columns](#)

### MYSQL CONSTRAINTS

[Primary Key](#)

[Foreign Key](#)

[Disable Foreign Key Checks](#)

[UNIQUE Constraint](#)

[NOT NULL Constraint](#)

[DEFAULT Constraint](#)

[CHECK Constraint](#)

ADVERTISEMENTS

## **INSERT DATA**

[Insert Into](#)

[Insert Multiple Rows](#)

[INSERT INTO SELECT](#)

[Insert On Duplicate Key Update](#)

[INSERT IGNORE](#)

[Insert DateTimes](#)

[Insert Dates](#)

## **UPDATE DATA**

[UPDATE](#)

[UPDATE JOIN](#)

## **DELETE DATA**

[DELETE JOIN](#)

[ON DELETE CASCADE](#)

[TRUNCATE TABLE](#)

## **MYSQL TRANSACTIONS**

[Table Locking](#)

## **MYSQL DATA TYPES**

[BIT](#)

[INT](#)

[BOOLEAN](#)

[DECIMAL](#)

[DATETIME](#)

[TIMESTAMP](#)

[DATE](#)

[TIME](#)

[CHAR](#)

[VARCHAR](#)

[TEXT](#)

[BINARY](#)

[VARBINARY](#)

[ENUM](#)

[BLOB](#)

## **MYSQL GLOBALIZATION**

[MySQL Character Sets](#)

[MySQL Collation](#)

## **MYSQL IMPORT & EXPORT**

[Import a CSV File Into a Table](#)

[Export a Table to a CSV File](#)

## ABOUT MYSQL TUTORIAL WEBSITE

MySQLTutorial.org helps you master MySQL quickly, easily, and with enjoyment. Our tutorials make learning MySQL a breeze.

All MySQL tutorials are clear, practical and easy-to-follow.  
[More About Us](#)

## LATEST TUTORIALS

[MySQL Port](#)

[MySQL Commands](#)

[innodb\\_dedicated\\_server:  
Configure InnoDB Dedicated  
Server](#)

[innodb\\_flush\\_method:  
Configure InnoDB Flush  
Method](#)

[innodb\\_log\\_buffer\\_size:  
Configure InnoDB Log Buffer  
Size](#)

[innodb\\_buffer\\_pool\\_chunk\\_size:  
Configure Buffer Pool Chunk  
Size](#)

[innodb\\_buffer\\_pool\\_instances:  
Configuring Multiple Buffer  
Pool Instances for Improved  
Concurrency in MySQL](#)

[innodb\\_buffer\\_pool\\_size:  
Configure InnoDB Buffer Pool  
Size](#)

[MySQL InnoDB Architecture](#)

[How to Kill a Process in MySQL](#)

## SITE LINKS

[Donation](#) 

[Contact Us](#)

[About](#)

[Privacy Policy](#)

## OTHERS

[MySQL Cheat Sheet](#)

[MySQL Resources](#)

[MySQL Books](#)