

Home » MySQL Basics » MySQL DATE Data Type

MySQL DATE Data Type



Summary: in this tutorial, we will introduce you to the MySQL `DATE` data type and show you some useful date functions to handle the date data effectively.

Introduction to MySQL DATE data type

MySQL `DATE` is one of the five temporal [data types](#) used for managing date values. MySQL uses `yyyy-mm-dd` format for storing a date value. This format is fixed and it is not possible to change it.

For example, you may prefer to use `mm-dd-yyyy` format but you can't. Instead, you follow the standard date format and use the [`DATE_FORMAT`](#) function to format the date the way you want.

MySQL uses three bytes to store a `DATE` value. The `DATE` values range from `1000-01-01` to `9999-12-31`.

If you want to store a date value that is out of this range, you need to use a non-temporal data type like an [`integer`](#) e.g., three columns, and each column for the year, month, and day.

Also, you need to create [`stored functions`](#) to simulate the built-in [`date functions`](#) provided by MySQL, which is not recommended.

MySQL Date values with two-digit years

MySQL stores the year of the date value using four digits. In case you use two-digit year values, MySQL still accepts them with the following rules:

- Year values in the range 00-69 are converted to 2000-2069.
- Year values in the range 70-99 are converted to 1970 – 1999.

However, a date value with two digits is ambiguous therefore you should avoid using it.

Let's take a look at the following example.

First, [create a table](#) named people with birth date column with `DATE` data type.

```
CREATE TABLE people (
    id INT AUTO_INCREMENT PRIMARY KEY,
    first_name VARCHAR(50) NOT NULL,
    last_name VARCHAR(50) NOT NULL,
    birth_date DATE NOT NULL
);
```

Next, [insert a row](#) into the `people` table.

```
INSERT INTO people(first_name,last_name,birth_date)
VALUES('John','Doe','1990-09-01');
```

Then, [query the data](#) from the `people` table.

```
SELECT
    first_name,
    last_name,
    birth_date
FROM
    people;
```

After that, use the two-digit year format to insert data into the `people` table.

```
INSERT INTO people(first_name,last_name,birth_date)
VALUES('Jack','Daniel','01-09-01'),
      ('Lily','Bush','80-09-01');
```

In the first row, we used 01 (range 00-69) as the year, so MySQL converted it to 2001. In the second row, we used 80 (range 70-99) as the year, MySQL converted it to 1980.

Finally, retrieve data from the `people` table to check whether data was converted based on the conversion rules.

```
SELECT
    first_name,
    last_name,
    birth_date
FROM
    people;
```

MySQL Date Functions

MySQL provides many useful [date functions](#) that allow you to manipulate dates effectively.

To get the current date and time, you use [`NOW\(\)`](#) function.

```
SELECT NOW();
```

```
+-----+
| NOW()           |
+-----+
| 2017-05-13 07:59:38 |
+-----+
1 row in set (0.02 sec)
```

To get only the date part of a [`DATETIME`](#) value, you use the [`DATE\(\)`](#) function.

```
SELECT DATE(NOW());
```

```
+-----+
| DATE(NOW()) |
+-----+
| 2015-07-13 |
+-----+
1 row in set (0.01 sec)
```

To get the current system date, you use [CURDATE\(\)](#) function as follows:

```
SELECT CURDATE();
```

```
+-----+
| CURDATE() |
+-----+
| 2015-07-13 |
+-----+
1 row in set (0.02 sec)
```

To format a date value, you use [DATE_FORMAT](#) function. The following statement formats the date as `mm/dd/yyyy` using the date format pattern `%m/%d/%Y` :

```
SELECT DATE_FORMAT(CURDATE(), '%m/%d/%Y') today;
```

```
+-----+
| today      |
+-----+
| 07/13/2015 |
+-----+
1 row in set (0.02 sec)
```

To calculate the number of days between two date values, you use the [DATEDIFF](#) function as follows:

```
SELECT DATEDIFF('2015-11-04','2014-11-04') days;
```

```
+-----+
| days |
+-----+
| 365 |
+-----+
1 row in set (0.02 sec)
```

To add a number of days, weeks, months, years, etc., to a date value, you use the [DATE_ADD](#) function:

```
SELECT
  '2015-01-01' start,
  DATE_ADD('2015-01-01', INTERVAL 1 DAY) 'one day later',
  DATE_ADD('2015-01-01', INTERVAL 1 WEEK) 'one week later',
  DATE_ADD('2015-01-01', INTERVAL 1 MONTH) 'one month later',
  DATE_ADD('2015-01-01', INTERVAL 1 YEAR) 'one year later';
```

Similarly, you can subtract an [interval](#) from a date using the [DATE_SUB](#) function:

```
SELECT
  '2015-01-01' start,
  DATE_SUB('2015-01-01', INTERVAL 1 DAY) 'one day before',
  DATE_SUB('2015-01-01', INTERVAL 1 WEEK) 'one week before',
  DATE_SUB('2015-01-01', INTERVAL 1 MONTH) 'one month before',
  DATE_SUB('2015-01-01', INTERVAL 1 YEAR) 'one year before';
```

If you want to get the day, month, quarter, and year of a date value, you can use the corresponding function [DAY](#), [MONTH](#), [QUARTER](#), and [YEAR](#) as follows:

```
SELECT DAY('2000-12-31') day,
       MONTH('2000-12-31') month,
      QUARTER('2000-12-31') quarter,
        YEAR('2000-12-31') year;
```

```
+-----+-----+-----+-----+
| day | month | quarter | year |
+-----+-----+-----+-----+
|    31 |     12 |        4 | 2000 |
+-----+-----+-----+-----+
1 row in set (0.00 sec)
```

To get the week's information, you use the week-related functions. For example, `WEEK` function returns the week number, `WEEKDAY` function returns the weekday index, and `WEEKOFYEAR` function returns the calendar week.

```
SELECT
  WEEKDAY('2000-12-31') weekday,
  WEEK('2000-12-31') week,
  WEEKOFYEAR('2000-12-31') weekofyear;
```

```
+-----+-----+-----+
| weekday | week | weekofyear |
+-----+-----+-----+
|      6 |   53 |      52 |
+-----+-----+-----+
1 row in set (0.04 sec)
```

The `week` function returns the week number with the zero-based index if you don't pass the second argument or if you pass 0. If you pass 1, it will return the week number with 1-indexed.

```
SELECT
  WEEKDAY('2000-12-31') weekday,
  WEEK('2000-12-31',1) week,
  WEEKOFYEAR('2000-12-31') weekofyear;
```

```
+-----+-----+-----+
| weekday | week | weekofyear |
+-----+-----+-----+
|      6 |   52 |      52 |
+-----+-----+-----+
1 row in set (0.00 sec)
```

In this tutorial, you have learned about the MySQL DATE data type and how to use some useful date functions to manipulate date values.

Was this tutorial helpful?



ADVERTISEMENTS

PREVIOUSLY

[MySQL TIMESTAMP Data Type](#)

UP NEXT

[MySQL TIME Data Type](#)

ADVERTISEMENTS



AI 개발 대회 총상금 2억원

비전공자로 시작해서
AI 서비스 개발 대회 우승까지.

빌더스 리그 총 상금
2억원 + α

DEEP DIVE | BUILDERS LEAGUE

열기 >

This advertisement promotes the Deep Dive Builders League, offering a total prize of 20 million won for AI development. It targets both beginners and professionals, promising success from the first competition to the final victory.

Search ...

GETTING STARTED

[What Is MySQL?](#)

[Install MySQL Database Server](#)

[Connect to MySQL Server](#)

[Download MySQL Sample Database](#)

[Load Sample Database](#)

QUERYING DATA

[SELECT FROM](#)

[SELECT](#)

[ORDER BY](#)

[WHERE](#)

[SELECT DISTINCT](#)

[AND](#)

[OR](#)

[IN](#)

[NOT IN](#)

[BETWEEN](#)

[LIKE](#)

[LIMIT](#)

[IS NULL](#)

[Table & Column Aliases](#)

[Joins](#)

[INNER JOIN](#)

[LEFT JOIN](#)

RIGHT JOIN

Self Join

CROSS JOIN

GROUP BY

HAVING

HAVING COUNT

ROLLUP

Subquery

Derived Tables

EXISTS

EXCEPT

INTERSECT

ADVERTISEMENTS

MANAGING DATABASES

Select a Database

Create Databases

Drop Databases

MANAGING TABLES

Create Tables

AUTO_INCREMENT

Rename Tables

Add Columns

Drop Columns

Drop Tables

[Temporary Tables](#)

[Generated Columns](#)

MYSQL CONSTRAINTS

[Primary Key](#)

[Foreign Key](#)

[Disable Foreign Key Checks](#)

[UNIQUE Constraint](#)

[NOT NULL Constraint](#)

[DEFAULT Constraint](#)

[CHECK Constraint](#)

ADVERTISEMENTS

INSERT DATA

[Insert Into](#)

[Insert Multiple Rows](#)

[INSERT INTO SELECT](#)

[Insert On Duplicate Key Update](#)

[INSERT IGNORE](#)

[Insert DateTimes](#)

[Insert Dates](#)

UPDATE DATA

[UPDATE](#)

[UPDATE JOIN](#)

DELETE DATA

[DELETE JOIN](#)

[ON DELETE CASCADE](#)

[TRUNCATE TABLE](#)

MYSQL TRANSACTIONS

[Table Locking](#)

MYSQL DATA TYPES

[BIT](#)

[INT](#)

[BOOLEAN](#)

[DECIMAL](#)

[DATETIME](#)

[TIMESTAMP](#)

[DATE](#)

[TIME](#)

[CHAR](#)

[VARCHAR](#)

[TEXT](#)

[BINARY](#)

[VARBINARY](#)

[ENUM](#)

[BLOB](#)

MYSQL GLOBALIZATION

[MySQL Character Sets](#)

[MySQL Collation](#)

MYSQL IMPORT & EXPORT

[Import a CSV File Into a Table](#)

[Export a Table to a CSV File](#)

ADVERTISEMENTS

ABOUT MYSQL TUTORIAL

WEBSITE

MySQLTutorial.org helps you master MySQL quickly, easily, and with enjoyment. Our tutorials make learning MySQL a breeze.

All MySQL tutorials are clear, practical and easy-to-follow.

[More About Us](#)

LATEST TUTORIALS

[MySQL Port](#)

[MySQL Commands](#)

[innodb_dedicated_server:](#)
[Configure InnoDB Dedicated Server](#)

[innodb_flush_method:](#)
[Configure InnoDB Flush Method](#)

[innodb_log_buffer_size:](#)
[Configure InnoDB Log Buffer Size](#)

[innodb_buffer_pool_chunk_size:](#)
[Configure Buffer Pool Chunk Size](#)

[innodb_buffer_pool_instances:](#)
[Configuring Multiple Buffer Pool Instances for Improved Concurrency in MySQL](#)

[innodb_buffer_pool_size:](#)
[Configure InnoDB Buffer Pool Size](#)

[MySQL InnoDB Architecture](#)

SITE LINKS

[Donation](#) 

[Contact Us](#)

[About](#)

[Privacy Policy](#)

OTHERS

[MySQL Cheat Sheet](#)

[MySQL Resources](#)

[MySQL Books](#)

How to Kill a Process in MySQL

Copyright © 2008 - Present by www.mysqltutorial.org. All Rights Reserved.