

MySQL DECIMAL Data Type



Summary: in this tutorial, you will learn about MySQL `DECIMAL` data type and how to use it to store exact numeric values in the databases.

Introduction to MySQL DECIMAL data type

The MySQL `DECIMAL` data type allows you to store exact numeric values in the database. In practice, you often use the `DECIMAL` data type for columns that preserve exact precision e.g., monetary data in financial systems.

To define a column whose data type is `DECIMAL`, you use the following syntax:

```
column_name DECIMAL(P,D);
```

In this syntax:

- `P` is the precision that represents the number of significant digits. The range of `P` is 1 to 65.
- `D` is the scale that represents the number of digits after the decimal point. The range of `D` is 0 and 30. MySQL requires that `D` is less than or equal to (\leq) `P`.

The `DECIMAL(P,D)` means that the column can store up to `P` digits with `D` decimals. The

actual range of the decimal column depends on the precision and scale.

Besides the `DECIMAL` keyword, you can also use `DEC` , `FIXED` , or `NUMERIC` because they are synonyms for `DECIMAL` .

The following example defines the `amount` column with `DECIMAL` data type.

```
amount DECIMAL(6,2);
```

In this example, the amount column can store 6 digits with 2 decimal places; therefore, the range of the amount column is from 9999.99 to -9999.99.

MySQL allows you to use the following syntax:

```
column_name DECIMAL(P);
```

This is equivalent to:

```
column_name DECIMAL(P,0);
```

In this case, the column contains no fractional part or decimal point.

In addition, you can even use the following syntax:

```
column_name DECIMAL;
```

The default value of P is 10 and D is 0, which is equivalent to the following:

```
column_name DECIMAL(10,0);
```

MySQL DECIMAL storage

MySQL assigns the storage for integer and fractional parts separately. MySQL uses a binary format to store the `DECIMAL` values. It packs 9 digits into 4 bytes.

For each part, it takes 4 bytes to store each multiple of 9 digits. The storage required for leftover digits is illustrated in the following table:

Leftover Digits	Bytes
0	0
1–2	1
3–4	2
5–6	3
7–9	4

For example, `DECIMAL(19,9)` has 9 digits for the fractional part and $19-9 = 10$ digits for the integer part. The fractional part requires 4 bytes. The integer part requires 4 bytes for the first 9 digits, for 1 leftover digit, it requires 1 more byte. In total, the `DECIMAL(19,9)` column requires 9 bytes.

MySQL DECIMAL data type and monetary data

We often use the `DECIMAL` data type for monetary data such as prices, salary, account balances, and so on. If you design a database that handles the monetary data, the following syntax should be fine.

```
amount DECIMAL(19,2);
```

However, if you want to comply with [Generally Accepted Accounting Principles \(GAAP\)](#) rules, the monetary column must have at least 4 decimal places to make sure that the rounding value does not exceed \$0.01. In this case, you should define the column with 4 decimal places as follows:

```
amount DECIMAL(19,4);
```

MySQL DECIMAL data type example

First, [create a new table](#) named `materials` :

```
CREATE TABLE materials (
```

```
id INT AUTO_INCREMENT PRIMARY KEY,  
description VARCHAR(255) NOT NULL,  
cost DECIMAL(19,4) NOT NULL  
);
```

The `materials` table has three columns:

- `id` is the [auto-increment primary key](#) column with the `INT` data type.
- `description` represents the material's description with the `VARCHAR` data type.
- `cost` represents the cost of the material, which has the `DECIMAL(19,4)`.

The `cost` column can store up to 19 digits with 4 decimal places.

Second, [insert data](#) into the `materials` table.

```
INSERT INTO materials(description, cost)  
VALUES  
('Bicycle', 500.34),  
('Seat', 10.23),  
('Break', 5.21);
```

Third, [query data](#) from the `materials` table.

```
SELECT  
*  
FROM  
materials;
```

Output:

```
+----+-----+-----+  
| id | description | cost      |  
+----+-----+-----+  
|  1 | Bicycle     | 500.3400 |  
|  2 | Seat        | 10.2300  |  
|  3 | Break       |  5.2100  |  
+----+-----+-----+  
3 rows in set (0.00 sec)
```

Summary

- Use MySQL `DECIMAL` data type to store exact numeric values such as financial data in the database.
- Use `column_name DECIMAL (P, D)` to define a column with the `DECIMAL` data type that has up to `P` digits and `D` decimal places.
- The `DECIMAL(P)` is equivalent to `DECIMAL(P,0)` and `DECIMAL` is equivalent to `DECIMAL(P, 0)`.

Was this tutorial helpful?



ADVERTISEMENTS

PREVIOUSLY

[MySQL BOOLEAN Data Type](#)

UP NEXT

[MySQL DATETIME Data Type](#)

ADVERTISEMENTS





VERSACE

GETTING STARTED

[What Is MySQL?](#)

[Install MySQL Database Server](#)

[Connect to MySQL Server](#)

[Download MySQL Sample Database](#)

[Load Sample Database](#)

QUERYING DATA

[SELECT FROM](#)

[SELECT](#)

[ORDER BY](#)

[WHERE](#)

[SELECT DISTINCT](#)

[AND](#)

[OR](#)

[IN](#)

[NOT IN](#)

[BETWEEN](#)

[LIKE](#)

[LIMIT](#)

[IS NULL](#)

[Table & Column Aliases](#)

[Joins](#)

[INNER JOIN](#)

[LEFT JOIN](#)

[RIGHT JOIN](#)

[Self Join](#)

[CROSS JOIN](#)

[GROUP BY](#)

[HAVING](#)

[HAVING COUNT](#)

[ROLLUP](#)

[Subquery](#)

[Derived Tables](#)

[EXISTS](#)

[EXCEPT](#)

[INTERSECT](#)

ADVERTISEMENT

MANAGING DATABASES

[Select a Database](#)

[Create Databases](#)

[Drop Databases](#)

MANAGING TABLES

[Create Tables](#)

[AUTO_INCREMENT](#)

[Rename Tables](#)

[Add Columns](#)

[Drop Columns](#)

[Drop Tables](#)

[Temporary Tables](#)

[Generated Columns](#)

MYSQL CONSTRAINTS

[Primary Key](#)

[Foreign Key](#)

[Disable Foreign Key Checks](#)

[UNIQUE Constraint](#)

[NOT NULL Constraint](#)

[DEFAULT Constraint](#)

[CHECK Constraint](#)

ADVERTISEMENTS

INSERT DATA

[Insert Into](#)

[Insert Multiple Rows](#)

[INSERT INTO SELECT](#)

[Insert On Duplicate Key Update](#)

[INSERT IGNORE](#)

[Insert DateTimes](#)

[Insert Dates](#)

UPDATE DATA

[UPDATE](#)

[UPDATE JOIN](#)

DELETE DATA

[DELETE JOIN](#)

[ON DELETE CASCADE](#)

[TRUNCATE TABLE](#)

MYSQL TRANSACTIONS

[Table Locking](#)

MYSQL DATA TYPES

[BIT](#)

[INT](#)

[BOOLEAN](#)

[DECIMAL](#)

[DATETIME](#)

[TIMESTAMP](#)

[DATE](#)

[TIME](#)

[CHAR](#)

[VARCHAR](#)

[TEXT](#)

[BINARY](#)

[VARBINARY](#)

[ENUM](#)

[BLOB](#)

MYSQL GLOBALIZATION

[MySQL Character Sets](#)

[MySQL Collation](#)

MYSQL IMPORT & EXPORT

[Import a CSV File Into a Table](#)

[Export a Table to a CSV File](#)

ADVERTISEMENTS

ABOUT MYSQL TUTORIAL WEBSITE

MySQLTutorial.org helps you master MySQL quickly, easily, and with enjoyment. Our tutorials make learning MySQL a breeze.

All MySQL tutorials are clear, practical and easy-to-follow.
[More About Us](#)

LATEST TUTORIALS

[MySQL Port](#)

[MySQL Commands](#)

[innodb_dedicated_server:
Configure InnoDB Dedicated
Server](#)

[innodb_flush_method:
Configure InnoDB Flush
Method](#)

[innodb_log_buffer_size:
Configure InnoDB Log Buffer
Size](#)

[innodb_buffer_pool_chunk_size:
Configure Buffer Pool Chunk
Size](#)

[innodb_buffer_pool_instances:
Configuring Multiple Buffer](#)

SITE LINKS

[Donation](#) 

[Contact Us](#)

[About](#)

[Privacy Policy](#)

OTHERS

[MySQL Cheat Sheet](#)

[MySQL Resources](#)

[MySQL Books](#)

Pool Instances for Improved
Concurrency in MySQL

innodb_buffer_pool_size:
Configure InnoDB Buffer Pool
Size

MySQL InnoDB Architecture

How to Kill a Process in MySQL

Copyright © 2008 - Present by www.mysqltutorial.org. All Rights Reserved.