

MySQL INT Data Type



Summary: in this tutorial, you will learn about MySQL `INT` data type, and how to use it to store whole numbers in the databases.

Introduction to MySQL INT data type

In MySQL, `INT` stands for the integer that represents the whole numbers. An integer can be written without a fractional component such as 1, 100, 4, -10, and it cannot be 1.2, 5/3, etc. An integer can be zero, positive, and negative.

MySQL supports all standard SQL integer types `INTEGER` or `INT` and `SMALLINT`. Additionally, MySQL provides `TINYINT`, `MEDIUMINT`, and `BIGINT` as extensions to the SQL standard.

MySQL `INT` [data type](#) can be signed and unsigned. The following table illustrates the characteristics of each integer type including storage in bytes, minimum value, and maximum value.

Type	Storage	Minimum Value	Maximum Value
	(Bytes)	(Signed/Unsigned)	(Signed/Unsigned)
TINYINT	1	-128	127

Type	Storage	Minimum Value	Maximum Value
	(Bytes)	(Signed/Unsigned)	(Signed/Unsigned)
		0	255
SMALLINT	2	-32768	32767
		0	65535
MEDIUMINT	3	-8388608	8388607
		0	16777215
INT	4	-2147483648	2147483647
		0	4294967295
BIGINT	8	-9223372036854775808	9223372036854775807
		0	18446744073709551615

MySQL INT data type examples

Let's look at some examples of using the integer data type.

1) Using INT for a column example

Because integer type represents exact numbers, you usually use it as the [primary key](#) of a table. In addition, the `INT` column can have an [AUTO_INCREMENT](#) attribute.

When you [insert](#) a `NULL` value or 0 into the `INT AUTO_INCREMENT` column, the value of the column is set to the next [sequence](#) value. Notice that the sequence value starts with 1.

When you insert a value, which is not `NULL` or zero, into the `AUTO_INCREMENT` column, the column accepts the value. In addition, the sequence is reset to the next value of the inserted value.

First, [create a new table](#) named `items` with an integer column as the [primary key](#):

```
CREATE TABLE items (
```

```
item_id INT AUTO_INCREMENT PRIMARY KEY,  
item_text VARCHAR(255)  
);
```

You can use either `INT` or `INTEGER` in the `CREATE TABLE` statement above because they are interchangeable. Whenever you insert a new row into the `items` table, the value of the `item_id` column is increased by 1.

Next, the following `INSERT` statement [inserts three rows](#) into the `items` table.

```
INSERT INTO  
items(item_text)  
VALUES  
( 'laptop' ),  
( 'mouse' ),  
( 'headphone' );
```

Then, query data from the `items` table using the following `SELECT` statement:

```
SELECT * FROM items;
```

Output:

```
+-----+-----+  
| item_id | item_text |  
+-----+-----+  
|      1 | laptop   |  
|      2 | mouse    |  
|      3 | headphone |  
+-----+-----+  
3 rows in set (0.00 sec)
```

After that, insert a new row whose value of the `item_id` column is specified explicitly.

```
INSERT INTO items(item_id,item_text)  
VALUES(10, 'Server');
```

Since the current value of the `item_id` column is 10, the sequence is reset to 11. If you insert a new row, the `AUTO_INCREMENT` column will use 11 as the next value.

```
INSERT INTO items(item_text)
VALUES('Router');
```

Finally, query the data of the `items` table again to see the result.

```
SELECT * FROM items;
```

Output:

```
+-----+-----+
| item_id | item_text |
+-----+-----+
|      1 | laptop   |
|      2 | mouse    |
|      3 | headphone |
|     10 | Server   |
|     11 | Router    |
+-----+-----+
5 rows in set (0.00 sec)
```

2) Using INT UNSIGNED example

First, [create a table](#) called `classes` that has the column `total_member` with the unsigned integer data type:

```
CREATE TABLE classes (
  class_id INT AUTO_INCREMENT,
  name VARCHAR(255) NOT NULL,
  total_member INT UNSIGNED,
  PRIMARY KEY (class_id)
);
```

Second, [insert a new row](#) into the `classes` table:

```
INSERT INTO classes(name, total_member)
```

```
VALUES('Weekend',100);
```

It worked as expected.

Third, attempt to insert a negative value into the `total_member` column:

```
INSERT INTO classes(name, total_member)
VALUES('Fly',-50);
```

MySQL issued the following error:

```
Error Code: 1264. Out of range value for column 'total_member' at row 1
```

Note that the display width has been deprecated. Additionally, the ZEROFILL attribute has also been deprecated, and the suggested alternatives are to use [LPAD](#) for zero-padding numbers or to store the formatted numbers in a [CHAR](#) column.

Summary

- `INT` represents the integer type.
- MySQL offers various variants of the `INT` type including `TINYINT`, `SMALLINT`, `MEDIUMINT`, and `BIGINT`.

Was this tutorial helpful?



ADVERTISEMENTS





PREVIOUSLY

[MySQL BIT Data Type](#)

UP NEXT

[MySQL BOOLEAN Data Type](#)

ADVERTISEMENTS

Discover more

[🔌 databases](#)

[🔌 Data management software](#)

[🔌 MySQL](#)

[🔌 MySQL hosting services](#)

[🔌 Version control systems](#)

[🔌 SQL programming tools](#)

[🔌 MySQL learning resources](#)

Search ...

GETTING STARTED

[What Is MySQL?](#)

[Install MySQL Database Server](#)

[Connect to MySQL Server](#)

[Download MySQL Sample Database](#)

[Load Sample Database](#)

QUERYING DATA

[SELECT FROM](#)

[SELECT](#)

ORDER BY

WHERE

SELECT DISTINCT

AND

OR

IN

NOT IN

BETWEEN

LIKE

LIMIT

IS NULL

Table & Column Aliases

Joins

INNER JOIN

LEFT JOIN

RIGHT JOIN

Self Join

CROSS JOIN

GROUP BY

HAVING

HAVING COUNT

ROLLUP

Subquery

Derived Tables

EXISTS

[EXCEPT](#)

[INTERSECT](#)

ADVERTISEMENTS

MANAGING DATABASES

[Select a Database](#)

[Create Databases](#)

[Drop Databases](#)

MANAGING TABLES

[Create Tables](#)

[AUTO_INCREMENT](#)

[Rename Tables](#)

[Add Columns](#)

[Drop Columns](#)

[Drop Tables](#)

[Temporary Tables](#)

[Generated Columns](#)

MYSQL CONSTRAINTS

[Primary Key](#)

[Foreign Key](#)

[Disable Foreign Key Checks](#)

[UNIQUE Constraint](#)

[NOT NULL Constraint](#)

[DEFAULT Constraint](#)

[CHECK Constraint](#)

ADVERTISEMENTS



INSERT DATA

[Insert Into](#)

[Insert Multiple Rows](#)

[INSERT INTO SELECT](#)

[Insert On Duplicate Key Update](#)

[INSERT IGNORE](#)

[Insert DateTimes](#)

[Insert Dates](#)

UPDATE DATA

[UPDATE](#)

[UPDATE JOIN](#)

DELETE DATA

[DELETE JOIN](#)

[ON DELETE CASCADE](#)

[TRUNCATE TABLE](#)

MYSQL TRANSACTIONS

[Table Locking](#)

MYSQL DATA TYPES

[BIT](#)

[INT](#)

[BOOLEAN](#)

[DECIMAL](#)

[DATETIME](#)

[TIMESTAMP](#)

[DATE](#)

[TIME](#)

[CHAR](#)

[VARCHAR](#)

[TEXT](#)

[BINARY](#)

[VARBINARY](#)

[ENUM](#)

[BLOB](#)

MYSQL GLOBALIZATION

[MySQL Character Sets](#)

[MySQL Collation](#)

MYSQL IMPORT & EXPORT

[Import a CSV File Into a Table](#)

[Export a Table to a CSV File](#)

ABOUT MYSQL TUTORIAL WEBSITE

MySQLTutorial.org helps you master MySQL quickly, easily, and with enjoyment. Our tutorials make learning MySQL a breeze.

All MySQL tutorials are clear, practical and easy-to-follow.
[More About Us](#)

LATEST TUTORIALS

[MySQL Port](#)

[MySQL Commands](#)

[innodb_dedicated_server:
Configure InnoDB Dedicated
Server](#)

[innodb_flush_method:
Configure InnoDB Flush
Method](#)

[innodb_log_buffer_size:
Configure InnoDB Log Buffer
Size](#)

[innodb_buffer_pool_chunk_size:
Configure Buffer Pool Chunk
Size](#)

[innodb_buffer_pool_instances:
Configuring Multiple Buffer
Pool Instances for Improved
Concurrency in MySQL](#)

[innodb_buffer_pool_size:
Configure InnoDB Buffer Pool
Size](#)

[MySQL InnoDB Architecture](#)

[How to Kill a Process in MySQL](#)

SITE LINKS

[Donation](#) 

[Contact Us](#)

[About](#)

[Privacy Policy](#)

OTHERS

[MySQL Cheat Sheet](#)

[MySQL Resources](#)

[MySQL Books](#)