


MySQL View Processing Algorithms

Discover more

 [Developer training courses](#)

 [Database security solutions](#)

 [Web development frameworks](#)

 [MySQL consulting services](#)

 [Performance tuning workshops](#)

 [databases](#)

 [Cloud database hosting platforms](#)

Summary: in this tutorial, you will learn about MySQL view processing algorithms including `MERGE` , `TEMPTABLE` , and `UNDEFINED` .

The [CREATE VIEW](#) and `ALTER VIEW` statements have an optional clause: `ALGORITHM` . The algorithm determines how MySQL process a view and can take one of three values `MERGE` , `TEMPTABLE` , and `UNDEFINE` .

Here is the `CREATE VIEW` statement with the `ALGORITHM` clause:

```
CREATE [OR REPLACE][ALGORITHM = {MERGE | TEMPTABLE | UNDEFINED}] VIEW
    view_name[(column_list)]
AS
    select-statement;
```

And this is the `ALTER VIEW` statement with the `ALGORITHM` clause:

```
CREATE [ALGORITHM = {MERGE | TEMPTABLE | UNDEFINED}] VIEW
    view_name[(column_list)]
AS
    select-statement;
```

MERGE

When you query from a `MERGE` view, MySQL processes the following steps:

- First, merge the input query with the `SELECT` statement in the view definition into a single query.
- Then, execute the combined query to return the result set.

Note that the combination of input query and the `SELECT` statement of the view definition into a single query is referred to as *view resolution*.

See the following `customers` from the [sample database](#):

customers
* customerNumber customerName contactLastName contactFirstName phone addressLine1 addressLine2 city state postalCode country salesRepEmployeeNumber creditLimit

The following statement creates a view based on the `customers` table with the name `contactPersons` with the `MERGE` algorithm:

```
CREATE ALGORITHM=MERGE VIEW contactPersons(  
    customerName,  
    firstName,  
    lastName,  
    phone  
) AS  
SELECT  
    customerName,  
    contactFirstName,  
    contactLastName,
```

```
phone
FROM customers;
```

Suppose that you issue the following statement:

```
SELECT * FROM contactPersons
WHERE customerName LIKE '%Co%';
```

MySQL performs these steps:

- Convert view name `contactPersons` to table name `customers` .
- Convert asterisk (*) to a list column names `customerName` , `firstName` , `lastName` , `phone` , which corresponds to `customerName` , `contactFirstName` , `contactLastName` , `phone` .
- Add the `WHERE` clause.

The resulting statement is:

```
SELECT
    customerName,
    contactFirstName,
    contactLastName,
    phone
FROM
    customers
WHERE
    customerName LIKE '%Co%';
```

TEMPTABLE

When you issue a query to a `TEMPTABLE` view, MySQL performs these steps:

- First, [create a temporary table](#) to store the result of the `SELECT` in the view definition.
- Then, execute the input query against the temporary table.

Because MySQL has to create the temporary table to store the result set and moves the data from the base tables to the temporary table, the algorithm `TEMPTABLE` is less efficient than the

MERGE algorithm.

Note that TEMPTABLE views cannot be [updatable](#).

UNDEFINED

The UNDEFINED is the default algorithm when you create a view without specifying the ALGORITHM clause or you explicitly specify ALGORITHM=UNDEFINED .

In addition, when you create a view with ALGORITHM = MERGE and MySQL can only process the view with a temporary table, MySQL automatically sets the algorithm to UNDEFINED and generates a warning.

The UNDEFINED allows MySQL to choose either MERGE or TEMPTABLE . And MySQL prefers MERGE over TEMPTABLE if possible because MERGE is often more efficient than TEMPTABLE .

In this tutorial, you have learned about the MySQL view processing algorithms including MERGE , TEMPTABLE , and UNDEFINED .

Was this tutorial helpful?



ADVERTISEMENTS

Discover more

⚡ SQL query optimization tools

⚡ Learning MySQL fast

⚡ Backup and recovery software

⚡ Database security solutions

⚡ SQL practice exercises

⚡ Database administration services

PREVIOUSLY

MySQL CREATE VIEW

UP NEXT

MySQL ALTER VIEW

MYSQL VIEWS[MySQL CREATE VIEW](#)[MySQL View Processing Algorithms](#)[Create MySQL Updatable Views](#)[Rename View](#)[Show View](#)[SHOW CREATE VIEW](#)[DROP VIEW](#)[WITH CHECK OPTION](#)[LOCAL & CASCADED](#)**ABOUT MYSQL TUTORIAL WEBSITE**

MySQLTutorial.org helps you master MySQL quickly, easily, and with enjoyment. Our tutorials make learning MySQL a breeze.

All MySQL tutorials are clear, practical and easy-to-follow.
[More About Us](#)

LATEST TUTORIALS[MySQL Port](#)[MySQL Commands](#)

[innodb_dedicated_server:](#)
[Configure InnoDB Dedicated Server](#)

[innodb_flush_method:](#)
[Configure InnoDB Flush Method](#)

[innodb_log_buffer_size:](#)

SITE LINKS[Donation !\[\]\(5ddb2a112276baa148775929432349f9_img.jpg\)](#)[Contact Us](#)[About](#)[Privacy Policy](#)**OTHERS**[MySQL Cheat Sheet](#)[MySQL Resources](#)

Configure InnoDB Log Buffer
Size

innodb_buffer_pool_chunk_size:
Configure Buffer Pool Chunk
Size

innodb_buffer_pool_instances:
Configuring Multiple Buffer
Pool Instances for Improved
Concurrency in MySQL

innodb_buffer_pool_size:
Configure InnoDB Buffer Pool
Size

MySQL InnoDB Architecture

How to Kill a Process in MySQL