

MySQL UNIQUE Constraint

Search for

1. **Live** Football Streaming



2. **Apply** for Job Now



3. **Humanize** Your AI Text for Free



Ad | Lifestyle Insights



Summary: in this tutorial, you will learn about MySQL `UNIQUE` constraint and how to use it to enforce the uniqueness of values in a column or a group of columns in a table.

Introduction to MySQL UNIQUE constraint

Sometimes, you want to ensure values in a column or a group of columns are unique. For example, email addresses of users in the `users` table, or phone numbers of customers in the `customers` table should be unique. To enforce this rule, you use a `UNIQUE` constraint.

A `UNIQUE` constraint is an integrity constraint that ensures the uniqueness of values in a column or group of columns. A `UNIQUE` constraint can be either a column constraint or a table constraint.

To define a `UNIQUE` constraint for a column when [creating a table](#), you use the following syntax:

```
CREATE TABLE table_name(  
    ...,  
    column1 datatype UNIQUE,  
    ...  
);
```

In this syntax, you include the `UNIQUE` keyword in the definition of the column that you want to enforce the uniqueness.

If you [insert](#) or [update](#) a value that causes a duplicate in the `column1`, MySQL rejects the change and issues an error.

This `UNIQUE` constraint is a column constraint. And you can use it to enforce the unique rule for one column.

To define a `UNIQUE` constraint for two or more columns, you use the following syntax:

```
CREATE TABLE table_name(  
    ...  
    column1 datatype,  
    column2 datatype,  
    ...,  
    UNIQUE(column1, column2)  
);
```

In this syntax, you add a comma-separated list of columns in parentheses after the `UNIQUE` keyword. In this case, MySQL will use the combination of values in both columns `column1` and `column2` to evaluate the uniqueness.

If you define a `UNIQUE` constraint without specifying a name, MySQL automatically generates a name for it. To define a `UNIQUE` constraint with a name, you use this syntax:

```
[CONSTRAINT constraint_name]  
UNIQUE(column_list)
```

In this syntax, you specify the name of the `UNIQUE` constraint after the `CONSTRAINT` keyword.

MySQL UNIQUE constraint example

First, [creates a new table](#) named `suppliers` with the two `UNIQUE` constraints:

```
CREATE TABLE suppliers (  
    supplier_id INT AUTO_INCREMENT,  
    name VARCHAR(255) NOT NULL,
```

```
phone VARCHAR(15) NOT NULL UNIQUE,  
address VARCHAR(255) NOT NULL,  
PRIMARY KEY (supplier_id),  
CONSTRAINT uc_name_address UNIQUE (name,address)  
);
```

In this example, the first `UNIQUE` constraint is defined for the `phone` column:

```
phone VARCHAR(12) NOT NULL UNIQUE
```

The second `UNIQUE` constraint includes both `name` and `address` columns:

```
CONSTRAINT uc_name_address UNIQUE (name , address)
```

Second, [insert a row](#) into the `suppliers` table:

```
INSERT INTO suppliers(name, phone, address)  
VALUES( 'ABC Inc',  
        '(408)-908-2476',  
        '4000 North 1st Street');
```

Third, attempt to insert a different supplier but has the phone number that already exists in the `suppliers` table.

```
INSERT INTO suppliers(name, phone, address)  
VALUES( 'XYZ Corporation','(408)-908-2476','3000 North 1st Street');
```

MySQL issued the following error:

```
Error Code: 1062. Duplicate entry '(408)-908-2476' for key 'phone'
```

Fourth, change the phone number to a different one and execute the insert statement again.

```
INSERT INTO suppliers(name, phone, address)  
VALUES( 'XYZ Corporation','(408)-908-3333','3000 North 1st Street');
```

Fifth, insert a row into the `suppliers` table with values that already exist in the columns `name` and `address` :

```
INSERT INTO suppliers(name, phone, address)
VALUES( 'ABC Inc',
        '(408)-908-1111',
        '4000 North 1st Street');
```

MySQL issued an error because the `UNIQUE` constraint `uc_name_address` was violated.

Error Code: 1062. Duplicate entry 'ABC Inc-4000 North 1st Street' for key 'uc_name_address'

MySQL UNIQUE constraint & NULL

In MySQL, NULL values are treated as distinct when it comes to unique constraints. Therefore, if you have a column that accepts NULL values, you can insert multiple values into the column.

First, [create a new table](#) called `contacts` :

```
CREATE TABLE contacts(
    id INT AUTO_INCREMENT PRIMARY KEY,
    name VARCHAR(255) NOT NULL,
    phone VARCHAR(20) UNIQUE
)
```

The contacts table has a `phone` column with a UNIQUE constraint. Also, the `phone` column can accept NULL values.

Second, insert some rows into the `contacts` table:

```
INSERT INTO contacts(name, phone)
VALUES
    ('Alice', '(408)-102-2456'),
    ('John', NULL),
    ('Jane', NULL);
```

In this example, we can insert two NULL values into the phone column without causing a duplicate.

Third, retrieve data from the `contacts` table:

```
SELECT * FROM contacts;
```

Output:

```
+----+-----+-----+
| id | name  | phone          |
+----+-----+-----+
|  1 | Alice | (408)-102-2456 |
|  2 | John  | NULL           |
|  3 | Jane  | NULL           |
+----+-----+-----+
3 rows in set (0.00 sec)
```

MySQL UNIQUE constraints and indexes

When you define a unique constraint for a column or a group of columns, MySQL creates a corresponding `UNIQUE index` and uses this index to enforce the rule.

The `SHOW CREATE TABLE` statement shows the definition of the `suppliers` table:

```
SHOW CREATE TABLE suppliers;
```

Table	Create Table
suppliers	<pre>CREATE TABLE `suppliers` (`supplier_id` int(11) NOT NULL AUTO_INCREMENT, `name` varchar(255) NOT NULL, `phone` varchar(15) NOT NULL, `address` varchar(255) NOT NULL, PRIMARY KEY (`supplier_id`), UNIQUE KEY `phone` (`phone`), UNIQUE KEY `uc name address` (`name`,`address`)) ENGINE=InnoDB AUTO_INCREMENT=5 DEFAULT CHARSET=latin1</pre>

The output indicates that MySQL created two `UNIQUE` indexes on the `suppliers` table: `phone` and `uc_name_address`.

The following `SHOW INDEX` statement displays all indexes associated with the `suppliers` table.

```
SHOW INDEX FROM suppliers;
```

Drop a unique constraint

To drop a `UNIQUE` constraint, you can use `DROP INDEX` or `ALTER TABLE` statement:

```
DROP INDEX index_name ON table_name;
```

```
ALTER TABLE table_name  
DROP INDEX index_name;
```

For example, the following statement drops the `uc_name_address` constraint on the `suppliers` table:

```
DROP INDEX uc_name_address ON suppliers;
```

Execute the `SHOW INDEX` statement again to verify if the `uc_name_unique` constraint has been removed.

```
SHOW INDEX FROM suppliers;
```

Add new unique constraint

The following `ALTER TABLE ADD CONSTRAINT` adds a unique constraint to a column of an existing table:

```
ALTER TABLE table_name  
ADD CONSTRAINT constraint_name
```

```
UNIQUE (column_list);
```

This statement adds a `UNIQUE` constraint `uc_name_address` back to the `suppliers` table:

```
ALTER TABLE suppliers  
ADD CONSTRAINT uc_name_address  
UNIQUE (name,address);
```

Note that MySQL will not add a unique constraint if the existing data in the columns of specified in the unique constraint does not comply with the uniqueness rule.

Summary

- Use MySQL `UNIQUE` constraint to enforce the uniqueness of values in a column or group of columns of a table.

Was this tutorial helpful?



ADVERTISEMENTS

PREVIOUSLY

[MySQL Disable Foreign Key Checks](#)

UP NEXT

[MySQL NOT NULL Constraint](#)

ADVERTISEMENTS

GETTING STARTED

[What Is MySQL?](#)

[Install MySQL Database Server](#)

[Connect to MySQL Server](#)

[Download MySQL Sample Database](#)

[Load Sample Database](#)

QUERYING DATA

[SELECT FROM](#)

[SELECT](#)

[ORDER BY](#)

[WHERE](#)

[SELECT DISTINCT](#)

[AND](#)

[OR](#)

[IN](#)

[NOT IN](#)

[BETWEEN](#)

[LIKE](#)

[LIMIT](#)

[IS NULL](#)

[Table & Column Aliases](#)

[Joins](#)

[INNER JOIN](#)

[LEFT JOIN](#)

[RIGHT JOIN](#)

[Self Join](#)

[CROSS JOIN](#)

[GROUP BY](#)

[HAVING](#)

[HAVING COUNT](#)

[ROLLUP](#)

[Subquery](#)

[Derived Tables](#)

[EXISTS](#)

[EXCEPT](#)

[INTERSECT](#)

ADVERTISEMENT

MANAGING DATABASES

[Select a Database](#)

[Create Databases](#)

[Drop Databases](#)

MANAGING TABLES

[Create Tables](#)

[AUTO_INCREMENT](#)

[Rename Tables](#)

[Add Columns](#)

[Drop Columns](#)

[Drop Tables](#)

[Temporary Tables](#)

[Generated Columns](#)

MYSQL CONSTRAINTS

[Primary Key](#)

[Foreign Key](#)

[Disable Foreign Key Checks](#)

[UNIQUE Constraint](#)

[NOT NULL Constraint](#)

[DEFAULT Constraint](#)

[CHECK Constraint](#)

ADVERTISEMENTS

INSERT DATA

[Insert Into](#)

[Insert Multiple Rows](#)

[INSERT INTO SELECT](#)

[Insert On Duplicate Key Update](#)

[INSERT IGNORE](#)

[Insert DateTimes](#)

[Insert Dates](#)

UPDATE DATA

[UPDATE](#)

[UPDATE JOIN](#)

DELETE DATA

[DELETE JOIN](#)

[ON DELETE CASCADE](#)

[TRUNCATE TABLE](#)

MYSQL TRANSACTIONS

[Table Locking](#)

MYSQL DATA TYPES

[BIT](#)

[INT](#)

[BOOLEAN](#)

[DECIMAL](#)

[DATETIME](#)

[TIMESTAMP](#)

[DATE](#)

[TIME](#)

[CHAR](#)

[VARCHAR](#)

[TEXT](#)

[BINARY](#)

[VARBINARY](#)

[ENUM](#)

[BLOB](#)

MYSQL GLOBALIZATION

[MySQL Character Sets](#)

[MySQL Collation](#)

MYSQL IMPORT & EXPORT

[Import a CSV File Into a Table](#)

[Export a Table to a CSV File](#)

ADVERTISEMENTS

ABOUT MYSQL TUTORIAL WEBSITE

MySQLTutorial.org helps you master MySQL quickly, easily, and with enjoyment. Our tutorials make learning MySQL a breeze.

All MySQL tutorials are clear, practical and easy-to-follow.
[More About Us](#)

LATEST TUTORIALS

[MySQL Port](#)

[MySQL Commands](#)

[innodb_dedicated_server:
Configure InnoDB Dedicated
Server](#)

[innodb_flush_method:
Configure InnoDB Flush
Method](#)

[innodb_log_buffer_size:
Configure InnoDB Log Buffer
Size](#)

[innodb_buffer_pool_chunk_size:
Configure Buffer Pool Chunk
Size](#)

[innodb_buffer_pool_instances:
Configuring Multiple Buffer](#)

SITE LINKS

[Donation](#) 

[Contact Us](#)

[About](#)

[Privacy Policy](#)

OTHERS

[MySQL Cheat Sheet](#)

[MySQL Resources](#)

[MySQL Books](#)

Pool Instances for Improved
Concurrency in MySQL

innodb_buffer_pool_size:
Configure InnoDB Buffer Pool
Size

MySQL InnoDB Architecture

How to Kill a Process in MySQL

Copyright © 2008 - Present by www.mysqltutorial.org. All Rights Reserved.