



USB
CAT5
USB
SWITCH
Power
USB
USB
audio
SD

Display

Panel Brand
AUO

Panel Model
T215HVN01.1

Panel Size
21.5"

Panel Type
a-Si TFT-LCD, LCM

Resolution
1920(RGB)×1080 , FHD

Pixel Format
RGB Vertical Stripe

Display Area
476.64(W)×268.11(H) mm

Bezel Opening
479.84(W)×271.31(H) mm

Outline Size
495.6(W)×292.2(H) ×11(D) mm

Surface

Antiglare, Hard coating (3H)

Brightness

250 cd/m² (Typ.)

Contrast Ratio

3000:1 (Typ.) (TM)

Viewing Angle

89/89/89/89 (Typ.)(CR≥10)

Display Mode

VA, Normally Black,

Transmissive

Best View on

Symmetry

Response Time

13/5 (Typ.)(Tr/Td)

Display Colors

16.7M 74% NTSC

Lamp Type

15S4P WLED , 30K hours ,

Without Driver

Frequency

60Hz

Touch Screen

Without

Panel Weight

1.67Kgs (Typ.)

Signal Interface

LVDS (2 ch, 8-bit) , 30 pins

Connector

Input Voltage

5.0V (Typ.)

Environment

Operating Temp.: 0 ~ 50 °C ; Storage Temp.: -20 ~ 60 °C











