Linux Basics for Hackers - Notes

Binaries

Located in -> /usr/bin and/or /usr/sbin

Linux File System

```
'/' -> The actual root system. The top most.
```

Inside it ->
/boot - Kernel image
/home - user dir
/proc - view of internal kernal data
/dev - special device files
/sbin - binaries
/root - SuperUser's Home Dir (different from '/')
/etc - Sys config
/mnt - GenPurpose Mount point
/sys - Kernel's view of HW
/bin - also binaries
/lib - libraries
/usr -> /sbin, /bin, /lib (more of the same stuff) /media - for ejectable media

cd Command

use '..' to move up 1 level
'.. ..' for 2 levels & '.. .. ..' for 3 levels and so on

Search-based commands

$ locate 'find_this' -> finds all occurences
$ whereis 'module_name' -> finds all BINARIES of the target (usually with man pages)
$ which aircrack-ng -> finds the binary file located in the PATH variable of the system
$ find -directory -option -targetExp -> finds literally everything [Eg: find /etc -type f -name apache2] -- altho apache2.* will find all file extensions but first name as apache2
Lastly, grep to filter
$ ps aux | grep apache2 -> will filter from all auxilliary processes containing apache2

'cat' is versatile remember

$ cat file_name -> will spill the file contents.
$ cat > file_name -> will let you write in it BUT WILL REPLACE ALL EXISTING DATA.
$ cat >> file_name -> will actually let you append the text you enter.

Renaming doesn't exist in Linux

So we use
$ mv newfile newfile2 -> to essentially rename the file

Removing a Dir

Only the directory : $ rmdir
When that fails : $ rm -r (recursively delete everything in it)

Text Manipulation

head and tail ->
$ head file_name -> first 10 lines
$ head -n file_name -> n number of lines from the start
$ tail -> for bottom lines (+ specialized with a count)

$ nl path_to_file_or_file_name -> will number all the lines. // cat can and should be clubbed with grep as and when needed. Eg: cat snort.conf | grep output

Sed command - for find and replace ->
$ sed s/search_term/replace_term/g path_to_filename > newfile_name
-> 's/' will find the term, '/g' is for replacing globally. Rest is elementary.
-> Removing the '/g' will only replace the first occurrence.
Adding a number there can limit the number of occurrences to be changed. '/3' will only replace the first 3.
Eg: sed s/mysql/MySQL/g /etc/snort/snort.conf > snort2.conf

$ more file_name -> offers a scroll-able page if the file is to big.
$ less file_name -> "less is more" -- offers a filter to search for the term should you need to -- use the '/' key. Still scroll-able but with better functionality.

Networking

'loopback' addr -- same as 'localhost' = 127.0.0.1
iwconfig - check for wireless adapter info -- good for getting power, the mode [monitor,

managed, promiscuous] etc.
Changing info -> MAC or IP Addr :
$ ifconfig eth0 192.1688.181.155
-> modifies what your router sees to redirect packets

Changing Netmask +/ Broadcast :
$ ifconfig eth0 192.168.181.155 netmask 255.255.0.0 broadcast 192.168.1.255
-> Netmask is the subnet mask -- determines the portion of the IP Addr to the NW and which refers to the host. Here, first 2 octets (16 bits) represent the network and last 2 show the hosts within that network.
-> Broadcast is the addr used to send packets to all hosts on the same network segment. Default (bcz of subnet) would become 192.168.255.255 but here overridden to 192.169.1.155 -- Basically packets sent to this will be broad-casted on that specific sub-network.

MAC Spoofing :
Take down the interface, change the Addr, restart
$ ifconfig eth0 down > ifconfig eth0 hw ether 00:11:22:33:44:55 > ifconfig eth0 up

Assigning new IP via DHCP Server :
Server runs of '*dhcpd*' - the daemon. Requested via '*dhclient*'. Requires a DHCP assigned IP addr. (Note : 'dhclient' is for Debian, different for all other distros.)
$ dhclient eth0
->DHCPDISCOVER req is sent by this command and then receives an offer from the DHCP i.e DHCPOFFER. Now, ifconfig will show a difft IP addr as given by the DHCP Server.

Manipulating DNS :
Use 'dig' :
Directly pass-on the domain and add the 'ns' tag to make the domain as the nameserver itself. 'mx' will fetch the mail-exchange server.
$ dig hackerarise.com ns OR $ dig hackerarise.com mx
-- Some Linux servers use BIND (Berkeley Internet Name Domain) which is just a fancy name for DNS.

Changing your DNS Server :
Edit a file stored in '/etc/resolv.conf'. There you will see the domain, search & nameserver fields. Swap the values here to switch your DNS server.
Other method to do the same (although this cleanly overwrites the file's content) ->
$ echo "nameserver 8.8.8.8" > /etc/resolv.conf

Mapping your own IP Addrs :
'hosts' file located in /etc/hosts. Useful for hijacking a TCP connection on your LAN to direct traffic to a malicious webserver by using a tool like *'dnsspoof'*
Usually this file has a mapping for your localhost only BUT you can map any website to any IP Address. Eg : "192.168.181.131 bankofamerica.com". Decent for local network attacks.
[dnsspoof & Ettercap can be used]

Handling SW Packages

Search for package in local repo:
$ apt-cache search *'keyword'*
-> Eg: $ apt-cache search snort

Install, Remove, Purge, Update, Upgrade :
$ apt-get install --name--
$ apt-get remove --name--
$ sudo apt-get update
$ sudo apt-get upgrade
$ apt-get purge --name--
(purge removes the config as well)
or use a package manager like *'synaptic'* or *'gdebi'* like a normie.

Adding Repos to Sources.list file :
$ mousepad /etc/apt/sources.list -> will open the list
Categories : main (OSS), universe (community maintained OSS), multiverse (SW restricted by copyright), restricted (proprietary device drivers), backports (packages from later releases)
Format : "deb http:// ------ --package_name-- main non-free contrib" etc.

File Directories & Permission

r,w,x -> read, write and execute

Granting ownership :
$ chown *username file-path-name* -> Provides the ownership of that file to that user
$ chgrp *group-name package-or-module-name* -> Provides a user-group access to that module

Checking Permissions :
$ ls -l *file-or-path-to-it* -> will lay down the whole sheet. The type, permission on the file for

owner/groups/users, number of links, the owner, size in bytes, creation/mod date & its name.
Eg: "drwxr-xr-x" vs "-rw-r--r--". First letter denotes directory if 'd' or file if empty dash.
Followed by the permission values for 3 groups i.e owner then group then other_users.
Hence we observe 3 values at a time. Dash means no permission ofc.
In '-rw-r--r--' -> File, owner has read/write, group and other users only have read permissions.
2nd way : There is a proper calculation done in Octal terms as well.

```
001 : 1 : --x
010 : 2 : -w-
011 : 3 : -wx
100 : 4 : r--
101 : 5 : r-x
110 : 6 : rw-
111 : 7 : rwx
```

Total RWX is 7. Since we have 3 sets of permissions, giving a full read+write+execute permission to everyone, for example, would look like ->
$ chmod 777 hashcat.hcstat

3rd way : UGO Syntax
Here, '-' removes a permission, '+' adds and '=' sets a permission.
Eg: Remove the write (w) permission from user on a file
$ chmod u-w hashcat.hcstat -> Now -rw-r--r-- becomes -r-xr-xr--
Or for user and other users at once
$ chmod u+x, o+x hashcat.hcstat
Now, you can set execute permission for yourself on a newly downloaded tool/script bcz by default Linux won't set it
$ chmod 766 some_new_tool -> grants us (the owner) all permission including execute -- and everyone else only R/W permissions.

Masking can be done :
$ umask 007 -> set it so only the user and members of the user's group have permissions.

Special Permissions :
SUID - set user ID & SGID - set group ID
1) Granting Temp Root w/ SUID
/etc/shadow contains all user's password -- requires root privileges to execute. SUID requires an additional bit before the permission bit. So 644 becomes 4644 i.e
$ chmod 4644 *file_name*

2) Granting the Root user's Group permissions SGID
SGID works differently. Someone without execute permission can execute a file if the owner belongs to the group that has the permission to execute that file. When the bit is set on a directory -- t**he ownership of new files created in that directory goes to the directory's creator's group rather than the file creator's group.**
$ chmod 2644 *file_name* [SGID bit is represented by 2 and SUID uses 4]

Privilege Escalation :
One way - exploit the **SUID Bit** in the system. Eg: Scripts that need to change the password usually come with the SUID bit set already. Use that to gain temporary root priv - then do something shady like getting the file at /etc/shadow.
To proceed -> Use commands like 'find' to find the files and see their bit. Example :
$ find / -user root -perm -4000
Kali now starts at the top of the filesystem (because of '/') and looks everywhere below this -- the file that are owned by 'root' & specified with 'user root' + have the SUID bit set (-perm -4000). This command will give an output like ->
/usr/bin/chsh ; /usr/bin/gpasswd; /usr/bin/pkexec; /usr/bin/sudo; /usr/bin/passwd,.. etc.
Navigating to this directory, and observing, let's say "sudo" using ls-alh, you will see ->
-rwsr-xr-x root root 140944 *date* sudo
Here, the 's' in place of 'x' determines the SUID bit. Logically, anyone who runs the *sudo* file has the priv of a root user -- which becomes an attack vector IF an application -- which needs access to /etc/shadow file to successfully complete their task -- can be hijacked.

Process Management

To view - use -> $ ps
Every process ofc has a PID or process ID. You can use -> $ kill *PID_value* to kill any process.
Issue ? 'ps' command won't give you much info either ways. We have another command for that ->
$ ps aux
It shows the USER, PID, %CPU, VSZ, RSS, TTY, STAT, START, TIME & COMMAND.

Filtering by Process Name
For instance, try running *msfconsole* command to have its process running. Then use *grep* to filter it. This way you can filter all the processes running/attached to it.
$ ps aux | grep msfconsole
You might see a few, such as the attached DB running, the ruby script, etc, and finally the program itself.

We also have commands like "*top*" to monitor the processes sorted by their resource usage. It's active i.e refreshes on its own (every 3-4 seconds)

Managing Processes

We can alter the affinity/priority of any process by using the *"nice"* command (by passing a numeric value to its argument '-n'). Kernel always has the final say, we're just suggesting. The value ranges from -20 to +19. Sadly, **HIGH value means LOW priority and vice versa**. So -20 is most likely to receive priority, 0 is default ofc, and +19 is least likely. Usually, any process inherits the *nice* value of its parent process.
Unsurprisingly, you can alter the priority by using the *"renice"* command.
DIFFERENCE !!
nice is relative. Its adds/subtracts the priority value given what you pass to it. A process with a priority of 15, when asked 'nicely' to be -10 will have a priority of 5 now. OR when asked to be +5, it will now be 20. 'nice' can use the process via its location as well.
renice is absolute. Requires a fixed value b/w -20 and +19. BUT it sets the process to that level, cuz you've altered the deal and it prays you don't alter it any further. It also requires the PID.
Examples :
$ nice -n 10 /bin/some_slow_process [lowers it]
or
$ nice -n -9 /bin/some_slow_process [improves it]
and
$ renice 20 6996 [6996 is the PID of some_slow_process, and 20 is setting it]
NOTE: 'top' can also be used to alter these values.

Killing Processes

'kill' command is your friend. Just pass the PID and pass the required kill signal. There are 64 of them.