Stedi maintains this guide based on public documentation from X12 HIPAA. Contact X12 HIPAA for official EDI specifications. To report any errors in this guide, please **contact us**.

Go to Stedi Network

X12 HIPAA

X12 277 Claim Acknowledgement (X214)

X12 Release 5010 Revised May 3, 2024

This X12 Transaction Set contains the format and establishes the data contents of the Health Care Information Status Notification Transaction Set (277) for use within the context of an Electronic Data Interchange (EDI) environment. This transaction set can be used by a health care payer or authorized agent to notify a provider, recipient, or authorized agent regarding the status of a health care claim or encounter or to request additional information from the provider regarding a health care claim or encounter, health care services review, or transactions related to the provisions of health care. This transaction set is not intended to replace the Health Care Claim Payment/Advice Transaction Set (835) and therefore, will not be used for account payment posting. The notification may be at a summary or service line detail level. The notification may be solicited or unsolicited.

Delimiters ~ Segment * Element > Component ^ Repetition

View the latest version of this implementation guide as an interactive webpage
https://www.stedi.com/app/guides/view/hipaa/claim-acknowledgement-x214/01HACJ4MNFWR3GV3BCVAMG04PK

POWERED BY stedi

Build EDI implementation guides at **stedi.com**

Overview

ISA	-	Interchange Control Header	Max use 1	Required
GS	-	Functional Group Header	Max use 1	Required

Heading

ST	0100	Transaction Set Header	Max use 1	Required
BHT	0200	Beginning of Hierarchical Transaction	Max use 1	Required

Detail

Information Source Level Loop

HL	0100	Hierarchical Level	Max use 1	Required

Information Source Name Loop

NM1	0500	Information Source Name	Max use 1	Required

Transmission Receipt Control Identifier Loop

TRN	0900	Transmission Receipt Control Identifier	Max use 1	Required
DTP	1200	Information Source Receipt Date	Max use 1	Required
DTP	1200	Information Source Process Date	Max use 1	Required

Information Receiver Level Loop

HL	0100	Hierarchical Level	Max use 1	Required

Information Receiver Name Loop

NM1	0500	Information Receiver Name	Max use 1	Required

Information Receiver Application Trace Identifier Loop

TRN	0900	Information Receiver Application Trace Identifier	Max use 1	Required
STC	1000	Information Receiver Status Information	Max use 1	Required
QTY	1210	Total Accepted Quantity	Max use 1	Optional
QTY	1210	Total Rejected Quantity	Max use 1	Optional
AMT	1220	Total Accepted Amount	Max use 1	Optional
AMT	1220	Total Rejected Amount	Max use 1	Optional

Billing Provider of Service Level Loop

HL	0100	Hierarchical Level	Max use 1	Required

Billing Provider Name Loop

NM1	0500	Billing Provider Name	Max use 1	Required

Provider of Service Information Trace Identifier Loop

TRN	0900	Provider of Service Information Trace Identifier	Max use 1	Required
STC	1000	Billing Provider Status Information	Max use 1	Optional
REF	1100	Provider Secondary Identifier	Max use 3	Optional
QTY	1210	Total Accepted Quantity	Max use 1	Optional
QTY	1210	Total Rejected Quantity	Max use 1	Optional
AMT	1220	Total Accepted Amount	Max use 1	Optional
AMT	1220	Total Rejected Amount	Max use 1	Optional

Patient Level Loop

HL	0100	Hierarchical Level	Max use 1	Required

Patient Name Loop

NM1	0500	Patient Name	Max use 1	Required

Claim Status Tracking Number Loop

TRN	0900	Claim Status Tracking Number	Max use 1	Required
STC	1000	Claim Level Status Information	Max use 1	Required
REF	1100	Payer Claim Control Number	Max use 1	Optional
REF	1100	Claim Identifier For Transmission Intermediaries	Max use 1	Optional
REF	1100	Institutional Bill Type Identification	Max use 1	Optional
DTP	1200	Claim Level Service Date	Max use 1	Required

Service Line Information Loop

SVC	1800	Service Line Information	Max use 1	Required
STC	1900	Service Line Level Status Information	Max use 1	Required
REF	2000	Service Line Item Identification	Max use 1	Required
REF	2000	Pharmacy Prescription Number	Max use 1	Optional

DTP	2100	Service Line Date	Max use 1	Optional
SE	2700	Transaction Set Trailer	Max use 1	Required
GE	-	Functional Group Trailer	Max use 1	Required
IEA	-	Interchange Control Trailer	Max use 1	Required

ISA

Max use 1 Required

Interchange Control Header

To start and identify an interchange of zero or more functional groups and interchange-related control segments

Example

```
ISA*00*          *00*          *XX*XXXXXXXXXXXXXX
X*XX*XXXXXXXXXXXXXXX*240720*1317*^*00501*00000000
0*X*X*>~
```

ISA-01 I01 Authorization Information Qualifier

Identifier (ID) Required

Code identifying the type of information in the Authorization Information

00 No Authorization Information Present (No Meaningful Information in I02)

ISA-02 I02 Authorization Information

Min 10 Max 10 String (AN) Required

Information used for additional identification or authorization of the interchange sender or the data in the interchange; the type of information is set by the Authorization Information Qualifier (I01)

ISA-03 I03 Security Information Qualifier

Identifier (ID) Required

Code identifying the type of information in the Security Information

00 No Security Information Present (No Meaningful Information in I04)

ISA-04 I04 Security Information

Min 10 Max 10 String (AN) Required

This is used for identifying the security information about the interchange sender or the data in the interchange; the type of information is set by the Security Information Qualifier (I03)

ISA-05 I05 Interchange ID Qualifier

Min 2 Max 2 Identifier (ID) Required

Code indicating the system/method of code structure used to designate the sender or receiver ID element being qualified

› Codes

ISA-06 I06 Interchange Sender ID

Min 15 Max 15 String (AN) Required

Identification code published by the sender for other parties to use as the receiver ID to route data to them; the sender always codes this value in the sender ID element

ISA-07 **I05 Interchange ID Qualifier** Min 2 Max 2 Identifier (ID) Required

Code indicating the system/method of code structure used to designate the sender or receiver ID element being qualified

› Codes

ISA-08 **I07 Interchange Receiver ID** Min 15 Max 15 String (AN) Required

Identification code published by the receiver of the data; When sending, it is used by the sender as their sending ID, thus other parties sending to them will use this as a receiving ID to route data to them

ISA-09 **I08 Interchange Date** YYMMDD format Date (DT) Required

Date of the interchange

ISA-10 **I09 Interchange Time** HHMM format Time (TM) Required

Time of the interchange

ISA-11 **I65 Repetition Separator** Min 1 Max 1 String (AN) Required

Type is not applicable; the repetition separator is a delimiter and not a data element; this field provides the delimiter used to separate repeated occurrences of a simple data element or a composite data structure; this value must be different than the data element separator, component element separator, and the segment terminator

^ Repetition Separator

ISA-12 **I11 Interchange Control Version Number** Identifier (ID) Required

Code specifying the version number of the interchange control segments

00501 Standards Approved for Publication by ASC X12 Procedures Review Board through October 2003

ISA-13 **I12 Interchange Control Number** Min 9 Max 9 # Numeric (N0) Required

A control number assigned by the interchange sender

ISA-14 **I13 Acknowledgment Requested** Min 1 Max 1 Identifier (ID) Required

Code indicating sender's request for an interchange acknowledgment

0 No Interchange Acknowledgment Requested
1 Interchange Acknowledgment Requested (TA1)

ISA-15

I14 Interchange Usage Indicator

Min 1 Max 1 **Identifier (ID)** Required

Code indicating whether data enclosed by this interchange envelope is test, production or information

I Information
P Production Data
T Test Data

ISA-16

I15 Component Element Separator

Min 1 Max 1 **String (AN)** Required

Type is not applicable; the component element separator is a delimiter and not a data element; this field provides the delimiter used to separate component data elements within a composite data structure; this value must be different than the data element separator and the segment terminator

> Component Element Separator

GS

Max use 1 Required

Functional Group Header

To indicate the beginning of a functional group and to provide control information

Example

```
GS*HN*XXXXX*XXXXXXX*20240720*1312*0*X*005010X214~
```

GS-01 **479 Functional Identifier Code** Identifier (ID) Required

Code identifying a group of application related transaction sets

HN Health Care Information Status Notification (277)

GS-02 **142 Application Sender's Code** Min 2 Max 15 String (AN) Required

Code identifying party sending transmission; codes agreed to by trading partners

GS-03 **124 Application Receiver's Code** Min 2 Max 15 String (AN) Required

Code identifying party receiving transmission; codes agreed to by trading partners

GS-04 **373 Date** CCYYMMDD format Date (DT) Required

Date expressed as CCYYMMDD where CC represents the first two digits of the calendar year

GS-05 **337 Time** HHMM, HHMMSS, HHMMSSD, or HHMMSSDD format Time (TM) Required

Time expressed in 24-hour clock time as follows: HHMM, or HHMMSS, or HHMMSSD, or HHMMSSDD, where H = hours (00-23), M = minutes (00-59), S = integer seconds (00-59) and DD = decimal seconds; decimal seconds are expressed as follows: D = tenths (0-9) and DD = hundredths (00-99)

GS-06 **28 Group Control Number** Min 1 Max 9 # Numeric (N0) Required

Assigned number originated and maintained by the sender

GS-07 **455 Responsible Agency Code** Min 1 Max 2 Identifier (ID) Required

Code identifying the issuer of the standard; this code is used in conjunction with Data Element 480

T Transportation Data Coordinating Committee (TDCC)

GS-08

480 Version / Release / Industry Identifier Code

String (AN) Required

Code indicating the version, release, subrelease, and industry identifier of the EDI standard being used, including the GS and GE segments; if code in DE455 in GS segment is X, then in DE 480 positions 1-3 are the version number; positions 4-6 are the release and subrelease, level of the version; and positions 7-12 are the industry or trade association identifiers (optionally assigned by user); if code in DE455 in GS segment is T, then other formats are allowed

005010X214

Heading

ST 0100 Heading > ST

Max use 1 Required

Transaction Set Header

To indicate the start of a transaction set and to assign a control number

Example

ST*277*0001*005010X214~

ST-01 **143 Transaction Set Identifier Code**

Identifier (ID) Required

Code uniquely identifying a Transaction Set

- The transaction set identifier (ST01) is used by the translation routines of the interchange partners to select the appropriate transaction set definition (e.g., 810 selects the Invoice Transaction Set).

277 Health Care Information Status Notification

ST-02 **329 Transaction Set Control Number**

Min 4 Max 9 # Numeric (N) Required

Identifying control number that must be unique within the transaction set functional group assigned by the originator for a transaction set

Usage notes

- The Transaction Set Control Numbers in ST02 and SE02 must be identical. This unique number also aids in error resolution research. Submitter could begin sending transactions using the number 0001 in this element and increment from there. The number must be unique within a specific functional group (GS to GE) and interchange (ISA to IEA), but can be repeated in other groups and interchanges.

ST-03 **1705 Version, Release, or Industry Identifier**

String (AN) Required

Reference assigned to identify Implementation Convention

- The implementation convention reference (ST03) is used by the translation routines of the interchange partners to select the appropriate implementation convention to match the transaction set definition. When used, this implementation convention reference takes precedence over the implementation reference specified in the GS08.

Usage notes

- This field contains the same value as data element GS08. The value is 005010X214. Some translator products strip off the ISA and GS segments prior to application (ST - SE) processing. Providing the information from GS08 at this level will help ensure the appropriate application mapping is utilized at translation time.

005010X214

BHT 0200 Heading > BHT

Max use 1 Required

Beginning of Hierarchical Transaction

To define the business hierarchical structure of the transaction set and identify the business application purpose and reference data, i.e., number, date, and time

Example

```
BHT*0085*08*XXX*20240720*1755*TH~
```

BHT-01 1005 Hierarchical Structure Code

Identifier (ID) Required

Code indicating the hierarchical application structure of a transaction set that utilizes the HL segment to define the structure of the transaction set

0085 Information Source, Information Receiver, Provider of Service, Patient

BHT-02 353 Transaction Set Purpose Code

Identifier (ID) Required

Code identifying purpose of transaction set

08 Status

BHT-03 127 Reference Identification

Min 1 Max 50 String (AN) Required

Reference information as defined for a particular Transaction Set or as specified by the Reference Identification Qualifier

- BHT03 is the number assigned by the originator to identify the transaction within the originator's business application system.

Usage notes

- The inventory file number of the transmission assigned by the Information Source's system. This number operates as a transaction (batch) control number.

BHT-04 373 Transaction Set Creation Date

CCYYMMDD format Date (DT) Required

Date expressed as CCYYMMDD where CC represents the first two digits of the calendar year

- BHT04 is the date the transaction was created within the business application system.

BHT-05 337 Transaction Set Creation Time

Time (TM) Required

HHMM, HHMMSS, HHMMSSD, or HHMMSSDD format

Time expressed in 24-hour clock time as follows: HHMM, or HHMMSS, or HHMMSSD, or HHMMSSDD, where H = hours (00-23), M = minutes (00-59), S = integer seconds (00-59) and DD = decimal seconds; decimal seconds are expressed as follows: D = tenths (0-9) and DD = hundredths (00-99)

- BHT05 is the time the transaction was created within the business application system.

BHT-06 **640 Transaction Type Code** Identifier (ID) Required

Code specifying the type of transaction

TH Receipt Acknowledgment Advice

Heading end

Detail

2000A Information Source Level Loop

Max 1 Required

HL 0100 Detail > Information Source Level Loop > HL

Max use 1 Required

Hierarchical Level

To identify dependencies among and the content of hierarchically related groups of data segments

Example

```
HL*1**20*1~
```

HL-01 **628 Hierarchical ID Number** Min 1 Max 12 String (AN) Required

A unique number assigned by the sender to identify a particular data segment in a hierarchical structure

- HL01 shall contain a unique alphanumeric number for each occurrence of the HL segment in the transaction set. For example, HL01 could be used to indicate the number of occurrences of the HL segment, in which case the value of HL01 would be "1" for the initial HL segment and would be incremented by one in each subsequent HL segment within the transaction.

HL-03 **735 Hierarchical Level Code** Identifier (ID) Required

Code defining the characteristic of a level in a hierarchical structure

- HL03 indicates the context of the series of segments following the current HL segment up to the next occurrence of an HL segment in the transaction. For example, HL03 is used to indicate that subsequent segments in the HL loop form a logical grouping of data referring to shipment, order, or item-level information.

20 Information Source

HL-04 **736 Hierarchical Child Code** Identifier (ID) Optional

Code indicating if there are hierarchical child data segments subordinate to the level being described

- HL04 indicates whether or not there are subordinate (or child) HL segments related to the current HL segment.

1 Additional Subordinate HL Data Segment in This Hierarchical Structure.

2100A Information Source Name Loop

Max 1 Required

NM1 0500 Detail > Information Source Level Loop > Information Source Name Loop > NM1 Max use 1 Required

Information Source Name

To supply the full name of an individual or organizational entity

Example

```
NM1*PR*2*XXXXXX*****FI*XXXXX~
```

NM1-01 98 Entity Identifier Code

Identifier (ID) Required

Code identifying an organizational entity, a physical location, property or an individual

AY Clearinghouse

Health care clearinghouse means a public or private entity that does either of the following:

(1) Processes or facilitates the processing of information received from another entity in a nonstandard format or containing nonstandard data content into standard data elements or a standard transaction.
(2) Receives a standard transaction from another entity and processes or facilitates the processing of information into nonstandard format or nonstandard data content for a receiving entity.

PR Payer

NM1-02 1065 Entity Type Qualifier

Identifier (ID) Required

Code qualifying the type of entity

- NM102 qualifies NM103.

2 Non-Person Entity

NM1-03 1035 Information Source Name

Min 1 Max 60 String (AN) Required

Individual last name or organizational name

NM1-08 66 Identification Code Qualifier

Identifier (ID) Required

Code designating the system/method of code structure used for Identification Code (67)

46 Electronic Transmitter Identification Number (ETIN)

This number is used for entities identified in translation software typically called "Trading Partner Profiles". It is used for non-health plan entities.

FI Federal Taxpayer's Identification Number

PI Payor Identification

XV Centers for Medicare and Medicaid Services PlanID

NM1-09

67 Information Source Identifier

Min 2 Max 80 **String (AN)** Required

Code identifying a party or other code

2100A Information Source Name Loop end

2200A Transmission Receipt Control Identifier Loop

Max 1 Required

TRN 0900 Detail > Information Source Level Loop > Transmission Receipt Control Identifier Loop > TRN Max use 1 Required

Transmission Receipt Control Identifier

To uniquely identify a transaction to an application

Example

TRN*1*XXX~

TRN-01 481 Trace Type Code

Identifier (ID) Required

Code identifying which transaction is being referenced

1 Current Transaction Trace Numbers

TRN-02 127 Information Source Application Trace Identifier

String (AN) Required

Min 1 Max 50

Reference information as defined for a particular Transaction Set or as specified by the Reference Identification Qualifier

- TRN02 provides unique identification for the transaction.

Usage notes

- This is a unique trace number that identifies a specific transaction. This number is assigned by the Information Source.

DTP 1200 Detail > Information Source Level Loop > Transmission Receipt Control Identifier Loop > DTP Max use 1 Required

Information Source Receipt Date

To specify any or all of a date, a time, or a time period

Example

```
DTP*050*D8*X~
```

Variants (all may be used)

DTP Information Source Process Date

DTP-01 374 Date Time Qualifier

Identifier (ID) Required

Code specifying type of date or time, or both date and time

050 Received

DTP-02 1250 Date Time Period Format Qualifier

Identifier (ID) Required

Code indicating the date format, time format, or date and time format

- DTP02 is the date or time or period format that will appear in DTP03.

D8 Date Expressed in Format CCYYMMDD

DTP-03 1251 Information Source Receipt Date

Min 1 Max 35 String (AN) Required

Expression of a date, a time, or range of dates, times or dates and times

Usage notes

- This is the receipt date of the 837 by the entity creating the 277 acknowledgment. This date may or may not be the same date as the Information Source's Process Date.

Information Source Process Date

To specify any or all of a date, a time, or a time period

Usage notes

- Payers and clearinghouses often collect claim transmissions throughout the business day. A process which is usually called "batch" is initiated at least once per business day. Some entities may initiate this process more than one time per day. As claim transmission files are processed, EDI reports and or data files are generated from the entity's computer system(s) and are distributed to the Information Receiver.
- The Information Source Process Date applies to the processing of the 837 claim transaction file through a pre-adjudication/electronic data interchange (EDI) system. This date may or may not be the same date as the Information Source Receipt Date.

Example

```
DTP*009*D8*XXXXX~
```

Variants (all may be used)

DTP Information Source Receipt Date

DTP-01 **374 Date Time Qualifier** — Identifier (ID) — Required

Code specifying type of date or time, or both date and time

009 Process

DTP-02 **1250 Date Time Period Format Qualifier** — Identifier (ID) — Required

Code indicating the date format, time format, or date and time format

- DTP02 is the date or time or period format that will appear in DTP03.

D8 Date Expressed in Format CCYYMMDD

DTP-03 **1251 Information Source Process Date** — Min 1 — Max 35 — String (AN) — Required

Expression of a date, a time, or range of dates, times or dates and times

2000B Information Receiver Level Loop

Max 1 Required

HL 0100 Detail > Information Source Level Loop > Information Receiver Level Loop > HL Max use 1 Required

Hierarchical Level

To identify dependencies among and the content of hierarchically related groups of data segments

Example

```
HL*2*1*21*1~
```

HL-01 **628 Hierarchical ID Number** Min 1 Max 12 String (AN) Required

A unique number assigned by the sender to identify a particular data segment in a hierarchical structure

- HL01 shall contain a unique alphanumeric number for each occurrence of the HL segment in the transaction set. For example, HL01 could be used to indicate the number of occurrences of the HL segment, in which case the value of HL01 would be "1" for the initial HL segment and would be incremented by one in each subsequent HL segment within the transaction.

HL-02 **734 Hierarchical Parent ID Number** Min 1 Max 12 String (AN) Required

Identification number of the next higher hierarchical data segment that the data segment being described is subordinate to

- HL02 identifies the hierarchical ID number of the HL segment to which the current HL segment is subordinate.

HL-03 **735 Hierarchical Level Code** Identifier (ID) Required

Code defining the characteristic of a level in a hierarchical structure

- HL03 indicates the context of the series of segments following the current HL segment up to the next occurrence of an HL segment in the transaction. For example, HL03 is used to indicate that subsequent segments in the HL loop form a logical grouping of data referring to shipment, order, or item-level information.

21 Information Receiver

HL-04 **736 Hierarchical Child Code** Identifier (ID) Optional

Code indicating if there are hierarchical child data segments subordinate to the level being described

- HL04 indicates whether or not there are subordinate (or child) HL segments related to the current HL segment.

0 No Subordinate HL Segment in This Hierarchical Structure.

1 Additional Subordinate HL Data Segment in This Hierarchical Structure.

2100B Information Receiver Name Loop

Max 1 Required

NM1 0500 Detail > Information Source Level Loop > Information Receiver Level Loop > Information Receiver Name Loop > NM1

Max use 1 Required

Information Receiver Name

To supply the full name of an individual or organizational entity

Usage notes

- The Information Receiver identified in the NM1 is always the electronic connection to the Information Source EDI environment. The Information Receiver has a trading partner profile set up at the Information Source's site and is generally the entity that submitted the claim transaction(s) for processing.
- For situations where a person such as a single practitioner submits claim transactions to a payer, the entity identified in the Provider of Service Loop (HL03 = 19) will be the same entity identified here in the Information Receiver Loop (HL03 = 21). The difference may be that the trading partner profile set up in the EDI environment is a separate identification scheme from the identification number set up for the entity in the adjudication system.
- In the situation where there is more than one clearinghouse involved in the transmission of the Health Care Claim Acknowledgement as part of the Trading Partner Agreement, this segment will be used to identify the clearinghouse that is passing the information. This segment will be changed to display the information for the next clearinghouse before they continue passing on the transmission. This process will continue until the transmission reaches the initiator of the claim/encounter.

Example

```
NM1*41*1*XXXXXX*XXXXX*XXXXX***46*XXX~
```

NM1-01 98 Entity Identifier Code

Identifier (ID) Required

Code identifying an organizational entity, a physical location, property or an individual

41 Submitter

NM1-02 1065 Entity Type Qualifier

Identifier (ID) Required

Code qualifying the type of entity

- NM102 qualifies NM103.

1 Person
2 Non-Person Entity

NM1-03 1035 Information Receiver Last or Organization Name

String (AN) Required

Min 1 Max 60

Individual last name or organizational name

NM1-04 **1036 Information Receiver First Name** Min 1 Max 35 String (AN) Optional

Individual first name

NM1-05 **1037 Information Receiver Middle Name** Min 1 Max 25 String (AN) Optional

Individual middle name or initial

NM1-08 **66 Identification Code Qualifier** Identifier (ID) Required

Code designating the system/method of code structure used for Identification Code (67)

46 Electronic Transmitter Identification Number (ETIN)

NM1-09 **67 Information Receiver Primary Identifier** Min 2 Max 80 String (AN) Required

Code identifying a party or other code

2100B Information Receiver Name Loop end

2200B Information Receiver Application Trace Identifier Loop

Max 1 Required

TRN 0900 Detail > Information Source Level Loop > Information Receiver Level Loop > Information Receiver Application Trace Identifier Loop > TRN

Max use 1 Required

Information Receiver Application Trace Identifier

To uniquely identify a transaction to an application

Usage notes

- This segment contains the value submitted in the BHT03 data element from the 837.

Example

```
TRN*2*X~
```

TRN-01 481 Trace Type Code

Identifier (ID) Required

Code identifying which transaction is being referenced

2 Referenced Transaction Trace Numbers

TRN-02 127 Claim Transaction Batch Number

Min 1 Max 50 String (AN) Required

Reference information as defined for a particular Transaction Set or as specified by the Reference Identification Qualifier

- TRN02 provides unique identification for the transaction.

Usage notes

- This element contains the value submitted in the BHT03 data element from the 837.

STC 1000 Detail > Information Source Level Loop > Information Receiver Level Loop > Information Receiver Application Trace Identifier Loop > STC

Max use >1 Required

Information Receiver Status Information

To report the status, required action, and paid information of a claim or service line

Usage notes

- This segment will be used to convey information about an entire unit of work (e.g. single transaction of claims). Information contained at this level will be summary details pertaining to the unit of work being acknowledged. Examples include but are not limited to accepted for processing, trading partner not authorized to submit to the Information Source's system, etc.
- See Section 1.4.2 - Status Information (STC) Segment Usage for specific STC segment information, composites and code use.

Example

```
STC*X>XXXXX>PR*20240720*U*00000******XXXX>XXXXX>X
X*XXX>XXXX>XX~
```

STC-01 **C043 Health Care Claim Status**

Used to convey status of the entire claim or a specific service line

Max use 1 Required

C043-01 **1271 Health Care Claim Status Category Code**

String (AN) Required Min 1 Max 30

Code indicating a code from a specific industry code list

- C043-01 is used to specify the logical groupings of Health Care Claim Status Codes (See Code Source 507).

Usage notes

- For this business application acknowledgment, use of the Claim Status Category Code is limited to category types `A' for batch. For real time acknowledgements category types A'` and `E' may be used except for E0. Use of the category type E'` is limited to indicating the business application system is unavailable.
- CODE SOURCE 507: Health Care Claim Status Category Code

C043-02 **1271 Health Care Claim Status Code**

Min 1 Max 30 String (AN) Required

Code indicating a code from a specific industry code list

- C043-02 is used to identify the status of an entire claim or a serviceline. Code Source 508 is referenced unless qualified by C043-04.

Usage notes

- This code provides further detail of the status. See Section 1.4.2 Status Information (STC Segment Usage).
- CODE SOURCE 508: Health Care Claim Status Code

C043-03 **98 Entity Identifier Code**

Identifier (ID) Optional

Code identifying an organizational entity, a physical location, property or an individual

- C043-03 identifies the entity associated with the Health Care Claim Status Code.

36 Employer
40 Receiver
41 Submitter
AY Clearinghouse
PR Payer

STC-02 **373 Status Information Effective Date** CCYYMMDD format **Date (DT)** Required

Date expressed as CCYYMMDD where CC represents the first two digits of the calendar year

- STC02 is the effective date of the status information.

STC-03 **306 Action Code** **Identifier (ID)** Required

Code indicating type of action

Usage notes

- STC03 at this level is intended to convey the electronic transmission status of the ST - SE envelope. The terms "Accept" and "Reject" refer to the electronic transmission status of the 837 transaction not the billing status.

U Reject
Required when the entire claim transaction (ST-SE) is rejected due to submitter level errors. No subordinate HL information is reported.

WQ Accept
Required when code value "U" is not used. At least one subordinate HL loop must be reported.

STC-04 **782 Total Submitted Charges for Unit Work** **# Decimal number (R)** Required
Min 1 Max 15

Monetary amount

- STC04 is the amount of original submitted charges.

Usage notes

- This will be the sum of all CLM02 values (claim charge) for the claims being acknowledged. In most instances, this will be the sum of charges submitted from ST to SE of a single 837 transaction set.

In situations where the 837 transaction from the Information Receiver is separated (e.g. due to clearinghouse involvement), this amount will be the sum of the CLM02 values for the claims being acknowledged.

STC-10 **C043 Health Care Claim Status** Max use 1 Optional
Used to convey status of the entire claim or a specific service line

Usage notes

Required if additional clarification to STC01 is needed. If not required by this implementation guide, do not send.

C043-01 **1271 Health Care Claim Status Category Code**

String (AN) Required

Min 1 Max 30

Code indicating a code from a specific industry code list

- C043-01 is used to specify the logical groupings of Health Care Claim Status Codes (See Code Source 507).

Usage notes

- See STC01-1 for valid values.
- CODE SOURCE 507: Health Care Claim Status Category Code

C043-02 **1271 Health Care Claim Status Code**

Min 1 Max 30 String (AN) Required

Code indicating a code from a specific industry code list

- C043-02 is used to identify the status of an entire claim or a serviceline. Code Source 508 is referenced unless qualified by C043-04.

Usage notes

- This code provides further detail of the status. See Section 1.4.2 Status Information (STC Segment Usage).
- CODE SOURCE 508: Health Care Claim Status Code

C043-03 **98 Entity Identifier Code**

Min 2 Max 3 Identifier (ID) Optional

Code identifying an organizational entity, a physical location, property or an individual

- C043-03 identifies the entity associated with the Health Care Claim Status Code.

Usage notes

- See STC01-3 for valid values.

STC-11 **C043 Health Care Claim Status**

Used to convey status of the entire claim or a specific service line

Max use 1 Optional

Usage notes

Required if additional clarification to STC01 and STC10 is needed. If not required by this implementation guide, do not send.

C043-01 **1271 Health Care Claim Status Category Code**

String (AN) Required

Min 1 Max 30

Code indicating a code from a specific industry code list

- C043-01 is used to specify the logical groupings of Health Care Claim Status Codes (See Code Source 507).

Usage notes

- See STC01-1 for valid values.
- CODE SOURCE 507: Health Care Claim Status Category Code

C043-02 **1271 Health Care Claim Status Code** Min 1 Max 30 String (AN) Required

Code indicating a code from a specific industry code list

- C043-02 is used to identify the status of an entire claim or a serviceline. Code Source 508 is referenced unless qualified by C043-04.

Usage notes

- This code provides further detail of the status. See Section 1.4.2 Status Information (STC Segment Usage).
- CODE SOURCE 508: Health Care Claim Status Code

C043-03 **98 Entity Identifier Code** Min 2 Max 3 Identifier (ID) Optional

Code identifying an organizational entity, a physical location, property or an individual

- C043-03 identifies the entity associated with the Health Care Claim Status Code.

Usage notes

- See STC01-3 for valid values.

QTY 1210 Detail > Information Source Level Loop > Information Receiver Level Loop > Information Receiver Application Trace Identifier Loop > QTY

Max use 1 Optional

Total Accepted Quantity

To specify quantity information

Usage notes

- The purpose of this segment is to report the total number of claims accepted by the Information Source.
- Required when at least one claim is accepted for this Information Receiver. If not required by this implementation guide, do not send.

Example

```
QTY*90*00000000~
```

Variants (all may be used)

QTY Total Rejected Quantity

QTY-01 **673 Quantity Qualifier** Identifier (ID) Required

Code specifying the type of quantity

90 Acknowledged Quantity

QTY-02 **380 Total Accepted Quantity** Min 1 Max 15 # Decimal number (R) Required

Numeric value of quantity

QTY 1210 Detail > Information Source Level Loop > Information Receiver Level Loop > Information Receiver Application Trace Identifier Loop > QTY

Max use 1 Optional

Total Rejected Quantity

To specify quantity information

Usage notes

- The purpose of this segment is to report the total number of claims rejected for this Information Receiver (e.g. not accepted) by the Information Source.
- Required when at least one claim is rejected for this Information Receiver. If not required by this implementation guide, do not send.

Example

```
QTY*AA*0000000000~
```

Variants (all may be used)

QTY Total Accepted Quantity

QTY-01 673 **Quantity Qualifier** Identifier (ID) Required

Code specifying the type of quantity

AA Unacknowledged Quantity

QTY-02 380 **Total Rejected Quantity** Min 1 Max 15 # Decimal number (R) Required

Numeric value of quantity

Total Accepted Amount

To indicate the total monetary amount

Usage notes

- The purpose of this segment is to report the total dollar amount of claims accepted by the Information Source.
- Required when at least one claim is accepted for this Information Receiver. If not required by this implementation guide, do not send.

Example

```
AMT*YU*000000000000000~
```

Variants (all may be used)

AMT Total Rejected Amount

AMT-01 **522 Amount Qualifier Code** Identifier (ID) Required

Code to qualify amount

YU In Process

AMT-02 **782 Total Accepted Amount** Min 1 Max 15 # Decimal number (R) Required

Monetary amount

Max use 1 Optional

Total Rejected Amount

To indicate the total monetary amount

Usage notes

- The purpose of this segment is to report the total dollar amount of claims rejected for this Information Receiver (e.g. not accepted) by the Information Source.
- Required when at least one claim is rejected for this Information Receiver. If not required by this implementation guide, do not send.

Example

```
AMT*YY*000000000000000~
```

Variants (all may be used)

AMT Total Accepted Amount

AMT-01 **522 Amount Qualifier Code** Identifier (ID) Required

Code to qualify amount

YY Returned

AMT-02 **782 Total Rejected Amount** Min 1 Max 15 # Decimal number (R) Required

Monetary amount

2200B Information Receiver Application Trace Identifier Loop end

2000C Billing Provider of Service Level Loop

Max >1 Optional

HL 0100 Detail > Information Source Level Loop > Information Receiver Level Loop > Billing Provider of Service Level Loop > HL

Max use 1 Required

Hierarchical Level

To identify dependencies among and the content of hierarchically related groups of data segments

Example

HL*3*2*19*1~

HL-01 **628 Hierarchical ID Number** Min 1 Max 12 String (AN) Required

A unique number assigned by the sender to identify a particular data segment in a hierarchical structure

- HL01 shall contain a unique alphanumeric number for each occurrence of the HL segment in the transaction set. For example, HL01 could be used to indicate the number of occurrences of the HL segment, in which case the value of HL01 would be "1" for the initial HL segment and would be incremented by one in each subsequent HL segment within the transaction.

HL-02 **734 Hierarchical Parent ID Number** Min 1 Max 12 String (AN) Required

Identification number of the next higher hierarchical data segment that the data segment being described is subordinate to

- HL02 identifies the hierarchical ID number of the HL segment to which the current HL segment is subordinate.

HL-03 **735 Hierarchical Level Code** Identifier (ID) Required

Code defining the characteristic of a level in a hierarchical structure

- HL03 indicates the context of the series of segments following the current HL segment up to the next occurrence of an HL segment in the transaction. For example, HL03 is used to indicate that subsequent segments in the HL loop form a logical grouping of data referring to shipment, order, or item-level information.

19 Provider of Service

HL-04 **736 Hierarchical Child Code** Identifier (ID) Optional

Code indicating if there are hierarchical child data segments subordinate to the level being described

- HL04 indicates whether or not there are subordinate (or child) HL segments related to the current HL segment.

0 No Subordinate HL Segment in This Hierarchical Structure.

1 Additional Subordinate HL Data Segment in This Hierarchical Structure.

2100C Billing Provider Name Loop

Max 1 Required

NM1 0500 Detail > Information Source Level Loop > Information Receiver Level Loop > Billing Provider of Service Level Loop > Billing Provider Name Loop > NM1

Max use 1 Required

Billing Provider Name

To supply the full name of an individual or organizational entity

Usage notes

- This segment contains information which can be found in the 837 Dental, Institutional, and Professional implementation guides at the 2010AA loop.

Example

```
NM1*85*1*XXXX*XXXX*XXXXX**XXXXX*FI*XX~
```

NM1-01 98 Entity Identifier Code

Identifier (ID) Required

Code identifying an organizational entity, a physical location, property or an individual

85 Billing Provider

NM1-02 1065 Entity Type Qualifier

Identifier (ID) Required

Code qualifying the type of entity

- NM102 qualifies NM103.

1 Person
2 Non-Person Entity

NM1-03 1035 Provider Last or Organization Name

Min 1 Max 60 String (AN) Required

Individual last name or organizational name

NM1-04 1036 Provider First Name

Min 1 Max 35 String (AN) Optional

Individual first name

NM1-05 1037 Provider Middle Name

Min 1 Max 25 String (AN) Optional

Individual middle name or initial

NM1-07 1039 Provider Name Suffix

Min 1 Max 10 String (AN) Optional

Suffix to individual name

NM1-08 **66 Identification Code Qualifier** Identifier (ID) Required

Code designating the system/method of code structure used for Identification Code (67)

FI Federal Taxpayer's Identification Number
XX Centers for Medicare and Medicaid Services National Provider Identifier

The "XX" qualifier is required only when the National Provider ID is mandated for use.

After the National Provider ID implementation period, enumerated providers use only the NM108 and NM109 data elements and discontinue the generation of the REF segment in Loop ID 2200C.

NM1-09 **67 Billing Provider Identifier** Min 2 Max 80 String (AN) Required

Code identifying a party or other code

2100C Billing Provider Name Loop end

2200C Provider of Service Information Trace Identifier Loop

Max 1 Optional

TRN 0900 Detail > Information Source Level Loop > Information Receiver Level Loop > Billing Provider of Service Level Loop > Provider of Service Information Trace Identifier Loop > TRN

Max use 1 Required

Provider of Service Information Trace Identifier

To uniquely identify a transaction to an application

Usage notes

- Required when 2200C Loop is used to provide the status of a specific provider's group of claims in the STC segment or a secondary provider identifier needs to be reported in the Provider Secondary REF segment. If not required by this implementation guide, may be provided at the sender's discretion but cannot be required by the receiver.
- Because the TRN segment is syntactically required in order to use Loop 2200C, TRN02 can either be a sender assigned value or a default value of zero (0).

Example

```
TRN*1*XX~
```

TRN-01 **481 Trace Type Code**

Identifier (ID) Required

Code identifying which transaction is being referenced

1 Current Transaction Trace Numbers

TRN-02 **127 Provider of Service Information Trace Identifier**

String (AN) Required

Min 1 Max 50

Reference information as defined for a particular Transaction Set or as specified by the Reference Identification Qualifier

- TRN02 provides unique identification for the transaction.

STC 1000 Detail > Information Source Level Loop > Information Receiver Level Loop > Billing Provider of Service Level Loop > Provider of Service Information Trace Identifier Loop > STC

Max use >1 Optional

Billing Provider Status Information

To report the status, required action, and paid information of a claim or service line

Usage notes

- Required when needed to provide the status of a specific Billing Provider's group of claims. If not required by this implementation guide, may be provided at the sender's discretion, but cannot be required by the receiver.
- See Section 1.4.2 - Status Information (STC) Segment Usage for specific STC segment information, composites and code use.

Example

```
STC*X>XX>77**WQ*00000000000******XX>X>XXX*X>X>XX~
```

STC-01 **C043 Health Care Claim Status**

Used to convey status of the entire claim or a specific service line

Max use 1 Required

C043-01 **1271 Health Care Claim Status Category Code**

String (AN) Required

Min 1 Max 30

Code indicating a code from a specific industry code list

- C043-01 is used to specify the logical groupings of Health Care Claim Status Codes (See Code Source 507).

Usage notes

- For this business application acknowledgment, use of the Claim Status Category Code is limited to category types `A' for batch. For real time acknowledgements category types A'` and `E' may be used except for E0. Use of the category type E'` is limited to indicating the business application system is unavailable.
- CODE SOURCE 507: Health Care Claim Status Category Code

C043-02 **1271 Health Care Claim Status Code**

Min 1 Max 30 String (AN) Required

Code indicating a code from a specific industry code list

- C043-02 is used to identify the status of an entire claim or a serviceline. Code Source 508 is referenced unless qualified by C043-04.

Usage notes

- This code provides further detail of the status. See Section 1.4.2 Status Information (STC Segment Usage).
- CODE SOURCE 508: Health Care Claim Status Code

C043-03 **98 Entity Identifier Code**

Identifier (ID) Optional

Code identifying an organizational entity, a physical location, property or an individual

- C043-03 identifies the entity associated with the Health Care Claim Status Code.

36 Employer
40 Receiver
41 Submitter
77 Service Location
82 Rendering Provider
85 Billing Provider
87 Pay-to Provider
AY Clearinghouse
PR Payer

STC-03 **306 Action Code**

Identifier (ID) Required

Code indicating type of action

Usage notes

- STC03 at this level is intended to convey the electronic claim status of the Billing Provider Claims. The terms "Accept" and "Reject" refer to the status of claims for the Billing Provider not the billing status.

U Reject

Use this code to indicate the provider's group of claims has been rejected. If any portion of the provider's group of claims is accepted then the code "WQ" - Accept must be used.

WQ Accept

STC-04 **782 Total Submitted Charges for Unit Work**

Decimal number (R) Required

Min 1 Max 15

Monetary amount

- STC04 is the amount of original submitted charges.

Usage notes

- Sum of the Billing Provider claims within the 837 transaction being acknowledged.
- In situations where the 837 transaction from the Information Receiver is separated (e.g. due to clearinghouse involvement), this amount will be the sum of the CLM02 values for the claims being acknowledged.

STC-10 **C043 Health Care Claim Status**

Used to convey status of the entire claim or a specific service line

Max use 1 Optional

Usage notes

Required if additional clarification to STC01 is needed. If not required by this implementation guide, do not send.

C043-01 **1271 Health Care Claim Status Category Code**

String (AN) Required

Min 1 Max 30

Code indicating a code from a specific industry code list

- C043-01 is used to specify the logical groupings of Health Care Claim Status Codes (See Code Source 507).

Usage notes

- See STC01-1 for valid values.
- CODE SOURCE 507: Health Care Claim Status Category Code

C043-02 **1271 Health Care Claim Status Code** Min 1 Max 30 String (AN) Required

Code indicating a code from a specific industry code list

- C043-02 is used to identify the status of an entire claim or a serviceline. Code Source 508 is referenced unless qualified by C043-04.

Usage notes

- This code provides further detail of the status. See Section 1.4.2 Status Information (STC Segment Usage).
- CODE SOURCE 508: Health Care Claim Status Code

C043-03 **98 Entity Identifier Code** Min 2 Max 3 Identifier (ID) Optional

Code identifying an organizational entity, a physical location, property or an individual

- C043-03 identifies the entity associated with the Health Care Claim Status Code.

Usage notes

- See STC01-3 for valid values.

STC-11 **C043 Health Care Claim Status** Max use 1 Optional

Used to convey status of the entire claim or a specific service line

Usage notes

Required if additional clarification to STC01 and STC10 is needed. If not required by this implementation guide, do not send.

C043-01 **1271 Health Care Claim Status Category Code** String (AN) Required Min 1 Max 30

Code indicating a code from a specific industry code list

- C043-01 is used to specify the logical groupings of Health Care Claim Status Codes (See Code Source 507).

Usage notes

- See STC01-1 for valid values.
- CODE SOURCE 507: Health Care Claim Status Category Code

C043-02 **1271 Health Care Claim Status Code** Min 1 Max 30 String (AN) Required

Code indicating a code from a specific industry code list

- C043-02 is used to identify the status of an entire claim or a serviceline. Code Source 508 is referenced unless qualified by C043-04.

Usage notes

- This code provides further detail of the status. See Section 1.4.2 Status Information (STC Segment Usage).
- CODE SOURCE 508: Health Care Claim Status Code

C043-03 **98 Entity Identifier Code** Min 2 Max 3 **Identifier (ID)** Optional

Code identifying an organizational entity, a physical location, property or an individual

- C043-03 identifies the entity associated with the Health Care Claim Status Code.

Usage notes

- See STC01-3 for valid values.

Max use 3 Optional

Provider Secondary Identifier

To specify identifying information

Usage notes

- Required when an additional identification number to that provided in NM109 of this loop is necessary for the claim processor to identify the entity. If not required by this implementation guide, do not send.

Example

REF*0B*XXX~

REF-01 **128 Reference Identification Qualifier** Identifier (ID) Required

Code qualifying the Reference Identification

0B State License Number
1G Provider UPIN Number
G2 Provider Commercial Number
LU Location Number
SY Social Security Number
TJ Federal Taxpayer's Identification Number

REF-02 **127 Billing Provider Additional Identifier** Min 1 Max 50 String (AN) Required

Reference information as defined for a particular Transaction Set or as specified by the Reference Identification Qualifier

Total Accepted Quantity

To specify quantity information

Usage notes

- Required when reporting status for a specific provider's group of claims and at least one claim is accepted. If not required by this implementation guide, do not send.
- The purpose of this segment is to report the total number of claims (sum of CLM02) accepted to the adjudication process by the Information Source for the Billing Provider in this acknowledgment.

Example

```
QTY*QA*00000000000~
```

Variants (all may be used)

QTY Total Rejected Quantity

QTY-01 **673 Quantity Qualifier** Identifier (ID) Required

Code specifying the type of quantity

QA Quantity Approved

QTY-02 **380 Total Accepted Quantity** Min 1 Max 15 # Decimal number (R) Required

Numeric value of quantity

QTY 1210 Detail > Information Source Level Loop > Information Receiver Level Loop > Billing Provider of Service Level Loop > Provider of Service Information Trace Identifier Loop > QTY

Max use 1 Optional

Total Rejected Quantity

To specify quantity information

Usage notes

- Required when reporting status for a specific provider's group of claims and at least one claim is rejected. If not required by this implementation guide, do not send.
- The purpose of this segment is to report the total number of claims rejected by the Information Source for the Billing Provider.

Example

```
QTY*QC*00000000~
```

Variants (all may be used)

QTY Total Accepted Quantity

QTY-01 673 **Quantity Qualifier** Identifier (ID) Required

Code specifying the type of quantity

QC Quantity Disapproved

QTY-02 380 **Total Rejected Quantity** Min 1 Max 15 # Decimal number (R) Required

Numeric value of quantity

AMT 1220 Detail > Information Source Level Loop > Information Receiver Level Loop > Billing Provider of Service Level Loop > Provider of Service Information Trace Identifier Loop > AMT

Max use 1 Optional

Total Accepted Amount

To indicate the total monetary amount

Usage notes

- Required when reporting status for a specific provider's group of claims and at least one claim is accepted. If not required by this implementation guide, do not send.
- The purpose of this segment is to report the total dollar amount of claims (sum of CLM02) accepted by the Information Source for the Billing Provider in this acknowledgment.

Example

```
AMT*YU*0000000~
```

Variants (all may be used)

AMT Total Rejected Amount

AMT-01 **522 Amount Qualifier Code** — Identifier (ID) — Required

Code to qualify amount

YU In Process

AMT-02 **782 Total Accepted Amount** — Min 1 — Max 15 — # Decimal number (R) — Required

Monetary amount

AMT 1220 Detail > Information Source Level Loop > Information Receiver Level Loop > Billing Provider of Service Level Loop > Provider of Service Information Trace Identifier Loop > AMT Max use 1 Optional

Total Rejected Amount

To indicate the total monetary amount

Usage notes

- Required when reporting status for a specific provider's group of claims and at least one claim is rejected. If not required by this implementation guide, do not send.
- The purpose of this segment is to report the total dollar amount of claims (sum of CLM02) rejected by the Information Source for the Billing Provider in this acknowledgment.

Example

```
AMT*YY*00000000~
```

Variants (all may be used)

AMT Total Accepted Amount

AMT-01 **522 Amount Qualifier Code** Identifier (ID) Required

Code to qualify amount

YY Returned

AMT-02 **782 Total Rejected Amount** Min 1 Max 15 # Decimal number (R) Required

Monetary amount

2200C Provider of Service Information Trace Identifier Loop end

2000D Patient Level Loop

Max >1 Optional

HL 0100 Detail > Information Source Level Loop > Information Receiver Level Loop > Billing Provider of Service Level Loop > Patient Level Loop > HL

Max use 1 Required

Hierarchical Level

To identify dependencies among and the content of hierarchically related groups of data segments

Example

```
HL*4*3*PT*0~
```

HL-01 **628 Hierarchical ID Number** Min 1 Max 12 String (AN) Required

A unique number assigned by the sender to identify a particular data segment in a hierarchical structure

- HL01 shall contain a unique alphanumeric number for each occurrence of the HL segment in the transaction set. For example, HL01 could be used to indicate the number of occurrences of the HL segment, in which case the value of HL01 would be "1" for the initial HL segment and would be incremented by one in each subsequent HL segment within the transaction.

HL-02 **734 Hierarchical Parent ID Number** Min 1 Max 12 String (AN) Required

Identification number of the next higher hierarchical data segment that the data segment being described is subordinate to

- HL02 identifies the hierarchical ID number of the HL segment to which the current HL segment is subordinate.

HL-03 **735 Hierarchical Level Code** Identifier (ID) Required

Code defining the characteristic of a level in a hierarchical structure

- HL03 indicates the context of the series of segments following the current HL segment up to the next occurrence of an HL segment in the transaction. For example, HL03 is used to indicate that subsequent segments in the HL loop form a logical grouping of data referring to shipment, order, or item-level information.

PT Patient

HL-04 **736 Hierarchical Child Code** Identifier (ID) Optional

Code indicating if there are hierarchical child data segments subordinate to the level being described

- HL04 indicates whether or not there are subordinate (or child) HL segments related to the current HL segment.

0 No Subordinate HL Segment in This Hierarchical Structure.

2100D Patient Name Loop

Max 1 Required

NM1 0500 Detail > Information Source Level Loop > Information Receiver Level Loop > Billing Provider of Service Level Loop > Patient Level Loop > Patient Name Loop > NM1

Max use 1 Required

Patient Name

To supply the full name of an individual or organizational entity

Example

```
NM1*QC*1*XXXX*XXXX*XX**XX*MI*XXXXXX~
```

NM1-01 98 Entity Identifier Code

Identifier (ID) Required

Code identifying an organizational entity, a physical location, property or an individual

QC Patient

NM1-02 1065 Entity Type Qualifier

Identifier (ID) Required

Code qualifying the type of entity

- NM102 qualifies NM103.

1 Person

NM1-03 1035 Patient Last Name

Min 1 Max 60 String (AN) Required

Individual last name or organizational name

NM1-04 1036 Patient First Name

Min 1 Max 35 String (AN) Optional

Individual first name

NM1-05 1037 Patient Middle Name or Initial

Min 1 Max 25 String (AN) Optional

Individual middle name or initial

NM1-07 1039 Patient Name Suffix

Min 1 Max 10 String (AN) Optional

Suffix to individual name

NM1-08 66 Identification Code Qualifier

Identifier (ID) Required

Code designating the system/method of code structure used for Identification Code (67)

II Standard Unique Health Identifier for each Individual in the United States

Required if the HIPAA Individual Patient Identifier is mandated for use. If not required use MI.

MI Member Identification Number

NM1-09

67 Patient Identification Number

Min 2 Max 80 **String (AN)** Required

Code identifying a party or other code

Usage notes

- This may be a unique identification number for the patient or it may be the subscriber's identification number. This data element is the value from the NM109 identifying the patient in the submitted claim.

When the payer does not use a unique member identification number for the patient, the subscriber identification number should be used.

2100D Patient Name Loop end

2200D Claim Status Tracking Number Loop

Max >1 Required

TRN 0900 Detail > Information Source Level Loop > Information Receiver Level Loop > Billing Provider of Service Level Loop > Patient Level Loop > Claim Status Tracking Number Loop > TRN

Max use 1 Required

Claim Status Tracking Number

To uniquely identify a transaction to an application

Usage notes

- This segment is the patient control number submitted in the CLM01 of the 837.
- This number must be returned exactly as submitted in the 837 up to the 20 character limit as defined in the 837 guide.

Example

```
TRN*2*X~
```

TRN-01 481 Trace Type Code

Identifier (ID) Required

Code identifying which transaction is being referenced

2 Referenced Transaction Trace Numbers

TRN-02 127 Patient Control Number

Min 1 Max 50 String (AN) Required

Reference information as defined for a particular Transaction Set or as specified by the Reference Identification Qualifier

- TRN02 provides unique identification for the transaction.

STC 1000 Detail > Information Source Level Loop > Information Receiver Level Loop > Billing Provider of Service Level Loop > Patient Level Loop > Claim Status Tracking Number Loop > STC Max use >1 Required

Claim Level Status Information

To report the status, required action, and paid information of a claim or service line

Usage notes

- See Section 1.4.2 - Status Information (STC) Segment Usage for specific STC segment information, composites and code use.

Example

STC*XXX>XX>FA*20240720*U*000000******XXXX>XXXX>XX
X*X>X>XX*XXXXXX~

STC-01 C043 Health Care Claim Status

Used to convey status of the entire claim or a specific service line

Max use 1 Required

C043-01 1271 Health Care Claim Status Category Code

String (AN) Required

Min 1 Max 30

Code indicating a code from a specific industry code list

- C043-01 is used to specify the logical groupings of Health Care Claim Status Codes (See Code Source 507).

Usage notes

- For this business application acknowledgment, use of the Claim Status Category Code is limited to category types `A' for batch. For real time acknowledgements category types A'` and `E' may be used except for E0. Use of the category type E'` is limited to indicating the business application system is unavailable.
- CODE SOURCE 507: Health Care Claim Status Category Code

C043-02 1271 Health Care Claim Status Code

Min 1 Max 30 String (AN) Required

Code indicating a code from a specific industry code list

- C043-02 is used to identify the status of an entire claim or a serviceline. Code Source 508 is referenced unless qualified by C043-04.

Usage notes

- This code provides further detail of the status. See Section 1.4.2 Status Information (STC Segment Usage).
- CODE SOURCE 508: Health Care Claim Status Code

C043-03 98 Entity Identifier Code

Identifier (ID) Optional

Code identifying an organizational entity, a physical location, property or an individual

- C043-03 identifies the entity associated with the Health Care Claim Status Code.

1P Provider

1Z Home Health Care
03 Dependent
40 Receiver
41 Submitter
71 Attending Physician
72 Operating Physician
73 Other Physician
77 Service Location
82 Rendering Provider
85 Billing Provider
87 Pay-to Provider
DK Ordering Physician
DN Referring Provider
DQ Supervising Physician
FA Facility
GB Other Insured
HK Subscriber
IL Insured or Subscriber
LI Independent Lab
MSC Mammography Screening Center
PR Payer
PRP Primary Payer
QB Purchase Service Provider
QC Patient
QD Responsible Party
SEP Secondary Payer
TL Testing Laboratory
TTP Tertiary Payer
TU Third Party Repricing Organization (TPO)

STC-02 **373 Status Information Effective Date** CCYYMMDD format **Date (DT)** Required

Date expressed as CCYYMMDD where CC represents the first two digits of the calendar year

- STC02 is the effective date of the status information.

STC-03 **306 Status Information Action Code** **Identifier (ID)** Required

Code indicating type of action

U Reject
WQ Accept

STC-04 **782 Total Claim Charge Amount** Min 1 Max 15 **# Decimal number (R)** Required

Monetary amount

- STC04 is the amount of original submitted charges.

Usage notes

- Zero is an acceptable amount.

- Sum of the charges (CLM02) submitted from original claim. If an original claim is split, report the original claim total here. Note that this amount may be reported in two or more claims.

STC-10 **C043 Health Care Claim Status**

Used to convey status of the entire claim or a specific service line

Max use 1 Optional

Usage notes

Required if additional clarification to STC01 is needed. If not required by this implementation guide, do not send.

C043-01 **1271 Health Care Claim Status Category Code**

String (AN) Required

Min 1 Max 30

Code indicating a code from a specific industry code list

- C043-01 is used to specify the logical groupings of Health Care Claim Status Codes (See Code Source 507).

Usage notes

- See STC01-1 for valid values.
- CODE SOURCE 507: Health Care Claim Status Category Code

C043-02 **1271 Health Care Claim Status Code**

Min 1 Max 30 String (AN) Required

Code indicating a code from a specific industry code list

- C043-02 is used to identify the status of an entire claim or a serviceline. Code Source 508 is referenced unless qualified by C043-04.

Usage notes

- This code provides further detail of the status. See Section 1.4.2 Status Information (STC Segment Usage).
- CODE SOURCE 508: Health Care Claim Status Code

C043-03 **98 Entity Identifier Code**

Min 2 Max 3 Identifier (ID) Optional

Code identifying an organizational entity, a physical location, property or an individual

- C043-03 identifies the entity associated with the Health Care Claim Status Code.

Usage notes

- See STC01-3 for valid values.

STC-11 **C043 Health Care Claim Status**

Used to convey status of the entire claim or a specific service line

Max use 1 Optional

Usage notes

Required if additional clarification to STC01 and STC10 is needed. If not required by this implementation guide, do not send.

C043-01 **1271 Health Care Claim Status Category Code**

String (AN) Required

Min 1 Max 30

Code indicating a code from a specific industry code list

- C043-01 is used to specify the logical groupings of Health Care Claim Status Codes (See Code Source 507).

Usage notes

- See STC01-1 for valid values.
- CODE SOURCE 507: Health Care Claim Status Category Code

C043-02 **1271 Health Care Claim Status Code**

Min 1 Max 30 String (AN) Required

Code indicating a code from a specific industry code list

- C043-02 is used to identify the status of an entire claim or a serviceline. Code Source 508 is referenced unless qualified by C043-04.

Usage notes

- This code provides further detail of the status. See Section 1.4.2 Status Information (STC Segment Usage).
- CODE SOURCE 508: Health Care Claim Status Code

C043-03 **98 Entity Identifier Code**

Min 2 Max 3 Identifier (ID) Optional

Code identifying an organizational entity, a physical location, property or an individual

- C043-03 identifies the entity associated with the Health Care Claim Status Code.

Usage notes

- See STC01-3 for valid values.

STC-12 **933 Free Form Message Text**

Min 1 Max 264 String (AN) Optional

Free-form message text

- STC12 allows additional free-form status information.

Usage notes

- See Section 1.4.2.1 for more information on use of STC12 and Status Code `448'.

REF 1100 Detail > Information Source Level Loop > Information Receiver Level Loop > Billing Provider of Service Level Loop > Patient Level Loop > Claim Status Tracking Number Loop > REF Max use 1 Optional

Payer Claim Control Number

To specify identifying information

Usage notes

- This number will be used to track the adjudication of the claim throughout the adjudication system.
- Required when a payer assigns a specific number to the claim for processing and the number is available at the time of this acknowledgment. If not required by this implementation guide, do not send.

Example

```
REF*1K*X~
```

Variants (all may be used)

REF Claim Identifier For Transmission Intermediaries

REF Institutional Bill Type Identification

REF-01 **128 Reference Identification Qualifier** Identifier (ID) Required

Code qualifying the Reference Identification

1K Payor's Claim Number

REF-02 **127 Payer Claim Control Number** Min 1 Max 50 String (AN) Required

Reference information as defined for a particular Transaction Set or as specified by the Reference Identification Qualifier

REF 1100 Detail > Information Source Level Loop > Information Receiver Level Loop > Billing Provider of Service Level Loop > Patient Level Loop > Claim Status Tracking Number Loop > REF

Max use 1 Optional

Claim Identifier For Transmission Intermediaries

To specify identifying information

Usage notes

- Required when the Claim Identifier Number for Clearinghouse and Other Transmission Intermediary was sent in the 837. If not required by this implementation guide, do not send.
- This number must be returned as received in the 837.

Example

REF*D9*XXX~

Variants (all may be used)

REF Payer Claim Control Number

REF Institutional Bill Type Identification

REF-01 **128 Reference Identification Qualifier** Identifier (ID) Required

Code qualifying the Reference Identification

D9 Claim Number

REF-02 **127 Clearinghouse Trace Number** Min 1 Max 50 String (AN) Required

Reference information as defined for a particular Transaction Set or as specified by the Reference Identification Qualifier

REF 1100 Detail > Information Source Level Loop > Information Receiver Level Loop > Billing Provider of Service Level Loop > Patient Level Loop > Claim Status Tracking Number Loop > REF

Max use 1 Optional

Institutional Bill Type Identification

To specify identifying information

Usage notes

- Required for Institutional claims when Institutional Type of Bill was received on the claim. If not required by this implementation guide, do not send.

Example

REF*BLT*X~

Variants (all may be used)

REF Payer Claim Control Number

REF Claim Identifier For Transmission Intermediaries

REF-01 **128 Reference Identification Qualifier** Identifier (ID) Required

Code qualifying the Reference Identification

BLT Billing Type

Use this code only for an Institutional Claim.

REF-02 **127 Bill Type Identifier** Min 1 Max 50 String (AN) Required

Reference information as defined for a particular Transaction Set or as specified by the Reference Identification Qualifier

Usage notes

- See 837 Institutional Implementation Guide for definition of Institutional Bill Type components.

Concatenate the 837I CLM05-1 (Facility Type Code) and CLM05-3 (Claim Frequency Code) values. Code Source = 236 - Uniform Billing Claim Form Bill Type, Code Source 235 - Claim Frequency Type Code respectively.

DTP 1200 Detail > Information Source Level Loop > Information Receiver Level Loop > Billing Provider of Service Level Loop > Patient Level Loop > Claim Status Tracking Number Loop > DTP Max use 1 Required

Claim Level Service Date

To specify any or all of a date, a time, or a time period

Usage notes

- For Institutional claims, it is the statement period in loop 2300 (DTP01 - 434). For Professional claims this information is derived from the earliest service level dates in loop 2400 (DTP01-472) to the latest service level date. For Dental claims it is the service date at the claim loop 2300 (DTP01=472).

Example

DTP*472*RD8*XX~

DTP-01 **374 Date Time Qualifier** Identifier (ID) Required

Code specifying type of date or time, or both date and time

472 Service

DTP-02 **1250 Date Time Period Format Qualifier** Identifier (ID) Required

Code indicating the date format, time format, or date and time format

- DTP02 is the date or time or period format that will appear in DTP03.

D8 Date Expressed in Format CCYYMMDD
RD8 Range of Dates Expressed in Format CCYYMMDD-CCYYMMDD

DTP-03 **1251 Claim Service Period** Min 1 Max 35 String (AN) Required

Expression of a date, a time, or range of dates, times or dates and times

2220D Service Line Information Loop

Max >1 Optional

SVC 1800 Detail > Information Source Level Loop > Information Receiver Level Loop > Billing Provider of Service Level Loop > Patient Level Loop > Claim Status Tracking Number Loop > Service Line Inform > SVC

Max use 1 Required

Service Line Information

To supply payment and control information to a provider for a particular service

Usage notes

- Required when a service line is being rejected and caused the rejection of a claim. If not required by this implementation guide, do not send.
- Not used if the claim is being accepted into the adjudication system.
- For Institutional claims, when both an NUBC revenue code and HCPCS or HIPPS code are reported, the HCPCS or HIPPS code is reported in SVC01-2 and the revenue code is reported in SVC04. When only a revenue code is used, it is reported in SVC01-2.

Example

```
SVC*ER>XXX>XX>XX>XX>XX*00000000000000**XX***00000
00~
```

SVC-01 **C003 Composite Medical Procedure Identifier**

To identify a medical procedure by its standardized codes and applicable modifiers

Max use 1 Required

- SVC01 is the medical procedure upon which adjudication is based.
- For Medicare Part A claims, SVC01 would be the Health Care Financing Administration (HCFA) Common Procedural Coding System (HCPCS) Code (see code source 130) and SVC04 would be the Revenue Code (see code source 132).

C003-01 **235 Procedure Code**

Identifier (ID) Required

Code identifying the type/source of the descriptive number used in Product/Service ID (234)

- C003-01 qualifies C003-02 and C003-08.

AD American Dental Association Codes

ER Jurisdiction Specific Procedure and Supply Codes

This code set is not allowed for use under HIPAA at the time of this writing. The qualifier can only be used:
If a new rule names the Jurisdiction Specific Procedure and Supply Codes as an allowable code set under HIPAA,
OR
The Secretary grants an exception to use the code set as a pilot project as allowed under the law,
OR
For claims which are not covered under HIPAA.

HC Health Care Financing Administration Common Procedural Coding System (HCPCS) Codes

HP Health Insurance Prospective Payment System (HIPPS) Skilled Nursing Facility Rate Code

IV Home Infusion EDI Coalition (HIEC) Product/Service Code

NU National Uniform Billing Committee (NUBC) UB92 Codes

This is the NUBC code.

WK Advanced Billing Concepts (ABC) Codes

C003-02 **234 Procedure Code** Min 1 Max 48 **String (AN)** Required

Identifying number for a product or service

- If C003-08 is used, then C003-02 represents the beginning value in the range in which the code occurs.

Usage notes

- If the value in SVC01-1 is "NU", then this element is an NUBC Revenue Code. If the Revenue Code is present in SVC01-2, then SVC04 is not used.
- Value submitted on the original claim.

C003-03 **1339 Procedure Modifier** Min 2 Max 2 **String (AN)** Optional

This identifies special circumstances related to the performance of the service, as defined by trading partners

- C003-03 modifies the value in C003-02 and C003-08.

C003-04 **1339 Procedure Modifier** Min 2 Max 2 **String (AN)** Optional

This identifies special circumstances related to the performance of the service, as defined by trading partners

- C003-04 modifies the value in C003-02 and C003-08.

C003-05 **1339 Procedure Modifier** Min 2 Max 2 **String (AN)** Optional

This identifies special circumstances related to the performance of the service, as defined by trading partners

- C003-05 modifies the value in C003-02 and C003-08.

C003-06 **1339 Procedure Modifier** Min 2 Max 2 **String (AN)** Optional

This identifies special circumstances related to the performance of the service, as defined by trading partners

- C003-06 modifies the value in C003-02 and C003-08.

SVC-02 **782 Line Item Charge Amount** Min 1 Max 15 **# Decimal number (R)** Required

Monetary amount

- SVC02 is the submitted service charge.

Usage notes

- Zero is an acceptable amount.

SVC-04

234 Revenue Code

Min 1 Max 48 **String (AN)** Optional

Identifying number for a product or service

- SVC04 is the National Uniform Billing Committee Revenue Code.

SVC-07

380 Original Units of Service Count

Min 1 Max 15 **# Decimal number (R)** Optional

Numeric value of quantity

- SVC07 is the original submitted units of service.

Service Line Level Status Information

To report the status, required action, and paid information of a claim or service line

Usage notes

- See Section 1.4.2 - Status Information (STC) Segment Usage for specific STC segment information, composites and code use.

Example

STC*X>XXXXX>85**U*******X>XX>XX*XX>XX>XX*XXXXXX~

STC-01 C043 Health Care Claim Status

Used to convey status of the entire claim or a specific service line

Max use 1 Required

C043-01 1271 Health Care Claim Status Category Code

String (AN) Required

Min 1 Max 30

Code indicating a code from a specific industry code list

- C043-01 is used to specify the logical groupings of Health Care Claim Status Codes (See Code Source 507).

Usage notes

- For this business application acknowledgment, use of the Claim Status Category Code is limited to category types `A' for batch. For real time acknowledgements category types A'` and `E' may be used except for E0. Use of the category type E'` is limited to indicating the business application system is unavailable.
- CODE SOURCE 507: Health Care Claim Status Category Code

C043-02 1271 Health Care Claim Status Code

Min 1 Max 30 String (AN) Required

Code indicating a code from a specific industry code list

- C043-02 is used to identify the status of an entire claim or a serviceline. Code Source 508 is referenced unless qualified by C043-04.

Usage notes

- This code provides further detail of the status. See Section 1.4.2 Status Information (STC Segment Usage).
- CODE SOURCE 508: Health Care Claim Status Code

C043-03 98 Entity Identifier Code

Identifier (ID) Optional

Code identifying an organizational entity, a physical location, property or an individual

- C043-03 identifies the entity associated with the Health Care Claim Status Code.

1P Provider

1Z Home Health Care

03 Dependent
40 Receiver
41 Submitter
71 Attending Physician
72 Operating Physician
73 Other Physician
77 Service Location
82 Rendering Provider
85 Billing Provider
87 Pay-to Provider
DK Ordering Physician
DN Referring Provider
DQ Supervising Physician
FA Facility
GB Other Insured
HK Subscriber
IL Insured or Subscriber
LI Independent Lab
MSC Mammography Screening Center
PR Payer
PRP Primary Payer
QB Purchase Service Provider
QC Patient
QD Responsible Party
SEP Secondary Payer
TL Testing Laboratory
TTP Tertiary Payer
TU Third Party Repricing Organization (TPO)

STC-03 **306 Action Code**

Identifier (ID) Required

Code indicating type of action

U Reject

STC-10 **C043 Health Care Claim Status**

Used to convey status of the entire claim or a specific service line

Max use 1 Optional

Usage notes

Required if additional clarification to STC01 is needed. If not required by this implementation guide, do not send.

C043-01 **1271 Health Care Claim Status Category Code**

String (AN) Required

Min 1 Max 30

Code indicating a code from a specific industry code list

- C043-01 is used to specify the logical groupings of Health Care Claim Status Codes (See Code Source 507).

Usage notes

- See STC01-1 for valid values.
- CODE SOURCE 507: Health Care Claim Status Category Code

C043-02 **1271 Health Care Claim Status Code** Min 1 Max 30 String (AN) Required

Code indicating a code from a specific industry code list

- C043-02 is used to identify the status of an entire claim or a serviceline. Code Source 508 is referenced unless qualified by C043-04.

Usage notes

- This code provides further detail of the status. See Section 1.4.2 Status Information (STC Segment Usage).
- CODE SOURCE 508: Health Care Claim Status Code

C043-03 **98 Entity Identifier Code** Min 2 Max 3 Identifier (ID) Optional

Code identifying an organizational entity, a physical location, property or an individual

- C043-03 identifies the entity associated with the Health Care Claim Status Code.

Usage notes

- See STC01-3 for valid values.

STC-11 **C043 Health Care Claim Status** Max use 1 Optional

Used to convey status of the entire claim or a specific service line

Usage notes

Required if additional clarification to STC01 and STC10 is needed. If not required by this implementation guide, do not send.

C043-01 **1271 Health Care Claim Status Category Code** String (AN) Required Min 1 Max 30

Code indicating a code from a specific industry code list

- C043-01 is used to specify the logical groupings of Health Care Claim Status Codes (See Code Source 507).

Usage notes

- See STC01-1 for valid values.
- CODE SOURCE 507: Health Care Claim Status Category Code

C043-02 **1271 Health Care Claim Status Code** Min 1 Max 30 String (AN) Required

Code indicating a code from a specific industry code list

- C043-02 is used to identify the status of an entire claim or a serviceline. Code Source 508 is referenced unless qualified by C043-04.

Usage notes

- This code provides further detail of the status. See Section 1.4.2 Status Information (STC Segment Usage).
- CODE SOURCE 508: Health Care Claim Status Code

C043-03 98 Entity Identifier Code

Min 2 Max 3 **Identifier (ID)** Optional

Code identifying an organizational entity, a physical location, property or an individual

- C043-03 identifies the entity associated with the Health Care Claim Status Code.

Usage notes

- See STC01-3 for valid values.

STC-12 933 Free Form Message Text

Min 1 Max 264 **String (AN)** Optional

Free-form message text

- STC12 allows additional free-form status information.

Usage notes

- See Section 1.4.2.1 for more information on use of STC12 and Status Code `448'.

Service Line Item Identification

To specify identifying information

Usage notes

- This is the line Item Control Number exactly as submitted on the original claim in Loop 2400, REF02 (REF01-6R). If a Line Item Control Number is not submitted, this will be the line sequence number (LX01) of the service line.

Example

REF*FJ*XXXXXX~

Variants (all may be used)

REF Pharmacy Prescription Number

REF-01 **128 Reference Identification Qualifier** Identifier (ID) Required

Code qualifying the Reference Identification

FJ Line Item Control Number

REF-02 **127 Line Item Control Number** Min 1 Max 50 String (AN) Required

Reference information as defined for a particular Transaction Set or as specified by the Reference Identification Qualifier

REF 2000 Detail > Information Source Level Loop > Information Receiver Level Loop > Billing Provider of Service Level Loop > Patient Level Loop > Claim Status Tracking Number Loop > Service Line Informa > REF

Max use 1 Optional

Pharmacy Prescription Number

To specify identifying information

Usage notes

- Required when a Pharmacy Prescription Number was sent in the 837 at the Service Line. If not required by this implementation guide, do not send.

Example

REF*XZ*XXXXXX~

Variants (all may be used)

REF Service Line Item Identification

REF-01 128 **Reference Identification Qualifier** Identifier (ID) Required

Code qualifying the Reference Identification

XZ Pharmacy Prescription Number

REF-02 127 **Pharmacy Prescription Number** Min 1 Max 50 String (AN) Required

Reference information as defined for a particular Transaction Set or as specified by the Reference Identification Qualifier

DTP 2100 Detail > Information Source Level Loop > Information Receiver Level Loop > Billing Provider of Service Level Loop > Patient Level Loop > Claim Status Tracking Number Loop > Service Line Informa > DTP

Max use 1 Optional

Service Line Date

To specify any or all of a date, a time, or a time period

Usage notes

- Required when the Date of Service from the original submitted claim for a specific line item is present. If not required by this implementation guide, do not send.

Example

DTP*472*D8*XXXXXX~

DTP-01 **374 Date Time Qualifier** Identifier (ID) Required

Code specifying type of date or time, or both date and time

472 Service

DTP-02 **1250 Date Time Period Format Qualifier** Identifier (ID) Required

Code indicating the date format, time format, or date and time format

- DTP02 is the date or time or period format that will appear in DTP03.

D8 Date Expressed in Format CCYYMMDD
RD8 Range of Dates Expressed in Format CCYYMMDD-CCYYMMDD

DTP-03 **1251 Service Line Date** Min 1 Max 35 String (AN) Required

Expression of a date, a time, or range of dates, times or dates and times

2220D Service Line Information Loop end

2200D Claim Status Tracking Number Loop end

2000D Patient Level Loop end

2000C Billing Provider of Service Level Loop end

2000B Information Receiver Level Loop end

SE 2700 Detail > SE

Max use 1 Required

Transaction Set Trailer

To indicate the end of the transaction set and provide the count of the transmitted segments (including the beginning (ST) and ending (SE) segments)

Example

```
SE*00000000*0001~
```

SE-01 **96 Transaction Segment Count** Min 1 Max 10 # Numeric (N0) Required

Total number of segments included in a transaction set including ST and SE segments

SE-02 **329 Transaction Set Control Number** Min 4 Max 9 # Numeric (N) Required

Identifying control number that must be unique within the transaction set functional group assigned by the originator for a transaction set

Usage notes

- Data value in SE02 must be identical to ST02.

Detail end

GE

Max use 1 Required

Functional Group Trailer

To indicate the end of a functional group and to provide control information

Example

```
GE*0000*0000000~
```

GE-01 **97 Number of Transaction Sets Included** Min 1 Max 6 # Numeric (N0) Required

Total number of transaction sets included in the functional group or interchange (transmission) group terminated by the trailer containing this data element

GE-02 **28 Group Control Number** Min 1 Max 9 # Numeric (N0) Required

Assigned number originated and maintained by the sender

IEA

Max use 1 Required

Interchange Control Trailer

To define the end of an interchange of zero or more functional groups and interchange-related control segments

Example

```
IEA*0000*000000000~
```

IEA-01 **I16 Number of Included Functional Groups** Min 1 Max 5 # Numeric (N0) Required

A count of the number of functional groups included in an interchange

IEA-02 **I12 Interchange Control Number** Min 9 Max 9 # Numeric (N0) Required

A control number assigned by the interchange sender

EDI Samples

Example 01 - Payer Response

```
ISA*00* *00* *ZZ*SENDER *ZZ*RECEIVER *230915*1402*U*00401*000000001*0*T*>~
GS*HN*SENDERGS*RECEIVERGS*20230915*140226*000000001*X*005010X214~
ST*277*0003*005010X214~
BHT*0085*08*277X2140003*20230221*1025*TH~
HL*1**20*1~
NM1*PR*2*YOUR INSURANCE COMPANY*****PI*YIC01~
TRN*1*0091182~
DTP*050*D8*20230220~
DTP*009*D8*20230221~
HL*2*1*21*1~
NM1*41*1*JONES*HARRY*B***46*S00003~
TRN*2*2002022045678~
STC*A1>19>PR*20230221*WQ*365.5~
QTY*90*3~
QTY*AA*2~
AMT*YU*200.5~
AMT*YY*165~
HL*3*2*19*1~
NM1*85*1*JONES*HARRY*B**MD*FI*234567894~
HL*4*3*PT~
NM1*QC*1*PATIENT*FEMALE****MI*2222222222~
TRN*2*PATIENT22222~
STC*A2>20*20230221*WQ*100~
REF*1K*220216359803X~
DTP*472*D8*20230214~
HL*5*3*PT~
NM1*QC*1*PATIENT*MALE****MI*3333333333~
TRN*2*PATIENT33333~
STC*A3>21*20230221*U*65******A3>187~
DTP*472*D8*20230229~
HL*6*3*PT~
NM1*QC*1*JONES*LARRY****MI*4444444444~
TRN*2*JONES44444~
STC*A7>21*20230221*U*100******A7>249~
DTP*472*D8*20230211~
HL*7*3*PT~
NM1*QC*1*JOHNSON*MARY****MI*5555555555~
TRN*2*JOHNSON55555~
STC*A2>20*20230221*WQ*50.5~
REF*1K*220216359806X~
DTP*472*D8*20230210~
HL*8*3*PT~
NM1*QC*1*MILLER*HARRIETT****MI*6666666666~
TRN*2*MILLS66666~
STC*A2>20*20230221*WQ*50~
REF*1K*220216359807X~
DTP*472*D8*20230205~
SE*46*0003~
GE*1*000000001~
IEA*1*000000001~
```

Stedi is a registered trademark of Stedi, Inc. All names, logos, and brands of third parties listed on this page are trademarks of their respective owners (including “X12”, which is a trademark of X12 Incorporated). Stedi, Inc. and its products and services are not endorsed by, sponsored by, or affiliated with these third parties. Use of these names, logos, and brands is for identification purposes only, and does not imply any such endorsement, sponsorship, or affiliation.