Rigorous Evaluation of LLM Components in HPC Research

Daniel Nichols, Abhinav Bhatele, Harshitha Menon

This work is performed under the auspices of the U.S. Department of Energy by Lawrence Livermore National Laboratory under Contract DE-AC52-07NA27344.

Section 1: Introduction

- Tutorial Objectives
  - Learn how to properly evaluate LLMs in HPC and scientific research
  - Learn the dangers and common pitfalls from using LLMs in research

- Overview
  - Intro to LLMs
  - How to Lie with LLM Results
  - Experimental Design for Stochastic Components
  - Transparency and Reproducibility
  - Human Validation: When and How
  - Baselines, Metrics, and Ablations
  - HPC and Scientific Computing Specifics


Section II: Introduction to LLMs

- Goal for this section: shared vocabulary for using LLMs
- You should be able to answer:
  - What are tokens?
  - What is text generation?
  - Where does randomness come from?
  - What is a model?

- Overview
  - What is an LLM?
  - What are tokens?
  - Text Generation
  - Sampling: How Randomness is Introduced
  - Randomness in LLMs


What is an LLM?

- Large Language Models are neural networks based on the transformer architecture that are state-of-the-art for modeling sequential data (e.g. text, language)
- Often trained for causal language modeling
  - Input: text sequence → output: probabilities of next token




What are tokens?

- LLMs learn from integer sequences, not text
- *Tokenization* is the process of mapping text to integer sequences
- LLMs take sequences of tokens as input and outputs token probabilities
- Tokens *do not* correspond 1-1 with words or characters



Text Generation

- LLMs learn from integer sequences, not text
- *Tokenization* is the process of mapping text to integer sequences
- LLMs take sequences of tokens as input and outputs token probabilities
- Tokens *do not* correspond 1-1 with words or characters



Text Generation

- Auto-regressive text generation is the process of repeatedly sampling the next token to generate sequences
- Stop when the model generates stop or EOS token
- Note: early differences in sequences can cascade into very different outputs

Sampling: The Introduction of Randomness

- Using the most probable next token leads to bad, repetitive generations (A. Holtzman et al. “The Curious Case of Neural Text Degeneration”)
- Randomly sampling yields much better results
- Popular sampling strategies
  - Top-K
  - Top-P or Nucleus Sampling
  - Beam search
- Temperature often used to scale probabilities before sampling

Randomness in LLMs

- Transformers with fixed weights and inputs are deterministic in the log-probs they output *
- Randomness is introduced by:
  - Prompt variance: multiple ways of prompting the same question, e.g. “Find the square root of N” vs “What multiplied by itself equals N?”
  - Sampling: Using randomness to sample the next token in text generation

* Parallelism and floating point arithmetic can cause non-determinism in some implementations

Section III: How to Lie with LLM Results

- Goal for this section: understand where LLMs can go wrong when used in research components

- Overview
  - Case study
  - Lie 1: Not considering randomness
  - Lie 2: Cherry picking examples
  - Lie 3: not considering other axes of evaluation
  - Lie 4: Benchmark leakage / data contamination
  - Lie 5: LLM-as-a-judge, rubric drift
  - Lie 6: Human-as-a-judge, inconsistent evaluation
  - Lie 7: Unreported human intervention
  - Lie 8: Not reporting cost / GPU hours
  - Lie 9: Conflating Formatting Abilities with Technical Abilities

Lie #1: Not Considering Randomness

- LLM outputs are *random*; reporting metrics for a single output can be misleading
- You should report: *What is the probability/likelihood that a model outputs the correct solution?*
- This is true of any system with LLM subcomponents
- Many works/benchmarks employ this through probabilistic metrics e.g. mean accuracy, pass@k
- Often only sampling variance is covered
- Prompt variance matters! (Y. Zi et al. “More Than a Score: Probing the Impact of Prompt Specificity on LLM Code Generation”)

Lie #2: Cherry Picking Examples

- Another facet of random outputs from LLMs is that we must report all results
- Only reporting the “best” results can mislead to thinking the LLM is doing better than it actually is
- Sampling parameters need to be transparent: If the LLM tool only works for some sampling parameters, this is *ok*, but it needs to be reported

Lie #3: Ignoring Important Axes of Evaluation

- To avoid lies 1-2 practitioners often sample many outputs and, thus, need easy-to-automatically-compute metrics for evaluation
- This often leads to Lie #3: using too simple of metrics that don't paint the whole picture
- Consider evaluating LLMs on generating MPI code

This is functionally correct, but not really correct

```
def compute_and_share(data):
    output = compute(data)
    for rank in other_ranks:
        mpi_send(output, rank)
```

This is what we want to see the LLM generate

```
def compute_and_share(data):
    output = compute(data)
    mpi_bcast(output)
```

Lie #4: Benchmark Leakage and Data Contamination

- If your benchmark is in the training set, then the model could be over-fitting the answers
- You're testing how well the model can memorize your problems and not actually solve them
- This is only okay if your benchmark is *exhaustive*, which is almost never the case
- Even if your questions are private, make sure they are not too similar to existing public sources

Lie #5: LLM-as-a-Judge, Rubric Drift

- Rubric drift: small changes in prompts and judge models can drastically alter results
- LLM judging often conflates style and correctness
- LLM-based evaluation is a useful new research tool, but is *insufficient* and *potentially dangerous* for scientific evaluation

Lie #6: Human-as-a-Judge, Inconsistent Eval

- Humans are just as prone to evaluation biases as LLMs
- Evaluation criteria not public or precise. Evaluation data not public
- Social science fields have best practices for using humans to evaluate / rank / label data. It is still very difficult to implement correctly.
- As with lie #5, human judgement is *insufficient* and *dangerous* in scientific results reporting

Lie #7: Unreported Human Intervention

- LLM / Agent pipeline relied on human intervention somewhere and it is not reported
  - Data cleaning between components
  - Prompt design and/or variation
  - Sampling parameter and/or model choice changes
- Approach is not reproducible without documenting and studying these human interventions

Lie #8: Not Reporting Cost / GPU Hours

- API costs or GPU time when self-hosting are imperative to report, particularly when comparing with other approaches
- If an approach yields better results, but costs significantly more this is of interest to users of the approach
- All costs and GPU hours need to be reported
  - Costs fluctuate, so token counts should also be reported.

Lie #9: Conflating Formatting Abilities with Technical Abilities

- If we are testing an LLM/Agent on its ability to do task *X*, then we don't want to conflate performance on *X* with performance on formatting outputs for task *X*.
- An example: You task an LLM with solving a math problem and outputting the final number; your script checks accuracy with `int(llm_answer) == ground_truth`.
  - The LLM would get this wrong if it generated "The answer is …"
  - Even if it knew the answer we've marked it as wrong
- Give LLMs the benefit of the doubt in parsing outputs, unless your task *X* includes formatting as part of the task

Section IV: Experimental Design for Stochastic Components

- Goal for this section: how to design experiments that rely on stochastic subcomponents

- Overview
  - Why careful consideration is important
  - Probabilistic metrics
  - Structured inputs/outputs; mitigating stochasticity
  - Testing individual subcomponents
  - Ablation studies on system
  - Human validation

Section V: Transparency and Reproducibility

- Goal for this section: how to ensure LLM subcomponents are reproducible

- Overview
  - Reproducibility requires transparency
  - What to report
  - Logging LLM inputs/outputs
  - Anonymizing LLM artifacts for peer review

Reproducibility and Transparency

- LLMs are stochastic
  - There are ways to make them reproducible, but it is difficult or impossible for large open models or commercial models
  - Thus, generated outputs need to be part of the artifact to make them reproducible
- An independent researcher should be able to reproduce your research by “replaying” generated outputs, instead of generating them again

Logging Generations and Making Them Available for Peer Review

- APIs
  - Simply log API outputs or wrap API calls in a logging function
- Agents
  - Most, if not all, agent frameworks provide tracing functionality
  - Use agent traces to save sequence of actions and generations
- Anonymizing agent traces
  - Anonymizing requirements vary by venue
  - Tools like anonymous4science can host files and mask out provided key words – it provides a link that can be included in a paper or artifact submission

Section VI: Human Validation: When and How

- Goal for this section: how should humans interact with LLM research components

- Overview
  - When to keep humans in the loop
  - How to employ human evaluation on LLM subcomponents

Issues with Human Validation

- Humans are inconsistent scorers
  - Even the same person may score things differently across time
- It is not reproducible
- Humans are very easily swayed; it is easy to measure the wrong metric
  - Example: people often find longer, more technical answers better regardless of their correctness

When and How to Use Human Validation

- Use as a supplement to reproducible metrics
- All human scoring and raw results need to be publicly available
  - This is part of the methodology now
- Use metrics that are less susceptible to subjectivity
  - Example: rather than ask “Which output summarizes the scientific result better?”, instead ask “Based on the following generated output, please answer the following multiple-choice questions about a scientific result?”
  - Provide a reproducible metric

Section VII: Baselines, Metrics, and Ablations

- Goal for this section: best practices for experimental setups for LLM-based research

- Overview
  - What's a good baseline
  - Metrics for LLMs
  - How to structure ablation studies

LLM Baselines

- Representative baselines are important!
- Compare with models of similar: cost, performance (time), quality, availability
- Compare with frontier models / agents
  - Being the best open model is valuable research
  - But comparison to SotA is still necessary context

Probabilistic Metrics

- pass@k – How often are outputs correct?

$$\text{pass@}k = \frac{1}{|P|} \sum_{p \in P} \left[1 - \binom{N - c_p}{k} \Big/ \binom{N}{k} \right]$$

N samples generated per prompt

Set of 420 prompts

Number of correct generations

prompt

```
/* Compute the dot product of x and y using
OpenMP */
int product(int *x, int *y, size_t N) {
```

LLM

What is the probability at least one of k responses is correct?

response 1

```
int sum = 0;
#pragma omp parallel for
for (int i = 0; i < N; i++) {
  sum += x[i] * y[i];
}
return sum;
```

response 2

```
int sum = 0;
for (int i = 0; i < N; i++) {
  sum += x[i] * y[i];
}
return sum;
```

⋮

response k

Measuring Performance of LLM Generated Code

- speedup@k – What's the expected max speedup?

Baseline runtime

$$\mathbb{E}\left[\max\left\{\frac{T^*}{T_{s_1}}, \ldots, \frac{T^*}{T_{s_k}}\right\}\right]$$

Runtime of LLM generations

prompt

```
/* Compute the dot product of x and y
using OpenMP */
int product(int *x, int *y, size_t N) {
```

LLM

What is the *expected max speedup* over k response?

response 1

```
int sum = 0;
#pragma omp parallel for
for (int i = 0; i < N; i++) {
   sum += x[i] * y[i];
}
return sum;
```

response 2

```
int sum = 0;
for (int i = 0; i < N; i++) {
   sum += x[i] * y[i];
}
return sum;
```

⋮

response k

Measuring Performance of LLM Generated Code

- speedup@k – What's the expected max speedup?

Baseline sequential runtime

$$\mathbb{E}\left[\max\left\{\frac{T^*}{T_{s_1,n}},\ldots,\frac{T^*}{T_{s_k,n}}\right\}\right]$$

Runtime of LLM generations on *n* processors

prompt

```
/* Compute the dot product of x and y
using OpenMP */
int product(int *x, int *y, size_t N) {
```

LLM

What is the *expected max speedup* over k response?

response 1

```
int sum = 0;
#pragma omp parallel for
for (int i = 0; i < N; i++) {
   sum += x[i] * y[i];
}
return sum;
```

response 2

```
int sum = 0;
for (int i = 0; i < N; i++) {
   sum += x[i] * y[i];
}
return sum;
```


⋮

response k

Measuring Performance of LLM Generated Code

- speedup@k – What's the expected max speedup?

$$\text{speedup}_n@k = \frac{1}{|P|} \sum_{p \in P} \sum_{j=1}^{N} \frac{\binom{j-1}{k-1}}{\binom{N}{k}} \frac{T_p^*}{T_{p,j,n}}$$



Conclusion