

Rajalakshmi Engineering College

Name: Parameswari P

Email: 240701378@rajalakshmi.edu.in

Roll no: 240701378

Phone: 9500133836

Branch: REC

Department: I CSE FD

Batch: 2028

Degree: B.E - CSE

Scan to verify results



NeoColab_REC_CS23231_DATA STRUCTURES

REC_DS using C_Week 4_MCQ_Updated

Attempt : 1

Total Mark : 20

Marks Obtained : 18

Section 1 : MCQ

1. What does the front pointer in a linked list implementation of a queue contain?

Answer

The address of the first element

Status : Correct

Marks : 1/1

2. The essential condition that is checked before insertion in a queue is?

Answer

Overflow

Status : Correct

Marks : 1/1

3. Front and rear pointers are tracked in the linked list implementation of a queue. Which of these pointers will change during an insertion into the EMPTY queue?

Answer

Both front and rear pointer

Status : Correct

Marks : 1/1

4. In linked list implementation of a queue, the important condition for a queue to be empty is?

Answer

FRONT is null

Status : Correct

Marks : 1/1

5. Which of the following can be used to delete an element from the front end of the queue?

Answer

```
public Object deleteFront() throws emptyDequeException{if(isEmpty())throw new emptyDequeException("Empty");else{Node temp = head.getNext();Node cur = temp;Object e = temp.getEle();head.setNext(cur);size--;return e;}}
```

Status : Wrong

Marks : 0/1

6. What is the functionality of the following piece of code?

```
public void function(Object item)
{
    Node temp=new Node(item,trail);
    if(isEmpty())
    {
        head.setNext(temp);
        temp.setNext(trail);
    }
}
```

```

else
{
    Node cur=head.getNext();
    while(cur.getNext()!=trail)
    {
        cur=cur.getNext();
    }
    cur.setNext(temp);
}
size++;
}

```

Answer

Insert at the rear end of the dequeue

Status : Correct

Marks : 1/1

7. Insertion and deletion operation in the queue is known as

Answer

Enqueue and Dequeue

Status : Correct

Marks : 1/1

8. What will the output of the following code?

```

#include <stdio.h>
#include <stdlib.h>
typedef struct {
    int* arr;
    int front;
    int rear;
    int size;
} Queue;
Queue* createQueue() {
    Queue* queue = (Queue*)malloc(sizeof(Queue));
    queue->arr = (int*)malloc(5 * sizeof(int));
    queue->front = 0;

```

```
    queue->rear = -1;
    queue->size = 0;
    return queue;
}
int main() {
    Queue* queue = createQueue();
    printf("%d", queue->size);
    return 0;
}
```

Answer

0

Status : Correct

Marks : 1/1

9. After performing this set of operations, what does the final list look to contain?

```
InsertFront(10);
InsertFront(20);
InsertRear(30);
DeleteFront();
InsertRear(40);
InsertRear(10);
DeleteRear();
InsertRear(15);
display();
```

Answer

10 30 40 15

Status : Correct

Marks : 1/1

10. The process of accessing data stored in a serial access memory is similar to manipulating data on a

Answer

Queue

Status : Correct

Marks : 1/1

11. In what order will they be removed If the elements "A", "B", "C" and "D" are placed in a queue and are deleted one at a time

Answer

ABCD

Status : Correct

Marks : 1/1

12. In a linked list implementation of a queue, front and rear pointers are tracked. Which of these pointers will change during an insertion into a non-empty queue?

Answer

Only rear pointer

Status : Correct

Marks : 1/1

13. Which of the following properties is associated with a queue?

Answer

Last In First Out

Status : Wrong

Marks : 0/1

14. What are the applications of dequeue?

Answer

All the mentioned options

Status : Correct

Marks : 1/1

15. A normal queue, if implemented using an array of size MAX_SIZE, gets full when

Answer

Rear = MAX_SIZE - 1

Status : Correct

Marks : 1/1

16. What will be the output of the following code?

```
#include <stdio.h>
#define MAX_SIZE 5
typedef struct {
    int arr[MAX_SIZE];
    int front;
    int rear;
    int size;
} Queue;

void enqueue(Queue* queue, int data) {
    if (queue->size == MAX_SIZE) {
        return;
    }
    queue->rear = (queue->rear + 1) % MAX_SIZE;
    queue->arr[queue->rear] = data;
    queue->size++;
}

int dequeue(Queue* queue) {
    if (queue->size == 0) {
        return -1;
    }
    int data = queue->arr[queue->front];
    queue->front = (queue->front + 1) % MAX_SIZE;
    queue->size--;
    return data;
}

int main() {
    Queue queue;
    queue.front = 0;
    queue.rear = -1;
    queue.size = 0;
```

```

enqueue(&queue, 1);
enqueue(&queue, 2);
enqueue(&queue, 3);
printf("%d ", dequeue(&queue));
printf("%d ", dequeue(&queue));
enqueue(&queue, 4);
enqueue(&queue, 5);
printf("%d ", dequeue(&queue));
printf("%d ", dequeue(&queue));
return 0;
}

```

Answer

1 2 3 4

Status : Correct

Marks : 1/1

17. What will be the output of the following code?

```

#include <stdio.h>
#include <stdlib.h>
#define MAX_SIZE 5
typedef struct {
    int* arr;
    int front;
    int rear;
    int size;
} Queue;
Queue* createQueue() {
    Queue* queue = (Queue*)malloc(sizeof(Queue));
    queue->arr = (int*)malloc(MAX_SIZE * sizeof(int));
    queue->front = -1;
    queue->rear = -1;
    queue->size = 0;
    return queue;
}
int isEmpty(Queue* queue) {
    return (queue->size == 0);
}

```

```
int main() {  
    Queue* queue = createQueue();  
    printf("Is the queue empty? %d", isEmpty(queue));  
    return 0;  
}
```

Answer

Is the queue empty? 1

Status : Correct

Marks : 1/1

18. When new data has to be inserted into a stack or queue, but there is no available space. This is known as

Answer

overflow

Status : Correct

Marks : 1/1

19. Which one of the following is an application of Queue Data Structure?

Answer

All of the mentioned options

Status : Correct

Marks : 1/1

20. Which operations are performed when deleting an element from an array-based queue?

Answer

Dequeue

Status : Correct

Marks : 1/1