

Back To Practice

Save

Round Robin CPU Scheduling Algorithm

Completed

Write a C program to implement the Round Robin (RR) CPU Scheduling Algorithm. The program should accept the number of processes, their Arrival Times (AT), Burst Times (BT), and a Time Quantum (TQ). The CPU should rotate through the processes in the ready queue, granting each a maximum of one TQ of execution time. Calculate the Completion Time (CT), Turnaround Time (TAT), and Waiting Time (WT) for each process and the overall averages.

Input Format

1. The first line of input contains an integer representing the number of processes.
2. The second line contains an integer representing the Time Quantum.
3. The next lines contain two integers for each process, where
 - The first integer denotes the Arrival Time (AT)
 - The second integer denotes the Burst Time (BT) of the process.

Select Language : C (GCC 9.2.0)

```

1 #include <stdio.h>
2
3 int main() {
4     int n, tq, i, time = 0, done = 0;
5
6     printf("Enter number of processes: \n");
7     scanf("%d", &n);
8
9     printf("Enter Time Quantum: \n");
10    scanf("%d", &tq);
11
12    int at[n], bt[n], rt[n], ct[n], tat[n], wt[n];
13
14    for(i = 0; i < n; i++) {
15        printf("Enter AT and BT for P%d: \n", i+1);
16        scanf("%d %d", &at[i], &bt[i]);
17        rt[i] = bt[i];
18    }
19
20    while(done < n) {
21        int executed = 0;
22
23        for(i = 0; i < n; i++) {
24            if(at[i] <= time && rt[i] > 0) {

```

Test Cases

Run Sample Cases

Run All Cases

Custom Test Case

> Custom Test

Sample Test Case

> Test Case - 1

> Test Case - 2

Round Robin CPU Scheduling Algorithm

Completed

Write a C program to implement the Round Robin (RR) CPU Scheduling Algorithm. The program should accept the number of processes, their Arrival Times (AT), Burst Times (BT), and a Time Quantum (TQ). The CPU should rotate through the processes in the ready queue, granting each a maximum of one TQ of execution time. Calculate the Completion Time (CT), Turnaround Time (TAT), and Waiting Time (WT) for each process and the overall averages.

Input Format

1. The first line of input contains an integer representing the number of processes.
2. The second line contains an integer representing the Time Quantum.
3. The next lines contain two integers for each process, where
 - The first integer denotes the Arrival Time (AT)
 - The second integer denotes the Burst Time (BT) of the process.

Select Language : C (GCC 9.2.0)

```

19
20     while(done < n) {
21         int executed = 0;
22
23         for(i = 0; i < n; i++) {
24             if(at[i] <= time && rt[i] > 0) {
25                 executed = 1;
26
27                 if(rt[i] > tq) {
28                     time += tq;
29                     rt[i] -= tq;
30                 }
31                 else {
32                     time += rt[i];
33                     ct[i] = time;
34                     rt[i] = 0;
35                     done++;
36                 }
37             }
38         }
39
40         if(!executed)
41             time++;
42     }

```

Test Cases

Run Sample Cases

Run All Cases

Custom Test Case

Custom Test

Success ✓

Input :

Expected Output :

```

3
2
0 5
1 3
2 1

```

```

Enter number of
processes:
Enter Time Quantum:
Enter AT and BT for P1:
Enter AT and BT for P2:
Enter AT and BT for P3:

```

Average Turnaround