Agents That Forget How to Chat: Self-Distilled Rehearsal Preserves General Behavior Through SFT and RL Post-Training of a Shopping Agent

Param Madan
Northeastern University
madan.pa@northeastern.edu

Abstract

Post-training a general instruction-tuned model into a tool-using agent can silently destroy its ability to behave as a general assistant. We study this in a multi-turn, permission-gated shopping environment with hidden user constraints, fine-tuning Qwen2.5-7B-Instruct with LoRA, first by supervised fine-tuning (SFT) on expert demonstrations and then by RLOO reinforcement learning against a ground-truth reward. A specialist trained only on shopping data reaches 93.8 $\pm$2.7% task success on a held-out catalog after RL (3 seeds), but answers only 22.5 $\pm$9.0% of 40 general questions without collapsing into store actions (base model: 95.0%), and its IFEval prompt-level strict accuracy falls from 64.5% to 38.8 $\pm$0.8%. MMLU log-likelihood accuracy is unchanged ($\approx$74% in every arm): the model's knowledge survives while its behavior does not. Mixing 25% *self-distilled* rehearsal (open-ended Dolly prompts answered by the untrained base model) into SFT keeps general behavior at or above the base model through both SFT and RL (100.0% retention, 65.5 $\pm$0.5% IFEval), at a cost in task success (83.9 $\pm$9.4% vs. 93.8 $\pm$2.7%) and higher seed variance. We release code, configurations, per-run manifests and all raw evaluation outputs.

1 Introduction

A common recipe for building an LLM agent is to take an instruction-tuned model, fine-tune it on task demonstrations, and then improve it with reinforcement learning against a task reward. Deployed agents, however, rarely see only in-task traffic: a shopping assistant is also asked what the capital of Australia is. If post-training teaches the model to respond to *everything* with a store action, the agent becomes worse at the general assistance it was supposed to retain.

Catastrophic forgetting under sequential training is long known [8, 6] and has been measured in LLM continual fine-tuning [7]; replaying old data (rehearsal) is one of the oldest mitigations [11], and mixing pre-training data into RLHF updates is standard practice [9]. Self-distillation, i.e. training on the base model's own responses, has been proposed to narrow the distribution gap during fine-tuning [13]. What is less documented is how forgetting behaves across the *two-stage* agent pipeline (SFT then RL), whether RL repairs or compounds it, and *what kind* of ability is lost. This paper contributes a small, controlled, fully reproducible measurement of those questions:

- **Behavioral forgetting, not knowledge loss.** Shopping-only post-training collapses general chat into store actions and halves IFEval accuracy, while MMLU (scored by log-likelihood, independent of output format) is unchanged (§5).
- **RL neither causes nor repairs it.** For both arms, retention and IFEval after RL are close to their post-SFT values (within seed variation); the damage is set during SFT.
- **Self-distilled rehearsal prevents it, at a measured cost.** 25% rehearsal keeps general behavior at base-model level on all three seeds, but lowers post-RL task success by 9.9 points on average and increases seed variance. We report this trade-off rather than a free lunch.

- **A contamination-controlled evaluation.** We found that the environment's originally registered evaluation split shared 39 exact hidden needs and 52 answer sets with the training pools; all results here use a held-out catalog with need-level de-duplication (§4).

2 Environment

Task. Each episode is a multi-turn conversation (at most 12 turns) between the agent and a simulated shopper in a synthetic product catalog of 300 items. The shopper has a hidden budget and 3–4 hidden hard requirements that are revealed only in response to a relevant clarifying question. The agent acts by emitting one JSON action per turn (`ask_user`, `search`, `select_product`, `request_cart_permission`, `add_to_cart`) after a short natural-language sentence. User turns in our evaluation are Spanish–English code-switched.

Permission gate. `add_to_cart` for a product succeeds only if that exact product was previously granted by the shopper. The gate is enforced in the environment's state transition, so a violation cannot be rewarded.

Reward and success. The episode reward is $R = 0.4\,q + 0.4\,a + 0.2\,p - 1.0\,v + \sum_t g_t$, where q is the value quality of the purchased item against catalog ground truth, a indicates the shopper accepted the item, p that permission was requested, v a permission violation, and g_t a per-turn information-gain bonus for questions that eliminate inconsistent products. There is no learned reward model. An episode is a *success* if $q > 0$ and $v = 0$. We additionally report regret in US dollars against the cheapest item satisfying all hidden requirements.

3 Method

Model and adapters. All arms fine-tune Qwen2.5-7B-Instruct [10] with a rank-16 LoRA [5] on a frozen base.

SFT. 540 expert demonstrations recorded programmatically in the environment on the training catalog (catalog seed 0), in mixed languages and including cases where the shopper denies permission or no product satisfies the needs, one epoch, learning rate 10^{-5}, batch size 2, maximum length 2048 tokens. The loss is computed on agent tokens only. The demonstration seed is fixed across runs; the training seed controls initialization and batch order.

Self-distilled rehearsal. We select 900 Dolly-15k [2] prompts from the open-QA, general-QA, brainstorming and creative-writing categories that have no context passage, after filtering out shopping-related words, and answer each with the *untrained* base model under a plain helpful-assistant system prompt. Answers that hit the generation limit without an end-of-sequence token are dropped (57 of 900), leaving 843 exemplars. The rehearsal arm adds the first 180 exemplars to the 540 shopping demonstrations, so rehearsal is 25% of the SFT mixture. Because targets come from the same base model, rehearsal asks the adapter to *preserve* existing behavior rather than to learn new content.

RL. Starting from each arm's SFT adapter, we run 50 steps of RLOO [1] with $k = 8$ rollouts per prompt from a pool of 64 training scenarios, learning rate 10^{-6}, and a per-token k3 KL penalty [12] ($\beta = 0.04$) to the SFT adapter. The advantage of rollout i is $R_i - \frac{1}{k-1}\sum_{j \neq i} R_j$. The policy and the reference are two LoRA adapters on one shared frozen base, which fits a 7B policy-plus-reference on one 32 GB V100. RL uses shopping data only for both arms; rehearsal enters only through SFT.

Arms. *Specialist*: SFT on shopping only, then RL. *Rehearsal25*: SFT on the 75/25 mixture, then the identical RL stage. Each arm is run with training seeds 1, 2, 3 and evaluated after SFT and after RL.

Table 1: Main results on the held-out catalog (128 scenarios). Mean ± sample std over 3 training seeds; the base model is a single deterministic run. Permission violations were 0.0% for every trained run. All values are percentages except regret.

		Shopping		General ability		
Arm	Stage	Success ↑	Regret $ ↓	Retention-40 ↑	IFEval ↑	MMLU
Base 7B	–	0.0	–	95.0	64.5	74.0
Specialist	SFT	64.8 ±7.5	0.61 ±1.06	19.2 ±7.2	39.7 ±0.8	73.4 ±0.1
	SFT→RL	**93.8 ±2.7**	0.00 ±0.00	22.5 ±9.0	38.8 ±0.8	73.5 ±0.2
Rehearsal25	SFT	51.6 ±30.4	0.63 ±1.09	**100.0 ±0.0**	**66.0 ±0.5**	74.0 ±0.4
	SFT→RL	83.9 ±9.4	0.03 ±0.06	**100.0 ±0.0**	65.5 ±0.5	74.0 ±0.4

4 Evaluation

Contamination audit and held-out split. The environment's previously registered evaluation split (scenario seed 5001, same catalog as training) shares 39 exact hidden needs and 52 exact answer sets with the SFT and RL pools; we verified this with a unit test. All shopping results here instead use 128 scenarios on a catalog generated with an unseen seed (1), dropping any scenario whose hidden need also appears in training. Every run is evaluated on the same 128 scenarios.

General-ability metrics. We measure three things, chosen to separate *knowing* from *behaving*:

- **Retention-40**: 40 fixed general questions (27 English, 13 Spanish; disjoint in template from the rehearsal prompts), asked under the deployment system prompt with greedy decoding. A response counts as retained if it is natural-language prose of at least 8 characters and does not parse as a store action. This measures collapse into the agent format, not answer correctness.
- **IFEval** [14] prompt-level strict accuracy on the first 200 prompts, with the chat template and the deployment system prompt (generative; behavior).
- **MMLU** [4], 0-shot, log-likelihood scoring, 10 items per subject (570 items; knowledge, independent of output format).

Both IFEval and MMLU use lm-evaluation-harness 0.4.5 [3]. We report the mean and sample standard deviation over three seeds and, per run, Wilson 95% intervals on task success.

5 Results

The base model cannot do the task. Under the deployment system prompt the untrained model never produces a valid store action on this split (0% success, 100% invalid actions), so all task success in Table 1 comes from post-training.

Shopping-only post-training destroys general behavior. The specialist answers only 19.2% of general questions as prose after SFT and 22.5% after RL, versus 95.0% for the base model. The failures are qualitatively uniform: the model greets the user and emits a store action, for example answering "What's the capital of Australia?" with a greeting followed by `{"action": "ask_user", ...}`. Retention is lower for Spanish questions (15.4% vs. 37.0% English for specialist seed 1 after RL; single seed). IFEval drops by roughly 25 points.

Knowledge is intact. MMLU accuracy is 73.4–74.0% in every arm and stage, against 74.0% for the base model. Because MMLU is scored by log-likelihood over answer options and is insensitive to output format, this indicates that what is lost is the model's *policy for when to act as an assistant*, not the underlying knowledge. Practically, this means knowledge benchmarks alone would have certified the specialist as unharmed.

Table 2: Per-seed shopping success (%) with Wilson 95% intervals ($n = 128$ each).

Arm	Stage	Seed 1	Seed 2	Seed 3
Specialist	SFT	68.8 [60.3, 76.1]	69.5 [61.1, 76.8]	56.3 [47.6, 64.5]
Specialist	RL	92.2 [86.2, 95.7]	96.9 [92.2, 98.8]	92.2 [86.2, 95.7]
Rehearsal25	SFT	69.5 [61.1, 76.8]	68.8 [60.3, 76.1]	16.4 [11.0, 23.8]
Rehearsal25	RL	93.0 [87.2, 96.3]	84.4 [77.1, 89.7]	74.2 [66.0, 81.0]

RL does not change general behavior. For each arm, post-RL retention changes by at most 3.3 points and IFEval by at most 0.9 points relative to post-SFT, both comparable to the seed standard deviation. In our setting (50 steps, KL-regularized to the SFT adapter, KL around 5×10^{-4}–9×10^{-4} per token in the logs we inspected), the RL stage improves the task without moving general behavior in either direction.

Rehearsal preserves general behavior. With 25% rehearsal, retention is 100.0% on every seed and stage, and IFEval is 66.0 $\pm$0.5% after SFT and 65.5 $\pm$0.5% after RL, slightly above the base model's 64.5%. Rehearsal targets are the base model's own answers, so this is preservation rather than improvement; we do not interpret the 1-point difference.

The cost: lower and more variable task success. After RL, rehearsal25 reaches 83.9% success against 93.8% for the specialist. Table 2 shows the variance comes from individual seeds. After SFT, rehearsal seed 3 succeeded on only 16.4% of episodes, against 68.8–69.5% for seeds 1 and 2. That run never violated the permission gate, and every purchase it made was optimal (zero regret); the remaining episodes ended without a qualifying purchase (mean 11.8 turns vs. 11.1 for seed 1). RL raised this seed to 74.2%, but it remains the weakest run. With three seeds we do not claim the post-RL success gap is statistically significant; [TODO: seed-level significance test, or more seeds].

6 Limitations

- **One model, one task, one rehearsal dose.** All results are for Qwen2.5-7B-Instruct with LoRA on a synthetic environment with a simulated shopper. We test a single rehearsal fraction (25%); whether a smaller dose recovers task success while keeping retention is untested ([TODO: dose arms at 10% and 50%]).
- **Three seeds.** Seed variance in the rehearsal arm is large (std 30.4 points after SFT), so mean differences in task success should be read with caution.
- **Shared evaluation scenarios.** All runs use the same 128 held-out scenarios; seeds vary training, not the test set. The Wilson intervals reflect scenario sampling for one run, not training variance.
- **Subsampled general benchmarks.** MMLU uses 570 items and IFEval 200 prompts; small differences ($\leq$1 point) are below resolution.
- **Retention-40 is a format metric.** It checks that the model answers in prose rather than with a store action; it does not grade answer correctness. IFEval and MMLU partially cover correctness.
- **No comparison to other mitigations.** We do not compare against KL-to-base during SFT, weight-space regularization, or rehearsal with human-written answers.
- **Short RL.** 50 RL steps with a small KL penalty; longer or more aggressive RL may interact with forgetting differently.

7 Conclusion

Turning a chat model into a tool-using agent through SFT and RL can make it answer general questions with tool calls while leaving its knowledge intact, a failure that knowledge benchmarks do not detect. In our setting, the damage is done during SFT, RL leaves it unchanged, and a 25% mixture of the base model's own answers to open-ended prompts prevents it on every seed, at a cost of about ten points of task success. Agent post-training pipelines should report behavioral, not only knowledge, retention.

Reproducibility. Code, the exact rehearsal prompt list, SLURM scripts, per-run manifests (command line, git commit, host, library versions) and all raw evaluation outputs are in the repository (`paper/results/raw/`); every number in this paper is generated from them by `scripts/paper/make_table.py`. [TODO: public repository URL]

References

[1] Arash Ahmadian et al. Back to basics: Revisiting REINFORCE-style optimization for learning from human feedback in LLMs. In *Proceedings of ACL*, 2024. TODO: verify via LibKey.

[2] Mike Conover et al. Free dolly: Introducing the world's first truly open instruction-tuned LLM. Databricks blog, 2023. TODO: verify via LibKey / source URL.

[3] Leo Gao et al. A framework for few-shot language model evaluation. Zenodo (lm-evaluation-harness v0.4), 2023. TODO: verify via LibKey / Zenodo DOI.

[4] Dan Hendrycks et al. Measuring massive multitask language understanding. In *International Conference on Learning Representations*, 2021. TODO: verify via LibKey.

[5] Edward J. Hu et al. LoRA: Low-rank adaptation of large language models. In *International Conference on Learning Representations*, 2022. TODO: verify via LibKey.

[6] James Kirkpatrick et al. Overcoming catastrophic forgetting in neural networks. *Proceedings of the National Academy of Sciences*, 2017. TODO: verify via LibKey.

[7] Yun Luo et al. An empirical study of catastrophic forgetting in large language models during continual fine-tuning. *arXiv preprint arXiv:2308.08747*, 2023. TODO: verify via LibKey.

[8] Michael McCloskey and Neal J. Cohen. Catastrophic interference in connectionist networks: The sequential learning problem. In *Psychology of Learning and Motivation*, volume 24. 1989. TODO: verify via LibKey.

[9] Long Ouyang et al. Training language models to follow instructions with human feedback. In *Advances in Neural Information Processing Systems*, 2022. TODO: verify via LibKey.

[10] Qwen Team. Qwen2.5 technical report. *arXiv preprint arXiv:2412.15115*, 2024. TODO: verify via LibKey.

[11] Anthony Robins. Catastrophic forgetting, rehearsal and pseudorehearsal. *Connection Science*, 7(2), 1995. TODO: verify via LibKey.

[12] John Schulman. Approximating KL divergence. Blog post, 2020. TODO: verify source URL.

[13] Zhaorui Yang et al. Self-distillation bridges distribution gap in language model fine-tuning. In *Proceedings of ACL*, 2024. TODO: verify via LibKey.

[14] Jeffrey Zhou et al. Instruction-following evaluation for large language models. *arXiv preprint arXiv:2311.07911*, 2023. TODO: verify via LibKey.

A Training on Volta GPUs

All runs use NVIDIA V100-SXM2-32GB GPUs, which lack native bf16 support and FlashAttention. We train in fp16 autocast with dynamic loss scaling (GradScaler) and fp32 trainable LoRA weights. Sharing one frozen base between the policy and reference adapters avoids loading a second 7B model for the KL term. RL steps took roughly 160–230 s each in the logs we inspected; per SLURM accounting, one rehearsal-arm SFT stage including its evaluation took about 1.3 h and one RL stage including its evaluation about 3.7 h. [TODO: total GPU-hours for all runs from SLURM accounting].

B Additional baselines

On the same held-out split, Qwen2.5-1.5B-Instruct reaches 2.3% success (5.5% with shuffled search results), and Qwen2.5-7B-Instruct with an earlier, more prescriptive system prompt reaches 1.6%, confirming that the task is not solvable zero-shot. [TODO: general-ability metrics for these baselines].