

Reverse a linked list in groups of size k

Given a linked list, write a function to reverse every k nodes (where k is an input to the function).

Example:

Input: 1->2->3->4->5->6->7->8->NULL, K = 3

Output: 3->2->1->6->5->4->8->7->NULL

Input: 1->2->3->4->5->6->7->8->NULL, K = 5


Output: 5->4->3->2->1->8->7->6->NULL

- Reverse the first sub-list of size k. While reversing keep track of the next node and previous node. Let the pointer to the next node be *next* and pointer to the previous node be *prev*. See [this post](#) for reversing a linked list.
- *head->next = reverse(next, k)* (Recursively call for rest of the list and link the two sub-lists)
- Return *prev* (*prev* becomes the new head of the list (see the diagrams of an iterative method of [this post](#))

Below is image shows how the reverse function works:



Dash


 All


Below is the implementation of the above approach:

C++

Java

```
// Java program to reverse a linked list in groups of
// given size
class LinkedList {
    Node head; // head of list

    /* Linked list Node*/
    class Node {
        int data;
        Node next;
        Node(int d)
        {
            data = d;
            next = null;
        }
    }
}
```

Menu

Track Progress

97 of 132 Complete. (74%)

{

Dash



All

Node **next** = null;Node **prev** = null;

Articles

int **count** = 0;

Videos

/* Reverse first k nodes of linked list */

while (**count** < **k** && **current** != null) { **next** = **current.next**;

Problems

current.next = **prev**; **prev** = **current**; **current** = **next**; **count**++;

Quiz

}



Contest

/* **next** is now a pointer to (k+1)th node

Recursively call for the list starting from

current. And make rest of the list as next of

first node */

if (**next** != null) **head.next** = reverse(**next**, **k**);// **prev** is now head of input listreturn **prev**;

}

/* Utility functions */

/* Inserts a new Node at front of the list. */

public void push(int **new_data**)

{

/* 1 & 2: Allocate the Node &

Put in the data*/

 Node **new_node** = new Node(**new_data**);

/* 3. Make next of new Node as head */

new_node.next = **head**;

Menu

Track Progress

97 of 132 Complete. (74%)

Dash



Articles



Videos



Problems



Quiz



Contest

```
{
    Node temp = head;
    while (temp != null) {
        System.out.print(temp.data + " ");
        temp = temp.next;
    }
    System.out.println();
}

/* Driver program to test above functions */
public static void main(String args[])
{
    LinkedList llist = new LinkedList();

    /* Constructed Linked List is 1->2->3->4->5->6->
    7->8->8->9->null */
    llist.push(9);
    llist.push(8);
    llist.push(7);
    llist.push(6);
    llist.push(5);
    llist.push(4);
    llist.push(3);
    llist.push(2);
    llist.push(1);

    System.out.println("Given Linked List");
    llist.printList();

    llist.head = llist.reverse(llist.head, 3);

    System.out.println("Reversed list");
    llist.printList();
}
```

Menu

Track Progress

97 of 132 Complete. (74%)

Dash

Given linked list



Articles

Complexity Analysis:

- **Time Complexity:** $O(n)$.

Traversal of list is done only once and it has 'n' elements.

- **Auxiliary Space:** $O(n/k)$.

For each Linked List of size n, n/k or $(n/k)+1$ calls will be made during the recursion.



Problems

We can solve this question in $O(1)$ Space Complexity.

**Approach – 2 Space Optimized – Iterative**

Quiz

The following steps are required for this Algorithm:



1. Create a dummy node and point it to the head of input i.e dummy->next = head.
2. Calculate the length of the linked list which takes $O(N)$ time, where N is the length of the linked list.
3. Initialize three-pointers prev, curr, next to reverse k elements for every group.
4. Iterate over the linked lists till next!=NULL.
5. Points curr to the prev->next and next to the curr next.
6. Then, Using the inner for loop reverse the particular group using these four steps:

- $curr \rightarrow next = next \rightarrow next$
- $next \rightarrow next = prev \rightarrow next$
- $prev \rightarrow next = next$
- $next = curr \rightarrow next$

7. This for loop runs for k-1 times for all groups except the last remaining element, for the last remaining element it runs for the remaining length of the linked list - 1.

8. Decrement count after for loop by k count -= k, to determine the length of the remaining linked list.

9. Change prev position to curr, prev = curr.

Track Progress

97 of 132 Complete. (74%)

C++

Java



All

// Linked List Node

class Node {

int data;

Node next;

Node(int a)

{

data = a;

next = null;

}

}

class GFG {

// utility function to insert node in the list

static Node push(Node head, int val)

{

Node newNode = new Node(val);

if (head == null) {

head = newNode;

return head;

}

Node temp = head;

while (temp.next != null)

temp = temp.next;

temp.next = newNode;

return head;

}

// utility function to reverse k nodes in the list

static Node reverse(Node head, int k)

{

// If head is NULL or K is 1 then return head

if (head == null || head.next == null)

return head;



Articles



Videos



Problems



Quiz



Geotest



Menu

Track Progress

97 of 132 Complete. (74%)

`dummy.next = head;`

Dash



All

`Node curr = dummy;``Node next = dummy;`

Articles

`// Calculating the length of linked list``int count = 0;``while (curr != null) {` `count++;` `curr = curr.next;``}`

Videos



Problems

`// Iterating till next is not NULL``while (next != null) {` `curr = prev.next; // Curr position after every` `// reverse group` `next = curr.next; // Next will always next to` `// curr``int toLoop` `= count > k` `? k` `: count - 1; // toLoop will set to` `// count - 1 in case of` `// remaining element``for (int i = 1; i < toLoop; i++) {` `// 4 steps as discussed above` `curr.next = next.next;` `next.next = prev.next;` `prev.next = next;` `next = curr.next;``}``prev = curr; // Setting prev to curr``count -= k; // Update count``}``return dummy.next; // dummy -> next will be our new` `// head for output linked``// list``}`

Menu

Track Progress

97 of 132 Complete. (74%)

90% Money-Back!

Courses

Tutorials

Jobs

Practice

Contests

Dash

All

System.out.println(head.data);

public static void main(String args[])

{

Node head = null;

int k = 3;

head = push(head, 1);

head = push(head, 2);

head = push(head, 3);

head = push(head, 4);

head = push(head, 5);

head = push(head, 6);

head = push(head, 7);

head = push(head, 8);

head = push(head, 9);

System.out.println("Given Linked List");

print(head);

System.out.println("Reversed list");

Node newHead = reverse(head, k);

print(newHead);

}

}

Problems

Quiz

Contest

Videos

Problems

Quiz

Contest

P

Output

```
Given linked list
1 2 3 4 5 6 7 8 9
Reversed Linked list
3 2 1 6 5 4 9 8 7
```

Menu

Complexity Analysis

Track Progress

97 of 132 Complete. (74%)

<https://www.geeksforgeeks.org/batch/dsa-4/track/DSASP-LinkedList/article/NzMwMQ%3D%3D>

8/9

Space Complexity: $O(1)$: No extra space is used.



Articles
Report An Issue

If you are facing any issue on this page. Please let us know.



Videos



Problems



Quiz



Contest



Menu



Track Progress
97 of 132 Complete. (74%)