

Find a Peak Element

Introduction

In this problem, we are given an array of unsorted integers . Our task is to find a peak element in the array. A peak element is an element whose neighbors have value smaller than that of the element.



Note: For corner elements, we need to consider only one neighbor.

Example:

Input: `array[] = {5, 10, 20, 15}`

Output: 20

Explanation: The element 20 has neighbors 10 and 15, both of them are less than 20.

Input: `array[] = {10, 20, 15, 2, 23, 90, 67}`

Output: 20 or 90

Explanation: The element 20 has neighbors 10 and 15, both of them are less than 20, similarly 90 has neighbors 23 and 67.

Naive Approach:

The idea is to traverse the array and return the element that has higher value than its neighbors.

Steps:

- If the element at index 0 is greater than the element at index 1, return `arr[0]`.
- If the element at index `n-1` is greater than the element at index `n-2`, return `arr[n-1]`.
- If none of the above cases prevail, we traverse the remaining elements and check for a peak element.

Below is the implementation of above idea.

C++

Java

Track Progress

31 of 60 Complete. (52%)

Dash



All

```
int getPeak(int arr[], int n)
```

```
{
```

```
    if(n == 1)
```

```
        return arr[0];
```

```
    if(arr[0] >= arr[1])
```

```
        return arr[0];
```

```
    if(arr[n - 1] >= arr[n - 2])
```

```
        return arr[n - 1];
```

```
    for(int i = 1; i < n - 1; i++)
```

```
        if(arr[i] >= arr[i - 1] && arr[i] >= arr[i + 1])
```

```
            return arr[i];
```

```
}
```

```
int main() {
```

```
    int arr[] = {5, 10, 7, 8, 20, 12}, n = 6;
```

```
    cout << getPeak(arr, n);
```

```
    return 0;
```

```
}
```



Articles



Videos



Problems



Quiz



Contest



Output

10

Time Complexity: $O(N)$, Where n is the number of elements in the input array.

Auxiliary Space: $O(1)$.

Find a peak element using iterative Binary search

Menu

The interesting fact about using Binary search in this unsorted array problem is that if the element to the left of the mid element is greater, then a peak will definitely be present in the left part of the array.

Track Progress

31 of 60 Complete. (52%)

would be present in the right of the array. We will be using this logic to



- We calculate the mid as $(low+high)/2$ where low is the lower bound and high is the upper bound of the array.
- We run a loop while low is lesser than or equal to high.
- We check the condition : If the mid is 0 or arr [mid-1] is smaller than arr[mid] and if mid is n-1 and arr[mid+1] is smaller than arr[mid], we return mid.
- If mid is greater than 0 and arr[mid-1] is greater than arr[mid] , we update high to mid-1.
- If both the conditions do not prevail, we update low to mid+1.

Courses

Tutorials

Jobs

Practice

Contests



```
#include <iostream>
using namespace std;
```

```
int getPeak(int arr[], int n)
{
    int low = 0, high = n - 1;

    while(low <= high)
    {
        int mid = (low + high) / 2;

        if((mid == 0 || arr[mid - 1] <= arr[mid]) &&
            (mid == n - 1 || arr[mid + 1] <= arr[mid]))
            return mid;
        if(mid > 0 && arr[mid - 1] >= arr[mid])
            high = mid - 1;
        else
            low = mid + 1;
    }
    return -1;
}
```

Menu

Track Progress

31 of 60 Complete. (52%)

```
int arr[] = {5, 20, 40, 30, 20, 50, 60}, n = 7;
```



```
return 0;  
}
```



Time Complexity: $O(\log N)$, Where n is the number of elements in the input array.
Auxiliary Space: $O(1)$, No extra space is required, so the space complexity is constant.



Mark as Read



Report An Issue

If you are facing any issue on this page. Please let us know.



Contest

Menu



Track Progress
31 of 60 Complete. (52%)