

Index of first Occurrence and last Occurrence in Sorted

Given a sorted array `arr[]` with possibly duplicate elements, the task is to find indexes of the first and last occurrences of an element `x` in the given array.



Examples:

Input : `arr[] = {1, 3, 5, 5, 5, 5, 67, 123, 125}`, `x = 5`

Output : First Occurrence = 2

Last Occurrence = 5

Input : `arr[] = {1, 3, 5, 5, 5, 5, 7, 123, 125 }`, `x = 7`

Output : First Occurrence = 6

Last Occurrence = 6

A Naive Approach:

The idea to solve this problem is iterate on the elements of given array and check given elements in an array and keep track of **first** and **last** occurrence of the found element's index.

Below are the steps to implement the above idea:

- Run a for loop and for `i = 0` to `n-1`
- Take `first = -1` and `last = -1`
- When we find an element first time then we update `first = i`
- We always update `last=i` whenever we find the element.
- We print `first` and `last`.

Below is the implementation of the above approach:

C++

Java

```
// C++ program to find first and last occurrence of
```

Track Progress

Courses

Tutorials



Jobs

Practice

Contests

using namespace std;

Dash



All

void findFirstAndLast(int arr[], int n, int x)

{

int first = -1, last = -1;

for (int i = 0; i < n; i++) {

if (x != arr[i])

continue;

if (first == -1)

first = i;

last = i;

}

if (first != -1)

cout << "First Occurrence = " << first

<< "\nLast Occurrence = " << last;

else

cout << "Not Found";

}

// Driver code

int main()

{

int arr[] = { 1, 2, 2, 2, 2, 3, 4, 7, 8, 8 };

int n = sizeof(arr) / sizeof(int);

int x = 8;

findFirstAndLast(arr, n, x);

return 0;

}



Articles



Videos



Problems



Quiz



Contest



Output

First Occurrence = 8

Last Occurrence = 9



Menu

Time Complexity: O(n)

Track Progress

15 of 60 Complete. (25%)

An efficient approach using binary search:



a) If ($high \geq low$)
 b) Calculate $mid = low + (high - low) / 2$;
 c) If ($(mid == 0 \parallel x > arr[mid-1]) \&\& arr[mid] == x$)
 return mid ;
 d) Else if ($x > arr[mid]$)
 return $first(arr, (mid + 1), high, x, n)$;
 e) Else
 return $first(arr, low, (mid - 1), x, n)$;
 f) Otherwise return -1;



Videos



Problems



Quiz

2. For the last occurrence of a number

a) if ($high \geq low$)
 b) calculate $mid = low + (high - low) / 2$;
 c) if ($(mid == n-1 \parallel x < arr[mid+1]) \&\& arr[mid] == x$)
 return mid ;
 d) else if ($x < arr[mid]$)
 return $last(arr, low, (mid - 1), x, n)$;
 e) else
 return $last(arr, (mid + 1), high, x, n)$;
 f) otherwise return -1;



Contests

Below is the implementation of the above approach:

C++

Java

```
// C++ program to find first and last occurrences of
// a number in a given sorted array
#include <bits/stdc++.h>
using namespace std;

/* if x is present in arr[] then returns the index of
FIRST occurrence of x in arr[0..n-1], otherwise
returns -1 */
int first(int arr[], int low, int high, int x, int n)
```

Menu

Track Progress

15 of 60 Complete. (25%)

```
if ((mid == 0 || x > arr[mid - 1]) && arr[mid] == x)
```



```
else
```

```
return first(arr, low, (mid - 1), x, n);
```

```
}
```

```
return -1;
```

```
}
```



Videos

```
/* if x is present in arr[] then returns the index of
LAST occurrence of x in arr[0..n-1], otherwise
returns -1 */
```

```
int last(int arr[], int low, int high, int x, int n)
```

```
{
```

```
if (high >= low) {
```

```
int mid = low + (high - low) / 2;
```

```
if ((mid == n - 1 || x < arr[mid + 1])
```

```
&& arr[mid] == x)
```

```
return mid;
```

```
else if (x < arr[mid])
```

```
return last(arr, low, (mid - 1), x, n);
```

```
else
```

```
return last(arr, (mid + 1), high, x, n);
```

```
}
```

```
return -1;
```

```
}
```

```
// Driver program
```

```
int main()
```

```
{
```

```
int arr[] = { 1, 2, 2, 2, 2, 3, 4, 7, 8, 8 };
```

```
int n = sizeof(arr) / sizeof(int);
```

```
int x = 8;
```

```
printf("First Occurrence = %d\t",
```

```
first(arr, 0, n - 1, x, n));
```

```
printf("\nLast Occurrence = %d\n",
```

```
last(arr, 0, n - 1, x, n));
```

```
return 0;
```

```
}
```

Menu

Track Progress

15 of 60 Complete. (25%)

Dash



First Occurrence = 8

Last Occurrence = 9



Articles

Time Complexity: $O(\log n)$ **Auxiliary Space:** $O(1)$ 

Videos

An Iterative Implementation of Binary Search Solution :



Problems



1. For the **first occurrence**, we will first find the index of the number and then search again in the left subarray as long as we are finding the number.

Quiz



Contest

2. For the **last occurrence**, we will first find the index of the number and then search again in the right subarray as long as we are finding the number

First occurrence:

- Do while low \leq high:
 - First, find the mid element
 - Check if the $\text{arr}[\text{mid}] > x$ then the first element will occur on the left side of mid. So, bring the high pointer to mid - 1
 - Check if the $\text{arr}[\text{mid}] < x$ then the first element will occur on the right side of mid. So, bring the low pointer to mid + 1
 - If $\text{arr}[\text{mid}] == x$ then this may be the first element. So, update the result to mid and move the high pointer to mid - 1.
- Return the result.

Last occurrence:

- Do while low \leq high:
 - First, find the mid element
 - Check if the $\text{arr}[\text{mid}] > x$ then the last element will occur on the left side of mid. So, bring the low pointer to mid - 1

Menu



Track Progress

15 of 60 Complete. (25%)

- If `arr[mid] == x` then this may be the last element. So, update the result



Below is the implementation of the above approach:



Articles

C++

Java



Videos

// C++ program to find first and last occurrences
// of a number in a given sorted array

#include <bits/stdc++.h>

using namespace std;



Problems

/* if x is present in arr[] then returns the
index of FIRST occurrence of x in arr[0..n-1],
otherwise returns -1 */



Quiz

int first(int arr[], int x, int n)

{



Contest

int low = 0, high = n - 1, res = -1;

while (low <= high) {

// Normal Binary Search Logic

int mid = (low + high) / 2;

if (arr[mid] > x)

high = mid - 1;

else if (arr[mid] < x)

low = mid + 1;

// If arr[mid] is same as x, we

// update res and move to the left

// half.

else {

res = mid;

high = mid - 1;

}

}

return res;

}

/* If x is present in arr[] then returns



Menu

Track Progress

15 of 60 Complete. (25%)

```
int last(int arr[], int x, int n)
```

Dash



All

// Normal Binary Search Logic



Articles

```
int mid = (low + high) / 2;
```

```
if (arr[mid] > x)
```



Videos

```
    high = mid - 1;
```

```
else if (arr[mid] < x)
```



Problems

```
    low = mid + 1;
```

```
// If arr[mid] is same as x, we
```

```
// update res and move to the right
```



Quiz

```
// half.
```

```
else {
```

```
    res = mid;
```



Contest

```
    low = mid + 1;
```

```
}
```

```
}
```

```
return res;
```

```
}
```

```
// Driver code
```

```
int main()
```

```
{
```

```
    int arr[] = { 1, 2, 2, 2, 2, 3, 4, 7, 8, 8 };
```

```
    int n = sizeof(arr) / sizeof(int);
```

```
    int x = 8;
```

```
    cout << "First Occurrence = " << first(arr, x, n);
```

```
    cout << "\nLast Occurrence = " << last(arr, x, n);
```

```
    return 0;
```

```
}
```

Menu

Track Progress

15 of 60 Complete. (25%)

Dash

First Occurrence = 8



All

Auxiliary Space: $O(1)$



Articles



Videos

Marked as Read

 Report An Issue



If you are facing any issue on this page. Please let us know.

Problems



Quiz



Contest



Menu



Track Progress

15 of 60 Complete. (25%)