



Binary Search (Recursive)

Problem: Given a sorted array `arr[]` of `n` elements, write a function to search a given element `x` in `arr[]` and return the index of `x` in the array.

Consider array is 0 base index.



Examples:

Input: `arr[] = {10, 20, 30, 50, 60, 80, 110, 130, 140, 170}`, `x = 110`

Output: 6

Explanation: Element `x` is present at index 6.

Input: `arr[] = {10, 20, 30, 40, 60, 110, 120, 130, 170}`, `x = 175`

Output: -1

Explanation: Element `x` is not present in `arr[]`.

Binary Search Approach:

Binary Search is a searching algorithm used in a sorted array by **repeatedly dividing the search interval in half**. The idea of binary search is to use the information that the array is sorted and reduce the time complexity to $O(\log n)$.

Binary Search Algorithm: The basic steps to perform Binary Search are:

- Begin with the mid element of the whole array as a search key.
- If the value of the search key is equal to the item then return an index of the search key.
- Or if the value of the search key is less than the item in the middle of the interval, narrow the interval to the lower half.
- Otherwise, narrow it to the upper half.
- Repeatedly check from the second point until the value is found or the interval is empty.

```
high = mid - 1
```

Track Progress

4 of 60 Complete. (7%)

binarySearch(arr, x, low, high)

Dash

All

else

mid = (low + high) / 2

if x == arr[mid]

return mid

else if x > arr[mid]

// x is on the right side

return binarySearch(arr, x, mid + 1, high)

else

// x is on the left side

return binarySearch(arr, x, low, mid - 1)

Illustration of Binary Search Algorithm: Quiz

Binary Search

	0	1	2	3	4	5	6	7	8	9
Search 23	2	5	8	12	16	23	38	56	72	91
23 > 16 take 2 nd half	L=0	1	2	3	M=4	5	6	7	8	H=9
23 < 56 take 1 st half	0	1	2	3	4	L=5	6	M=7	8	H=9
Found 23, Return 5	0	1	2	3	4	L=5, M=5	H=6	7	8	9

Example of Binary Search Algorithm

Step-by-step Binary Search Algorithm: We basically ignore half of the elements just after one comparison.

1. Compare x with the middle element.
2. If x matches with the middle element, we return the mid index.
3. Else If x is greater than the mid element, then x can only lie in the right half subarray after the mid element. So we recur for the right half.
4. Else (x is smaller) recur for the left half.

Menu

Track Progress

4 of 60 Complete. (7%)

C++

Java



Articles



Videos



Problems



Quiz



Contest

```
#include <bits/stdc++.h>
```

```
using namespace std;
```

```
// A recursive binary search function. It returns
```

```
// location of x in given array arr[l..r] is present,
```

```
// otherwise -1
```

```
int binarySearch(int arr[], int l, int r, int x)
```

```
{
```

```
    if (r >= l) {
```

```
        int mid = l + (r - l) / 2;
```

```
        // If the element is present at the middle
```

```
        // itself
```

```
        if (arr[mid] == x)
```

```
            return mid;
```

```
        // If element is smaller than mid, then
```

```
        // it can only be present in left subarray
```

```
        if (arr[mid] > x)
```

```
            return binarySearch(arr, l, mid - 1, x);
```

```
        // Else the element can only be present
```

```
        // in right subarray
```

```
        return binarySearch(arr, mid + 1, r, x);
```

```
    }
```

```
    // We reach here when element is not
```

```
    // present in array
```

```
    return -1;
```

```
}
```

```
int main(void)
```

```
{
```

```
    int arr[] = { 2, 3, 4, 10, 40 };
```

```
    int x = 10;
```

```
    int n = sizeof(arr) / sizeof(arr[0]);
```

```
    int result = binarySearch(arr, 0, n - 1, x);
```

Menu

Track Progress

4 of 60 Complete. (7%)

```
: cout << "Element is present at index " << result;
```



Articles

Output

Element is present at index 3



Videos

Time Complexity: $O(\log n)$
Auxiliary Space: $O(\log n)$



Problems



Quiz

Marked as Read



Contest

Report An Issue

If you are facing any issue on this page. Please let us know.



Menu

Track Progress
4 of 60 Complete. (7%)