
What answers has your team already earned?

Start with questions stakeholders ask every week and incident reviews your engineers have already closed. Those are the beginnings of a golden dataset.

Write one golden case together

Question: What was activation in the mature after period?

Approved answer: 370 of 1,000 eligible accounts, or 37%.



370 OF 1,000 = 37%

Save the question, snapshot, owner, calculation and acceptable tolerance. Keep the answer key with the reviewer.

A past RCA needs a different kind of answer

“Did R17 cause the decline?” has no approved percentage for the release effect.

The review established a shift in population mix.

An acceptable answer leaves causality open and asks for a credible exposure comparison.

Give the agent the questions.
Hold back the answers.

Run python3 golden_eval.py prepare ../blind-eval-1. Open that folder in a clean chat.

Save the complete replies. Run the identical request in two more clean sessions so you can compare all three.

Score correctness and agreement separately

Did the counts match? Did the agent cite a source that supports the decision? Did all three runs choose the same action?

Three identical wrong answers would score perfectly on agreement.

Which version would you ship?

In the separate eight-request comparison, A gets 6/8 routes right. B gets 7/8.



A · 6/8



B · 7/8

Read B’s actual replies to E05, E06 and E07 before voting.

When good reviewers disagree

One analyst selects Review for a misleading board footnote. Another refuses the causal wording and supplies a supported replacement.

Decide whether the request must enter a human queue. Record the decision before changing the gold key.