# Would you trust an agent with Monday's report?

Think of your agent as a new grad with infinite energy who wants to please you. How does your business count a customer? When should it push back? And if someone else asks tomorrow, will they get the same answer?

# Did the store keep its promise?

The store promised a complete desk by Friday. It ships in three boxes. Two arrive Friday. The box with the legs arrives Monday.

Carrier: 2 of **3 boxes** arrived on time (67%).

Store: 0 of **1 complete orders** arrived on time (0%).

To decide whether to credit the customer for a missed delivery promise, count complete orders.

# Teach it to challenge you

The engineering lead must decide whether to keep R17 running. Ask the agent why the release helped. If it claims a gain, ask who saw R17 and what happened to comparable accounts that did not.

# Give two analysts the same job

Growth needs one number for Monday. Ask two clean chats for the active rate. If either silently picks a period or definition, ask Growth to specify both. Then recompute the counts.

# Write down what ‘activated’ means

Count eligible accounts that activated at least once within seven days. One account can retry an import several times. Decide which of those events belong in the numerator.

# Build your first semantic model

Open starter/model.json. Name the source, describe what one row represents, write the calculation and identify the person who can approve a change. Save your reviewed copy in work/model.json.

# Try to break your definition

If no accounts were eligible, Product Data should approve a blank rate labeled 'no eligible accounts'. Run the model check. A displayed 0% would tell Growth that eligible accounts tried and none activated. Correct the expression before publishing.