

Theorem Proving

Three important concepts for Logical Inference

Horn Clauses

- * A disjunction in which at most one literal is positive
- * Equivalent in form to an implication
- * Example

$$\neg L_{1,1} \vee \neg Breeze \vee B_{1,1} \Rightarrow (L_{1,1} \wedge Breeze) \Rightarrow B_{1,1}$$

$$P_{1,1} \vee \neg P_{2,1} \vee B_{1,2}$$

Inference Algorithms: Forward and Backward Chaining

Forward and Backward Chaining

Horn Form (restricted)

KB = **conjunction** of **Horn clauses**

Horn clause =

◇ proposition symbol; or

◇ (conjunction of symbols) \Rightarrow symbol

E.g., $C \wedge (B \Rightarrow A) \wedge (C \wedge D \Rightarrow B)$

- * Restrict sentences to be written a particular way
- * Only need one inference rule in your search for entailment

Forward and Backward Chaining

Horn Form (restricted)

KB = **conjunction** of **Horn clauses**

Horn clause =

- ◇ proposition symbol; or
- ◇ (conjunction of symbols) \Rightarrow symbol

E.g., $C \wedge (B \Rightarrow A) \wedge (C \wedge D \Rightarrow B)$

Modus Ponens (for Horn Form): complete for Horn KBs

$$\alpha_1, \dots, \alpha_n, \quad \alpha_1 \wedge \dots \wedge \alpha_n \Rightarrow \beta$$

Can be used with **forward chaining** or **backward chaining**.
These algorithms are very natural and run in **linear** time

Forward Chaining

Idea: fire any rule whose premises are satisfied in the *KB*,
add its conclusion to the *KB*, until query is found

$$P \Rightarrow Q$$

$$L \wedge M \Rightarrow P$$


$$B \wedge L \Rightarrow M$$

$$A \wedge P \Rightarrow L$$

$$A \wedge B \Rightarrow L$$

A

B




Forward Chaining

```
function PL-FC-ENTAILS?(KB, q) returns true or false
  inputs: KB, the knowledge base, a set of propositional Horn clauses
         q, the query, a proposition symbol
  local variables: count, a table, indexed by clause, initially the number of premises
                  inferred, a table, indexed by symbol, each entry initially false
                  agenda, a list of symbols, initially the symbols known in KB

  while agenda is not empty do
    p ← POP(agenda)
    unless inferred[p] do
      inferred[p] ← true
      for each Horn clause c in whose premise p appears do
        decrement count[c]
        if count[c] = 0 then do
          if HEAD[c] = q then return true
          PUSH(HEAD[c], agenda)

  return false
```

Forward chaining example



$$P \Rightarrow Q$$

$$L \wedge M \Rightarrow P$$

$$B \wedge L \Rightarrow M$$


$$A \wedge P \Rightarrow L$$

$$A \wedge B \Rightarrow L$$

A

B

Forward chaining example



$$P \Rightarrow Q$$

$$L \wedge M \Rightarrow P$$

$$B \wedge L \Rightarrow M$$


$$A \wedge P \Rightarrow L$$

$$A \wedge B \Rightarrow L$$

A

B

Forward chaining example



$$P \Rightarrow Q$$

$$L \wedge M \Rightarrow P$$

$$B \wedge L \Rightarrow M$$

$$A \wedge P \Rightarrow L$$


$$A \wedge B \Rightarrow L$$

A

B

L

Forward chaining example



$$P \Rightarrow Q$$

$$L \wedge M \Rightarrow P$$

$$B \wedge L \Rightarrow M$$

$$A \wedge P \Rightarrow L$$


$$A \wedge B \Rightarrow L$$

A

B

L

Forward chaining example



$$P \Rightarrow Q$$

$$L \wedge M \Rightarrow P$$

$$B \wedge L \Rightarrow M$$

$$A \wedge P \Rightarrow L$$

$$A \wedge B \Rightarrow L$$


A

B

L

M

Forward chaining example



$$P \Rightarrow Q$$

$$L \wedge M \Rightarrow P$$

$$B \wedge L \Rightarrow M$$

$$A \wedge P \Rightarrow L$$

$$A \wedge B \Rightarrow L$$

A


B

L

M

P

Forward chaining example



$$P \Rightarrow Q$$

$$L \wedge M \Rightarrow P$$

$$B \wedge L \Rightarrow M$$

$$A \wedge P \Rightarrow L$$

$$A \wedge B \Rightarrow L$$

A


B

L

M

P

Forward chaining example



$$P \Rightarrow Q$$

$$L \wedge M \Rightarrow P$$

$$B \wedge L \Rightarrow M$$

$$A \wedge P \Rightarrow L$$

$$A \wedge B \Rightarrow L$$

A

B

L

M

P

Q

Proof of Completeness

FC derives every atomic sentence that is entailed by KB

1. FC reaches a **fixed point** where no new atomic sentences are derived
2. Consider the final state as a model m , assigning true/false to symbols
3. Every clause in the original KB is true in m

Proof: Suppose a clause $a_1 \wedge \dots \wedge a_k \Rightarrow b$ is false in m

Then $a_1 \wedge \dots \wedge a_k$ is true in m and b is false in m

Therefore the algorithm has not reached a fixed point!

4. Hence m is a model of KB
5. If $KB \models q$, q is true in **every** model of KB , including m

General idea: construct any model of KB by sound inference, check α

Backward Chaining

Idea: work backwards from the query q :

- to prove q by BC,

- check if q is known already, or

- prove by BC all premises of some rule concluding q


Avoid loops: check if new subgoal is already on the goal stack

Avoid repeated work: check if new subgoal


- 1) has already been proved true, or

- 2) has already failed


Backward chaining example




Backward chaining example




Backward chaining example




Backward chaining example




Backward chaining example




Backward chaining example




Backward chaining example




Backward chaining example




Backward chaining example



Backward chaining example



Backward chaining example



Forward vs. Backward Chaining

FC is **data-driven**, cf. automatic, unconscious processing,
e.g., object recognition, routine decisions

May do lots of work that is irrelevant to the goal

BC is **goal-driven**, appropriate for problem-solving,
e.g., Where are my keys? How do I get into a PhD program?

Complexity of BC can be **much less** than linear in size of KB

Inference Algorithms: Resolution

Resolution

Conjunctive Normal Form (CNF—universal)

conjunction of **disjunctions of literals**
clauses

E.g., $(A \vee \neg B) \wedge (B \vee \neg C \vee \neg D)$

Resolution

Conjunctive Normal Form (CNF—universal)

conjunction of **disjunctions** of **literals**
clauses

E.g., $(A \vee \neg B) \wedge (B \vee \neg C \vee \neg D)$


Resolution inference rule (for CNF): complete for propositional logic

$$\frac{l_1 \vee \dots \vee l_k, \quad m_1 \vee \dots \vee m_n}{l_1 \vee \dots \vee l_{i-1} \vee l_{i+1} \vee \dots \vee l_k \vee m_1 \vee \dots \vee m_{j-1} \vee m_{j+1} \vee \dots \vee m_n}$$

where l_i and m_j are complementary literals. E.g.,

$$\frac{P_{1,3} \vee P_{2,2}, \quad \neg P_{2,2}}{P_{1,3}}$$

Resolution is sound and complete for propositional logic



Resolution Algorithm

Proof by contradiction, i.e., show $KB \wedge \neg\alpha$ unsatisfiable

Resolution Algorithm

Proof by contradiction, i.e., show $KB \wedge \neg\alpha$ unsatisfiable

```
function PL-RESOLUTION( $KB, \alpha$ ) returns true or false
  inputs:  $KB$ , the knowledge base, a sentence in propositional logic
          $\alpha$ , the query, a sentence in propositional logic

   $clauses \leftarrow$  the set of clauses in the CNF representation of  $KB \wedge \neg\alpha$ 
   $new \leftarrow \{ \}$ 
  loop do
    for each  $C_i, C_j$  in  $clauses$  do
       $resolvents \leftarrow$  PL-RESOLVE( $C_i, C_j$ )
      if  $resolvents$  contains the empty clause then return true
       $new \leftarrow new \cup resolvents$ 
  if  $new \subseteq clauses$  then return false
   $clauses \leftarrow clauses \cup new$ 
```

Resolution Example

$$KB = (B_{1,1} \Leftrightarrow (P_{1,2} \vee P_{2,1})) \wedge \neg B_{1,1} \quad \alpha = \neg P_{1,2}$$

$$\neg P_{2,1} \vee B_{1,1}$$

$$\neg B_{1,1} \vee P_{1,2} \vee P_{2,1}$$


$$\neg P_{1,2} \vee B_{1,1}$$

$$\neg B_{1,1}$$

$$P_{1,2}$$

Resolution Example


$$KB = (B_{1,1} \Leftrightarrow (P_{1,2} \vee P_{2,1})) \wedge \neg B_{1,1} \quad \alpha = \neg P_{1,2}$$



Note: Typo!! This should be $\neg P_{2,1}$

Resolution Example


$$KB = (B_{1,1} \Leftrightarrow (P_{1,2} \vee P_{2,1})) \wedge \neg B_{1,1} \quad \alpha = \neg P_{1,2}$$



Note: Typo!! This should be $\neg P_{2,1}$

Resolution Example


$$KB = (B_{1,1} \Leftrightarrow (P_{1,2} \vee P_{2,1})) \wedge \neg B_{1,1} \quad \alpha = \neg P_{1,2}$$



Note: Typo!! This should be $\neg P_{2,1}$

Resolution Example


$$KB = (B_{1,1} \Leftrightarrow (P_{1,2} \vee P_{2,1})) \wedge \neg B_{1,1} \quad \alpha = \neg P_{1,2}$$



Note: Typo!! This should be $\neg P_{2,1}$

Resolution Example

$$KB = (B_{1,1} \Leftrightarrow (P_{1,2} \vee P_{2,1})) \wedge \neg B_{1,1} \quad \alpha = \neg P_{1,2}$$



Note: Typo!! This should be $\neg P_{2,1}$

Contradiction, therefore our sentence is entailed.