



Dimensional & Pressure Details

VRV/VRF COPPER TUBES AS PER JIS H3300

Ø Size (inches)	Ø Size (mm)	Temper	Thickness (mm)	≈Thickness (SWG)	Weight per Ft. (KG)	Weight per Mtr. (KG)	Max Working Pressure (MPa)	Bursting pressure (MPa)
1/4"	6.35	HARD	0.80	21	0.039	0.125	44.14	88.27
3/8"	9.53		0.80	21	0.061	0.197	28.35	56.69
1/2"	12.70		0.80	21	0.082	0.268	20.90	41.79
5/8"	15.88		0.80	21	0.104	0.339	16.54	33.07
5/8"	15.88		1.00	19	0.128	0.418	20.89	41.78
3/4"	19.05		0.80	21	0.126	0.411	13.69	27.38
3/4"	19.05		1.00	19	0.155	0.507	17.26	34.52
7/8"	22.23		0.80	21	0.147	0.482	11.67	23.34
7/8"	22.23		1.00	19	0.182	0.597	14.70	29.40
1"	25.40		0.88	20	0.186	0.607	11.23	22.45
1"	25.40		1.00	19	0.210	0.686	12.81	25.61
1 1/8"	28.58		1.00	19	0.237	0.775	11.34	22.68
1 1/4"	31.75		1.10	18.5	0.289	0.947	11.23	22.45
1 3/8"	34.93		1.21	18	0.350	1.146	11.23	22.45
1 1/2"	38.10		1.32	17.5	0.416	1.364	11.23	22.45
1 5/8"	41.28		1.43	17	0.488	1.601	11.23	22.45
1/4"	6.35	SOFT (O)	0.80	21	0.039	0.125	19.15	57.44
3/8"	9.53		0.80	21	0.061	0.197	12.30	36.90
1/2"	12.70		0.80	21	0.082	0.268	9.07	27.20
5/8"	15.88		0.80	21	0.104	0.339	7.17	21.52
5/8"	15.88		1.00	19	0.128	0.418	9.06	27.19
3/4"	19.05		1.00	19	0.155	0.507	7.49	22.47

