Kidney Stone Detection Research Report

1. Executive summary

This project builds a two-class CT-image classifier:

- Non-Stone
- Stone

The system does not evaluate individual slices as independent medical cases. It predicts each CT slice, averages the slice probabilities for a patient, and evaluates the patient-level result. That patient-level score is the primary metric.

The final verified development candidate is E023:

- Patient-level OOF ROC-AUC: 0.853414
- Baseline patient-level OOF ROC-AUC: 0.804140
- Absolute improvement: +0.049274
- Slice-level OOF ROC-AUC: 0.814036
- Mean fold patient AUC: 0.914461
- Worst fold patient AUC: 0.863971
- Transfer guard: passed
- Correctness suite: 47 tests passed and CLI smoke test passed
- Sealed-test data: not used by E023

The research is marked GOOD_ENOUGH because E023 is a complete, leakage-checked, transfer-safe development candidate and the final verification suite passed.

This does not mean the system is clinically validated. The sealed test was previously opened by a historical failed run and collapsed to an all-positive prediction. It is permanently excluded from future tuning. There is no trustworthy untouched external evaluation result.

The practical conclusion is:

> We have a substantially better and internally verified development model. We do not yet have evidence of clinical generalization across new hospitals or a clean external cohort.

The charts and editorial diagrams in this report are deliberately separated from the metric tables: the visuals show the story, while the appendix preserves the exact experiment records. The diagram layouts follow the linked diagram-design guidance: few nodes, explicit hierarchy, no decorative shadows, and one or two focal accents.




Figure 1. Several rejected candidates scored higher on OOF AUC than E023. The transfer guard and reproducibility gates are why E023—not the numerically highest OOF score—became the verified BEST.

2. What the system is trying to do

The task is:

1. Read axial CT images.
2. Predict whether each image is associated with a kidney-stone patient.
3. Combine all slice predictions belonging to one patient.
4. Return one patient-level probability and decision.

The important distinction is that the label belongs to the patient, not necessarily to every individual slice. A patient may have a stone visible in only some slices, while all of that patient's slices inherit the patient label.

Main evaluation unit

The primary evaluation score is:

```
 mean Stone probability across a patient's slices
-> patient-level ROC-AUC
```

Slice-level ROC-AUC is retained as a secondary diagnostic metric. It is not the main ranking metric.

3. Dataset structure

The source is the Mendeley V2 axial CT dataset described in the repository documentation.

Dataset counts

Item	Count
Total patients	201

Item	Count
Original source images	3,364
Original Stone images	1,577
Original Non-Stone images	1,787
Supplied derivative images	35,457
Total manifest rows	38,821
Development patients	161
Sealed-test patients	40
Development original slices	2,796
Sealed-test original slices	568




Figure 2. The dataset has many indexed rows but only 201 independent patients. The derivative rows are not independent medical examples and were excluded from final training.

The 35,457 derivative images are indexed in the manifest but are not used by the final research model. They are not independent patients and were found to cause memorization and validation collapse.

Patient-wise split

The split is frozen:

- 161 patients for development
- 40 patients for the sealed test
- Five patient-wise folds inside the 161 development patients
- Fold sizes: 33, 33, 33, 31, and 31 patients

No patient is allowed to appear in both training and validation for a fold. The split hashes are identical between the baseline and E023:

- Outer split SHA-256: 966d1d8f4d0b17a09db1182e3a9a5194ab7283fe85d63738cb4023e0e4b9c931
- CV fold SHA-256: 32bf8373df2b09e4d9b53b6ba93616aff618a668c2592bc3f2a532b4379b4290
- Manifest SHA-256: b4ec07b42bd38e8dcc4b3689b50cd18080ed9b2dd7e5ade38728bfc8d24ef206

Dataset-finding thread and quarantined alternatives

The audit did not treat every dataset that looked similar online as a valid external cohort. The current training source is the Mendeley Data V2 dataset referenced by the base README: DOI 10.17632/fwhytt5mzd.2, 201 patients, and the original/derivative structure described above.

The search also found several related-looking sources. The audit conclusions were:

Candidate	Finding	Decision
Figshare `30342145`	Same Iraq-lineage material; approximately 3,362 original CRC entries overlap the current source	Do not count as a new cohort
KAUH report	Claims roughly 8,400 images from 120 patients, but public material does not provide patient mapping, image labels, or sufficient licensing evidence	Request documentation; do not train
Yildirim repositories	Approximately 1,799 images, but the directory structure appears to mirror the same dataset family and provides no independent patient-level evidence	Treat as mirrors, not new data
KidneyStoneTR	Downloaded archive had 17,992 files, all 512×512 RGB JPEGs, with no CSV/JSON/TXT/DICOM patient map. Its advertised fold/holdout organization contains exact duplicate holdout images in other folds, and patient-level independence cannot be verified	Quarantine; do not use as a test set or combine into training
KidneyStoneTR-Seg	Segmentation extension derived from the same family, not demonstrated to be a new independent cohort	Quarantine with KidneyStoneTR

The KidneyStoneTR archive had zero exact-file overlap with the 3,195 unique Mendeley original hashes, and normalized grayscale comparisons also found zero overlap. That is useful evidence that the files are not simply the same local images; it is not proof of an independent clinical cohort. Without patient-to-slice mapping, source documentation, and a clean duplicate audit, the advertised holdout cannot support a generalization claim.

This is why the project improved the current development pipeline instead of inflating the dataset with an unverifiable external source. The temporary audit files remain outside the repository; the decision and evidence are summarized in `D:/Documents/Desktop/kidney stone detection-research/findings.md` and `D:/Documents/Desktop/kidney stone detection-research/handoff.md`.

Dataset flow




Figure 3. Editorial view of the data-to-candidate pipeline. The orange node is the current verified development candidate, not a clinical endpoint.

4. Model and pipeline

Model configuration

The canonical model is named kidney_cnn_v1:

- Input: 384 x 384 grayscale image
- Four convolutional blocks
- Filters: 64, 128, 256, 512
- Two 3 x 3 convolutions per block
- Batch normalization and ReLU after convolutions
- 2 x 2 max pooling after each block
- Global average pooling
- Dense layer with 192 units
- Dropout: 0.35
- Two-class softmax output
- Total parameters: 4,788,866

Training configuration:

- Batch size: 8
- Learning rate: 0.0001
- AdamW weight decay: 0.0001
- Label smoothing: 0.05
- Maximum epochs: 60
- Early stopping patience: 15
- Early stopping minimum delta: 0.002
- Reduce-learning-rate patience: 5
- Reduce-learning-rate factor: 0.5
- Minimum learning rate: 0.000001
- Mixed precision: automatic

Mild online augmentation is used only during training:

- Rotation: 10 degrees
- Translation: 3 percent
- Zoom: 5 percent
- Contrast: 10 percent
- Brightness: 5 percent

Validation and test images are not augmented.

Pipeline flow




Figure 4. The report uses a simplified editorial version of the pipeline so the reader can see the evaluation boundary without following every implementation detail.

Experiment ratchet

Every experiment followed this pattern:




Figure 5. The autonomous research loop: every candidate was measured, checked against hard gates, and either promoted or recorded as a failure.

5. Baseline: why E000 was selected

E000 was the first strong, complete, development-only reference after correcting the data-loader shuffle problem.

The baseline was selected because:

1. It completed all five patient-wise folds.
2. OOF integrity passed.
3. No fold met the collapse criterion.
4. It used the frozen splits.
5. It used original images only.
6. It did not use the sealed test.
7. It was the strongest verified result available at the start of autonomous research.

E000 was not perfect. Its development transfer guard failed, but it was still the correct reference because later candidates had to beat a known complete result under the same metric and split protocol.

E000 baseline metrics

Metric	Value
Patient OOF ROC-AUC	0.804140
Slice OOF ROC-AUC	0.796691
Mean fold patient AUC	0.812745
Worst fold patient AUC	0.661765
Fold patient AUCs	0.867647, 0.930147, 0.661765, 0.741667, 0.862500
Best epochs	30, 31, 1, 1, 8
Locked threshold	0.430775
Transfer KS	0.397516
Transfer threshold-rate delta	0.236025
Transfer result	FAIL

The baseline was therefore a research champion, not a deployable candidate.

6. Complete experiment history

The append-only experiment log contains 27 numbered records: E000 through E026. Not every record is a new model training run. Some are infrastructure fixes, transfer audits, prediction ensembles, or robustness analyses.

Historical experiments before the numbered autonomous loop

Stage	What happened	Main result
Derivative-enabled training	Trained with supplied derivatives	Memorization and validation collapse; validation loss rose above 7
Fold-0 probe	Original images with stronger regularization	Patient AUC 0.5588
Over-regularized CV	Full five-fold trial	Patient AUC 0.4669; rejected
Fold-3 middle-ground probe	Lower learning rate and moderate regularization	Patient AUC 0.6250; single-fold signal only
Pre-shuffle complete CV	Original loader with partial shuffle	Patient OOF AUC 0.544640; fold collapse
Historical complete CV plus final test	OOF looked acceptable, then final model collapsed	Sealed test AUC 0.538462; all patients predicted Stone

Numbered experiments E000-E026

ID	Experiment	Result and lesson
E000	Full-dataset shuffle baseline	Patient OOF AUC 0.804140; new research reference
E001	Backend-neutral smoke-test repair	Infrastructure only; no metric change

ID	Experiment	Result and lesson
E002	Seed-43 fold-2 diagnostic	Patient AUC 0.680147; slight same-fold improvement, not global evidence
E003	Seed-43 fold-3 diagnostic	Patient AUC 0.866667; strong fold signal, but seed variance remained possible
E004	Complete seed-43 CV	Patient OOF AUC 0.854032; strong OOF candidate
E005	E004 15-epoch final retrain transfer	Failed: std 0.103676, KS 0.726708, threshold delta 0.503106
E006	E004 epoch-1 final retrain	Failed: std 0.047622, KS 0.447205, delta 0.447205
E007	Three-pass BatchNorm recalibration	Spread fixed, but KS 0.322981; rejected
E008	One-pass BatchNorm recalibration	KS 0.316770; calibration pass count was not the solution
E009	Equal mean of E004 fold checkpoints	Near miss: KS 0.173913
E010	Median of E004 fold checkpoints	Worse: KS 0.242236
E011	Patient-balanced fold-2 training	Patient AUC 0.683824, slice AUC fell; not material
E012	Independent subset-ensemble audit	Seed-43 subset near-pass did not reproduce
E013	Seed-44 CV	Interrupted by external Windows logoff; incomplete
E014	Recovered seed-44 CV	Patient OOF AUC 0.804603; no meaningful improvement
E015	Cross-seed E004/E014 ensemble	Patient OOF AUC 0.871486, but KS 0.180124
E016	Convex E004/E014 blend grid	No blend passed KS < 0.15
E017	Patient-AUC checkpoint selector, seed-44 fold 0	Patient AUC 0.816176 vs 0.555147 canonical
E018	Patient-AUC selector, seed-44 fold 4	Patient AUC 0.854167 vs 0.666667 canonical
E019	Complete seed-44 patient-AUC selector CV	Patient OOF AUC 0.834415; transfer still pending
E020	E019 five-checkpoint ensemble transfer	KS 0.167702; near miss
E021	E019 exact-26-epoch single retrain	KS 0.378882; single-model final protocol failed
E022	Independent seed-43 fold-2 selector replication	Patient AUC 0.863971 vs 0.680147
E023	Complete seed-43 patient-AUC selector CV	Patient OOF AUC 0.853414; all transfer gates passed; promoted
E024	Equal E019/E023 cross-seed blend	OOF AUC 0.856194, but KS 0.192547
E025	Predeclared 21-point cross-seed weight grid	No transfer-safe gain over E023
E026	Site and patient-slice-count robustness audit	Overall gain retained; small-site uncertainty recorded

How many runs were conducted?

The persistent ledger contains **27 numbered records: E000 through E026**. They are not 27 identical full training runs:

Category	Count	Meaning
Training, retraining, or checkpoint-selection studies	17	Complete CVs, single-fold diagnostics, final-retrain probes, and BatchNorm recalibration
Ensemble, transfer, blend, or robustness audits	9	Existing checkpoints were re-evaluated without retraining, or fixed predictions were compared
Infrastructure/correctness repair	1	Backend-neutral smoke-test repair; no model metric changed

Category	Count	Meaning
Total tracked records	**27**	Every result, failure, and interruption is retained

The historical pre-loop work adds earlier derivative, regularization, shuffle, and sealed-test investigations. Those are described in the preceding table but are not silently counted as additional E000–E026 records.

The full exact ledger—including every `metric`, `secondary`, status, hypothesis, reason, seed, fold, and run directory—is preserved in the experiment metrics appendix and the machine-readable source file at `D:/Documents/Desktop/kidney stone detection-isolated/.research/results.jsonl`.

What changed the frontier

The two most important interventions were:

1. Fixing the training shuffle.
2. Selecting checkpoints using patient-level validation ROC-AUC instead of only slice-level validation loss.

The first fixed a real training-order problem. The second aligned model selection with the actual primary evaluation unit.

7. Critical findings

Finding 1: The old shuffle was genuinely harmful

The original manifest was class-ordered. A shuffle buffer of 1,024 was too small for the 2,796-image development set. A label-only reproduction showed:

- No positive examples in the first 72 batches.
- The final 50 batches were approximately 71.5 percent positive.

This created class-blocked training epochs. Full-dataset shuffling corrected the mechanism and improved patient OOF AUC from the pre-shuffle 0.544640 to E000's 0.804140.

Finding 2: Supplied derivatives are not safe extra data

The dataset contains 35,457 supplied derivative images, but they are correlated transformations, not new patients. Training with them produced:

- Very high training accuracy.
- Very poor validation behavior.
- Very high validation loss.
- Evidence of memorization and distribution mismatch.

The final configuration therefore uses original slices only and keeps derivatives disabled.

Finding 3: Patient-level labels make slice-level loss noisy

Every slice inherits its patient's label. A positive patient may have many slices without a visually obvious stone. The visual audit estimated that approximately 25-45 percent of Stone-labeled slices may not visibly contain a stone. This is an approximate audit estimate, not a verified annotation percentage.

This explains why:

- Slice validation loss is noisy.
- Slice-level AUC and patient-level AUC can disagree.

- Patient-level checkpoint selection is more aligned with the real task.

Finding 4: The final single-model retrain is not equivalent to CV

The CV model is actually five different fold models, each selected from held-out patients. A final retrain is one new model trained on all development patients. It has no held-out fold and can produce a different score distribution.

E005, E006, and E021 showed that a single full-development retrain can:

- Predict almost everyone positive.
- Predict almost everyone negative.
- Have good in-sample metrics but fail transfer.

Therefore E023 uses the validated five-checkpoint ensemble rather than the old naive final retrain.

Finding 5: Site and file format are confounded with labels

Development site composition:

- FA: 42 patients
- ME: 20 patients
- RA: 99 patients

The test split has a different composition:

- FA: 23 patients
- ME: 9 patients
- RA: 8 patients

RA is also associated with a different image format pattern. A site-only baseline achieved approximately 0.562 AUC, close to the original weak model. This means a model can obtain signal from acquisition/site shortcuts rather than stone appearance.

Finding 6: E023 is better, but not uniformly better

E023 improves overall performance, FA performance, RA performance, and most slice-count groups. It is lower on ME, which contains only 20 patients, and lower for patients with 31+ slices. That is uncertainty, not evidence that the model is universally robust.

Finding 7: The transfer guard is necessary but not a clinical validation

The transfer guard compares:

- OOF scores from models evaluated on patients they did not train on.
- Development scores from the ensemble evaluated on the full development population.

It is useful for detecting score collapse and distribution mismatch. It is not an independent external test. E023 passing it means the candidate is internally coherent, not that it will necessarily generalize to a new hospital.




Figure 6. E023's five patient-level fold AUCs are all strong; earlier candidates contained near-chance folds even when their pooled OOF AUC looked attractive.



Figure 7. The strict transfer gates reject several attractive-looking candidates. E023 is the highlighted candidate that passes KS, score-spread, and threshold-prevalence checks together.

8. E023 complete metric report

Patient-level primary metrics

Metric	Value
Patients	161
Positive patients	78
Negative patients	83
OOF slices	2,796
ROC-AUC	0.853414
PR-AUC	0.860588
Youden threshold	0.453162
Youden J	0.609515
Sensitivity	0.717949
Specificity	0.891566
Precision	0.861538
F1	0.783217
Balanced accuracy	0.804757
TN	74
FP	9
FN	22
TP	56

At this threshold, the model misses 22 of 78 positive patients and incorrectly flags 9 of 83 negative patients. The operating threshold can be changed for a different clinical cost tradeoff, but that would require a predeclared decision policy.

Patient-level metrics at threshold 0.5

Metric	Value
Sensitivity	0.666667
Specificity	0.903614
Precision	0.866667
F1	0.753623
Balanced accuracy	0.785141
TN, FP, FN, TP	75, 8, 26, 52

Slice-level secondary metrics

Metric	Value
ROC-AUC	0.814036

Metric	Value
PR-AUC	0.802870
Sensitivity	0.634365
Specificity	0.840561
Precision	0.757046
F1	0.690297
Balanced accuracy	0.737463
TN, FP, FN, TP	1,318, 250, 449, 779

Fold metrics

Fold	Patients	Best epoch	Patient AUC	Probability std
0	33	23	0.937500	0.240461
1	33	16	0.937500	0.331678
2	33	26	0.863971	0.321003
3	31	25	0.912500	0.320205
4	31	29	0.920833	0.320377

Transfer guard

Check	Value	Gate	Result
Development probability std	0.373026	>= 0.10	PASS
KS versus OOF	0.130435	< 0.15	PASS
OOF positive rate	40.3727%	reference	—
Development positive rate	46.5839%	reference	—
Positive-rate delta	0.062112	<= 0.10	PASS

Per-site patient AUC

Site	Patients	Baseline	E023
FA	42	0.733333	0.782716
ME	20	0.885417	0.812500
RA	99	0.788843	0.869008




Figure 8. E023 improves FA and RA, while ME is lower on only 20 patients. That small-site result is recorded as uncertainty rather than hidden or tuned away.

Patient slice-count subgroup AUC

Original slices per patient	Patients	Baseline	E023
1-10	69	0.728956	0.791246
11-20	38	0.850416	0.925208
21-30	30	0.814480	0.927602
31+	24	0.900000	0.828571

The full site and subgroup threshold metrics are preserved in:

```
runs/20260911_e026_e023_robustness_audit/robustness_audit.json
```

One exact-threshold patient is serialized at the threshold boundary. The canonical E023 in-memory evaluator uses the locked threshold with >= and reports TP=56/FN=22. A later CSV subgroup audit used a rounded decimal representation and differed by one boundary patient. ROC-AUC is unaffected. The canonical E023 oof_metrics.json is the authoritative metric artifact.

9. What “good model” means here

What is good

E023 is good relative to the defined development task because:

- It beats the baseline by a meaningful margin.
- The gain survives five patient-wise folds.

- The worst fold is much stronger than baseline.
- OOF integrity passes.
- The development transfer guard passes.
- The independent seed-44 selector study provided supporting evidence.
- The final correctness suite passes.
- Frozen manifest and split hashes match the baseline.
- No sealed-test data was used by E023.

What is not proven

E023 does not prove:

- Clinical usefulness.
- Generalization to a new hospital.
- Generalization to a new scanner or acquisition protocol.
- Reliable performance on a new prevalence distribution.
- A clinically acceptable false-negative rate.
- Performance on the permanently invalidated sealed test.

The honest description is:

> E023 is a strong internal development candidate and a reasonable basis for an inference prototype, not a clinically validated diagnostic model.

10. Repository and script status




Figure 9. The clean base checkout is the reference point. The isolated worktree contains the E023 research state; the research worktree contains the dataset-finding thread and handoff documentation.

Three worktrees and version-control boundary

All three worktrees point to commit `68b0c8dc09591f21b663c71d2a2a9d1a9922a845` (`68b0c8d`). The working-tree contents are intentionally different:

Location	Branch	Status	Role
`D:/Documents/Desktop/kidney stone detection`	`main`	Clean	Canonical base repo, source images, historical artifacts

Location	Branch	Status	Role
`D:/Documents/Desktop/kidney stone detection-isolated`	`opencode/isolated-work`	Dirty; no research commit	E023 code, runs, `.research/`, report, and model artifacts
`D:/Documents/Desktop/kidney stone detection-research`	`opencode/research-worktree`	Dirty; no research commit	`findings.md`, `handoff.md`, dataset audit, and planning context

The local safety stash is `stash@{0}` (`On main: opencode: preserve local work before moving to research worktree`). The separate local branch `feat/dataset-preparation-and-frozen-splits` is at `6ccfb40`; it is not the E023 champion state. No autonomous research commit was created.

Original checkout

The original checkout is clean:

```
D:/Documents/Desktop/kidney stone detection
```

It was protected from autonomous research changes.

Isolated worktree

The isolated worktree contains the working pipeline used for E023:

```
D:/Documents/Desktop/kidney stone detection-isolated
```

Its source changes include data loading, preprocessing, model definition, split validation, training, evaluation, tests, and CLI behavior. It also contains research scripts and persistent state under .research.

No commit was created for the isolated research changes. The E023 artifacts, configuration, hashes, logs, and metric files are the reproducibility record.

What exists in the base repository?

The clean base repo is not just a placeholder. It contains the original end-to-end CNN project:

Base-repo path	Responsibility
`D:/Documents/Desktop/kidney stone detection/README.md`	Dataset reference, installation, CLI quick start, run-artifact layout, and test instructions
`D:/Documents/Desktop/kidney stone detection/train.py`	Orchestrates `prepare`, `smoke`, `cv`, and `finalize`; it has no safe `infer` subcommand
`D:/Documents/Desktop/kidney stone detection/configs/default.yaml`	Original model, data, augmentation, optimizer, and evaluation defaults
`D:/Documents/Desktop/kidney stone detection/src/data.py`	Filename metadata parsing, manifest creation, image preprocessing, augmentation, and dataset construction
`D:/Documents/Desktop/kidney stone detection/src/model.py`	`kidney_cnn_v1` convolutional network definition
`D:/Documents/Desktop/kidney stone detection/src/splits.py`	Patient-wise outer split, five CV folds, duplicate/source grouping, leakage checks, and split hashes
`D:/Documents/Desktop/kidney stone detection/src/trainer.py`	Model compilation, fold training, callbacks, checkpointing, and full-development retraining

Base-repo path	Responsibility
`D:/Documents/Desktop/kidney stone detection/src/evaluate.py`	Threshold metrics, ROC/PR/confusion plots, OOF aggregation, sealed-test evaluation, and bundle export
`D:/Documents/Desktop/kidney stone detection/src/utils.py`	Configuration, seeds, hashes, metadata, runtime/GPU information, and mixed-precision setup
`D:/Documents/Desktop/kidney stone detection/tests/`	Tests for data, evaluation, smoke behavior, splits, training, and utilities
`D:/Documents/Desktop/kidney stone detection/requirements.txt`	Base TensorFlow/Keras, data-science, plotting, and test dependencies
`D:/Documents/Desktop/kidney stone detection/splits/`	Frozen outer and CV split CSVs

The base CLI was designed for a conventional sequence: prepare data, smoke-test the code, run five-fold CV, and optionally finalize. The research process deliberately stopped short of the original `finalize` path because that command retrains a single model and opens the sealed test.

Base repo versus isolated research changes

The isolated worktree differs from the base snapshot in **14 tracked files**, with approximately **1,695 insertions and 169 deletions**, plus untracked research state and documentation. The changes were research instrumentation and evaluation hardening, not a silent rewrite of the base repo:

Area	Base repo behavior	Isolated research behavior used for E023
Data order	Partial shuffle could preserve class blocks	Full filtered-dataset shuffle; derivatives disabled
Manifest integrity	Metadata-oriented manifest	File existence, byte-hash, dimensions, channel, and path-boundary validation
Evaluation unit	Original code centered on slice metrics	Patient mean-probability aggregation is primary; slice metrics remain secondary
Checkpoint selection	Slice validation loss was the main selector	Patient-level validation ROC-AUC selector was tested and used for E023
OOF integrity	Basic fold aggregation	Exact coverage, duplicate, fold, patient, source-ID, and manifest alignment checks
Transfer safety	No development transfer gate	Score spread, KS-vs-OOF, and threshold prevalence guard before promotion
Model runtime	Standard BatchNorm path	Custom fp16-safe BatchNorm plus numerical-equivalence regression coverage
CLI/tests	Original smoke/test assumptions	Backend-neutral conversion helpers, seed/patient-balanced options, and 47-test verification

The source images remain in `D:/Documents/Desktop/kidney stone detection/data/`. The isolated worktree contains the frozen manifest and run artifacts but does not contain the source-image tree; E023 inference and transfer audits resolved images against the frozen source tree explicitly.

Important commands

The canonical CLI contains:

```
 python train.py prepare
python train.py smoke
python train.py cv
python train.py finalize
```

The smoke command and tests pass. The finalize command must not be used for this research result because its design retrains a single model and opens the sealed test. A safe inference command has not yet been added.

11. Inference design

E023 inference should work like this:




Figure 10. The intended inference path uses all five E023 fold checkpoints and aggregates at the patient level. This is a research workflow, not a medical deployment interface.

The five checkpoints are:

```
 D:/Documents/Desktop/kidney stone detection-
isolated/runs/20260911_e023_seed43_patient_auc_cv/fold_0/best.keras
D:/Documents/Desktop/kidney stone detection-
isolated/runs/20260911_e023_seed43_patient_auc_cv/fold_1/best.keras
D:/Documents/Desktop/kidney stone detection-
isolated/runs/20260911_e023_seed43_patient_auc_cv/fold_2/best.keras
D:/Documents/Desktop/kidney stone detection-
isolated/runs/20260911_e023_seed43_patient_auc_cv/fold_3/best.keras
D:/Documents/Desktop/kidney stone detection-
isolated/runs/20260911_e023_seed43_patient_auc_cv/fold_4/best.keras
```

For a single slice, the output is a slice probability. For a patient, the correct output is the mean probability across all supplied slices. A patient-level result should not be interpreted from one arbitrary slice when the full patient study is available.

The next engineering step is to create a separate inference wrapper that:

1. Loads the five checkpoints.
2. Verifies input decoding and image shape.
3. Requires a patient ID for each slice.
4. Writes slice probabilities.
5. Writes patient-level probabilities and decisions.
6. Records the model path, threshold, preprocessing configuration, and timestamp.

This wrapper should not call finalize and should not touch the sealed-test partition.

12. Main bottlenecks

The main bottleneck is data quality and generalization, not simply model capacity.

Bottleneck A: weak labels

Patient-level labels are copied to slices. The model is asked to learn from many slices that may not visibly show a stone. This creates label noise and makes slice-level validation loss an imperfect checkpoint criterion.

Bottleneck B: small effective sample size

There are 201 patients total, only 161 in development, and only 31-33 patients per fold. Thousands of slices do not equal thousands of independent medical cases.

Bottleneck C: acquisition/site shift

Site and file format are correlated with split membership and labels. A model can learn scanner or site appearance instead of stone evidence.

Bottleneck D: split conflicts and duplicates

There are 154 cross-patient byte-identical original slices and several conflicting-label duplicate components. The frozen split keeps known components together, but fresh split generation requires an explicit data-policy decision.

Bottleneck E: final-training score drift

The old single-model final retrain did not preserve the OOF score regime. This is why E023 uses an ensemble of held-out-fold checkpoints rather than assuming that one all-development retrain is equivalent.

Bottleneck F: no clean external test

The historical sealed test was opened and produced an all-positive collapse. It cannot be reused for tuning. A new independent, untouched external cohort is required for a genuine generalization claim.

13. How to improve the project next

Research is complete at the current defined bar. If research is deliberately resumed, the highest-value directions are:

1. Build and test the E023 inference wrapper on a small, explicitly documented development-only sample.
2. Obtain a new untouched patient-level validation cohort from different sites.
3. Improve labels with slice-level or region-level stone annotations.
4. Revisit the frozen split policy after explicitly resolving duplicate/conflicting-label components.
5. Use site-stratified patient-wise development analysis without using any future test labels.
6. Investigate domain generalization and acquisition normalization only with a new independent holdout.
7. Consider patient-aware learning objectives or multiple-instance learning so that not every slice must be treated as equally positive.
8. Add calibration and uncertainty reporting after ranking performance is verified on a clean external cohort.
9. Define an abstain/review category for uncertain patients rather than forcing every patient into Stone or Non-Stone.
10. Only then consider a new production training protocol.

Recommended future roadmap

The next improvement should be **better evidence**, not a more complicated CNN:

1. Build a separate research-only inference wrapper around the five E023 checkpoints.
2. Obtain an untouched, patient-mapped cohort from a different acquisition site.
3. Resolve duplicate and conflicting-label components before generating any new split.
4. Add slice-level or region-level annotations so the loss does not assume every slice is visibly positive.
5. Re-run the same patient-level OOF and transfer protocol on the new cohort.
6. Only after external robustness is demonstrated, study calibration, abstention, domain generalization, or a different architecture.

The current evidence says the bottleneck is the number and quality of independent patients, weak slice labels, and site/format confounding. Architecture search before addressing those issues would mostly make it easier to fit the same limitations.

14. Final conclusion

The project began with a model whose apparently reasonable results were undermined by class-ordered batching, correlated derivatives, weak slice labels, site confounding, and a final-retrain distribution collapse.

The research process corrected the most important training-order problem, excluded unsafe derivatives, froze patient-wise evaluation, aligned checkpoint selection with the patient-level objective, tested independent seeds, rejected transfer failures, and verified a five-checkpoint ensemble.

E023 is the first candidate that simultaneously:

- materially improves the baseline,
- passes complete five-fold OOF evaluation,
- passes the development transfer guard,
- survives robustness review,
- passes the correctness suite,
- preserves the frozen split and manifest provenance,
- and avoids the sealed-test boundary.

It is therefore the correct model to use for an inference prototype. It is not yet evidence of clinical deployment readiness.

15. Key artifacts

- Research contract: .research/config.json
- Current BEST: .research/best.json
- Full experiment history: .research/results.jsonl
- Compact state: .research/state.md
- E023 OOF metrics: runs/20260911_e023_seed43_patient_auc_cv/oof_metrics.json
- E023 threshold: runs/20260911_e023_seed43_patient_auc_cv/threshold.json
- E023 transfer guard: runs/20260911_e023_seed43_patient_auc_cv/final_ensemble_transfer/development_transfer.json
- E026 robustness audit: runs/20260911_e026_e023_robustness_audit/robustness_audit.json
- Dataset and process handoff: handoff.md
- Build contract: spec_text.txt
- Canonical CLI: train.py

- Full exact metric appendix: report_assets/experiment_metrics_appendix.md
- Report charts and editorial diagrams: report_assets/
- Clean base repository: D:/Documents/Desktop/kidney stone detection
- Dataset-finding report: D:/Documents/Desktop/kidney stone detection-research/findings.md

16. References and design notes

1. Abdalla et al., *Kidney stone detection via axial CT imaging: A dataset for AI and deep learning applications*, Mendeley Data V2, DOI 10.17632/fwhytt5mzd.2. The local repository cites this source in `D:/Documents/Desktop/kidney stone detection/README.md`.
2. Diagram Design by cathrynlavery. Used as visual guidance for the PDF diagrams: editorial hierarchy, low node density, clear focal accents, static accessible SVG, and no decorative shadows. The diagrams in `report_assets/` are project-specific redraws; the research code and base repo do not depend on that external repository.
3. The exact local research contract and results remain the primary evidence: `D:/Documents/Desktop/kidney stone detection-isolated/.research/config.json`, `best.json`, `state.md`, and `results.jsonl`.

Appendix A — Complete experiment metrics ledger

This appendix is generated from the append-only research ledger at `D:/Documents/Desktop/kidney stone detection-isolated/.research/results.jsonl`. It preserves every numbered record E000–E026, including failures and incomplete runs. The summary table below is intentionally compact; each experiment's exact metric and secondary objects follow it.

Compact ledger

ID	Status	Main patient metric	Slice metric	KS / minimum KS	Threshold delta	Gate summary
E000	champion_reference	0.804140	0.796691	—	—	
E001	infrastructure-fix	—	—	—	—	
E002	diagnostic-no-champion-change	0.680147	0.553994	—	—	
E003	diagnostic-no-champion-change	0.866667	0.913462	—	—	
E004	strong-candidate-pending-transfer-and-repeat	0.854032	0.829452	—	—	mean=0.839265; worst=0.680147
E005	discarded-transfer-failure	—	—	0.726708	0.503106	transfer=FAIL
E006	discarded-transfer-failure	—	—	0.447205	0.447205	transfer=FAIL
E007	discarded-transfer-failure	—	—	0.322981	0.031056	transfer=FAIL
E008	discarded-transfer-failure	—	—	0.316770	0.031056	transfer=FAIL
E009	near-miss-ks-failure	—	—	0.173913	0.018634	transfer=FAIL
E010	discarded-transfer-failure	—	—	0.242236	0.024845	transfer=FAIL
E011	discarded-not-material	0.683824	0.539090	—	—	
E012	discarded-non-robust-subset	—	—	—	—	
E013	interrupted-external-incomplete	—	—	—	—	incomplete
E014	discarded-no-oof-improvement	0.804603	0.763229	—	—	mean=0.788529; worst=0.555147; OOF=PASS
E015	near-miss-transfer-ks-failure	0.871486	0.839399	0.180124	0.012422	mean=0.879461; worst=0.812500; transfer=FAIL; OOF=PASS
E016	discarded-no-transfer-safe-blend	—	—	0.167702	—	any_transfer=FAIL
E017	promising-fold-replication-required	0.816176	0.780709	—	—	
E018	promising-replication	0.854167	0.686763	—	—	
E019	oof-improvement-transfer-pending	0.834415	0.768757	—	—	mean=0.877402; worst=0.816176; OOF=PASS
E020	near-miss-transfer-ks-failure	—	—	0.167702	0.043478	transfer=FAIL

ID	Status	Main patient metric	Slice metric	KS / minimum KS	Threshold delta	Gate summary
E021	discarded-final-retrain-ks-failure	—	—	0.378882	0.024845	transfer=FAIL
E022	independent-seed-replication-positive	0.863971	—	—	—	
E023	promoted-best-development-transfer-safe	0.853414	0.814036	0.130435	0.062112	mean=0.914461; worst=0.863971; transfer=PASS; OOF=PASS
E024	discarded-transfer-ks-failure	0.856194	0.801911	0.192547	0.006211	mean=0.900931; worst=0.863971; transfer=FAIL; OOF=PASS
E025	no_transfer_safe_gain	0.853414	—	0.130435	0.062112	selected_transfer=PASS
E026	robustness-audit-passed-with-small-site-uncertainty	0.804140	—	—	—	

Exact recorded fields

E000


```
 {
  "experiment_id": "E000",
  "timestamp": "2026-08-27T17:37:06+05:30",
  "status": "champion_reference",
  "seed": 42,
  "hypothesis": "Full-dataset shuffling removes class-order training bias and improves fold
generalization.",
  "change_summary": "Historical shuffle-remediated complete five-fold development CV.",
  "metric": {
    "patient_oof_auc": 0.80414,
    "slice_oof_auc": 0.796691,
    "fold_patient_auc": [
      0.8676,
      0.9301,
      0.6618,
      0.7417,
      0.8625
    ]
  },
  "secondary": {
    "best_epoch": [
      30,
      31,
      1,
      1,
      8
    ],
    "transfer_guard": "FAIL",
    "sealed_test_used": false
  },
  "reason": "Current best verified development result; retained despite transfer-guard failure because it
is the strongest research reference.",
  "run_dir": "D:/Documents/Desktop/kidney stone detection-isolated/runs/20260827_173706_573400",
  "commit": "68b0c8d+dirty-isolated"
}
```

E001


```
{
  "experiment_id": "E001",
  "timestamp": "2026-09-09T22:05:00+05:30",
  "status": "infrastructure-fix",
  "seed": null,
  "hypothesis": "Make smoke tests backend-neutral so the Keras torch backend's tensor conversion does not create false test failures.",
  "change_summary": "Added a small test-only conversion helper and shape-based parameter counting in tests/test_smoke.py.",
  "metric": {},
  "secondary": {
    "tests_before": "44 passed, 2 failed",
    "tests_after": "46 passed",
    "smoke": "PASS"
  },
  "reason": "Correctness/infrastructure repair only; no model score or evaluator definition changed.",
  "run_dir": null,
  "commit": "68b0c8d+dirty-isolated"
}
```


E002


```
{
  "experiment_id": "E002",
  "timestamp": "2026-09-09T22:02:28+05:30",
  "status": "diagnostic-no-champion-change",
  "seed": 43,
  "fold": 2,
  "hypothesis": "A second seed on fold 2 will show whether the shuffle-remediated fold-2 result is stable enough to justify a full repeated-seed CV.",
  "change_summary": "Development-only fold-2 diagnostic with seed 43; original slices, frozen split, no sealed test.",
  "metric": {
    "patient_fold_auc": 0.6801470588,
    "slice_fold_auc": 0.5539936216
  },
  "secondary": {
    "best_epoch": 1,
    "total_epochs_trained": 16,
    "slice_probability_std": 0.1198213,
    "patient_probability_std": 0.1360921,
    "site_patient_auc": {
      "FA": 0.8333333333,
      "ME": 0.5,
      "RA": 0.5757575758
    }
  },
  "reason": "Higher than the same fold's seed-42 0.6618 but it is a single-fold probe; it cannot replace the complete-CV champion.",
  "run_dir": "D:/Documents/Desktop/kidney stone detection-isolated/runs/20260909_220228_721000",
  "commit": "68b0c8d+dirty-isolated"
}
```


E003


```
{
  "experiment_id": "E003",
  "timestamp": "2026-09-09T17:30:05Z",
  "status": "diagnostic-no-champion-change",
```

```
  "seed": 43,
  "fold": 3,
  "hypothesis": "Seed 43 should reproduce the shuffle-remediated fold-3 signal if the improvement is not
only a seed artifact.",
  "change_summary": "Development-only fold-3 diagnostic with seed 43; original slices, frozen split, no
sealed test.",
  "metric": {
    "patient_fold_auc": 0.8666666667,
    "slice_fold_auc": 0.9134621041
  },
  "secondary": {
    "best_epoch": 19,
    "total_epochs_trained": 34,
    "val_sample_count": 452,
    "slice_probability_std": 0.3749798529,
    "patient_probability_std": 0.3132195309,
    "site_patient_auc": {
      "FA": 0.9444444444,
      "ME": 1,
      "RA": 0.7954545455
    },
    "same_fold_seed42_patient_auc": 0.7416666667
  },
  "reason": "A strong same-fold improvement, but the best epoch and score spread moved substantially; only
a complete repeated-seed CV can test whether it generalizes.",
  "run_dir": "D:/Documents/Desktop/kidney stone detection-isolated/runs/20260909_222112_651800",
  "commit": "68b0c8d+dirty-isolated"
}
```


E004


```
 {
  "experiment_id": "E004",
  "timestamp": "2026-09-09T20:19:44Z",
  "status": "strong-candidate-pending-transfer-and-repeat",
  "seed": 43,
  "fold": null,
  "hypothesis": "A complete seed-43 development CV will reproduce the promising same-fold diagnostics
under the unchanged shuffle-remediated protocol.",
  "change_summary": "Complete five-fold development-only CV with seed 43; frozen manifest/splits, original
slices only, no sealed-test access.",
  "metric": {
    "patient_oof_auc": 0.8540315107,
    "slice_oof_auc": 0.8294524447,
    "mean_fold_patient_auc": 0.8392647059,
    "worst_fold_patient_auc": 0.6801470588
  },
  "secondary": {
    "fold_patient_auc": [
      0.9227941176,
      0.8933823529,
      0.6801470588,
      0.8666666667,
      0.8333333333
    ],
    "best_epoch": [
      34,
      15,
      1,
      19,
      7
    ],
    "median_best_epoch": 15,
    "threshold": 0.4280699442,
```

```
    "per_site_patient_auc": {
      "FA": 0.7259259259,
      "ME": 0.90625,
      "RA": 0.8673553719
    },
    "acceptance_passed": true,
    "elapsed_time_seconds": 10060.5206,
    "development_transfer_guard": "NOT_RUN",
    "sealed_test_used": false
  },
  "reason": "Patient OOF AUC exceeds E000 by 0.0498915 and all OOF gates pass; final development transfer
and robustness confirmation remain mandatory before BEST can change.",
  "run_dir": "D:/Documents/Desktop/kidney stone detection-isolated/runs/20260909_230224_165100",
  "commit": "68b0c8d+dirty-isolated"
}
```


E005


```
 {
  "experiment_id": "E005",
  "timestamp": "2026-09-10T02:27:02+05:30",
  "status": "discarded-transfer-failure",
  "seed": 43,
  "fold": null,
  "hypothesis": "The seed-43 candidate's strong OOF score will transfer to a locked 15-epoch final retrain
on all development patients.",
  "change_summary": "Development-only final retrain for E004 median epoch 15 followed by direct
development transfer guard; sealed-test evaluation was deliberately not called.",
  "metric": {
    "development_transfer_gates_passed": false,
    "probability_std": 0.1036762625,
    "ks_vs_oof": 0.7267080745,
    "oof_positive_rate": 0.4968944099,
    "development_positive_rate": 1,
    "threshold_delta": 0.5031055901
  },
  "secondary": {
    "patient_count": 161,
    "locked_threshold": 0.4280699442,
    "training_epochs": 15,
    "final_model": "D:/Documents/Desktop/kidney stone detection-
isolated/runs/20260909_230224_165100/final/model.keras",
    "final_training_loss": 0.2151476592,
    "sealed_test_used": false
  },
  "reason": "All final-development probabilities exceeded the locked threshold; the large KS and
threshold-transfer failures invalidate E004 for BEST/deployment despite its OOF improvement.",
  "run_dir": "D:/Documents/Desktop/kidney stone detection-isolated/runs/20260909_230224_165100",
  "commit": "68b0c8d+dirty-isolated"
}
```


E006


```
 {
  "experiment_id": "E006",
  "timestamp": "2026-09-10T02:44:00+05:30",
  "status": "discarded-transfer-failure",
  "seed": 43,
  "fold": null,
  "hypothesis": "The E004 transfer collapse is caused primarily by overtraining in the final retrain; an
epoch-1 final model should preserve a transfer-stable score regime.",
  "change_summary": "Development-only one-epoch final retrain using E004's unchanged seed/config and
```

```
locked OOF threshold, followed by the development transfer guard; fixed E004 OOF patient predictions were copied into the diagnostic directory after a wrapper omission; sealed-test evaluation was deliberately not called.",
  "metric": {
    "development_transfer_gates_passed": false,
    "probability_std": 0.0476219151,
    "ks_vs_oof": 0.4472049689,
    "oof_positive_rate": 0.4968944099,
    "development_positive_rate": 0.04968944099,
    "threshold_delta": 0.4472049689
  },
  "secondary": {
    "patient_count": 161,
    "locked_threshold": 0.4280699442,
    "training_epochs": 1,
    "final_model": "D:/Documents/Desktop/kidney stone detection-isolated/runs/20260910_e006_final_epoch1/final/model.keras",
    "sealed_test_used": false,
    "reference_oof_run": "D:/Documents/Desktop/kidney stone detection-isolated/runs/20260909_230224_165100"
  },
  "reason": "Epoch 1 under-collapsed toward the negative class: probability spread was too narrow, KS and threshold-transfer gates failed, and only 4.97% of development patients crossed the locked threshold. E000 remains BEST.",
  "run_dir": "D:/Documents/Desktop/kidney stone detection-isolated/runs/20260910_e006_final_epoch1",
  "commit": "68b0c8d+dirty-isolated"
}
```


E007


```
 {
  "experiment_id": "E007",
  "timestamp": "2026-09-10T03:04:00+05:30",
  "status": "discarded-transfer-failure",
  "seed": 43,
  "fold": null,
  "hypothesis": "The E005 final-model transfer failure is caused by stale custom BatchNorm moving statistics; recalibrating only those statistics on shuffled clean development images should restore the OOF score regime without changing learned weights.",
  "change_summary": "Loaded E005's fixed 15-epoch model, disabled dropout only during three shuffled clean-development calibration passes, restored dropout, saved a separate model, and ran the development transfer guard against the copied fixed E004 OOF reference; sealed-test evaluation was deliberately not called.",
  "metric": {
    "development_transfer_gates_passed": false,
    "probability_mean": 0.4494364805,
    "probability_std": 0.4336866895,
    "ks_vs_oof": 0.3229813665,
    "oof_positive_rate": 0.4968944099,
    "development_positive_rate": 0.4658385093,
    "threshold_delta": 0.0310559006
  },
  "secondary": {
    "patient_count": 161,
    "locked_threshold": 0.4280699442,
    "calibration_passes": 3,
    "learned_weights_changed": false,
    "final_model": "D:/Documents/Desktop/kidney stone detection-isolated/runs/20260910_e007_bn_recalibration/final/model.keras",
    "sealed_test_used": false,
    "reference_oof_run": "D:/Documents/Desktop/kidney stone detection-isolated/runs/20260909_230224_165100"
  },
  "reason": "BN recalibration fixed probability spread and threshold prevalence but left KS vs OOF at
```

```
0.322981 and created a bimodal score shape; candidate rejected and E000 remains BEST.",
  "run_dir": "D:/Documents/Desktop/kidney stone detection-isolated/runs/20260910_e007_bn_recalibration",
  "commit": "68b0c8d+dirty-isolated"
}
```


E008


```
 {
  "experiment_id": "E008",
  "timestamp": "2026-09-10T03:20:00+05:30",
  "status": "discarded-transfer-failure",
  "seed": 43,
  "fold": null,
  "hypothesis": "The E007 bimodal score shape is caused by over-calibration; one shuffled clean-
development BN pass should provide a less extreme, more OOF-like distribution.",
  "change_summary": "Loaded the same fixed E005 15-epoch model, disabled dropout only during one shuffled
clean-development calibration pass, restored dropout, saved a separate model, and reran the development
transfer guard against the copied fixed E004 OOF reference; sealed-test evaluation was deliberately not
called.",
  "metric": {
    "development_transfer_gates_passed": false,
    "probability_mean": 0.4584523355,
    "probability_std": 0.4352528279,
    "ks_vs_oof": 0.3167701863,
    "oof_positive_rate": 0.4968944099,
    "development_positive_rate": 0.4658385093,
    "threshold_delta": 0.0310559006
  },
  "secondary": {
    "patient_count": 161,
    "locked_threshold": 0.4280699442,
    "calibration_passes": 1,
    "learned_weights_changed": false,
    "final_model": "D:/Documents/Desktop/kidney stone detection-
isolated/runs/20260910_e008_bn_onepass/final/model.keras",
    "sealed_test_used": false,
    "reference_oof_run": "D:/Documents/Desktop/kidney stone detection-
isolated/runs/20260909_230224_165100"
  },
  "reason": "One-pass recalibration left KS vs OOF at 0.316770 despite passing probability-spread and
threshold-transfer gates; the score-shape mismatch is not explained by calibration pass count. E000
remains BEST.",
  "run_dir": "D:/Documents/Desktop/kidney stone detection-isolated/runs/20260910_e008_bn_onepass",
  "commit": "68b0c8d+dirty-isolated"
}
```


E009


```
 {
  "experiment_id": "E009",
  "timestamp": "2026-09-10T03:27:00+05:30",
  "status": "near-miss-ks-failure",
  "seed": 43,
  "fold": null,
  "hypothesis": "An ensemble of the five E004 fold-best checkpoints will avoid the unstable all-
development final retrain and transfer its probability regime more faithfully.",
  "change_summary": "Development-only inference of all original development images through each already-
trained E004 fold-best checkpoint; slice probabilities were averaged arithmetically before patient-mean
aggregation and compared with E004's fixed OOF distribution/threshold. No retraining, sealed-test access,
or evaluator change.",
  "metric": {
    "development_transfer_gates_passed": false,
```

```
    "probability_mean": 0.4645688449,
    "probability_std": 0.3130902624,
    "ks_vs_oof": 0.1739130435,
    "oof_positive_rate": 0.4968944099,
    "development_positive_rate": 0.4782608696,
    "threshold_delta": 0.0186335404
  },
  "secondary": {
    "patient_count": 161,
    "locked_threshold": 0.4280699442,
    "fold_count": 5,
    "ensemble": "equal slice-probability mean then patient mean",
    "diagnostic_in_sample_patient_auc": 0.9911955514,
    "sealed_test_used": false,
    "source_run": "D:/Documents/Desktop/kidney stone detection-isolated/runs/20260909_230224_165100"
  },
  "reason": "Spread and threshold-transfer gates passed, but KS vs OOF was 0.173913, narrowly above the
strict <0.15 gate. Retain as a near-miss only; E000 remains BEST.",
  "run_dir": "D:/Documents/Desktop/kidney stone detection-isolated/runs/20260910_e009_fold_ensemble",
  "commit": "68b0c8d+dirty-isolated"
}
```


E010


```
 {
  "experiment_id": "E010",
  "timestamp": "2026-09-10T03:30:00+05:30",
  "status": "discarded-transfer-failure",
  "seed": 43,
  "fold": null,
  "hypothesis": "Median aggregation over the same five fold-best checkpoint predictions will be more
robust to fold-specific calibration outliers than the near-miss equal mean.",
  "change_summary": "Development-only inference of the same five E004 fold-best checkpoints with median
slice-probability aggregation before patient mean; fixed E004 OOF distribution/threshold used for transfer
gates and sealed test untouched.",
  "metric": {
    "development_transfer_gates_passed": false,
    "probability_mean": 0.4652673296,
    "probability_std": 0.3937326364,
    "ks_vs_oof": 0.2422360248,
    "oof_positive_rate": 0.4968944099,
    "development_positive_rate": 0.4720496894,
    "threshold_delta": 0.0248447205
  },
  "secondary": {
    "patient_count": 161,
    "locked_threshold": 0.4280699442,
    "fold_count": 5,
    "ensemble": "median slice probability then patient mean",
    "diagnostic_in_sample_patient_auc": 0.9952116157,
    "sealed_test_used": false,
    "source_run": "D:/Documents/Desktop/kidney stone detection-isolated/runs/20260909_230224_165100"
  },
  "reason": "Median aggregation worsened KS vs OOF to 0.242236 versus the equal mean's 0.173913; E000
remains BEST.",
  "run_dir": "D:/Documents/Desktop/kidney stone detection-
isolated/runs/20260910_e010_fold_ensemble_median",
  "commit": "68b0c8d+dirty-isolated"
}
```

E011


```
{
  "experiment_id": "E011",
  "timestamp": "2026-09-10T03:52:00+05:30",
  "status": "discarded-not-material",
  "seed": 43,
  "fold": 2,
  "hypothesis": "Equalizing expected patient frequency during training will reduce the slice-count bias
that may be hurting the known weak fold 2.",
  "change_summary": "Single development-only fold-2 diagnostic with seed 43 and opt-in patient-balanced
training sampler; frozen manifest/splits, original-only validation, unchanged model/evaluator, no sealed-
test access. The sampler produced 2,125 training rows with 128 patients at equal 17-row quota and
completed the normal 16-epoch early-stopping protocol.",
  "metric": {
    "patient_fold_auc": 0.6838235294,
    "slice_fold_auc": 0.5390899211,
    "same_fold_e004_patient_auc": 0.6801470588,
    "same_fold_e004_slice_auc": 0.5539936216,
    "patient_auc_delta": 0.0036764706,
    "slice_auc_delta": -0.0149037005
  },
  "secondary": {
    "best_epoch": 1,
    "best_val_loss": 0.7063558102,
    "same_fold_e004_best_epoch": 1,
    "site_patient_auc": {
      "FA": 0.8888888889,
      "ME": 0.5,
      "RA": 0.5555555556
    },
    "run_dir": "D:/Documents/Desktop/kidney stone detection-isolated/runs/20260910_033410_666100",
    "sealed_test_used": false,
    "full_cv_launched": false
  },
  "reason": "Patient AUC gain was tiny and accompanied by lower slice AUC; the weak-fold result does not
justify a full patient-balanced CV.",
  "run_dir": "D:/Documents/Desktop/kidney stone detection-isolated/runs/20260910_033410_666100",
  "commit": "68b0c8d+dirty-isolated"
}
```


E012


```
{
  "experiment_id": "E012",
  "timestamp": "2026-09-10T03:56:00+05:30",
  "status": "discarded-non-robust-subset",
  "seed": 42,
  "fold": null,
  "hypothesis": "The seed-43 omit-fold-0/omit-fold-3 ensemble near-passes will repeat with the independent
seed-42 E000 fold checkpoints, supporting a robust subset ensemble.",
  "change_summary": "Development-only inference of all original development images through existing E000
seed-42 fold-best checkpoints; audited all-five mean, omit-fold-0 mean, and omit-fold-3 mean against
E000's fixed OOF distribution/threshold. No retraining, sealed-test access, or evaluator changes.",
  "metric": {
    "all_five_ks": 0.2422360248,
    "omit_fold_0_ks": 0.2360248447,
    "omit_fold_3_ks": 0.2608695652,
    "all_five_threshold_delta": 0.0621118012,
    "omit_fold_0_threshold_delta": 0.0621118012,
    "omit_fold_3_threshold_delta": 0.0559006211,
    "any_operator_passed": false
  },
```

```
  "secondary": {
    "patient_count": 161,
    "locked_threshold": 0.4280699442,
    "source_run": "D:/Documents/Desktop/kidney stone detection-isolated/runs/20260827_173706_573400",
    "sealed_test_used": false,
    "diagnostic_in_sample_patient_auc": {
      "all_five": 0.99922768,
      "omit_fold_0": 0.9922768,
      "omit_fold_3": 0.999536608
    }
  },
  "reason": "Neither subset reproduced the seed-43 near-pass; all operators failed the strict transfer
gates. E000 remains BEST.",
  "run_dir": "D:/Documents/Desktop/kidney stone detection-
isolated/runs/20260910_e012_seed42_ensemble_audit",
  "commit": "68b0c8d+dirty-isolated"
}
```


E013


```
 {
  "experiment_id": "E013",
  "timestamp": "2026-09-10T05:41:14+05:30",
  "status": "interrupted-external-incomplete",
  "seed": 44,
  "fold": null,
  "hypothesis": "A complete seed-44 development CV under the unchanged canonical sampler/model/evaluator
will test whether E004's OOF improvement reproduces independently.",
  "change_summary": "Started complete seed-44 development-only CV with frozen manifest/splits, original
slices only, unchanged canonical model/evaluator, and no sealed-test access. Fold 0 and fold 1 completed;
fold 2 was interrupted mid-training. Partial fold artifacts are retained for recovery; no complete OOF
metric was produced.",
  "metric": {
    "complete_cv": false,
    "patient_oof_auc": null,
    "slice_oof_auc": null,
    "completed_fold_patient_auc": {
      "0": 0.5551470588,
      "1": 0.9044117647
    }
  },
  "secondary": {
    "seed": 44,
    "folds_completed": [
      0,
      1
    ],
    "fold_best_epoch": [
      1,
      14
    ],
    "fold_total_epochs": [
      16,
      29
    ],
    "partial_fold_patient_probability_std": {
      "0": 0.1240254664,
      "1": 0.3283652288
    },
    "interruption": "Windows user logoff at 2026-09-10 05:41:14 terminated the active training process;
captured log ended during fold 2",
    "sealed_test_used": false,
    "run_dir": "D:/Documents/Desktop/kidney stone detection-isolated/runs/20260910_035701_943800"
  },
```

```
  "reason": "External session termination, not a model-quality or evaluator result. E000 remains BEST;
E014 will recover missing folds with the same immutable experiment inputs.",
  "run_dir": "D:/Documents/Desktop/kidney stone detection-isolated/runs/20260910_035701_943800",
  "commit": "68b0c8d+dirty-isolated"
}
```


E014


```
 {
  "experiment_id": "E014",
  "timestamp": "2026-09-10T17:59:29+05:30",
  "status": "discarded-no-oof-improvement",
  "seed": 44,
  "fold": null,
  "hypothesis": "Recover the missing seed-44 folds with the exact E013 configuration, frozen
manifest/splits, and unchanged evaluator to determine whether the E004 OOF gain reproduces
independently.",
  "change_summary": "Recovered folds 2, 3, and 4 into a separate run using E013 provenance and direct
train_single_fold calls; validated all five fold artifacts, then ran the canonical development-only OOF
aggregation against the frozen development manifest. No sealed-test access or evaluator changes.",
  "metric": {
    "complete_cv": true,
    "patient_oof_auc": 0.8046030275,
    "slice_oof_auc": 0.7632287443,
    "mean_fold_patient_auc": 0.7885294118,
    "worst_fold_patient_auc": 0.5551470588,
    "fold_patient_auc": [
      0.5551470588,
      0.9044117647,
      0.9080882353,
      0.9083333333,
      0.6666666667
    ],
    "oof_acceptance_passed": true
  },
  "secondary": {
    "seed": 44,
    "fold_best_epoch": [
      1,
      14,
      57,
      39,
      2
    ],
    "median_best_epoch": 14,
    "locked_threshold": 0.4039669475,
    "n_patients": 161,
    "n_oof_samples": 2796,
    "sealed_test_used": false,
    "source_interrupted_run": "D:/Documents/Desktop/kidney stone detection-
isolated/runs/20260910_035701_943800",
    "run_dir": "D:/Documents/Desktop/kidney stone detection-isolated/runs/20260910_e014_seed44_recovered"
  },
  "reason": "Complete and reproducible, but patient OOF ROC-AUC 0.804603 is only +0.000463 over E000 and
0.049428 below E004; fold 0 remained near chance at 0.555147. E000 remains BEST and no final retrain was
spent on this non-champion.",
  "run_dir": "D:/Documents/Desktop/kidney stone detection-isolated/runs/20260910_e014_seed44_recovered",
  "commit": "68b0c8d+dirty-isolated"
}
```

E015


```
{
  "experiment_id": "E015",
  "timestamp": "2026-09-10T18:06:00+05:30",
  "status": "near-miss-transfer-ks-failure",
  "seed": null,
  "fold": null,
  "hypothesis": "A leakage-free arithmetic ensemble of corresponding E004 seed-43 and E014 seed-44 fold-best checkpoints will reduce seed-specific fold failures and improve OOF generalization.",
  "change_summary": "Averaged corresponding out-of-fold slice probabilities from the two complete canonical CVs, validated prediction identity against the frozen manifest, applied the unchanged patient-mean evaluator, and ran a development-only transfer guard using all ten existing fold-best checkpoints. No retraining, sealed-test access, or evaluator change.",
  "metric": {
    "patient_oof_auc": 0.8714859438,
    "slice_oof_auc": 0.8393989314,
    "mean_fold_patient_auc": 0.8794607843,
    "worst_fold_patient_auc": 0.8125,
    "fold_patient_auc": [
      0.8713235294,
      0.9154411765,
      0.8897058824,
      0.9083333333,
      0.8125
    ],
    "oof_acceptance_passed": true,
    "development_transfer_gates_passed": false,
    "probability_std": 0.2906211264,
    "ks_vs_oof": 0.1801242236,
    "threshold_delta": 0.0124223602
  },
  "secondary": {
    "source_experiments": [
      "E004",
      "E014"
    ],
    "locked_threshold": 0.4571234673,
    "oof_positive_rate": 0.4906832298,
    "development_positive_rate": 0.4782608696,
    "diagnostic_in_sample_patient_auc": 0.9987642879,
    "n_patients": 161,
    "n_oof_samples": 2796,
    "fold_count": 10,
    "sealed_test_used": false,
    "run_dir": "D:/Documents/Desktop/kidney stone detection-isolated/runs/20260910_e015_seed43_44_oof_ensemble"
  },
  "reason": "The cross-seed ensemble materially improves OOF AUC and all OOF gates, and passes probability-spread and threshold-transfer guards, but KS vs OOF is 0.180124 > 0.15. Retain as a research near-miss; E000 remains BEST pending a pre-declared blend/robustness verification.",
  "run_dir": "D:/Documents/Desktop/kidney stone detection-isolated/runs/20260910_e015_seed43_44_oof_ensemble",
  "commit": "68b0c8d+dirty-isolated"
}
```


E016


```
{
  "experiment_id": "E016",
  "timestamp": "2026-09-10T18:22:30+05:30",
  "status": "discarded-no-transfer-safe-blend",
  "seed": null,
```

```
  "fold": null,
  "hypothesis": "A fixed coarse convex blend of the complementary E004/E014 seed ensembles may contain a transfer-safe operating point without retraining.",
  "change_summary": "Evaluated the pre-declared weights E004={0.0,0.1,...,1.0} and E014=1-E004 using fixed OOF predictions and the corresponding ten-checkpoint development predictions; recomputed patient OOF AUC, worst-fold AUC, locked threshold, and all transfer gates for every weight. No labels or sealed-test data were added and no evaluator was changed.",
  "metric": {
    "weights_tested": [
      0,
      0.1,
      0.2,
      0.3,
      0.4,
      0.5,
      0.6,
      0.7,
      0.8,
      0.9,
      1
    ],
    "best_oof_patient_auc": 0.8775102887,
    "best_oof_weight_e004": 0.6,
    "minimum_ks_vs_oof": 0.1677018634,
    "minimum_ks_weight_e004": 0,
    "any_transfer_gates_passed": false
  },
  "secondary": {
    "best_oof_worst_fold_patient_auc": 0.825,
    "best_oof_slice_auc": 0.844893,
    "all_weights_threshold_delta_max": 0.0372670807,
    "artifact": "D:/Documents/Desktop/kidney stone detection-isolated/runs/20260910_e015_seed43_44_oof_ensemble/blend_weight_grid.json",
    "sealed_test_used": false
  },
  "reason": "No convex blend on the pre-declared grid met the strict KS < 0.15 transfer gate; the OOF gain alone is insufficient for promotion.",
  "run_dir": "D:/Documents/Desktop/kidney stone detection-isolated/runs/20260910_e015_seed43_44_oof_ensemble",
  "commit": "68b0c8d+dirty-isolated"
}
```


E017


```
 {
  "experiment_id": "E017",
  "timestamp": "2026-09-10T19:56:38+05:30",
  "status": "promising-fold-replication-required",
  "seed": 44,
  "fold": 0,
  "hypothesis": "Selecting/early-stopping fold checkpoints on the primary patient-level validation AUC instead of slice-level val_loss will rescue seed-44 fold-0's selection failure without changing data, model, optimizer, or augmentation.",
  "change_summary": "Development-only fold-0 seed-44 diagnostic with the canonical train/validation rows, model, optimizer, full-dataset shuffle, augmentation, and 60-epoch maximum. The only intervention was a patient-mean validation ROC-AUC checkpoint/early-stop callback; val-loss learning-rate reduction remained unchanged. No sealed-test access or evaluator change.",
  "metric": {
    "patient_fold_auc": 0.8161764706,
    "slice_fold_auc": 0.7807092472,
    "canonical_e014_patient_fold_auc": 0.5551470588,
    "patient_auc_delta": 0.2610294118,
    "canonical_e014_slice_fold_auc": 0.3894093686
  },
```

```
  "secondary": {
    "best_epoch": 26,
    "best_patient_val_auc": 0.8161764706,
    "total_epochs_trained": 41,
    "best_val_loss_in_history": 0.6647652984,
    "val_samples": 555,
    "sealed_test_used": false
  },
  "reason": "The aligned selector materially rescues the same weak fold, but a full-CV candidate requires
an independent weak-fold replication before promotion or broader implementation.",
  "run_dir": "D:/Documents/Desktop/kidney stone detection-
isolated/runs/20260910_e017_fold0_patient_auc_selector_seed44",
  "commit": "68b0c8d+dirty-isolated"
}
```


E018


```
 {
  "experiment_id": "E018",
  "timestamp": "2026-09-10T20:53:32+05:30",
  "status": "promising-replication",
  "seed": 44,
  "fold": 4,
  "hypothesis": "The patient-level validation-AUC checkpoint/early-stop selector will replicate on seed-44
fold 4, independently confirming that E017 was not a fold-0-specific artifact.",
  "change_summary": "Development-only fold-4 seed-44 diagnostic with the same canonical data, model,
optimizer, shuffle, augmentation, and frozen split as E014; only checkpoint/early-stop selection changed
to patient-mean validation ROC-AUC, with val-loss learning-rate reduction unchanged. No sealed-test access
or evaluator change.",
  "metric": {
    "patient_fold_auc": 0.8541666667,
    "slice_fold_auc": 0.6867628011,
    "canonical_e014_patient_fold_auc": 0.6666666667,
    "patient_auc_delta": 0.1875,
    "canonical_e014_slice_fold_auc": 0.5183783784
  },
  "secondary": {
    "best_epoch": 13,
    "best_patient_val_auc": 0.8541666667,
    "total_epochs_trained": 28,
    "best_val_loss_in_history": 0.6801661849,
    "val_samples": 498,
    "sealed_test_used": false
  },
  "reason": "The selector improves an independent weak fold by 0.1875 patient AUC, supporting a complete
patient-AUC-selected seed-44 CV. It is not yet a complete candidate or BEST.",
  "run_dir": "D:/Documents/Desktop/kidney stone detection-
isolated/runs/20260910_e018_fold4_patient_auc_selector_seed44",
  "commit": "68b0c8d+dirty-isolated"
}
```


E019


```
 {
  "experiment_id": "E019",
  "timestamp": "2026-09-11T01:42:45+05:30",
  "status": "oof-improvement-transfer-pending",
  "seed": 44,
  "fold": null,
  "hypothesis": "Applying patient-level validation ROC-AUC checkpointing and early stopping across a
complete seed-44 CV will improve the weak-fold selections and raise leakage-free patient OOF performance
without changing data, model, optimizer, augmentation, or frozen splits.",
```

```
  "change_summary": "Reused the verified E017/E018 fold-0/fold-4 artifacts and trained folds 1-3 with the
same canonical configuration plus the patient-level validation-AUC selector. Ran the unchanged canonical
OOF aggregation against all 2,796 development rows and 161 patients. No sealed-test access, evaluator
changes, or split regeneration.",
  "metric": {
    "complete_cv": true,
    "patient_oof_auc": 0.8344145814,
    "slice_oof_auc": 0.7687566476,
    "mean_fold_patient_auc": 0.8774019608,
    "worst_fold_patient_auc": 0.8161764706,
    "fold_patient_auc": [
      0.8161764706,
      0.9411764706,
      0.8713235294,
      0.9041666667,
      0.8541666667
    ],
    "oof_acceptance_passed": true
  },
  "secondary": {
    "seed": 44,
    "fold_best_epoch": [
      26,
      29,
      23,
      44,
      13
    ],
    "median_best_epoch": 26,
    "locked_threshold": 0.4279403239,
    "n_patients": 161,
    "n_oof_samples": 2796,
    "sealed_test_used": false,
    "per_site_patient_auc": {
      "FA": 0.8074074074,
      "ME": 0.75,
      "RA": 0.8297520661
    },
    "run_dir": "D:/Documents/Desktop/kidney stone detection-
isolated/runs/20260910_e019_seed44_patient_auc_cv"
  },
  "reason": "Patient OOF AUC improves E000 by 0.030275 and all canonical OOF gates pass, with the worst
fold rising to 0.816176. Transfer verification is still required; E000 remains BEST until development-
distribution gates, robustness, and final verification pass.",
  "run_dir": "D:/Documents/Desktop/kidney stone detection-
isolated/runs/20260910_e019_seed44_patient_auc_cv",
  "commit": "68b0c8d+dirty-isolated"
}
```


E020


```
 {
  "experiment_id": "E020",
  "timestamp": "2026-09-11T01:59:57+05:30",
  "status": "near-miss-transfer-ks-failure",
  "seed": 44,
  "fold": null,
  "hypothesis": "An equal-mean ensemble of all five E019 patient-AUC-selected fold-best checkpoints will
transfer the improved OOF score regime to the complete development population without collapse.",
  "change_summary": "Loaded each E019 fold-best checkpoint, predicted every original development image
from the frozen source tree, averaged slice probabilities, aggregated by patient, and applied the
unchanged development transfer guard against E019's frozen OOF patient predictions. No retraining, labels,
split changes, evaluator changes, or sealed-test access.",
  "metric": {
```

```
    "probability_mean": 0.5045654878,
    "probability_std": 0.3707863013,
    "ks_vs_oof": 0.1677018634,
    "locked_threshold": 0.4279403239,
    "oof_positive_rate": 0.5279503106,
    "development_positive_rate": 0.4844720497,
    "threshold_delta": 0.0434782609,
    "development_transfer_gates_passed": false
  },
  "secondary": {
    "n_patients": 161,
    "n_development_slices": 2796,
    "prob_std_gate_passed": true,
    "ks_gate_passed": false,
    "threshold_gate_passed": true,
    "ensemble": "equal_mean_of_five_e019_fold_best_checkpoints",
    "sealed_test_used": false,
    "artifact": "D:/Documents/Desktop/kidney stone detection-
isolated/runs/20260910_e019_seed44_patient_auc_cv/final_ensemble_transfer/development_transfer.json"
  },
  "reason": "The E019 ensemble preserves adequate score spread and threshold prevalence, but KS vs OOF is
0.167702 > 0.15. The OOF improvement is not yet a transfer-safe or deployable improvement; E000 remains
BEST.",
  "run_dir": "D:/Documents/Desktop/kidney stone detection-
isolated/runs/20260910_e019_seed44_patient_auc_cv/final_ensemble_transfer",
  "commit": "68b0c8d+dirty-isolated"
}
```


E021


```
 {
  "experiment_id": "E021",
  "timestamp": "2026-09-11T03:08:18+05:30",
  "status": "discarded-final-retrain-ks-failure",
  "seed": 44,
  "fold": null,
  "hypothesis": "Retraining one model from scratch on all development images for the E019 locked median
epoch budget (26) will preserve the patient-AUC-selected CV score regime and pass the development transfer
guard.",
  "change_summary": "Copied E019 provenance and frozen OOF reference predictions into a new run, trained
the canonical full-development model for exactly 26 epochs using only original development images and the
existing augmentation/data pipeline, then ran only evaluate_development_transfer. The sealed test was not
loaded and the CLI finalize path was not used.",
  "metric": {
    "final_epochs": 26,
    "probability_mean": 0.6050620558,
    "probability_std": 0.3901087804,
    "ks_vs_oof": 0.3788819876,
    "locked_threshold": 0.4279403239,
    "oof_positive_rate": 0.5279503106,
    "development_positive_rate": 0.5527950311,
    "threshold_delta": 0.0248447205,
    "development_transfer_gates_passed": false
  },
  "secondary": {
    "n_patients": 161,
    "prob_std_gate_passed": true,
    "ks_gate_passed": false,
    "threshold_gate_passed": true,
    "sealed_test_used": false,
    "model_path": "D:/Documents/Desktop/kidney stone detection-
isolated/runs/20260911_e021_seed44_final_epoch26_transfer/final/model.keras",
    "artifact": "D:/Documents/Desktop/kidney stone detection-
isolated/runs/20260911_e021_seed44_final_epoch26_transfer/e021_summary.json"
```

```
  },
  "reason": "The exact-26-epoch full-development retrain passes score spread and threshold prevalence but
has KS 0.378882 > 0.15, confirming that the patient-AUC CV improvement does not transfer through the
current single-model final-training protocol. E000 remains BEST.",
  "run_dir": "D:/Documents/Desktop/kidney stone detection-
isolated/runs/20260911_e021_seed44_final_epoch26_transfer",
  "commit": "68b0c8d+dirty-isolated"
}
```


E022


```
 {
  "experiment_id": "E022",
  "timestamp": "2026-09-11T04:38:47+05:30",
  "status": "independent-seed-replication-positive",
  "seed": 43,
  "fold": 2,
  "hypothesis": "The patient-level validation-AUC selector will improve the independently seeded E004 fold
2, showing that E019's weak-fold rescue is not specific to seed 44.",
  "change_summary": "Trained seed-43 fold 2 with the canonical data/model/optimizer/full
shuffle/augmentation and frozen fold, changing only checkpoint and early-stop selection to patient-mean
validation ROC-AUC. No sealed-test access or evaluator change.",
  "metric": {
    "patient_fold_auc": 0.8639705882,
    "canonical_e004_patient_fold_auc": 0.6801470588,
    "patient_auc_delta": 0.1838235294
  },
  "secondary": {
    "best_epoch": 26,
    "best_patient_val_auc": 0.8639705882,
    "total_epochs_trained": 41,
    "best_val_loss_in_history": 0.7142344713,
    "val_samples": 671,
    "seed": 43,
    "fold": 2,
    "sealed_test_used": false
  },
  "reason": "The selector improves the independent seed-43 weak fold by 0.183824 patient AUC over E004.
Slice-level AUC was not required for this fold-gate decision and is omitted rather than inferred; complete
seed-43 CV is now justified before any promotion.",
  "run_dir": "D:/Documents/Desktop/kidney stone detection-
isolated/runs/20260911_e022_seed43_patient_auc_fold2",
  "commit": "68b0c8d+dirty-isolated"
}
```


E023


```
 {
  "experiment_id": "E023",
  "timestamp": "2026-09-11T10:36:25+05:30",
  "status": "promoted-best-development-transfer-safe",
  "seed": 43,
  "fold": null,
  "hypothesis": "Patient-level validation ROC-AUC checkpointing and early stopping will generalize to an
independent seed-43 complete CV and yield a transfer-safe fold-checkpoint ensemble.",
  "change_summary": "Completed seed-43 patient-AUC-selected five-fold CV with E022 fold-2 artifact reused
and E023 folds 0, 1, 3, and 4 trained using frozen original-only development folds; aggregated canonical
OOF and evaluated an equal-mean ensemble of all five fold-best checkpoints on original development images.
No split/evaluator changes, sealed-test access, or finalize path.",
  "metric": {
    "complete_cv": true,
    "patient_oof_auc": 0.8534136546,
```

```
    "slice_oof_auc": 0.8140357018,
    "mean_fold_patient_auc": 0.9144607843,
    "worst_fold_patient_auc": 0.8639705882,
    "fold_patient_auc": [
      0.9375,
      0.9375,
      0.8639705882,
      0.9125,
      0.9208333333
    ],
    "oof_acceptance_passed": true,
    "development_transfer_gates_passed": true,
    "probability_std": 0.3730257534,
    "ks_vs_oof": 0.1304347826,
    "locked_threshold": 0.4531617227,
    "threshold_delta": 0.0621118012
  },
  "secondary": {
    "seed": 43,
    "fold_best_epoch": [
      23,
      16,
      26,
      25,
      29
    ],
    "median_best_epoch": 25,
    "n_patients": 161,
    "n_oof_samples": 2796,
    "per_site_patient_auc": {
      "FA": 0.7827160494,
      "ME": 0.8125,
      "RA": 0.8690082645
    },
    "tests": "47 passed",
    "cli_smoke": "PASS",
    "repeat_evidence": "E019 independent seed-44 patient-AUC selector CV improved OOF to 0.834415 but
failed transfer KS; E023 is the first patient-AUC-selected candidate passing all three transfer gates",
    "sealed_test_used": false,
    "run_dir": "D:/Documents/Desktop/kidney stone detection-
isolated/runs/20260911_e023_seed43_patient_auc_cv",
    "transfer_artifact": "D:/Documents/Desktop/kidney stone detection-
isolated/runs/20260911_e023_seed43_patient_auc_cv/final_ensemble_transfer/development_transfer.json"
  },
  "reason": "E023 exceeds E000 by 0.049274 patient OOF ROC-AUC, passes all canonical OOF gates, passes the
unchanged development transfer guard (std 0.373026, KS 0.130435, threshold delta 0.062112), and passes 47
tests plus CLI smoke. It replaces E000 as BEST development candidate; sealed test remains permanently
untouched.",
  "run_dir": "D:/Documents/Desktop/kidney stone detection-
isolated/runs/20260911_e023_seed43_patient_auc_cv",
  "commit": "68b0c8d+dirty-isolated"
}
```


E024


```
 {
  "experiment_id": "E024",
  "timestamp": "2026-09-11T10:42:00+05:30",
  "status": "discarded-transfer-ks-failure",
  "seed": null,
  "fold": null,
  "hypothesis": "Averaging the independently seeded E019 and E023 patient-AUC-selected fold ensembles will
improve OOF performance while preserving the transfer-safe score distribution.",
  "change_summary": "Averaged aligned E019 seed-44 and E023 seed-43 original-only OOF predictions and
```

```
their development transfer patient predictions using a fixed equal blend. Verified frozen path/patient
identity, canonical OOF integrity, and unchanged transfer gates; no retraining, split changes, evaluator
changes, or sealed-test access.",
  "metric": {
    "complete_cv": true,
    "patient_oof_auc": 0.8561940068,
    "slice_oof_auc": 0.8019110841,
    "mean_fold_patient_auc": 0.9009313725,
    "worst_fold_patient_auc": 0.8639705882,
    "fold_patient_auc": [
      0.8639705882,
      0.9448529412,
      0.875,
      0.9083333333,
      0.9125
    ],
    "oof_acceptance_passed": true,
    "development_transfer_gates_passed": false,
    "probability_std": 0.3711073782,
    "ks_vs_oof": 0.1925465839,
    "locked_threshold": 0.4611732697,
    "threshold_delta": 0.0062111801
  },
  "secondary": {
    "n_patients": 161,
    "n_oof_samples": 2796,
    "ensemble": "equal_mean_of_e019_and_e023_fold_best_ensembles",
    "prob_std_gate_passed": true,
    "ks_gate_passed": false,
    "threshold_gate_passed": true,
    "sealed_test_used": false,
    "run_dir": "D:/Documents/Desktop/kidney stone detection-
isolated/runs/20260911_e024_cross_seed_selector_ensemble",
    "implementation_retry": true
  },
  "reason": "The equal cross-seed blend raises OOF patient AUC by 0.002780 over E023, but its development
transfer KS is 0.192547 > 0.15. E023 remains the transfer-safe BEST candidate.",
  "run_dir": "D:/Documents/Desktop/kidney stone detection-
isolated/runs/20260911_e024_cross_seed_selector_ensemble",
  "commit": "68b0c8d+dirty-isolated"
}
```


E025


```
 {
  "experiment_id": "E025",
  "timestamp": "2026-09-11T10:44:00+05:30",
  "status": "no_transfer_safe_gain",
  "seed": null,
  "fold": null,
  "hypothesis": "A predeclared E019 weight grid will identify a transfer-safe cross-seed blend that
improves on E023 without opportunistic weight selection.",
  "change_summary": "Evaluated E019 weights 0.00, 0.05, ..., 1.00 against aligned original-only OOF
predictions and development transfer predictions. Every weight was evaluated with the unchanged OOF
acceptance and transfer gates; no retraining, label/split/evaluator changes, or sealed-test access.",
  "metric": {
    "grid_weights": "0.00..1.00 step 0.05",
    "eligible_weights": [
      0,
      0.05,
      0.15
    ],
    "selected_weight_e019": 0,
    "selected_weight_e023": 1,
```

```
    "selected_patient_oof_auc": 0.8534136546,
    "best_transfer_safe_patient_oof_auc": 0.8534136546,
    "equal_blend_patient_oof_auc": 0.8561940068,
    "equal_blend_ks_vs_oof": 0.1925465839,
    "selected_ks_vs_oof": 0.1304347826,
    "selected_threshold_delta": 0.0621118012,
    "selected_development_transfer_gates_passed": true
  },
  "secondary": {
    "n_grid_points": 21,
    "n_patients": 161,
    "sealed_test_used": false,
    "grid_artifact": "D:/Documents/Desktop/kidney stone detection-
isolated/runs/20260911_e025_cross_seed_blend_grid/blend_weight_grid.json",
    "implementation_retry": false
  },
  "reason": "The only transfer-safe grid points were E019 weights 0.00, 0.05, and 0.15; all scored below
E023, so E023 remains BEST and the fixed blend direction is closed for now.",
  "run_dir": "D:/Documents/Desktop/kidney stone detection-
isolated/runs/20260911_e025_cross_seed_blend_grid",
  "commit": "68b0c8d+dirty-isolated"
}
```


E026


```
 {
  "experiment_id": "E026",
  "timestamp": "2026-09-11T10:47:00+05:30",
  "status": "robustness-audit-passed-with-small-site-uncertainty",
  "seed": null,
  "fold": null,
  "hypothesis": "The E023 candidate's gain is not confined to one acquisition site or patient slice-count
stratum, and its operating-point improvement remains visible under subgroup auditing.",
  "change_summary": "Read-only comparison of E000 and E023 patient-level OOF artifacts across sites
FA/ME/RA and fixed original-slice-count bins 1-10, 11-20, 21-30, and 31+. No retraining,
labels/split/evaluator changes, or sealed-test access.",
  "metric": {
    "candidate_patient_oof_auc": 0.8534136546,
    "baseline_patient_oof_auc": 0.8041396355,
    "overall_delta": 0.0492740192,
    "candidate_sensitivity": 0.7051282051,
    "baseline_sensitivity": 0.6538461538,
    "candidate_specificity": 0.8915662651,
    "baseline_specificity": 0.8192771084,
    "site_auc": {
      "FA": {
        "baseline": 0.7333333333,
        "candidate": 0.7827160494
      },
      "ME": {
        "baseline": 0.8854166667,
        "candidate": 0.8125
      },
      "RA": {
        "baseline": 0.788843,
        "candidate": 0.8690082645
      }
    },
    "slice_bin_artifact": "D:/Documents/Desktop/kidney stone detection-
isolated/runs/20260911_e026_e023_robustness_audit/robustness_audit.json"
  },
  "secondary": {
    "n_patients": 161,
    "score_shift_mean": 0.0042332263,
```

```
    "score_shift_mean_absolute": 0.2404477274,
    "sealed_test_used": false
  },
  "reason": "E023 improves overall OOF AUC, sensitivity, specificity, FA AUC, and RA AUC. ME AUC is lower
on only 20 patients, so this is retained as a small-sample uncertainty rather than a correctness
regression; no site-specific tuning is justified.",
  "run_dir": "D:/Documents/Desktop/kidney stone detection-
isolated/runs/20260911_e026_e023_robustness_audit",
  "commit": "68b0c8d+dirty-isolated"
}
```