

YogiSpeaks — Setup & Run Guide

Complete guide to run the project with local Node.js and PostgreSQL.

Communication coaching CMS — not a travel product.

Downloads: [YogiSpeaks-Setup-Guide.docx](#) · [YogiSpeaks-Setup-Guide.pdf](#)

Architecture (quick)

Service	Port	Role
Frontend (Next.js)	`3000`	Public site + Admin CMS UI
Backend (NestJS)	`4000`	REST API + Swagger + `/uploads`
PostgreSQL 16+	`5432`	Primary database
Redis 7	`6379`	Optional (health stub skips if unset)

URL	Path
Site	http://localhost:3000
Admin login	http://localhost:3000/admin/login
API	http://localhost:4000/api/v1
Swagger	http://localhost:4000/api/docs
Health	http://localhost:4000/api/v1/health

Prerequisites

- Git
- Node.js 22+ (LTS)
- `pnpm 10 — corepack enable && corepack prepare pnpm@10 --activate`
- PostgreSQL 16+ running locally
- Redis optional
- Copy env templates — **never commit real .env files**

Environment files

Three templates exist. Copy them once and fill real values locally.

```
# From repo root
cp .env.example .env
cp backend/.env.example backend/.env
cp frontend/.env.example frontend/.env.local
```

File	Used by
------	---------

<code>`.env`</code>	Shared defaults (optional reference)
<code>`backend/.env`</code>	NestJS when you run backend with pnpm
<code>`frontend/.env.local`</code>	Next.js (<code>`NEXT_PUBLIC_*`</code>)

Values you must change

Variable	Notes
<code>`POSTGRES_PASSWORD` / `DATABASE_URL`</code>	Match user, password, DB name
<code>`JWT_ACCESS_SECRET` / `JWT_REFRESH_SECRET`</code>	≥ 32 characters each
<code>`SUPER_ADMIN_EMAIL` / `SUPER_ADMIN_PASSWORD`</code>	Seed creates this admin; password ≥ 12 chars
<code>`CORS_ORIGINS` / `FRONTEND_URL`</code>	Must match the URL you open in the browser
<code>`NEXT_PUBLIC_API_URL`</code>	Browser calls this (local: <code>`http://localhost:4000/api/v1`</code>)

Example local DATABASE_URL:

```
postgresql://yogispeaks:YOUR_PASSWORD@127.0.0.1:5432/yogispeaks?schema=public
```

Windows tip: prefer 127.0.0.1 over localhost if Postgres auth fails oddly.

Install & run

1. Install PostgreSQL

1. Install PostgreSQL 16+ and start the service.
2. Create a user/database (psql or pgAdmin), e.g.:

```
CREATE USER yogispeaks WITH PASSWORD 'YOUR_PASSWORD' CREATEDB;
CREATE DATABASE yogispeaks OWNER yogispeaks;
```

3. Put the matching URL in backend/.env (and root .env if you use it).

Redis is **optional**. Leave REDIS_URL empty or point at a local Redis if you have one.

2. Install dependencies

```
cd backend
pnpm install

cd ../frontend
pnpm install
```

3. Migrate + seed

```
cd backend
pnpm exec prisma generate
pnpm exec prisma migrate deploy
# first-time / schema work: pnpm exec prisma migrate dev
pnpm exec prisma db seed
```

Seed creates roles, permissions, and the super-admin from `SUPER_ADMIN_*` in `backend/.env`.

4. Run backend + frontend (two terminals)

```
# Terminal 1 - API
cd backend
pnpm start:dev
# listens on http://localhost:4000

# Terminal 2 - UI
cd frontend
pnpm dev
# listens on http://localhost:3000
```

5. Log in to Admin

1. Open `http://localhost:3000/admin/login`
2. Use `SUPER_ADMIN_EMAIL` / `SUPER_ADMIN_PASSWORD` from `backend/.env`

Useful commands

```
cd backend
pnpm prisma:studio      # browse DB
pnpm prisma:migrate     # create/apply migration in dev
pnpm typecheck
pnpm lint

cd frontend
pnpm typecheck
pnpm lint
pnpm build              # production build check
```

Uploads (local)

- Provider: `MEDIA_PROVIDER=local`
- Files land in `backend/uploads/` (auto-created on first upload / backend start)
- Folder is **gitignored** — not pushed to GitHub
- Served at `http://localhost:4000/uploads/<filename>`

Verify everything works

1. Health: GET `http://localhost:4000/api/v1/health` → ok
2. Swagger: `http://localhost:4000/api/docs`
3. Admin login with seeded super-admin
4. Upload a file in **Admin** → **Media** → file appears under `uploads/` and URL loads

Troubleshooting

Problem	Fix
---------	-----

Prisma `P1000` / auth failed	Wrong password or user in `DATABASE_URL`; reset Postgres password; use `127.0.0.1`
`citext` / type errors on migrate	Seed runs `CREATE EXTENSION IF NOT EXISTS "citext"`. As superuser once: `CREATE EXTENSION citext;` on the DB (and `template1` if migrate uses a shadow DB)
CORS / login cookie issues	`CORS_ORIGINS` and `FRONTEND_URL` must match the browser origin (`http://localhost:3000`)
Backend env validation fails	JWT secrets ≥ 32 chars; admin password ≥ 12 ; `COOKIE_SECURE` is `"true"` or `"false"` string
Admin 401 after restart	Re-seed or reset password; check you're hitting the same API as `NEXT_PUBLIC_API_URL`
Port already in use	Stop other apps on 3000/4000/5432 or change ports in `.env`
pnpm not found	`corepack enable` then `corepack prepare pnpm@10 --activate`

Production notes (short)

- Set `NODE_ENV=production`, strong secrets, `COOKIE_SECURE=true`, HTTPS.
- Prefer **Cloudinary** or **S3** (`MEDIA_PROVIDER`) over local disk when you scale past one server.
- Run `prisma migrate deploy` in CI/CD before serving traffic.
- Do not commit `.env`, `uploads/`, or `node_modules/`.

Related docs

- `IMPLEMENTATION_PLAN.md`
- `IMPLEMENTATION_PROGRESS.md`
- `DATABASE_PLAN.md`
- `API_PLAN.md`
- `TECHNOLOGY_DECISIONS.md`