

Intro to Memory Management

计算机系统导论 (Class 9)

老师: 汪小林

助教: 陈东武

北京大学 信息科学技术学院

2024 年 12 月 04 日

Overview

- Memory management is a critical aspect of programming that involves the allocation, use, and deallocation of memory in software.
- Different programming languages provide diverse approaches to memory management, balancing ease of use, performance, and control.

- Memory management is a critical aspect of programming that involves the allocation, use, and deallocation of memory in software.
- Different programming languages provide diverse approaches to memory management, balancing ease of use, performance, and control.
- Some languages use explicit control, requiring careful planning to avoid memory leaks and dangling pointers.
 - **C:** Memory is managed using functions like `malloc`, `calloc`, and `free`.
 - Developers are responsible for releasing memory.

- Memory management is a critical aspect of programming that involves the allocation, use, and deallocation of memory in software.
- Different programming languages provide diverse approaches to memory management, balancing ease of use, performance, and control.
- Some languages use explicit control, requiring careful planning to avoid memory leaks and dangling pointers.
 - **C**: Memory is managed using functions like `malloc`, `calloc`, and `free`.
 - Developers are responsible for releasing memory.
 - **C++**: Builds on C by introducing features like constructors and destructors, but still requires explicit calls to `new` and `delete`.
 - Smart pointers provide safer alternatives.

- Languages with automatic memory management use mechanisms like *garbage collection* to relieve developers of manual memory handling.

- Languages with automatic memory management use mechanisms like *garbage collection* to relieve developers of manual memory handling.
- **Mark and Sweep** algorithm:
 - Mark: mark all reachable objects recursively.
 - Sweep: free all unreachable objects.

- Languages with automatic memory management use mechanisms like *garbage collection* to relieve developers of manual memory handling.
- **Mark and Sweep** algorithm:
 - Mark: mark all reachable objects recursively.
 - Sweep: free all unreachable objects.
- **Reference Counting:**
 - Maintain a counter for each referenced object.
 - Free objects when their reference count drops to zero.
 - Problem: cyclic referencing!

- Languages with automatic memory management use mechanisms like *garbage collection* to relieve developers of manual memory handling.
- **Mark and Sweep** algorithm:
 - Mark: mark all reachable objects recursively.
 - Sweep: free all unreachable objects.
- **Reference Counting:**
 - Maintain a counter for each referenced object.
 - Free objects when their reference count drops to zero.
 - Problem: cyclic referencing!
- **Generational GC:**
 - Divide objects into generations based on their age.
 - Collect younger generations more frequently.
 - Young objects may be promoted to older generations.

- **Java:** Uses a garbage collector to reclaim memory.
 - Developers allocate objects on the heap using `new`,
 - but the GC automatically deallocates unreachable objects.

- **Java:** Uses a garbage collector to reclaim memory.
 - Developers allocate objects on the heap using `new`,
 - but the GC automatically deallocates unreachable objects.
- **Python:** Relies on reference counting and garbage collection.
 - It frees objects when their reference count drops to zero,
 - and periodically handles cycles using GC.

- Some languages use deterministic strategies, where memory is deallocated predictably at a certain scope or point in execution.
- **Swift**: Uses Automatic Reference Counting (ARC) to manage memory.
 - Objects are deallocated when their reference count drops to zero,
 - similar to reference counting in Python, but with stricter guarantees.

- Some languages use deterministic strategies, where memory is deallocated predictably at a certain scope or point in execution.
- **Swift:** Uses Automatic Reference Counting (ARC) to manage memory.
 - Objects are deallocated when their reference count drops to zero,
 - similar to reference counting in Python, but with stricter guarantees.
- **Rust:** Employs *ownership*, *borrowing*, and *lifetimes* at compile time,
 - ensuring safety without a garbage collector.
 - Memory is freed automatically when a variable goes out of scope.

Rust Safety Rules

- In Rust, each value has a variable that owns it.
- When the owner goes out of scope, the value is dropped.

```
▸ {  
    let x = String::from("Hello");  
} // `x` is dropped here.
```

- In Rust, each value has a variable that owns it.
- When the owner goes out of scope, the value is dropped.

```
▸ {  
    let x = String::from("Hello");  
} // `x` is dropped here.
```

- Ownership can be transferred using `move` semantics.

```
▸ let x = String::from("Hello");  
   let y = x; // Ownership moves to `y`.  
   // println!("{}", x); // Error: `x` is no longer valid.
```


- In Rust, each value has a variable that owns it.
- When the owner goes out of scope, the value is dropped.

```
▸ {  
    let x = String::from("Hello");  
} // `x` is dropped here.
```

- Ownership can be transferred using `move` semantics.

```
▸ let x = String::from("Hello");  
   let y = x; // Ownership moves to `y`.  
   // println!("{}", x); // Error: `x` is no longer valid.
```

- If you want to keep both variables, you can explicitly clone the value.

```
▸ let x = String::from("Hello");  
   let y = x.clone(); // Deep copy.  
   println!("{}", x); // Works fine.
```

Borrowing

- Borrowing allows a variable to let others temporarily access its value without transferring ownership.
- Rust ensures borrowing rules prevent unsafe memory access.
- **Immutable Borrowing:**

```
▶ let s = String::from("Hello");  
   let len = calculate_length(&s); // Borrow `s` immutably.  
   println!("Length is {}", len); // `s` can still be used here.  
   fn calculate_length(s: &String) -> usize { s.len() }
```

- **Borrowing Rules Enforcement:**

```
▶ let mut s = String::from("Hello");  
   let r1 = &s; // Immutable borrow.  
   let r2 = &s; // Another immutable borrow.  
   // let r3 = &mut s;  
   // Error: Cannot borrow as mutable while immutably borrowed.
```

#thanks