Eiger AI Security Assessment: Technical Screen Report

Forward Deployed Engineer (Delivery Pods), Network Intelligence
Candidate: Pari

1. Introduction and Scope

This report documents my work on the Eiger technical screen. Eiger is a deliberately vulnerable teaching lab that simulates an AI-first neobank called Halcyon, whose assistant, Halo, can be attacked across several layers: the chatbot, retrieval-augmented generation (RAG), agent tool use, and the Model Context Protocol (MCP). The exercise asks for four things: break one layer with the SEC_* flags off and capture the /validate/ output, fix it and capture the validation output again, explain what the vulnerability was, why the fix works and what it does not cover, and show the work.

I chose to go deep on one layer and also to test the others. My main layer is M2, the client-side injection module, because it gave me the clearest before-and-after validation evidence and the most concrete attack mechanism. I additionally investigated M1 (chatbot), M3 (RAG), M4 (supply chain), M5 (tool authorization) and M6 (MCP). I did this to test a hypothesis: that these apparently different vulnerabilities share one root cause. They do, and Section 5 explains it.

A note on reading the validation output. Eiger's /validate/ endpoint reports Core and Stretch conditions. In the vulnerable state, PASS means the attack succeeded. In the hardened state, FAIL means the same attack was blocked. A vulnerable run that shows PASS followed by a hardened run that shows FAIL is therefore the evidence that the fix works.


2. Environment and Methodology

I ran Eiger inside an 8 GB Kali Linux virtual machine using the provided local Ollama deployment, with no API key. I did not modify the application source code at any point. Instead, I enabled each security control through a temporary docker-compose.override.yml file. This was a deliberate choice: it keeps the application untouched, makes the diff trivial to review, and lets me bring the vulnerable and hardened configurations up independently and reproduce either one on demand.

For every layer I followed the same loop. First, I started the stack with the SEC_* flags off and carried out the attack manually, observing the application's real behaviour. Second, I called the /validate/ mechanism and saved the output as evidence. Third, I enabled the corresponding control through the override file, restarted the affected services, and repeated exactly the same attack. Fourth, I captured the validation output again and compared it with the first. Finally, I asked what the control would not stop. I saved every output as a named evidence file so that each claim in this report can be traced to a file.

I held one rule throughout: a timeout, a crash or an incomplete run is never counted as a successful vulnerability or a successful fix. Only observed behaviour backed by evidence is reported. Where I could not complete a step, I say so in Section 6.

Figure 1: Environment.



3. Main Layer: M2, Client-Side Injection

3.1 What the vulnerability was

The application lets a user set a profile display name. That value was stored exactly as entered and later inserted into the page as HTML rather than as plain text. This is stored cross-site scripting (XSS). The attacker does not need the victim to click a crafted link: the payload is saved on the server, and it runs whenever any page renders that name.

I set my display name to an <img> element with a deliberately broken src attribute and an onerror handler containing JavaScript. When the browser parses the page, it tries to load the image, the load fails, and the browser fires the onerror event. My JavaScript then executes inside the origin of the Halcyon application, which means it runs with the same privileges as the application's own scripts. In a real banking application, that is enough to read page content, act as the logged-in user, and exfiltrate data.

3.2 Evidence of the attack

With the SEC_* flags off, the /validate/ output reported Core PASS and Stretch PASS, saved as evidence-m2-before.txt. Both conditions passing means the injection executed and met the harder stretch objective as well. This is the mechanism-level proof the exercise asks for, as opposed to a description of what I believed would happen.

Figure 2: M2 attack executing.




Figure 3: M2 validation before the fix.




3.3 The fix and why it works

I enabled the M2 security controls through docker-compose.override.yml: safe output handling (output encoding) together with a content security policy. I then repeated the identical attack. The validation output changed to Core FAIL and Stretch FAIL, saved as validation_m2_secure.txt, which means the payload no longer executes.

The fix works for two independent reasons. First, output encoding converts the characters that give HTML its meaning, such as <, > and quotation marks, into harmless entities. The browser then displays the display name as literal text and never parses it as an element, so there is no img tag and no onerror handler to fire. Second, a content security policy restricts what scripts the browser may run, and in particular can refuse inline event handlers. If encoding were missed on some path, the policy is a second barrier. The important principle is that the decision is enforced by deterministic code at the output boundary, rather than depending on the input having been clean.

Figure 4: M2 validation after the fix.



3.4 What the fix does not cover

This is the part I consider most important, because a passing validation proves less than it appears to.

- **Other payload shapes.** The validation shows that this payload is blocked. It does not prove that the whole class is closed. Other vectors, such as an svg element with an onload handler, an input with autofocus and onfocus, or a

javascript: URL if the name is ever used inside a link, exercise different parser paths and must be tested separately.

- **Other places the name is rendered.** Encoding is context-specific. Correct encoding for an HTML body differs from correct encoding for an attribute, a JavaScript string or a URL. If the display name appears in an admin view, an export, an email or a chat transcript, each of those sinks needs its own correct handling. The fix only protects the sinks to which it was applied.
- **The stored data is still malicious.** The fix changes how data is displayed, not what is stored. The hostile string remains in the database, so any future page that renders it without encoding re-opens the vulnerability. Input validation at write time would reduce this, but it is also not a complete answer.
- **A weak policy.** A content security policy that permits unsafe-inline, or that trusts a script host an attacker can use, offers little protection. Its value depends entirely on how strict it is.
- **Wider browser hygiene.** Encoding and CSP do not replace broader practices such as hardened session cookies and framework-level protections.

3.5 A variation of the attack I would test next

If I were asked to think through one variation, I would look at where else the display name travels. If Halo ever receives the display name as part of its context, for example when greeting the user or summarising an account, then the same stored string becomes an input to the language model. A name containing instructions would turn a client-side injection into a prompt injection, which is exactly the M1 and M3 problem. Browser-side encoding would not stop that at all, because the data is consumed by the model rather than rendered by the browser. This shows why each trust boundary needs its own control.

4. The Other Layers

4.1 M1: Chatbot prompt injection

The attack was a prompt injection that attempted to make Halo disclose the contents of its system prompt. With the flags off, the validation output was Core PASS and Stretch PASS (validation_before.txt), meaning the model followed the attacker's instruction in place of its configured instructions. After enabling prompt and input hardening, the output was Core FAIL and Stretch FAIL (validation_m1_secure.txt).

The hardening works by making the boundary between trusted instructions and untrusted user text explicit and by screening input. It does not cover novel or obfuscated injections, such as encoded, translated or multi-turn attacks, because filters and hardened prompts recognise known patterns. The practical lesson is that nothing sensitive should live in a system prompt in the first place, since the model can never be relied upon to keep it secret.

Figure 6: M1 validation. *validation_before.txt beside validation_m1_secure.txt.*




4.2 M3: RAG

In the RAG layer, content retrieved from the knowledge base was treated as authoritative instructions rather than as data. A document containing instructions could therefore steer Halo. In the vulnerable state, the output was Core PASS and Stretch FAIL (validation_m3_vulnerable.txt). I report this as it is: the core attack worked, but the stretch objective was not reached. I did not round it up. After enabling RAG provenance controls, the result was Core FAIL and Stretch FAIL (validation_m3_secure.txt).

Provenance controls work by recording where each retrieved passage came from and refusing to give untrusted sources the standing of instructions. The limitation is that everything depends on correctly classifying sources. If an attacker can get content into a source that is labelled trusted, or if a trusted source is itself compromised, the control provides no protection.

Figure 7: M3 validation.



4.3 M4: Supply chain

This layer concerns the model artifact itself. I identified a malicious .pkl model file by static analysis, without executing it. Its SHA-256 hash begins 22e1a204. The pickle opcodes include STACK_GLOBAL, which resolves posix system, followed by REDUCE, which calls it. In plain terms, loading the file would run an operating system command. I also demonstrated the vulnerable loader behaviour. Pickle is not a data format; it is a program for the Python interpreter, so deserialising an untrusted pickle is code execution.

In the secure configuration, the loader rejected the .pkl file and restricted loading to the approved .safetensors format, which stores tensors and cannot carry executable code. The limits are important. An allowlist depends on correct hashes and a trustworthy distribution channel. A safetensors file cannot execute code on load, but it can still contain poisoned or backdoored weights, so format restrictions do not prove that a model behaves safely.

Figure 8: M4 static analysis.



Figure 9: M4 secure loader.




4.4 M5: Tool authorization

In the agent layer, I got Halo to issue a refund to an account that the requester did not own. The evidence file m5_vulnerable_final_evidence.txt shows the tool call issue_refund(amount=500, to_account=acct-attacker). The underlying flaw is missing authorization at the tool layer: the tool trusted the model's chosen arguments and never checked that the destination account belonged to the person asking. The model was effectively a confused deputy.

The appropriate control is an ownership and scope check enforced in the tool itself, outside the model, so that no phrasing of a prompt can bypass it. Its limit is that it is only as reliable as the identity and ownership data it consults. I want to be explicit that I could not complete a clean secure reproduction of M5 because of the local runtime, so I claim no validation result for the fixed state.

Figure 10: M5 unauthorized refund.




4.5 M6: MCP

MCP tool descriptions are text that the model reads and trusts. In this attack, a poisoned tool description caused an unintended cross-server account lookup: the evidence file m6_vulnerable_attempt.txt shows core_banking__get_account_details(acct-victim), a call the user never requested, against another server's data. This is tool poisoning combined with excessive access between servers.

The fix pins approved tool descriptions, so a changed or malicious description is rejected, and scopes tokens, so a server's credentials permit only what its own tools need. After enabling these controls, the output was Core FAIL and Stretch FAIL (validation_m6_secure.txt). They do not remove vulnerabilities in the underlying tools or flaws in business logic, and pinning only protects whatever was approved in the first place.

Figure 11: M6 validation.



5. Cross-Cutting Observations

5.1 One root cause behind six symptoms

Across all six layers the root cause was the same: a trust-boundary failure. In M1 the untrusted content was a user prompt, in M2 a profile field, in M3 a retrieved document, in M4 a model file, in M5 the destination of a requested refund, and in M6 a tool description. In each case that content was allowed to influence instructions, rendering, retrieval, artifact loading, tool execution or tool selection. The attacker never needed to defeat cryptography or find a memory-corruption bug. They only needed the system to treat data as if it were a command.

5.2 The model is not a security boundary

The second observation follows from the first: model behaviour is not an adequate security boundary. A language model cannot reliably tell instructions from data, so any security-sensitive decision that depends on the model getting it right will eventually fail. This is why prompt hardening in M1, while worthwhile, is the control I would trust least on its own. Security-sensitive actions should be enforced at the application and tool layer, where the outcome does not depend on how the model interprets a piece of text.

5.3 Effective fixes sit at deterministic boundaries

Each fix that worked in this exercise moved the decision into ordinary code at the boundary: encoding and a content security policy on output in M2, provenance tracking on retrieval in M3, a format and hash allowlist on artifact loading in M4, an ownership check inside the tool in M5, and description pinning with token scoping in M6. These controls do not ask the model to behave. They limit what can happen even when the model behaves badly, which is the property that matters in an adversarial setting.

5.4 Defense in depth, not guarantees

Third, none of these fixes is a guarantee. A FAIL in the hardened validation shows that a specific attack was blocked, not that the vulnerability class has been eliminated. Prompt hardening and input filtering can miss novel or obfuscated techniques, retrieval provenance depends on correctly identifying trusted sources, allowlists depend on trustworthy hashes and distribution, and tool-level checks depend on reliable identity and ownership data. That is why I have written down what each control leaves uncovered.

6. Assessment Coverage and Limitations

6.1 Coverage

I investigated the following Eiger modules during the assessment:

- **M1, Chatbot:** prompt injection.
- **M2, Client-side injection:** stored XSS and unsafe output handling.
- **M3, RAG:** knowledge-base poisoning.
- **M4, Supply chain:** malicious model artifact and unsafe deserialization.
- **M5, Agent tool authorization:** unauthorized financial tool execution.
- **M6, MCP:** tool-description poisoning and cross-server trust-boundary violation.

M1, M2, M3 and M6 produced both vulnerable and hardened validation evidence. M4 produced concrete malicious-artifact and secure-loader evidence. M5's vulnerable behaviour was successfully demonstrated, but its hardened reproduction could not be completed within the available runtime.

6.2 Not Completed

- **M7, Multi-agent:** I attempted the multi-agent attack path, but the required Core condition was not reproduced before the available time expired. I therefore did not include M7 as a successful finding.
- **M8, Production / guardrail layer:** not assessed within the available time.
- **Treasury Heist capstone:** not attempted. I prioritised obtaining reproducible evidence and secure validation for multiple individual attack surfaces rather than starting the capstone without enough time to validate it properly.

6.3 Runtime Limitations

The assessment ran in an 8 GB Kali Linux VM using CPU-only local Ollama inference. The original 8B model repeatedly exceeded request timeouts during agentic workflows. I switched to Llama 3.2 3B to reduce inference latency, which improved responsiveness but did not eliminate all agentic timeouts.

M5's vulnerable behaviour was demonstrated through an actual issue_refund tool call, but a clean secure reproduction could not be completed. I therefore make no claim of a secure M5 result.

I treated incomplete or timeout-affected runs as inconclusive rather than successful vulnerabilities.

7. How I Used AI

The exercise explicitly encourages heavy use of AI and says it will ask how the tools were used, so I approached AI as a set of tools with defined jobs at each stage of the work, rather than as a single prompt that produces an answer. I used two assistants for different purposes, and I want to be specific about which did what.

7.1 ChatGPT: understanding and execution

I used ChatGPT as a technical assistant while working through the lab itself. Its main jobs were interpreting the Eiger documentation so that I understood how the layers, the SEC_* flags and the /validate/ mechanism fit together; troubleshooting the Docker and Ollama environment, including the model timeouts described in Section 6; identifying the relevant configuration options and validation commands for each module; helping me interpret the Core and Stretch results that /validate/ returned; and helping me structure the assessment evidence so that every claim pointed to a named file.

7.2 Claude: drafting the written report

I used Claude to help structure and draft this written report from my own notes and the evidence files I had already captured. Claude did not run the lab, and it did not produce any of the validation evidence. Its role was to help me organise the findings, express the mechanisms clearly, and think about what each fix does not cover.

7.3 What stayed with me

The judgement stayed with me throughout. I executed every command myself, observed the application's actual behaviour, captured the validation outputs, and made the final decision about what counted as validated and what was incomplete. I treated AI output the same way the lab teaches me to treat model output: as something to verify rather than trust. A suggested command was only useful once I had run it and seen the result, and a claim in this report is only included if an evidence file supports it.

That discipline is why some results are reported as incomplete. Where AI suggestions or the runtime did not produce evidence, as with the secure reproduction for M5 and the Core condition for M7, I reported the gap honestly instead of claiming success. I also recognise that I am responsible for being able to explain everything here in my own words.

8. Conclusion

In this assessment I reproduced and validated attacks across the chatbot, client-side, RAG, supply-chain and MCP layers, and demonstrated an unauthorized financial tool action in the agent layer. For the validated layers, I applied fixes through configuration alone, using a temporary docker-compose.override.yml, left the application source unchanged, and captured before-and-after validation evidence so that each result can be reproduced independently. I explored M2 in depth, including what its fix fails to cover and a cross-layer variation in which a stored display name could reach the language model.

The central lesson is that all of these vulnerabilities share one root cause: untrusted content was allowed to cross a trust boundary and influence instructions, rendering, retrieval, artifact loading or tool execution. A language model cannot reliably distinguish instructions from data, so it cannot be the component that enforces security. The fixes that worked did so because they moved the decision into deterministic code at the boundary, through output encoding, retrieval provenance, an artifact allowlist, tool-level authorization and MCP description and token controls.

I also want to be clear about the limits of what I have shown. The controls are defense-in-depth rather than guarantees. A FAIL in the hardened validation shows that a specific attack was blocked, not that its whole class is closed. M5 has no secure result, M7 was not reproduced, M8 was not assessed and the capstone was not attempted, and I have reported those gaps plainly rather than counting inconclusive runs as success.

For a forward deployed engineering role, I think the most transferable outcome is the method rather than any single finding. Each layer was approached in the same way: reproduce the failure, prove it with the mechanism, apply a control at the boundary, prove that the attack now fails, and then document honestly what the control still misses. That approach applies equally to a chatbot, a retrieval pipeline, an agent with tools or an MCP integration in a customer environment, and it is the one I would bring to real delivery work.

With more time and a machine capable of running the larger model without timeouts, my next steps would be to complete the hardened reproduction for M5, retry the multi-agent path in M7, test the untried M2 payload variations against the fixed configuration, and then attempt the guardrail layer and the capstone. Working through an unfamiliar area of AI security quickly, with AI assistance, while keeping the evidence honest, is what I set out to demonstrate.