IP Subnetting

Table of Contents

► Subnetting Basics

# 1 Subnetting Basics

Subnetting Basics

- The process of taking an extensive network and splitting into smaller networks is known as subnetting

A class C network without sub-netting

Network 192.168.14.0

192.168.14.1

192.168.14.254

A class C network with 2 sub-nets

Network 192.168.14.0

Sub-net 192.168.14.0

192.168.14.1

192.168.14.126

Sub-net 192.168.14.128

192.168.14.129

192.168.14.254

Subnetting Basics

Why to use subnetting?

- Reduced Network Traffic

- Optimized Network Performance

- Simplified Management - Easier to identify and isolate network problems

- Facilitated Spanning of Large Geographical Distances - Connecting multiple smaller networks makes the system more efficient

Subnetting Basics

- IPv4 address is divided into network ID and host ID by using octets

- In subnetting we can borrow some bits from host ID to use as subnetwork

IP address

Before subnetting	Network identifier	Host identifier

After subnetting	Network identifier	Subnet identifier	Host identifier

Subnetting Basics

Subnetting IPv4 Address:

- A **Class A**, **B**, or **C** TCP/IP network can be further divided, or subnetted, by a system administrator

- For example, you have 150 hosts on three networks that are connected by a router

- You are allocated a **Class C** address: | 192.168.123 Network ID | .0 Host ID |

- You can use from | 192.168.123 | .1 | | 192.168.123 | .254 |
  (Just remember that the first and last address in any network or subnet cannot be assigned to any individual host, so you cannot use 192.168.123.0 and 192.168.123.255)

Subnetting Basics

Subnetting IPv4 Address:

- With the allocated Class C IP address we can map 254 hosts on one network

- But our 150 hosts are located 0n **three** separate networks

- Instead of requesting more address blocks for each network, we can divide our block into three subnets

But how?

Subnetting Basics

Subnetting IPv4 Address:

- Remember we can create subnets by borrowing bits from Host ID

- We need 3 subnets in total, so if we borrow 1 bit we will get 2 subnets which is not enough

- So we need more bits, if we borrow 2 bits we will get 4 subnets and our subnet mask will be:
  11111111.11111111.11111111.11000000 ⟶
  255.255.255.192

Subnetting Basics

Subnetting IPv4 Address:

- Since we borrowed 2 bits, there are only 6 bits left for Host ID which makes 2^6 - 2 = 62 hosts *(first and last numbers are reserved)*

- Our company has **3 networks** and **50 hosts** on each network

- We have **4 subnets**, and **62 host IDs** for each subnet *(that means 1 subnet with 62 host IDs will be reserved for future use)*

Subnetting Basics

Subnetting IPv4 Address:

- Using subnet mask 255.255.255.192, our 192.168.123.0 network will become 4 networks:
  - 192.168.123.0   `11111111.11111111.11111111` `000000`
  - 192.168.123.64   `11111111.11111111.11111111` `000000`
  - 192.168.123.128   `11111111.11111111.11111111` `000000`
  - 192.168.123.192   `11111111.11111111.11111111` `000000`

- Valid host addresses will be:

192.168.123.1-62   192.168.123.129-190

192.168.123.65-126   192.168.123.193-254

(Remember, again, that binary host addresses with all 1s or all 0s are reserved, so you cannot use addresses with the last octet of 0, 63, 64, 127, 128, 191, 192, and 255)

Subnetting Basics

Let's see how this works:

- Assume we have two IP addresses:
  - 192.168.123.71 and 192.168.123.133

- If we used default subnet mask of Class C which is 255.255.255.0 both addresses should be on the same network

- However we use subnet mask of 255.255.255.192 so
  - 192.168.123.71 host will be on the 192.168.123.64 network
  - 192.168.123.133 host will be on the 192.168.123.128 network

Well done!

Subnetting Basics

Default gateways

- If a host needs to communicate with a host on another network, it will communicate through a router

- A router specified on a host is called **default gateway**

- So how does TCP/IP knows if the destination host is on the same network or not?

Subnetting Basics

Default gateways

When a host wants to communicate with another device, it performs a comparison process using the defined subnet mask with the destination IP address and its own IP address

```
                              local ─── Send packets to local subnet
            Destination host
                              remote ── Send packets to router through
                                        default gateway
```

Subnetting Basics

- Source host   : **192.168.123.72**
- Subnet mask   : **255.255.255.192**
- Destination host   : **192.168.123.109**

Source IP :   Logical AND

11000000.10101000.01111011.01001000

Subnet mask : **11111111.11111111.11111111.11000000**

Network ID   **11000000.10101000.01111011.01000000**(192.168.123.64)

Destination IP : **11000000.10101000.01111011.01101101**   Logical AND

Subnet mask : **11111111.11111111.11111111.11000000**

Network ID   **11000000.10101000.01111011.01000000**(192.168.123.64)

Same result! Two hosts are on the same network.

Subnetting Basics

- Source host   : **192.168.123.46**
- Subnet mask   : **255.255.255.192**
- Destination host   : **192.168.123.202**

Source   IP   :   Logical AND
11000000.10101000.01111011.00101110

Subnet mask : **11111111.11111111.11111111.11000000**

Network ID   **11000000.10101000.01111011.00000000** (192.168.123.0)

Destination IP : **11000000.10101000.01111011.11001010**   Logical AND

Subnet mask : **11111111.11111111.11111111.11000000**

Network ID   **11000000.10101000.01111011.11000000** (192.168.123.192)

Not the same! Two hosts are on different networks.

Subnetting Basics

Classless Inter-Domain Routing (CIDR)

- In order to reduce the wastage of IP addresses, a new concept of **CIDR** is introduced

- CIDR provides the flexibility of borrowing bits of Host part of the IP address

- By using subnetting, one single Class A address can be used to have smaller sub-networks which provides better network management capabilities

Subnetting Basics

- **CIDR** notation examples:

IP address: 192.168.1.142
Subnet mask: 255.255.255.0 or 11111111.11111111.11111111.00000000

CIDR: 192.168.1.142 /24 ← 24 turned on bits (1s)

IP address: 172.16.56.140
Subnet mask: 255.255.255.240 or
11111111.11111111.11111111.11110000

28 turned on bits (1s)

CIDR: 172.16.56.140 /28

THANKS!

Any questions?