ondia



Connectors and Wiring Standards

Table of Contents

O


- Physical Media
- ► Cable Properties

Physical Media

Coaxial Cable

d

A type of copper cable specially built with a metal shield and other components engineered to block signal interference




Coaxial Cable

O

There are two types of coaxial cable:







Thinnet (10Base2)


Thicknet and thinnet are used in Ethernet implementations



Twisted-Pair Cable



The most common type of network medium used in AN today





Twisted-Pair Cable



N <Signaling> X

N: Signaling rate in Mbps

<Signaling>: Signalling type (baseband or broadband)

X: Unique identifier

Examples:

10Base-T: 10Mb or 10Megabits twisted pair

100Base-F: 100Mb or 100Megabits fiber





Twisted-Pair Cable



UTP Categories - Copper Cable


or categories copper casic							
Data Rate	Max. Length	Cable Type	Application				
Up to 1Mbps	-	Twisted Pair	Old Telephone Cable				
Up to 4Mbps	-	Twisted Pair Token Ring Networks					
Up to 10Mbps	100m	Twisted Pair	Token Rink & 10BASE-T Ethernet				
Up to 16Mbps	100m	Twisted Pair	Token Ring Networks				
Up to 100Mbps	100m	Twisted Pair	Ethernet, FastEthernet, Token Ring				
Up to 1 Gbps	100m	Twisted Pair	Ethernet, FastEthernet, Gigabit Ethernet				
Up to 10Gbps	100m	Twisted Pair	GigabitEthernet, 10G Ethernet (55 meters)				
Up to 10Gbps	100m	Twisted Pair	GigabitEthernet, 10G Ethernet (55 meters)				
Up to 10Gbps	100m	Twisted Pair	GigabitEthernet, 10G Ethernet (100 meters)				
	Up to 1Mbps Up to 4Mbps Up to 10Mbps Up to 16Mbps Up to 100Mbps Up to 100Mbps Up to 100bps Up to 10Gbps Up to 10Gbps	Data Rate Max. Length Up to 1Mbps - Up to 4Mbps - Up to 10Mbps 100m Up to 16Mbps 100m Up to 100Mbps 100m Up to 100mbps 100m Up to 1 Gbps 100m Up to 10Gbps 100m Up to 10Gbps 100m	Data RateMax. LengthCable TypeUp to 1Mbps-Twisted PairUp to 4Mbps-Twisted PairUp to 10Mbps100mTwisted PairUp to 16Mbps100mTwisted PairUp to 100Mbps100mTwisted PairUp to 1 Gbps100mTwisted PairUp to 10Gbps100mTwisted PairUp to 10Gbps100mTwisted PairUp to 10Gbps100mTwisted Pair				



Fiber-Optic Cable



Very thin strand of pure glass that acts as a waveguide for light over long distances





Total internal reflection




Fiber-Optic Cable

O

- Immune to EMI and RFI*
- Very long range
- ✓ Broad bandwidth (Tbits/s or THz)
- Low transmission loss
- Not dissipate heat

- Difficult to install
- More expensive than TP
- Troubleshooting equipment is more expensive then TP test equipment
- Harder to troubleshoot






*EMI: Electromagnetic interference

RFI: Radio frequency interference

Fiber-Optic Cable







Media Converters



Converts Ethernet or other communication protocols from one cable type to another type

Main types:

- Fiber-to-Ethernet
- Fiber-to-Coaxial
- Fiber-to-Fiber
- Ethernet-to-Coaxial



Fiber-to-Ethernet converter







Transmission Speeds

Based on the type of cable or fiber, network administrators can control the speed of a network to meet the network's traffic demands

Media Type	Bandwidth	Performance: Typical Error Rate	
Twisted-pair for analog voice applications	1 MHz	Poor to fair (10 ⁻⁵)	
Coaxial cable	1 GHz	Good (10 ⁻⁷ to 10 ⁻⁹)	
Microwave	100 GHz	Good (10 ⁻⁹)	
Satellite	100 GHz	Good (10 ⁻⁹)	
Fiber	75 THz	Great (10 ⁻¹¹ to 10 ⁻¹³)	

d


Distance

Sta	andard	Data Rate	Max Distance	Cable Type
10	Base2	10 Mbps	185 m	Coaxial
10	Base5	10 Mbps	500 m	Coaxial
10	BaseT	10 Mbps	100 m	Ethernet
10	0BaseT	100 Mbps	100 m	Ethernet
10	00BaseT	1 Gbps	100 m	Ethernet
10	BaseFL	10 Mbps	2 km	Fiber (Multi Mode)
10	0BaseSX	100 Mbps	300 m	Fiber (Multi Mode)
10	0BaseLX	100 Mbps	100 km	Fiber (Single Mode)
10	00BaseLH	1 Gbps	70 km	Fiber (Single Mode)






Simplex



Half-duplex



Full-duplex

