ondia

Open System Interconnection (OSI) Specifications

Table of Contents

- What is OSI Reference Model?
- Layers of OSI Model
- Data Encapsulation

1

What is OSI Reference Model?

What is OSI Reference Model?

The **OSI** provides a standard for different computer systems to be able to communicate with each other

Developed by ISO in 1984

What is OSI Reference Model?



- Human-computer interaction layer, where applications can access the network services

- Ensures that data is in a usable format and is where data encryption occurs

- Maintains connections and is responsible for controlling ports and sessions

- Transmits data using transmission protocols including TCP and UDP

- Decides which physical path the data will take

- Defines the format of the data on the network

- Transmits raw bit stream over the physical medium

2

Layers of the OSI Model

Application Layer (Layer 7)

- Directly interacts with data from the user
- Software applications (web browsers, email clients, etc.) rely on the application layer to initiate communications



Presentation Layer (Layer 6)

- Primarily responsible for preparing data
- Translates, encrypts, and compresses data

Session Layer (Layer 5)

- Responsible for opening and closing communication between the two devices
- The time between when the communication is opened and closed is known as the session
- Synchronizes data transfer

Session of communication

Transport Layer (Layer 4)

- Responsible for end-to-end communication between the two devices
- Takes data (from upper layer) and breaks into segments
- Responsible for flow control and error control

Network Layer (Layer 3)

- Facilitates data transfer between two different networks
- Takes data segments (from upper layer) and breaks into packets

Data Link Layer (Layer 2)

- Facilitates data transfer between two devices on the same network
- Takes data packets (from upper layer) and breaks into frames
- Responsible for flow control and error control

Physical Layer (Layer 1)

- Includes physical equipment
  - cables
  - repeaters
  - modems
  - transceivers
  - media converters
  - hubs
  - etc.

- Data is converted into bit streams

3

Data Encapsulation

Data Encapsulation

- For two nodes communicate they must use the same protocol
- Each layer *(OSI or DoD)* communicates with its equivalent layer on the other node via the lower layers of the model
- Each layer provides services for the layer above and uses the services of the layer below

Data Encapsulation



Data Encapsulation




OSI Model
TCP/IP
Application Layer
Presentation Layer
Session Layer
Transport Layer
Network Layer
Data Link Layer
Physical Layer
Application Layer
Transport Layer
Internet Layer
Network Access Layer

THANKS!

Any questions?