



# Synthesis

# Objectives

## ► After completing this module, you will be able to:

- Elaborate a design and perform analysis
- Make basic timing constraints with the Constraints viewer
- Use the `check_timing` report to verify constraint coverage of your design
- Build useful design reports that will help you avoid the most common design mistakes and assure design success
- Use the `clock_interaction` report to verify constraint coverage on datapaths between clock domains

# Outline


- ▶ *Elaboration*
- ▶ Synthesis
- ▶ Basic Timing Constraints
- ▶ Synthesis Reports
- ▶ Summary

# Elaboration

- ▶ **Elaboration is the RTL optimization to an FPGA technology**
- ▶ **Vivado IDE allows designers to import and manage RTL sources**
  - Verilog, System Verilog, VHDL, NGC, or testbenches
- ▶ **Create and modify sources with the RTL Editor**
  - Cross-selection between all the views
- ▶ **Sources view**
  - Hierarchy view: Display the modules in the design by hierarchy
  - Libraries view: Display sources by category

# Elaboration and Analysis

- ▶ In an RTL based design, elaboration is the first step
- ▶ Click on Open Elaborated Design under RTL Analysis to
  - Compile the RTL source files
  - Load the RTL netlist for interactive analysis
- ▶ You can check RTL structure, syntax, and logic definitions
- ▶ Analysis and reporting capabilities include:
  - RTL compilation validation and syntax checking
  - Netlist and schematic exploration
  - Design rule checks
  - Early I/O pin planning using an RTL port list
  - Ability to select an object in one view and cross probe to the object in other views, including instantiations and logic definitions within the RTL source files



# Analysis of an Elaborated Design

## ▶ Three options available after opening an Elaborated Design

- Report DRC
  - Runs DRC on the design
- Report Noise
  - Checks the SSO on the design based on a XDC file
- Schematic
  - Opens the schematic


### ▼ RTL ANALYSIS

#### ▼ Open Elaborated Design

 [Report Methodology](#)


Report DRC

Report Noise

 Schematic


# Schematic View of an Elaborated Design

- ▶ **When Schematic is clicked under the Elaborated Design, the schematic is opened showing the hierarchical blocks**
  - Note that no I/O buffers are inferred at this stage
  - Each block opens up to reveal underlying logic and sub-modules in the hierarchy
  - Closest representation to the actual coded design



# Cross Probing

- ▶ Select an object in the schematic, right-click, and select **Go To Source** to view where the object is defined in the source file



The source code view shows the file 'uart\_led.v' with the following code:

```
81 uart_rx #(
82     .CLOCK_RATE  (CLOCK_RATE),
83     .BAUD_RATE   (BAUD_RATE)
84 ) uart_rx_i0 (
85     .clk_rx      (clk_pin),
86     .rst_clk_rx  (rst_clk_rx),
87
88     .rx_data_rdy (rx_data_rdy),
89     .rx_data     (rx_data),
90     .frm_err     ()
91 );
92
93 led_ctl led_ctl_i0 (
94     .clk_rx      (clk_pin),
95     .rst_clk_rx  (rst_clk_rx),
96     .btn_clk_rx  (btn_clk_rx),
97     .rx_data     (rx_data),
98     .rx_data_rdy (rx_data_rdy),
99     .led_o       (led_pins)
100 );
101
102 endmodule
103
```




# Synthesis

# Synthesis: Logic Optimization and Mapping to Device Primitives

## ► Synthesis of an RTL design


- Optimizes the gate-level design
- Maps the netlist to Xilinx primitives
  - Sometimes called technology mapping

## ► The figure shows a generic FIFO behavioral component mapped to the dedicated FIFO hardware in a 7-Series FPGA





# Vivado IDE Synthesis

- ▶ **Applicable only for RTL (HDL) design flows**
  - EDIF is black boxed and linked after synthesis
- ▶ **Synthesis tool uses XDC constraints to drive synthesis optimization**
  - XDC file must exist
- ▶ **Timing constraints considerations**
  - Design must first be synthesized without timing constraints for constraints editor usage
  - Constraints Wizard is available after synthesis to define rudimentary timing constraints
- ▶ **Synthesis settings provide access to additional options**
- ▶ **Note the changes in the Flow Navigator when the synthesized design has been opened**
  - Set Up Debug allows for integration of debug feature




# Vivado IDE Synthesis Settings

- ▶ **Synthesis Settings brings up Project Settings dialog box**
  - Central location for all project settings
- ▶ **Select the Default Constraint Set as the active *constraint set*. Two types of the design constraints**
  - **Physical constraints** define pin placement, and absolute, or relative, placement of cells such as block RAMs, LUTs, Flip-Flops, and device configuration settings.
  - **Timing constraints**, written in industry standard SDC, define the frequency requirements for the design. Without timing constraints, the Vivado Design Suite optimizes the design solely for wire length and placement congestion.




# Vivado IDE Synthesis Settings

- ▶ The `tcl.pre` and `tcl.post` options are hooks for Tcl files that run immediately before and after synthesis
- ▶ **`flatten_hierarchy`: Determines how synthesis controls hierarchy**
  - none: Do not flatten the hierarchy.
    - Maintains the exact same hierarchy as the original RTL
  - full: Fully flatten the hierarchy leaving only the top level
  - rebuilt: Flatten the hierarchy, perform synthesis, and then rebuild the hierarchy based on the original RTL
    - Allows the QoR benefit of cross-boundary optimizations, with a final hierarchy that is similar to the RTL for ease of analysis
- ▶ **`gated_clock_conversion`: Turns on and off the synthesis tools ability to convert clock\_logic with enables**



# Vivado IDE Synthesis Settings

- ▶ **bufg:** Controls how many BUFGs the tool infers in the design
  - This option is used when other BUFGs in netlists are not visible to the synthesis process
- ▶ **fsm\_extraction:** Encode the state machine in a specific encoding type: one\_hot, sequential, johnson, gray, or auto
- ▶ **keep\_equivalent\_registers:** Prevents registers with the same input logic from being merged
- ▶ **resource\_sharing:** Sets the sharing of arithmetic operators between different signals
  - The values are auto, on and off



# Vivado IDE Synthesis Settings

- ▶ `control_set_opt_threshold`: Sets the threshold for clock enable optimization to the lower number of control sets
- ▶ `no_lc`: When checked, this option turns off LUT combining
- ▶ `shreg_min_size`: Is the threshold for inference of SRLs
  - This sets the number of sequential elements that would result in the inference of an SRL for fixed delay chains (static SRL)
- ▶ `max_bram`: Limits the number of BRAM allowed in the design
  - -1 default lets the tool pick as many BRAM as it can, limited by number of BRAMs in device
- ▶ `max_dsp`: Similar in concept to `max_bram`, except this applies to DSPs
- ▶ To see explanation of each option, click on the name of each option to highlight it

| Options                                 |      |
|---|------|
| <code>-control_set_opt_threshold</code> | auto |
| <code>-no_lc</code>                     |      |
| <code>-no_srlextract</code>             |      |
| <code>-shreg_min_size</code>            | 3    |
| <code>-max_bram</code>                  | -1   |
| <code>-max_uram</code>                  | -1   |
| <code>-max_dsp</code>                   | -1   |
| <code>-max_bram_cascade_height</code>   | -1   |
| <code>-max_uram_cascade_height</code>   | -1   |
| <code>-cascade_dsp</code>               | auto |
| <code>-assert</code>                    |      |
| More Options                            |      |

# Synthesis RTL Attributes Supported

| Attribute         | Description  |
|-------------------|--|
| translate_off/_on | Tells the tool to ignore blocks of code  |
| full_case         | Tells that all possible case values are specified  |
| parallel_case     | Case statement should be built as a parallel structure   |
| keep              | Tells tool to keep the signal the attribute is placed on   |
| keep_hierarchy    | Used to prevent optimizations along the hierarchy boundaries   |
| buffer_type       | Tells tool what buffer type to use on an input   |
| max_fanout        | Tells the tool the limits for fanout on registers and signals  |
| ram_style         | Tells the tool how to infer memory   |
| rom_style         | Tells the tool how to infer ROM memory   |
| use_dsp           | Tells the tool how to deal synthesis arithmetic structures   |
| black_box         | Turns a whole level of hierarchy off and enables synthesis to create a black box for that module/entity      |
| gated_clock       | Allows the conversion of gated clocks; must be enabled   |
| shreg_extract     | Tells the tool on whether to infer structures  |
| iob               | Not a synthesis attribute but is passed to the implementation tool indicating if a register should be in IOB |



# Synthesis RTL Attributes Supported, cont'd...

| Attribute         | Description  |
|-------------------|--|
| async_reg         | Tells the tool that a register can receive asynchronous data at D input                              |
| srl_style         | Specifies how SRL is inferred in design  |
| clock_buffer_type | Specifies a buffer other than the (default) BUFG for synthesis                                       |
| dont_touch        | Similar to KEEP attribute, use in place of KEEP. Attribute is forward-annotated to place & route     |
| fsm_encoding      | Specifies a specific FSM encoding scheme: one_hot, sequential, johnson, gray, auto (default), none   |
| fsm_safe_state    | Place on state machine state registers, used to define a safe state in the machine                   |
| IOB               | Not a synthesis attribute, used by Vivado implementation. Specifies if a register is packed into IOB |
| io_buffer_type    | Instructs the tool to not automatically infer I/O buffers for a specific top-level port.             |
| MARK_DEBUG        | Specifies that a net to be marked for debug.   |

# Attributes Example in RTL

- ▶ No support for timing constraints embedded in RTL
- ▶ Example of KEEP attribute

## VHDL

```
signal sig1 : std_logic;  
attribute KEEP : string;  
attribute KEEP of sig1 : signal is "true";  
sig1 <= in1 and in2;  
out1 <= sig1 and in3;
```

## Verilog

```
(* KEEP = "true" *) wire sig1;  
assign sig1 = in1 & in2;  
assign out1 = sig1 & in3; // without the attribute sig1 will be optimized away if it not  
                        // being used anywhere else in the model
```

# Attributes Example in RTL

## ► Attributes do not work with Verilog 2001 module syntax

### Does Not Work

```
module top ((* buffer_type = "none" *) input sys_clock,  
            input sys_reset,  
            (* buffer_type = "none" *) input serDataIn,
```

### Works

```
module top ( sys_clock,  
            sys_reset,  
            serDataIn,  
            ...  
            );  
(* buffer_type = "none" *) input sys_clock;  
input sys_reset;  
(* buffer_type = "none" *) input serDataIn;
```

# Mark\_Debug RTL Attribute

- ▶ **MARK\_DEBUG support with Vivado synthesis**
  - Tag signals in HDL
  - Corresponding nets preserved in netlist (DONT\_TOUCH behavior)
  - Tagged nets appear in the logic analyzer Unassigned nets view
  - XDC and elaborated design netlist support available
- ▶ **You can also mark nets after synthesis**

## Apply attribute in HDL

C:\xup\pga\_flow\2018\_2\_zynq\_labs\lab4\lab4.srcs\sources\_1\imports\lab4\cmd\_parse.v

```
129
130
131 //*****
132 // Reg declarations
133 //*****
134
135 reg [2:0] state; // State variable
136
137 reg old_rx_data_rdy; // rx_data_rdy on previous clock
138
139 reg [6:0] cur_cmd; // Current cmd - least 7 significant bits of char
140 reg [4*MAX_ARG_CH-5:0] arg_sav; // All but last char of args
141 reg [clogb2(MAX_ARG_CH)-1:0] arg_cnt; // Count the #chars in an argument
142
143 reg [NSAMP_WID-0] nsamp; // Number of samples to send
144 // Width is one more to code 2*N naturally
145 (* mark_debug = "TRUE" *) reg [PRE_WID-1:0] prescale; // Clock prescaler
146 (* mark_debug = "TRUE" *) reg [SPD_WID-1:0] speed; // Speed
147 (* mark_debug = "TRUE" *) reg nsamp_new;
148 (* mark_debug = "TRUE" *) reg prescale_new;
149 (* mark_debug = "TRUE" *) reg speed_new;
```

## After Synthesis

| Name                                     | Driver Cell | Driver Pin | Probe Type |
|--|-------------|------------|------------|
| Unassigned Debug Nets (35)               |             |            |            |
| > U0_wave_gen/cmd_parse_i0/prescale (16) | Multiple    | Q          |            |
| > U0_wave_gen/cmd_parse_i0/speed (16)    | Multiple    | Q          |            |
| U0_wave_gen/cmd_parse_i0/nsamp_new       | FDRE        | Q          |            |
| U0_wave_gen/cmd_parse_i0/prescale_new    | FDRE        | Q          |            |
| U0_wave_gen/cmd_parse_i0/speed_new       | FDRE        | Q          |            |

# Basic Timing Constraints

# Basic Timing Constraints


## ▶ There are three basic timing constraints applicable to a sequential machine

- Period
  - Paths between synchronous elements clocked by the reference clock net
    - Synchronous elements include flip-flops, latches, synchronous RAM, and DSP slices
  - Use `create_clock` to create the constraint
- Input Delay
  - Paths between input pin and synchronous elements
  - Use `set_input_delay` to create the constraint
- Output delay
  - Paths between synchronous elements and output pin
  - Use `set_output_delay` to create the constraint

## ▶ More about this in the module on Xilinx Design Constraints



# Constraints Viewer

- ▶ **Constraints Viewer allows you to see/edit the timing constraints contents of the XDC file**
  - All timing constraints are supported with the GUI
  - Right-clicking the constraint in the Create window allows you to modify/delete an existing constraint
  - Select a different constraint by clicking it in the All Constraints window
  - To create a different constraint, select the type from the GUI
- ▶ **After constraint entry is completed, constraints must be "saved" to have them stored in the XDC**
  - Changes will be written into the specified Target XDC only



# Creating Basic Timing Constraints in Vivado IDE

- ▶ Run Synthesis
- ▶ Open the synthesized design
- ▶ Invoke constraints editor





# Creating Basic Timing Constraints using Tcl

## ▶ Period constraint using `create_clock`

- `create_clock -period 10 [get_ports clk_pin]`
- `create_clock -period 10 -waveform {0.000 5.000} -name clk [get_ports clk_pin]`


## ▶ `set_input_delay`

- The input delay external to FPGA
- `set_input_delay -clock clk_pin 2.000 [all_inputs]`
- `set_input_delay -clock clk_pin 3.000 [get_ports in1]`
- `set_input_delay -clock clk_pin 2 [get_ports l_msn* ]`

## ▶ `set_output_delay`


- The output delay external to FPGA
- `set_output_delay -clock clk_pin -2 [all_output]`
- `set_output_delay -clock [get_clocks clk_pin] -2 [get_ports out1]`

# Timing Paths Example



# Constraints Wizard


- ▶ **Allows Vivado to *suggest* timing constraints missing from the design**
  - Recommended flow for an initially unconstrained design
  - User can ignore the recommended constraints
    - Option to deselect constraints at every stage of the wizard
  - Opens the Timing Constraints Editor with recommended constraints
    - User needs to consciously add the constraints to the target XDC file
  - A great alternative to using the Timing Constraints Editor in Vivado
    - User can still use the editor to add constraints



# Synthesis Reports

# After Synthesis

- ▶ In the Synthesized Design view:
  - Sources tab does not change
    - RTL Netlist tab (Elaborated Design) changes to Netlist (Synthesized Design)
  - However, the Flow Navigator now includes:
    - Constraints Wizard, Edit Timing Constraints, Set Up Debug, Report Timing Summary, Report Clock Networks, Report Clock Interaction, Report DRC, Report Noise, Report Utilization, Report Power, Schematic
  - Views can be selected by purpose
    - All timing information is only an estimate (until implementation has completed)
    - Setup debug tool




# Synthesized Design

- ▶ **Accessed through the Flow Navigator by selecting Open Synthesized Design**
- ▶ **Representation of the design after synthesis**
  - Interconnected netlist of hierarchical and BELs
    - Instances of modules/entities
    - BELs
      - LUTs, flip-flops, carry chain elements, wide MUXes
      - Block RAMs, DSP cells
      - Clocking elements (BUFG, BUFR, MMCM, ...)
      - I/O elements (IBUF, OBUF, I/O flip-flops)
- ▶ **Object names are the same as names in the elaborated netlist when possible**

# Synthesis Reports

- ▶ While the Flow Navigator points to the most important reports, the Reports tab contains several other useful reports
  - Vivado Synthesis Report shows
    - HDL files synthesized, synthesis progress, timing constraints read, and RTL primitives from the RTL design
    - Timing optimization goals, technology mapping, removed pins/ports, and final cell usage (technology-mapped cell usage)
  - Utilization Report shows
    - Technology-mapped cell usage in an easy-to-read tabular format




The screenshot shows the Vivado Reports tab with a table of reports. The table has columns for Report, Report Type, Options, Modified, and Size. Under the Synthesis Design (synth\_design) folder, two reports are listed: synth\_1\_synth\_report\_utilization\_0 and synth\_1\_synth\_synthesis\_report\_0.

| Report                             | Report Type  | Options | Modified        | Size    |
|------------------------------------|--|---------|-----------------|---------|
| ▼ Synthesis                        |  |         |                 |         |
| ▼ Synth Design (synth_design)      |  |         |                 |         |
| synth_1_synth_report_utilization_0 | Report on utilization of resources on the targeted device (report_utilization) |         | 1/14/19 1:41 PM | 7.4 KB  |
| synth_1_synth_synthesis_report_0   | Vivado Synthesis Report  |         | 1/14/19 1:41 PM | 68.4 KB |
| > Out-of-Context Module Runs       |  |         |                 |         |

# Synthesis Utilization Report

- Reports slice logic, memory, DSP slice, IO, clocking, and other resources used by the design




```
Project Summary x Device x uart_led.v x Utilization - Synth Design - synth_1 x
C:/vivado_tutorial/lab2/lab2.runs/synth_1/uart_led_utilization_synth.rpt
Read-only

1 Copyright 1986-2021 Xilinx, Inc. All Rights Reserved.
2
3 | Tool Version : Vivado v.2021.2 (win64) Build 3367213 Tue Oct 19 02:48:09 MDT 2021
4 | Date : Tue Feb 22 16:29:56 2022
5 | Host : XSHWELI20 running 64-bit major release (build 9200)
6 | Command : report_utilization -file uart_led_utilization_synth.rpt -pb uart_led_utilization_synt
7 | Design : uart_led
8 | Device : xc7s50csga324-1
9 | Speed File : -1
10 | Design State : Synthesized
11
12
13 Utilization Design Information
14
15 Table of Contents
16 -----
17 1. Slice Logic
18 1.1 Summary of Registers by Type
19 2. Memory
20 3. DSP
21 4. IO and GT Specific
22 5. Clocking
23 6. Specific Feature
24 7. Primitives
25 8. Black Boxes
26 9. Instantiated Netlists
27
28 1. Slice Logic
29 -----
```



# Commands Available After Synthesis

- ▶ **Flow Navigator is optimized to provide quick access to the options most frequently used after synthesis**
  - Constraints Wizard: Already mentioned
  - Edit Timing Constraints: Launch the timing constraints tab
  - Set Up Debug: Launch the view for marking nets for debug
  - Report Timing Summary: Generate a default timing report
  - Report Clock Networks: Generates a clock tree for the design
  - Report Clock Interaction: Verifies constraint coverage on paths between clock domains
  - Report DRC: Performs design rule check on the entire design
  - Report Noise: Performs an SSO analysis of output and bidirectional pins in the design
  - Report Utilization: Generates a graphical version of the Utilization Report
  - Report Power: Detailed power analysis reports
  - Schematic: Opens the Schematic viewer



# Report Timing Summary

## ▶ Vivado IDE

## ▶ Options tab

- Maximum number of paths




## ▶ Advanced tab

- Write to a file

## ▶ Timer Settings

- Interconnect delay can be ignored
- Flight delays can be disabled

Tcl command: `report_timing_summary`  
`report_timing_summary -delay_type max -`  
`report_unconstrained -check_timing_verbose -`  
`max_paths 10 -input_pins -name timing_1`



# Report Timing Summary

## ► Design Timing Summary

- WNS, TNS, total number of endpoints are of interest

## ► Clock Summary

- Primary and derived clocks

## ► Check Timing

- Number of unconstrained internal endpoints



The first screenshot shows the 'Design Timing Summary' report. It includes a left-hand navigation pane with categories like General Information, Timer Settings, Design Timing Summary, Clock Summary (2), Check Timing (0), Intra-Clock Paths, Inter-Clock Paths, Other Path Groups, User Ignored Paths, and Unconstrained Paths. The main content area displays a table with three columns: Setup, Hold, and Pulse Width. The Setup column shows Worst Negative Slack (WNS) as 0.282 ns, Total Negative Slack (TNS) as 0.000 ns, and Total Number of Endpoints as 122. The Hold column shows Worst Hold Slack (WHS) as 0.064 ns, Total Hold Slack (THS) as 0.000 ns, and Total Number of Endpoints as 122. The Pulse Width column shows Worst Pulse Width Slack (WPWS) as 3.500 ns, Total Pulse Width Negative Slack (TPWS) as 0.000 ns, and Total Number of Endpoints as 60. A summary statement at the bottom reads: 'All user specified timing constraints are met.'

The second screenshot shows the 'Clock Summary' report. It features a table with four columns: Name, Waveform, Period (ns), and Frequency (MHz). The table lists two clocks: 'clk\_pin' with a period of 8.000 ns and frequency of 125.000 MHz, and 'virtual\_clock' with a period of 8.000 ns and frequency of 125.000 MHz.

The third screenshot shows the 'Check Timing' report. It displays a table with three columns: Timing Check, Count, and Worst Severity. The table lists various timing checks, all with a count of 0, indicating that all timing constraints are met. The checks include: no\_clock, constant\_clock, pulse\_width\_clock, unconstrained\_internal\_endpoints, no\_input\_delay, no\_output\_delay, multiple\_clock, generated\_clocks, and loops.

# Report Clock Networks

- ▶ To generate a report on the clock networks in a design, use the tcl command
  - `report_clock_networks`
  - Creates a tree view of all the logical clock trees found in the design, annotated with existing and missing clock definitions on the roots of these trees
- ▶ Vivado IDE




# Report Clock Interaction

## ► Use Tcl command

- `report_clock_interaction -significant_digits 3 -name timing_1`

## ► Reports paths on inter-clock domain paths and unclocked registers

- Uses an inter-clock path matrix to show clock relationships and group paths
- Tells if timing is asynchronous and if paths are constrained (green)
- Uses the worst-slack value for each clock grouping






# Report DRC

## ► Use Tcl command

- `report_drc -name drc_1`

## ► DRCs performed early in the design flow allow for correction before a full implementation

- Objects listed in violations are cross-selectable with HDL sources
- Can select which DRCs to run, or run all
  - This check is more thorough than the I/O DRC checks that occur during pin planning
- Any problems will open a DRC window at the bottom of the GUI
- Run implementation for the final sign-off DRC





# Report Noise

## ► Use Tcl command

- `report_ssn -name ssn_1`

## ► Performs a SSN analysis of the planned I/O layout



- This report is looking to gauge the number of pins, I/O standard, and drive strength on a bank-by-bank basis
  - Banks that exceed what is recommended will be flagged in the Summary tab
  - SSN analysis can only be done on output and bidirectional ports

The screenshot displays the Xilinx IDE interface. On the left, the 'SYNTHESIS' menu is open, showing various options. The 'Report Noise' option is highlighted with a red rectangle. On the right, the 'I/O Bank Details' report is shown, which is a table with columns: Name, Port, I/O Std, Vcco, Slew, Drive Strength (...), Off-Chip Termina..., Remaining Margin ..., and Notes. The table lists details for I/O Bank 34 (10), including pins Y18, Y19, R14, P14, and W14, their respective I/O standards (LVCMOS33), Vcco values (3.30), slew rates (SLOW), drive strengths (12), and remaining margins.

| Name             | Port          | I/O Std  | Vcco | Slew | Drive Strength (...) | Off-Chip Termina... | Remaining Margin ... | Notes |
|------------------|---------------|----------|------|------|----------------------|---------------------|----------------------|-------|
| I/O Bank 0 (0)   |               |          |      |      |                      |                     |                      |       |
| I/O Bank 13 (0)  |               |          |      |      |                      |                     |                      |       |
| I/O Bank 34 (10) |               | LVCMOS33 | 3.30 | SLOW | 12                   | FP_VTT_50           |                      |       |
| Y18              | dac_clr_n_pin | LVCMOS33 | 3.30 | SLOW | 12                   | FP_VTT_50           | 83.22                |       |
| Y19              | dac_cs_n_pin  | LVCMOS33 | 3.30 | SLOW | 12                   | FP_VTT_50           | 81.32                |       |
| R14              | led_pins[0]   | LVCMOS33 | 3.30 | SLOW | 12                   | FP_VTT_50           | 87.86                |       |
| P14              | led_pins[1]   | LVCMOS33 | 3.30 | SLOW | 12                   | FP_VTT_50           | 83.54                |       |
| W14              | led_pins[4]   | LVCMOS33 | 3.30 | SLOW | 12                   | FP_VTT_50           | 50.32                |       |

# Report Power



- ▶ **Use Tcl command**
  - `report_power -results {power_1}`
- ▶ **Accurate power and thermal analysis**
- ▶ **Power estimates at every stage after synthesis**
- ▶ **Perform what-if analysis by varying switching activity**
- ▶ **Extensive debug capabilities through cross-probing**
- ▶ **Exports data to XPE**





# Power Utilization Details

- Select different resource types to see more details



# Summary

# Summary

- ▶ **Elaborated design allows early drc checks, noise analysis, and cross-probing between the source file and the generated hierarchical design**
- ▶ **Synthesis performs logic optimization and technology mapping to Xilinx primitives**
- ▶ **Vivado IDE supports VHDL, Verilog, and SystemVerilog**
- ▶ **Vivado IDE supports the use of Xilinx Design Constraint (XDC) syntax, which is used to drive synthesis design optimization**
- ▶ **check\_timing report is used to verify that a design has been sufficiently constrained by the designer**
- ▶ **Vivado IDE includes numerous reporting mechanisms for the designer to improve performance, avoid common design mistakes, and get the most out of the FPGA**



# Thank You

# Disclaimer and Attribution

The information contained herein is for informational purposes only and is subject to change without notice. While every precaution has been taken in the preparation of this document, it may contain technical inaccuracies, omissions and typographical errors, and AMD is under no obligation to update or otherwise correct this information. Advanced Micro Devices, Inc. makes no representations or warranties with respect to the accuracy or completeness of the contents of this document, and assumes no liability of any kind, including the implied warranties of noninfringement, merchantability or fitness for particular purposes, with respect to the operation or use of AMD hardware, software or other products described herein. No license, including implied or arising by estoppel, to any intellectual property rights is granted by this document. Terms and limitations applicable to the purchase or use of AMD's products are as set forth in a signed agreement between the parties or in AMD's Standard Terms and Conditions of Sale. GD-18

© Copyright 2022 Advanced Micro Devices, Inc. All rights reserved. Xilinx, the Xilinx logo, AMD, the AMD Arrow logo, Alveo, Artix, Kintex, Kria, Spartan, Versal, Vitis, Virtex, Vivado, Zynq, and other designated brands included herein are trademarks of Advanced Micro Devices, Inc. Other product names used in this publication are for identification purposes only and may be trademarks of their respective companies.

