Source: docs\STOREFRONT_THEMES_AND_OFFERS.md | Export: 11 November 2026

Storefront themes and Available Offers

Owner controls

Admin > Store Settings > Storefront Appearance > Colour Theme offers Classic Cream and Light Maroon. Selection previews only the card; **Save Theme** applies it. Cancel discards the selection. Existing Lora typography, artwork, layouts, semantic statuses and Admin colours are retained.

`siteSettings/storefrontAppearance` contains `schemaVersion: 1`, a positive `revision`, and `theme: "classic-cream" | "light-maroon"`. Trusted server writes also record the existing settings operation/audit metadata. Saves check both the admin claim and enabled access record, use revision conflict protection and merge unrelated fields. A missing setting defaults to Classic Cream. Public content exposes only the theme and revision; invalid public appearance safely falls back to Classic Cream. Other devices refresh within 15 seconds while visible, on focus/reconnection, or on reopening. No authentication or browser preference is needed to retain the store's saved theme.

Admin > Coupons > Add/Edit > **Show in Available Offers** publishes discovery details. This is separate from Enabled. Existing and newly created coupons are private unless this checkbox is explicitly saved. Private codes can still be entered manually at checkout. No existing production coupon is auto-published.

Customer behaviour and security

One component provides offers on Shop/category pages, Product Details, Bag and the checkout Review step beside the existing coupon input. It does not add a homepage section. Copy works for guests and customers; guests are asked to sign in for personal eligibility. Product offers use the selected colour/quantity; Shop and Bag use current Bag items.

`GET /api/catalog?coupons=available` returns a whitelist of public offer fields. `POST {action: "coupons:available", source?, eligibleOnly?}` additionally verifies the customer token and reads only that UID's Delivered orders and usage. Client UID/count parameters are rejected. This is read-only and does not reserve or redeem a code. Raw coupon documents, usage, customer identity and audit fields are not public. An explicit publication flag, validity, enabled state and global/customer usage limits govern visibility. Read failure is distinct from no offers and leaves manual checkout coupon entry usable. A bounded 10,000-published-offer limit (matching Admin listing) fails explicitly rather than exposing partial discovery results.

Validity, usage limits, sequence policy and discount arithmetic reuse checkout's validators. Order number N means exactly N-1 Delivered orders, including COD orders with unrecorded collection. Coupon names do not determine the sequence. Upcoming offers show the remaining Delivered count, eligible offers allow Apply, and offers already passed or used are omitted. Subtotals use server product data.

Checkout Available Coupons selector

The Review step now has a collapsed **Available Coupons** section beside manual code entry. Opening it fetches `eligibleOnly: true` through the same authenticated endpoint. This boolean filters the existing server projection to `eligible` offers only: future, expired, disabled, private, exhausted, below-minimum and not-yet-unlocked sequence offers are omitted. Other storefront offer sections keep their existing informational/upcoming behavior. An empty response explicitly says **No offers available for this order right now.** Loading skeletons and a separate retryable failure state never pretend to be an empty result.

Coupon cards derive their description from the saved discount type/value; the current coupon schema has no separate title/description, product/category scope or arbitrary customer allowlist. Existing customer restrictions are the saved per-customer usage limit and exact Delivered-order sequence. No new eligibility fields or coupon system are introduced. Cancelled, Rejected and other non-Delivered orders do not unlock a sequence offer.

Apply populates manual entry and requests the existing trusted checkout review. Only a successful current review displays **Coupon applied**, savings and the card's **Applied** indicator. Either Remove action clears the same draft code and recalculates totals. Points Apply/Remove and the existing stacking policy remain unchanged. The selector stays open across review refreshes; the initial full-page loading view is reserved for an account's first review.

Cart identity (including item IDs, quantities, prices and stock) and the review fingerprint refresh discovery even when a changed cart has the same subtotal. While expanded, discovery refreshes every 15 seconds and on focus/reconnection. A selected coupon also refreshes its authoritative review every 15 seconds while visible and on focus, suspended during order/payment recovery or submission. An invalid selected code is explicitly unconfirmed and blocks progression until removed or corrected. Both COD acceptance and online reservation continue their original final transaction checks; discovery never reserves or redeems anything.

`scripts/checkout-coupons-browser.test.py` covers the real loopback flow at 320/390/768/1440px in both themes, including loading, keyboard expansion, retry, empty results, Apply/Applied/Remove, trusted totals and live cart changes. The exported-handler assertions in `theme-offers-emulator.test.ts` cover token ownership, exact input rejection, lifecycle/limit filtering, Delivered-only sequence qualification and empty carts. Existing coupon/payment transaction regressions continue to cover concurrent redemption and reservations.

Apply on Shop/Bag/Product first invokes the existing `orders:review`, stores one coupon code in the existing UID-scoped checkout draft and opens checkout. Apply on Review populates the existing input and triggers its validator. Final `orders:place` still revalidates coupon, totals, usage, sequence and stock inside the existing acceptance transaction. Apply/Remove Points is unchanged; coupon savings are never accumulated by the discovery

component.

Offers refresh within 15 seconds while visible, and on focus/reconnection. An offer may change between discovery and acceptance; checkout remains authoritative.

Operations and verification

No new environment variables, secrets, functions, rules or composite indexes are required. The publication query uses the default single-field `discoverable` index; the existing token-owned Delivered query is reused. No index exemptions should be introduced for this field. Direct browser access to settings/coupons continues to be governed by the existing deny rules; all writes use the API.

Unit coverage is included in `npm test`. The loopback service/browser regressions are `scripts/theme-offers-emulator.test.ts` and `scripts/theme-offers-browser.test.py`, registered in the existing test harnesses. They use synthetic data only. Emulator readiness does not prove deployed indexes or production eligibility. Local screenshots are in `.cache/theme-offers/`.

Release through the existing GitHub/Vercel workflow after typecheck, build, runtime and regressions. Verify the deployment's commit SHA, READY state, public appearance/offer projections and responsive pages separately. Real production coupon redemption and customer-specific eligibility require owner acceptance with an existing account; no production business records are changed by tests.