Source: docs\operations\local-setup-environments.md | Export: 11 November 2026

> **Current shipping status (11 November 2026):** `DISTANCE_DELIVERY_ENABLED=false` by default. New checkout uses the existing saved flat shipping configuration, before coupons/points, with free shipping strictly above its saved threshold. Google Routes, dispatch coordinates, slabs and distance quotes are inactive. Historical order charges are unchanged. Distance-specific material below describes a retained, inactive implementation until a future explicitly approved re-enable. See current flat shipping reference.

Local setup and environment reference

For developers and configuration owners. Baseline: inspected source, 11 November 2026. This reference contains variable names and procedures only. No configuration was created, read from secret stores or changed during documentation.

Prerequisites and local processes

Use the locked dependencies. Existing setup evidence used Windows/PowerShell, Node 22.22.2 and npm 10.9.7; current Vercel Node selection is **Pending confirmation**. `package.json` is the command reference. Python Playwright/Chromium and a compatible Java runtime are additionally needed for the existing browser/emulator harnesses; npm does not install the host Python environment.

For a separately authorized local development setup:

```
npm.cmd ci
npm.cmd run dev:api
# In a second terminal:
npm.cmd run dev
```

Vite uses port 3000 and proxies `/api` to the local API on 3200. `dev:api` uses `scripts/catalog-dev.ts`; follow existing product setup for server-file loading. The example template is not automatically a populated environment. Ignore files containing credentials. Normal development may connect to real Firebase: it is not automatically a safe fixture environment.

Use the established emulator harness for synthetic accounts/orders. Auth is `127.0.0.1:9099`, Firestore `127.0.0.1:8080`. Never point fixture/seed/repair scripts at Production. Review harness port allocation before running concurrent suites.

Variable matrix

Values and exact current account scopes are **Pending confirmation**. `VITE_` variables are browser build inputs, not secret storage. Server credentials must never use that prefix.

Variable	Purpose/value source	Intended scope
`VITE_FIREBASE_API_KEY`, `VITE_FIREBASE_AUTH_DOMAIN`, `VITE_FIREBASE_PROJECT_ID`, `VITE_FIREBASE_STORAGE_BUCKET`, `VITE_FIREBASE_MESSAGING_SENDER_ID`, `VITE_FIREBASE_APP_ID`	Browser app configuration from the approved Firebase project; validated together	Build-time Production; separately approved local/Preview setup
`VITE_FIREBASE_DATABASE_ID`	Existing browser database selector; use `(default)` for this project	Same approved browser environments
`VITE_FIREBASE_CHECK_DOCUMENT_PATH`	Optional development read diagnostic, not commerce configuration	Development-only diagnostic use
`FIREBASE_PROJECT_ID`, `FIREBASE_CLIENT_EMAIL`, `FIREBASE_PRIVATE_KEY`	Existing supported split server service-account mechanism; project fixed to `parinaya-silks`	Trusted server; retain the chosen existing mechanism
`FIREBASE_SERVICE_ACCOUNT_JSON`	Alternative server credential JSON	Trusted server, only if this is the chosen mechanism
`GOOGLE_APPLICATION_CREDENTIALS`	Alternative local credential-file path, not the JSON contents	Trusted local/server environment supporting that file
`CLOUDINARY_CLOUD_NAME`, `CLOUDINARY_API_KEY`, `CLOUDINARY_API_SECRET`, `CLOUDINARY_UPLOAD_PRESET`	Signed upload/asset verification settings from Cloudinary	Trusted server; least-privilege account/preset
`RAZORPAY_MODE`	Exactly `test` or `live`	Approved Production server; separate local TEST setup

Variable	Purpose/value source	Intended scope
`RAZORPAY_KEY_ID`, `RAZORPAY_KEY_SECRET`	Matching mode/account API pair	Production server; never copy LIVE pair into fixtures/Preview
`RAZORPAY_WEBHOOK_SECRET`	Independent secret matching the configured mode's webhook	Production server; separate local synthetic/TEST values
`RAZORPAY_TEST_UIDS`	Comma-separated explicitly approved Firebase test UIDs	Production TEST allowlist where needed
`RAZORPAY_TEST_ENVIRONMENT`	Local TEST permission switch; not a Production bypass	Local-only intentional TEST setup; false on hosted deployments
`RAZORPAY_LIVE_ACTIVATED`	Explicit LIVE initiation gate; only approved cutover sets true	Production server; keep false for TEST/local
`PAYMENT_WORKER_SECRET`	Separate random secret, at least 32 characters; scheduler bearer authorization	Production server and scheduler's protected header
`GOOGLE_MAPS_API_KEY`	Restricted Routes API key, server-side only; unused while distance is disabled	Future approved distance release only
`DISTANCE_DELIVERY_ENABLED`	Server-only opt-in; default and required current state `false`; only exact `true` enables the retained distance branch	Keep false; no Production variable was changed
`VITE_GA_MEASUREMENT_ID`	Public GA4 web-stream ID; approved ID `G-R785L2F0K0`	Production build only
`VERCEL_ENV`, `NODE_ENV`, `VERCEL`	Platform/runtime identity	Platform-managed; do not falsify to bypass checks
`VITE_DEPLOYMENT_ENV`	Derived by `vite.config.ts` from build `VERCEL_ENV`	Generated build definition; do not manually use it as an activation bypass
`PARINAYA_SERVER_EMULATORS`, `FIRESTORE_EMULATOR_HOST`, `FIREBASE_AUTH_EMULATOR_HOST`	Guarded harness isolation	Exact loopback test environments only; not hosted deployments

`server/credentials.ts` supports split credentials first, then the JSON/file alternatives, then application default credentials where available. Do not add competing mechanisms to fix an unrelated issue. `.env.example` lists the main template but omits some supported alternatives and GA4; this documentation does not modify it.

Security and configuration hygiene

- Use service owners' protected environment stores; never put secret values in Git, screenshots, URLs, support chats or docs.
- Keep production payment credentials scoped to Production. Preview payment operations explicitly reject; copying keys into Preview is neither necessary nor supported.
- Browser Firebase configuration is public, but authorization still depends on Auth, rules and server checks. Never substitute Admin credentials for browser config.
- Keep Google Routes and Razorpay secrets server-side. Return only the intended public checkout key/contract from payment APIs, never secret material.
- Use value-free diagnostics: variable presence/scope, project/mode match and safe error code. Do not dump environment variables or service-account files.
- Vite/browser environment changes require a new build; server environment changes require a new deployed function version. Neither change is performed by this guide.

Troubleshooting setup

Missing browser Firebase variables show configuration failure; unsupported project IDs fail validation. Missing server credentials affect trusted API operations. Missing Cloudinary settings affect upload/verification. Missing Google setup has no effect on flat checkout while distance delivery is disabled. Missing payment readiness can hide online initiation while COD still depends on its own delivery/settings validity.

Existing detailed sources: Firebase, Admin access, Razorpay setup, GA4, distance setup. Older setup documents contain dated hosted inventories; do not interpret them as current variable audits.

Implementation sources: `package.json`, `.env.example`, `vite.config.ts`, `src/services/firebase/config.ts`, `server/credentials.ts`, `server/firebase.ts`, `server/cloudinary.ts`, `server/payments/config.ts`, `src/analytics/browser.ts`, `scripts/test-client-changes.mjs`.