Source: docs\overview.md | Export: 11 November 2026

> **Current shipping status (11 November 2026):** `DISTANCE_DELIVERY_ENABLED=false` by default. New checkout uses the existing saved flat shipping configuration, before coupons/points, with free shipping strictly above its saved threshold. Google Routes, dispatch coordinates, slabs and distance quotes are inactive. Historical order charges are unchanged. Distance-specific material below describes a retained, inactive implementation until a future explicitly approved re-enable. See current flat shipping reference.

Project overview

Baseline: 11 November 2026; local HEAD `405716c` plus existing distance-delivery working-tree changes. Production parity: **Pending confirmation**. Start at the documentation index.

Purpose and identity

Parinaya Sarees is a customer storefront and separate authenticated administration application for selling sarees, managing catalog/stock, accepting orders and maintaining customer relationships. Visible branding is defined in `src/config/brand.ts` as Parinaya Sarees. The repository name and Firebase project remain `parinaya-silks`; do not rename infrastructure identifiers to match display branding.

Stack and structure

Area	Implementation	Main location
Customer/Admin UI	React 19, TypeScript, Vite, Tailwind and module CSS; existing local Lora typography	`src/App.tsx`, `src/views/`, `src/admin/`
Routing	Application-managed history/popstate navigation with legacy hash handling; not React Router	`src/App.tsx`, `src/utils/routing.ts`, `src/admin/accessPolicy.ts`
Authentication/data	Firebase browser SDK; trusted Firebase Admin backend; Firestore `(default)` in `parinaya-silks`	`src/services/firebase/`, `server/firebase.ts`
API hosting	Vercel catalog function and dynamic payment function	`api/catalog.ts`, `api/payments/[action].ts`, `vercel.json`
Media	Signed and server-verified Cloudinary uploads	`server/cloudinary.ts`, module media editors
Payments	Razorpay TEST/LIVE support, signed verification/webhooks and scheduled recovery	`server/payments/`, `src/payments/`
Delivery	Server Google Routes driving quote; optional Leaflet/OpenStreetMap pin picker	`server/routes.ts`, `server/deliveryQuotes.ts`, `src/delivery/LocationPicker.tsx`
Analytics	Optional consented GA4 manual page views	`src/analytics/`, `src/content/Seo.tsx`
Verification	Node tests, Firebase emulators, Python Playwright and packaged-runtime checks	`scripts/`, module `*.test.ts/*.test.tsx`

`package.json` and the lockfile are the version reference. Existing setup records name Node 22.22.2/npm 10.9.7; the current hosted Node runtime is **Pending confirmation**.

Functional areas

- Storefront: categories, search/filters, product information/images/variants, Wishlist, Bag, Buy Now, campaigns and coupon discovery.
- Customer: email/password account, required registration contact, addresses, checkout, order history/progress, supported cancellation/return requests and loyalty balances/history.
- Administration: dashboard, categories, products, inventory, orders/bulk workflow, customers/exports, coupons, campaigns, banners, website content, contact, About, enquiries and settings.
- Commerce: trusted totals, coupon eligibility, loyalty redemption/earning, COD, online reservations, payment reconciliation and provider refund tracking.

- Delivery: saved flat fee and strict pre-coupon free-shipping threshold; COD availability remains independent. Dispatch/slabs/Routes are retained but inactive.

System flow

```
flowchart LR
  Customer[Customer browser] --> UI[React storefront]
  Admin[Authorized administrator] --> UI
  UI --> Auth[Firebase Authentication]
  UI --> Catalog[Catalog API]
  UI --> Payments[Payment API]
  Catalog --> DB[Firestore]
  Payments --> DB
  Catalog --> Media[Cloudinary]
  Catalog --> Routes[Google Routes]
  Payments --> Razorpay[Razorpay]
  Razorpay --> Hook[Signed webhook]
  Hook --> Payments
  Scheduler[External scheduler] --> Payments
```

The optional map's OSM tiles and opted-in GA4 requests are browser connections. Google Routes calculations and payment secrets stay on the server. See architecture for trust boundaries.

Boundaries

Flat checkout uses saved shipping settings and does not depend on Google Routes. Distance delivery is retained behind a server-only opt-in, disabled by default. No pickup option or independent Admin online-payment switch is present. Existing accepted orders retain snapshots.

Courier information and tracking URLs are managed manually; this documentation does not claim booking, label generation or carrier synchronization. Support WhatsApp/email/phone actions are links. No automated customer order email/SMS/WhatsApp delivery is established by the inspected integration. Refund initiation, replacement-exchange automation and billing/inventory-software synchronization must not be promised.

GA4 page views do not constitute ecommerce purchase/refund tracking. A separate reports component exists in source but is not mounted as a standalone Admin screen. Use the actual dashboard and available module exports.

Policy UI/content management is implemented; business-approved wording is **Pending confirmation**. Current deployed configuration, subscriptions, backups and integration acceptance belong in the handover register.

Sources: `package.json`, `src/config/brand.ts`, `src/App.tsx`, `src/admin/AdminPanel.tsx`, `server/catalog.ts`, `server/payments/`, `server/routes.ts`, `vercel.json`, `firebase.json`. Existing milestone documentation is retained in the index.