

Module Interface Specification for Park'd

Team #29, caPstOneGroup

Albert Zhou

Almen Ng

David Yao

Gary Gong

Jonathan Yapeter

Kabishan Suvendran

April 5, 2023

1 Revision History

Date	Version	Notes
Jan 18, 2023	1.0	Revision 0
Apr 3, 2023	1.1	Revision 1

2 Symbols, Abbreviations and Acronyms

See SRS Documentation at [Park'd Software Requirements Specification](#).

Symbol	Description
Park'd	Parking Lot Application
MIS	Module Interface Specification
MG	Module Guide
SRS	Software Requirements Specifications

Contents

1	Revision History	i
2	Symbols, Abbreviations and Acronyms	ii
3	Introduction	1
4	Notation	1
5	Module Decomposition	3
6	MIS of Authentication Module	4
6.1	Module	4
6.2	Uses	4
6.3	Syntax	4
6.3.1	Exported Constants	4
6.3.2	Exported Types	4
6.3.3	Exported Access Programs	4
6.4	Semantics	4
6.4.1	State Variables	4
6.4.2	Environment Variables	4
6.4.3	Assumptions	4
6.4.4	Access Routine Semantics	4
7	MIS of User Module	6
7.1	Template Module	6
7.2	Uses	6
7.3	Syntax	6
7.3.1	Exported Constants	6
7.3.2	Exported Types	6
7.3.3	Exported Access Programs	6
7.4	Semantics	6
7.4.1	State Variables	6
7.4.2	Environment Variables	6
7.4.3	Assumptions	6
7.4.4	Access Routine Semantics	7
8	MIS of Vehicle Module	8
8.1	Template Module	8
8.2	Uses	8
8.3	Syntax	8
8.3.1	Exported Constants	8
8.3.2	Exported Types	8

8.3.3	Exported Access Programs	8
8.4	Semantics	8
8.4.1	State Variables	8
8.4.2	Environment Variables	8
8.4.3	Assumptions	8
8.4.4	Access Routine Semantics	9
9	MIS of Admin Console Module	10
9.1	Module	10
9.2	Uses	10
9.3	Syntax	10
9.3.1	Exported Constants	10
9.3.2	Exported Types	10
9.3.3	Exported Access Programs	10
9.4	Semantics	10
9.4.1	State Variables	10
9.4.2	Environment Variables	10
9.4.3	State Invariant	10
9.4.4	Assumptions	10
9.4.5	Access Routine Semantics	11
10	MIS of Admin Module	12
10.1	Template Module	12
10.2	Uses	12
10.3	Syntax	12
10.3.1	Exported Constants	12
10.3.2	Exported Types	12
10.3.3	Exported Access Programs	12
10.4	Semantics	12
10.4.1	State Variables	12
10.4.2	Environment Variables	12
10.4.3	State Invariant	12
10.4.4	Assumptions	13
10.4.5	Access Routine Semantics	13
11	MIS of Parking Lot Layout Module	14
11.1	Template Module	14
11.2	Uses	14
11.3	Syntax	14
11.3.1	Exported Constants	14
11.3.2	Exported Types	14
11.3.3	Exported Access Programs	14
11.4	Semantics	14

11.4.1	State Variables	14
11.4.2	Environment Variables	15
11.4.3	State Invariant	15
11.4.4	Assumptions	15
11.4.5	Access Routine Semantics	15
12	MIS of Parking Layout Element Module	17
12.1	Template Module	17
12.2	Uses	17
12.3	Syntax	17
12.3.1	Exported Constants	17
12.3.2	Exported Types	17
12.3.3	Exported Access Programs	17
12.4	Semantics	17
12.4.1	State Variables	17
12.4.2	Environment Variables	17
12.4.3	State Invariant	17
12.4.4	Assumptions	17
12.4.5	Access Routine Semantics	18
13	MIS of Parking Spot Module	19
13.1	Template Module Inherits Parking Layout Element	19
13.2	Uses	19
13.3	Syntax	19
13.3.1	Exported Constants	19
13.3.2	Exported Types	19
13.3.3	Exported Access Programs	19
13.4	Semantics	19
13.4.1	State Variables	19
13.4.2	Environment Variables	20
13.4.3	State Invariant	20
13.4.4	Assumptions	20
13.4.5	Access Routine Semantics	20
14	MIS of Parking Stats Module	22
14.1	Module	22
14.2	Uses	22
14.3	Syntax	22
14.3.1	Exported Constants	22
14.3.2	Exported Types	22
14.3.3	Exported Access Programs	22
14.4	Semantics	22
14.4.1	State Variables	22

14.4.2	Environment Variables	22
14.4.3	State Invariant	22
14.4.4	Assumptions	22
14.4.5	Access Routine Semantics	23
15	MIS of Navigation Module	24
15.1	Module	24
15.2	Uses	24
15.3	Syntax	24
15.3.1	Exported Constants	24
15.3.2	Exported Types	24
15.3.3	Exported Access Programs	24
15.4	Semantics	24
15.4.1	State Variables	24
15.4.2	Environment Variables	24
15.4.3	State Invariant	24
15.4.4	Assumptions	24
15.4.5	Access Routine Semantics	25
16	MIS of Machine Learning Model Module	26
16.1	Module	26
16.2	Uses	26
16.3	Syntax	26
16.3.1	Exported Constants	26
16.3.2	Exported Types	26
16.3.3	Exported Access Programs	26
16.4	Semantics	26
16.4.1	State Variables	26
16.4.2	Environment Variables	26
16.4.3	State Invariant	26
16.4.4	Assumptions	26
16.4.5	Access Routine Semantics	27
17	MIS of DataBase Module	28
17.1	Module	28
17.2	Uses	28
17.3	Syntax	28
17.3.1	Exported Constants	28
17.3.2	Exported Types	28
17.3.3	Exported Access Programs	28
17.4	Semantics	28
17.4.1	State Variables	28
17.4.2	Environment Variables	28

17.4.3	Assumptions	28
17.4.4	Access Routine Semantics	28
18	MIS of Video Capture Module	30
18.1	Module	30
18.2	Uses	30
18.3	Syntax	30
18.3.1	Exported Constants	30
18.3.2	Exported Types	30
18.3.3	Exported Access Programs	30
18.4	Semantics	30
18.4.1	State Variables	30
18.4.2	Environment Variables	30
18.4.3	Assumptions	30
18.4.4	Access Routine Semantics	30
19	MIS of User Action Handler module	32
19.1	Module	32
19.2	Uses	32
19.3	Syntax	32
19.3.1	Exported Constants	32
19.3.2	Exported Types	32
19.3.3	Exported Access Programs	32
19.4	Semantics	32
19.4.1	State Variables	32
19.4.2	Environment Variables	32
19.4.3	State Invariant	32
19.4.4	Assumptions	33
19.4.5	Access Routine Semantics	33
20	MIS of View module	34
20.1	Module	34
20.2	Uses	34
20.3	Syntax	34
20.3.1	Exported Constants	34
20.3.2	Exported Types	34
20.3.3	Exported Access Programs	34
20.4	Semantics	34
20.4.1	State Variables	34
20.4.2	Environment Variables	34
20.4.3	State Invariant	34
20.4.4	Assumptions	34
20.4.5	Access Routine Semantics	35

20.4.6 Local Functions	35
21 Appendix	38

3 Introduction

The following document details the Module Interface Specifications for Park'd, our parking assistant application. Park'd aims to help drivers find parking spaces by using machine learning algorithms to locate empty spaces from overhead cameras. Our application then directs drivers to those spaces, taking into account restrictions like reserved or accessible spaces. It will maintain a database of spaces as well as a navigation layout for a given parking lot.

Complementary documents include the SRS and MG documents. The full documentation and implementation can be found at [Module Interface Specification](#) and [Module Guide](#) documents, respectively.

4 Notation

The structure of the MIS for modules comes from *Software Design, Automated Testing, and Maintenance: A Practical Approach* [Hoffman and Strooper \(1995\)](#), with the addition that template modules have been adapted from *Fundamentals of Software Engineering* [Ghezzi et al. \(2003\)](#). The mathematical notation comes from Chapter 3 of *Software Design, Automated Testing, and Maintenance: A Practical Approach* [Hoffman and Strooper \(1995\)](#). For instance, the symbol $:=$ is used for a multiple assignment statement and conditional rules follow the form $(c_1 \Rightarrow r_1 | c_2 \Rightarrow r_2 | \dots | c_n \Rightarrow r_n)$.

The following table summarizes the primitive data types used by Park'd.

Data Type	Notation	Description
character	char	a single symbol or digit
integer	\mathbb{Z}	a number without a fractional component in $(-\infty, \infty)$
natural number	\mathbb{N}	a number without a fractional component in $[1, \infty)$
real	\mathbb{R}	any number in $(-\infty, \infty)$
null	ϵ	empty value
Boolean	\mathbb{B}	true or false
String	String	a sequence of characters
Seq	Seq	an ordered collection of elements
exists	\exists	true if there exists an element that satisfies a property, false otherwise
for all	\forall	true if all elements satisfy a property, false otherwise
implies	\Rightarrow	false if the left is true and right is false, otherwise true
in	\in	true if a an element is in a Seq
and	\wedge	true if both operators are true, false otherwise
subset	\subseteq	true if a set contains another, false otherwise

The specification of Park'd uses some derived data types: sequences, strings, and tuples. Sequences are lists filled with elements of the same data type. Strings are sequences of characters. Tuples contain a list of values, potentially of different types. In addition, Park'd uses functions, which are defined by the data types of their inputs and outputs. Local functions are described by giving their type signature followed by their specification.

5 Module Decomposition

The following table is taken directly from the [Module Guide](#) document for this project.

Level 1	Level 2
Hardware Hiding Modules	None
Behaviour-Hiding Module	Video capture module
	Admin console module
	Admin module
	Parking lot layout module
	Parking layout element module
	Parking spot module
	Authentication module
	User module
	User action handler module
	Vehicle module
	View module
	Database module
Software Decision Module	Navigation module
	Parking Stats module
	Machine learning model module

Table 1: Module Hierarchy

6 MIS of Authentication Module

6.1 Module

AuthT

6.2 Uses

UserT DataBaseT

6.3 Syntax

6.3.1 Exported Constants

None

6.3.2 Exported Types

AuthT = ?

6.3.3 Exported Access Programs

Name	In	Out	Exceptions
authenticateUser	String, String	UserT	MissingUserException

6.4 Semantics

6.4.1 State Variables

None

6.4.2 Environment Variables

users: Seq of UserT

6.4.3 Assumptions

None

6.4.4 Access Routine Semantics

authenticateUser(id, pass):

- output: $\text{out} := \exists (i : \mathbb{N} | i < |\text{users}| \wedge \text{users}[i].\text{getUserId}() = \text{id} \wedge \text{users}[i].\text{getPassword}() = \text{pass})) \Rightarrow \text{users}[i]$

- exception: $\text{exc} := \neg \exists (i : \mathbb{N} \mid i < |\text{users}| \wedge \text{users}[i].\text{getUserId}() = id \wedge \text{users}[i].\text{getPassword}() = \text{pass})) \Rightarrow \text{MissingUserException}$

7 MIS of User Module

7.1 Template Module

UserT

7.2 Uses

VehicleT

7.3 Syntax

7.3.1 Exported Constants

None

7.3.2 Exported Types

UserT = ?

7.3.3 Exported Access Programs

Name	In	Out	Exceptions
new UserT	String, String, VehicleT	UserT	UserCreationException
getUserId		String	
getPassword		String	
getVehicle		VehicleT	

7.4 Semantics

7.4.1 State Variables

userId: String
password: String
vehicle: VehicleT

7.4.2 Environment Variables

None

7.4.3 Assumptions

None

7.4.4 Access Routine Semantics

new UserT(id, pass, veh):

- transition: $\text{userId, password, vehicle} := \text{id, pass, veh}$
- output: $\text{out} := \text{self}$
- exception: $\text{exc} := ((|\text{id}| = 0) \vee (|\text{pass}| = 0) \vee (\text{veh} = \epsilon) \Rightarrow \text{UserCreationException})$

getId():

- output: $\text{out} := \text{userId}$
- exception: none

getPassword():

- output: $\text{out} := \text{password}$
- exception: none

getVehicle():

- output: $\text{out} := \text{vehicle}$
- exception: none

8 MIS of Vehicle Module

8.1 Template Module

VehicleT

8.2 Uses

None

8.3 Syntax

8.3.1 Exported Constants

None

8.3.2 Exported Types

VehicleT = ?

8.3.3 Exported Access Programs

Name	In	Out	Exceptions
new VehicleT	\mathbb{R}, \mathbb{R}		VehicleCreationException
getLength		\mathbb{R}	
getWidth		\mathbb{R}	

8.4 Semantics

8.4.1 State Variables

length: \mathbb{R}

width: \mathbb{R}

8.4.2 Environment Variables

None

8.4.3 Assumptions

None

8.4.4 Access Routine Semantics

new VehicleT(len, wid):

- transition: length, width := len, wid
- output: out := self
- exception: exc := $((\text{len} \leq 0) \vee (\text{wid} \leq 0) \Rightarrow \text{VehicleCreationException})$

getLength():

- output: out := length
- exception: none

getWidth():

- output: out := width
- exception: none

9 MIS of Admin Console Module

9.1 Module

AdminConsoleT

9.2 Uses

[AdminT](#)

9.3 Syntax

9.3.1 Exported Constants

None

9.3.2 Exported Types

AdminConsoleT = ?

9.3.3 Exported Access Programs

Name	In	Out	Exceptions
authenticateAdmin	String, String	AdminT	MissingAdminException

9.4 Semantics

9.4.1 State Variables

None

9.4.2 Environment Variables

admins: Seq of AdminT

9.4.3 State Invariant

None

9.4.4 Assumptions

None

9.4.5 Access Routine Semantics

authenticateAdmin(id, pass):

- output: $\text{out} := \exists(i : \mathbb{N} | i < |\text{admins}| \wedge \text{admins}[i].\text{getAdminId}() = id \wedge \text{admins}[i].\text{getPassword}() = \text{pass})) \Rightarrow \text{admins}[i]$
- exception: $\text{exc} := \neg \exists(i : \mathbb{N} | i < |\text{admins}| \wedge \text{admins}[i].\text{getAdminId}() = id \wedge \text{admins}[i].\text{getPassword}() = \text{pass})) \Rightarrow \text{MissingAdminException}$

10 MIS of Admin Module

10.1 Template Module

AdminT

10.2 Uses

[ParkingLotLayoutT](#), [ParkingLayoutElemT](#), [ParkingSpotT](#)

10.3 Syntax

10.3.1 Exported Constants

None

10.3.2 Exported Types

AdminT = ?

10.3.3 Exported Access Programs

Name	In	Out	Exceptions
new AdminT	String, String	AdminT	AdminCreationException
getAdminId		String	
getPassword		String	
getLayout	String	ParkingLotLayoutT	LayoutNotFoundException
changeLayout	String, ParkingLayoutElemT		LayoutNotFoundException

10.4 Semantics

10.4.1 State Variables

adminId: String

password: String

layouts: seq of ParkingLotLayoutT

10.4.2 Environment Variables

None

10.4.3 State Invariant

None

10.4.4 Assumptions

None

10.4.5 Access Routine Semantics

new AdminT(id, pass):

- transition: adminId, password, layouts := id, pass, $\langle \rangle$
- output: out := self
- exception: exc := $((|id| = 0) \vee (|pass| = 0) \Rightarrow \text{AdminCreationException})$

getAdminId():

- output: out := adminId
- exception: none

getPassword():

- output: out := password
- exception: none

getLayout(layoutId):

- output: out := $\exists(i : \mathbb{N} | i < n : \text{layout}[i].\text{getLayoutId}() = \text{layoutId}) \Rightarrow \text{layout}[i]$
- exception: exc := $\neg \exists(i : \mathbb{N} | i < n : \text{layout}[i].\text{getLayoutId}() = \text{layoutId}) \Rightarrow \text{LayoutNotFoundException}$

changeLayout(layoutId, newSpot):

- transition: layout := $\langle i : \mathbb{N} | i < n : \text{layout}[i].\text{getLayoutSpotId}() = \text{spotId} \Rightarrow \text{layout}[i].\text{changeElem}(\text{newSpot.getelemId}(), \text{newSpot}) | \text{true} \Rightarrow \text{layout}[i] \rangle$
- exception: exc := $\neg \exists(i : \mathbb{N} | i < n : \text{layout}[i].\text{getLayoutId}() = \text{layoutId}) \Rightarrow \text{LayoutNotFoundException}$

11 MIS of Parking Lot Layout Module

11.1 Template Module

ParkingLotLayoutT

11.2 Uses

ParkingLayoutElemT

11.3 Syntax

11.3.1 Exported Constants

None

11.3.2 Exported Types

ParkingLotLayoutT = ?

11.3.3 Exported Access Programs

Name	In	Out	Exceptions
new ParkingLotLayoutT	String, \mathbb{N}	ParkingLotLayoutT	LayoutCreationException
setAllRoads			
getLayoutId		String	
getSize		\mathbb{N}	
changeElem	String, ParkingLayoutElemT		
getLayout		Seq of ParkingLayoutElemT	
getElem	String	ParkingLayoutElemT	ElemNotFoundException
getElemIndex	String	\mathbb{N}	ElemNotFoundException

11.4 Semantics

11.4.1 State Variables

layoutId: String

n: \mathbb{N}

layout: seq of ParkingLayoutElemT

11.4.2 Environment Variables

None

11.4.3 State Invariant

$|layout| = n^2$.

11.4.4 Assumptions

None

11.4.5 Access Routine Semantics

new ParkingLotLayoutT($id, size$):

- transition: $layoutId, n, layout := id, size, \langle \rangle$
- output: $out := self$
- exception: $exc := ((|id| = 0) \Rightarrow AdminCreationException)$

~~setAllRoads()~~:

- output: $layout := i : \mathbb{N} | i < n^2 : layout || \langle newParkingLayoutElem("road" + i, "road") \rangle$
- exception: none

getLayoutId():

- output: $out := layoutId$
- exception: none

getSize():

- output: $out := n$
- exception: none

changeElem($elemId, newElem$):

- transition: $layout := \langle i : \mathbb{N} | i < n : layout[i].getelemId() = elemId \Rightarrow newElem | true \Rightarrow layout[i] \rangle$
- exception: none

getLayout():

- output: $out := layout$

- exception: none

getElem(elemId):

- output: $\text{out} := \exists(i : \mathbb{N} \mid i < n : \text{layout}[i].\text{getLayoutId}() = \text{elemId}) \Rightarrow \text{layout}[i]$
- exception: $\text{exc} := \neg \exists(i : \mathbb{N} \mid i < n : \text{layout}[i].\text{getLayoutId}() = \text{elemId}) \Rightarrow \text{ElemNotFoundException}$

getElemIndex(elemId):

- output: $\text{out} := \exists(i : \mathbb{N} \mid i < n : \text{layout}[i].\text{getLayoutId}() = \text{elemId}) \Rightarrow i$
- exception: $\text{exc} := \neg \exists(i : \mathbb{N} \mid i < n : \text{layout}[i].\text{getLayoutId}() = \text{elemId}) \Rightarrow \text{ElemNotFoundException}$

12 MIS of Parking Layout Element Module

12.1 Template Module

ParkingElemT

12.2 Uses

None

12.3 Syntax

12.3.1 Exported Constants

None

12.3.2 Exported Types

ParkingElemT = ?

12.3.3 Exported Access Programs

Name	In	Out	Exceptions
new ParkingElemT	String, String	ParkingElemT	
getelemId		String	
getType		String	

12.4 Semantics

12.4.1 State Variables

elemId: String

~~type: String~~

12.4.2 Environment Variables

None

12.4.3 State Invariant

~~$type \in \{ "spot", "road", "obstacle" \}.$~~

12.4.4 Assumptions

None

12.4.5 Access Routine Semantics

new ParkingElem(id, s, x, y):

- transition: $\text{elemId}, \text{type} := \text{id}, \text{s}$
- output: $\text{out} := \text{self}$
- exception: $\text{exc} := \text{None}$

getelemId():

- output: $\text{out} := \text{elemId}$
- exception: none

getType():

- output: $\text{out} := \text{type}$
- exception: none

13 MIS of Parking Spot Module

13.1 Template Module Inherits Parking Layout Element

ParkingSpotT

13.2 Uses

[ParkingLayoutElemT](#)

13.3 Syntax

13.3.1 Exported Constants

None

13.3.2 Exported Types

ParkingSpotT = ?

13.3.3 Exported Access Programs

Name	In	Out	Exceptions
new ParkingSpotT	String, \mathbb{R} , \mathbb{R}	ParkingSpotT	
setEnabled	\mathbb{B}		
setOccupied	\mathbb{B}		
setReserved	\mathbb{B}		
setHandicapped	\mathbb{B}		
setAllProp	Seq of \mathbb{B}		InvalidParamException
getEnabled		\mathbb{B}	
getOccupied		\mathbb{B}	
getReserved		\mathbb{B}	
getHandicapped		\mathbb{B}	
getAllProp		Seq of \mathbb{B}	

13.4 Semantics

13.4.1 State Variables

enabled: \mathbb{B}

occupied: \mathbb{B}

reserved: \mathbb{B}

handicapped: \mathbb{B}

13.4.2 Environment Variables

None

13.4.3 State Invariant

None

13.4.4 Assumptions

None

13.4.5 Access Routine Semantics

new ParkingSpot(id):

- transition: spotId, ~~type~~, enabled, reserved, handicapped, occupied := id, ~~"spot"~~, true, false, false, false
- output: out := self
- exception: exc := None

setEnabled(e):

- transition: enabled := e
- exception: none

setOccupied(o):

- transition: occupied := o
- exception: none

setReserved(r):

- transition: reserved := r
- exception: none

setHandicapped(h):

- transition: handicapped := h
- exception: none

setAllProp(p):

- transition: enabled, occupied, reserved, handicapped := p[0], p[1], p[2], p[3]
- exception: $\text{exc} := |p| \neq 4 \Rightarrow \text{InvalidParamException}$

getEnabled():

- output: out := enabled
- exception: none

getOccupied():

- output: out := occupied
- exception: none

getReserved():

- output: out := reserved
- exception: none

getHandicapped():

- output: out := handicapped
- exception: none

getAllProp():

- output: out := $\langle \text{enabled}, \text{occupied}, \text{reserved}, \text{handicapped} \rangle$
- exception: none

14 MIS of Parking Stats Module

14.1 Module

ParkingStatsT

14.2 Uses

[ParkingLotLayoutT](#), [ParkingSpotT](#)

14.3 Syntax

14.3.1 Exported Constants

None

14.3.2 Exported Types

ParkingStatsT = ?

14.3.3 Exported Access Programs

Name	In	Out	Exceptions
getStat	ParkingLotLayoutT, Seq of \mathbb{B}	\mathbb{N}	InvalidParamException

14.4 Semantics

14.4.1 State Variables

None

14.4.2 Environment Variables

None

14.4.3 State Invariant

None

14.4.4 Assumptions

None

14.4.5 Access Routine Semantics

getStat(l, p):

- output: $\text{out} := +(\forall(e : \text{ParkingSpotT} | e \in l.\text{getLayout}() : \text{e.getType() = "spot"} \wedge e.\text{getAllProp}() = p \Rightarrow 1 | \text{true} \Rightarrow 0))$
- exception: $\text{exc} := |p| \neq 4 \Rightarrow \text{InvalidParamException}$

15 MIS of Navigation Module

15.1 Module

NavigationT

15.2 Uses

[ParkingLotLayoutT](#), [ParkingLayoutElemT](#)

15.3 Syntax

15.3.1 Exported Constants

None

15.3.2 Exported Types

NavigationT = ?

15.3.3 Exported Access Programs

Name	In	Out	Exceptions
findPath	ParkingLotLayoutT , String	Seq of String	NoPathException

15.4 Semantics

15.4.1 State Variables

None

15.4.2 Environment Variables

loc : String

15.4.3 State Invariant

None

15.4.4 Assumptions

None

15.4.5 Access Routine Semantics

findPath(L, stopId):

- output: $\text{out} := \langle s : \text{String} \rangle$ that satisfies the following:
 - $\text{out}[0] = \text{loc}$.
 - $\text{out}[|\text{out}| - 1] = \text{stopId}$.
 - $\text{out} \subseteq \langle \forall (e : \text{ParkingLayoutElemT} | e \in L.\text{getLayout}()) : e.\text{get}(\text{elemId}) \rangle$.
 - $\forall (i : \mathbb{N} | i < |\text{out}| - 2 : L.\text{getElem}(\text{out}[i]).\text{getType}() = \text{"Road"})$.
 - $L.\text{getElem}(\text{out}[|\text{out}| - 1]).\text{getType}() = \text{"Spot"}$.
 - $\forall (i : \mathbb{N} | i < |\text{out}| - 1 : l.\text{getElemIndex}(\text{out}[i]) - l.\text{getElemIndex}(\text{out}[i + 1]) \in \{1, -1, l.\text{getSize}(), -l.\text{getSize}()\})$.
- exception: $\text{exc} := \text{No out can satisfy the requirements} \Rightarrow \text{NoPathException}$

16 MIS of Machine Learning Model Module

16.1 Module

ModelT

16.2 Uses

[VideoCaptureT](#)

16.3 Syntax

16.3.1 Exported Constants

None

16.3.2 Exported Types

ModelT = ?

16.3.3 Exported Access Programs

Name	In	Out	Exceptions
setModel	String		
setInput	String, String		
getResult		Seq of \mathbb{B}	

16.4 Semantics

16.4.1 State Variables

None

16.4.2 Environment Variables

model: the pre-trained machine learning model in the machine. The model will be deserialized as a python object.

16.4.3 State Invariant

None

16.4.4 Assumptions

None

16.4.5 Access Routine Semantics

setModel(pickleAdd):

- transition: modelAddress, model := pickleAdd, load(pickleAdd)
- exception: $\text{exc} := \neg\exists(\text{address} : \text{String} \mid \neg\text{address.exist}()) \Rightarrow \text{InvalidAddressException}$

setInput(inputURL, inputTypes):

- transition: InputURL, Inputtype := inputURL,inputTypes
- exception: none

getResult():

- output: $\text{out} := \text{model.predict}()$
- exception: none

17 MIS of DataBase Module

17.1 Module

DbT

17.2 Uses

None

17.3 Syntax

17.3.1 Exported Constants

None

17.3.2 Exported Types

DbT = ?

17.3.3 Exported Access Programs

Name	In	Out	Exceptions
query_by_key	String	String	
set_by_key	String, String	\mathbb{B}	

17.4 Semantics

17.4.1 State Variables

None

17.4.2 Environment Variables

None

17.4.3 Assumptions

None

17.4.4 Access Routine Semantics

query_by_key(key):

- output: out := DbT[key]

set_by_key(key, value):

- output: out := DbT[key] := value

18 MIS of Video Capture Module

18.1 Module

VideoCaptureT

18.2 Uses

None

18.3 Syntax

18.3.1 Exported Constants

None

18.3.2 Exported Types

VideoCaptureT = ?

18.3.3 Exported Access Programs

Name	In	Out	Exceptions
getLatestFrame	String	Image File	

18.4 Semantics

18.4.1 State Variables

currentFrame: Image File

18.4.2 Environment Variables

None

18.4.3 Assumptions

None

18.4.4 Access Routine Semantics

getLatestFrame(url):

- transition: currentFrame := youtube.capture(url)

- output: `out := currentFrame`
- exception: `None`

`getLatestClip():`

- transition: `currentClip := picamera.record(directory)`
- output: `out := currentClip`
- exception: `None`

19 MIS of User Action Handler module

19.1 Module

UserActionHandlerT

19.2 Uses

[NavigationT](#), [AuthT](#), [AdminT](#), [ModelT](#), [ParkingStatsT](#), [ViewT](#)

19.3 Syntax

19.3.1 Exported Constants

none

19.3.2 Exported Types

UserHandlerT = ?

19.3.3 Exported Access Programs

Name	In	Out	Exceptions
handleChangeLayout	String, ParkingLayoutElemT		
handleParkingStats	ParkingLotLayoutT, Seq of \mathbb{B}	\mathbb{N}	
handleCheckAvailability		Seq of \mathbb{B}	
handleFindPath	ParkingLotLayoutT, String, String	Seq of String	
handleAuth	String, String	\mathbb{B}	

19.4 Semantics

19.4.1 State Variables

None

19.4.2 Environment Variables

None

19.4.3 State Invariant

None

19.4.4 Assumptions

None

19.4.5 Access Routine Semantics

handleCheckAvailability():

- output: `out := ModelT.getResult()`
- exception: none

handleChangeLayout(*st*, *parkingle*):

- output: `out := AdminT.changeLayout(st, parkingle)`
- exception: none

handleParkingStats(layout, boolArray):

- output: `out := ParkingStatsT.getStat(st, parkingle)`
- exception: none

handleFindPath(**l**, **stopId**):

- output: `out := navigationT.findPath(layout, String)`
- exception: none

handleAuth(id, pass):

- output: `out := AuthT.authenticateUser(id,pass)`
- exception: none

20 MIS of View module

20.1 Module

ViewT

20.2 Uses

[ParkingLotLayoutT](#), [ParkingLayoutElemT](#)

20.3 Syntax

20.3.1 Exported Constants

None

20.3.2 Exported Types

viewT = ?

20.3.3 Exported Access Programs

Name	In	Out	Exceptions
initLogin			
initPageUser			
initPageAdmin			

20.4 Semantics

20.4.1 State Variables

None

20.4.2 Environment Variables

win: two dimensional sequence of coloured pixels

20.4.3 State Invariant

None

20.4.4 Assumptions

None

20.4.5 Access Routine Semantics

initLogin():

- transition: modify win with the following:
 - a text input field for a user name.
 - a text input field for a password.
 - a button to confirm the text inputs.
- exception: none

initPageUser():

- transition: modify win with the following:
 - use showLayout() based on the location.
 - use showLayout() to show a path.
 - ~~a button to confirm logout.~~
 - a panel to show parking stats.
- exception: none

initPageAdmin():

- transition: modify win with the following:
 - use showLayout() based on the location.
 - a button to confirm logout.
 - a panel to show parking stats.
 - a button to modify parking lots.
- exception: none

20.4.6 Local Functions

showLayout(L):

- transition: modify win so the elements $e : \text{ParkingLotLayoutT}$ of L are displayed on a $L.\text{getSize}()$ by $L.\text{getSize}()$ grid with the following table:

getEnabled()	getHandicapped()	getReserved()	getOccupied()	character
true	false	false	false	Green + Green border
true	false	false	true	Red + green border
true	false	true	false	Green + red border
true	false	true	true	Green + red border
true	true	false	false	Green + blue border
true	true	false	true	Red + blue border
false				None

showPath(L, startId, stopId):

- transition: modify win first with showLayout(L).
 $\forall (s : \text{String} | s \in \text{NavigationT.findPath}(L, \text{stopId}) :$
then draw a line along each point representing L.getElem(s))
- exception: none

References

- Carlo Ghezzi, Mehdi Jazayeri, and Dino Mandrioli. *Fundamentals of Software Engineering*. Prentice Hall, Upper Saddle River, NJ, USA, 2nd edition, 2003.
- Daniel M. Hoffman and Paul A. Strooper. *Software Design, Automated Testing, and Maintenance: A Practical Approach*. International Thomson Computer Press, New York, NY, USA, 1995. URL <http://citeseer.ist.psu.edu/428727.html>.

21 Appendix

N/A