Measuring Emotional Trajectory Divergence in Interactive Narrative: Alignment and Contamination Metrics in *The Etched Mutation*

Anonymous Author(s)

Anonymous Institution

Abstract. Interactive narratives promise every participant a different experience, yet that difference is almost always described as a difference in plot branches. We present *The Etched Mutation* (TEM), a working browser-based interactive narrative in which the participant's emotional trajectory, not a branching graph, determines which scenes become accessible each turn, together with two computable metrics for how that trajectory departs from the author's: a real-time *alignment* score that compares the shape of emotional change independently of its level, and a two-axis *contamination* vector that separates directional *drift* from single-point *fixation*. Trajectories that reach *contact* with the author's are converted automatically into interpretive fragments for later participants. A 193-play persona simulation shows that the alignment metric discriminates personality profiles ($r = 0.55$–0.63) while exposing a ceiling bias in LLM-simulated readers; a three-participant human pilot (21 scene-plays) exhibits the low tail the simulation lacked and shows three readers diverging onto distinct scene sequences without any authored branch.

Keywords: Interactive narrative · Emotional trajectory · Affective computing · Reader modelling · Drama management

1 Introduction

The central promise of interactive narrative is that each participant has a different experience. Since Murray's *Hamlet on the Holodeck* [14], the tools that deliver this promise—Twine, Ink, articy:draft, and research systems such as StoryAssembler [8] and Versu [6]—have concentrated on the diversity of *paths* through a branching plot. The *emotional trajectory* a participant traces while passing through the work is not tracked as a first-class quantity.

Affective computing does not close this gap. Quantitative models of emotion are well established [18, 21, 20], and the Temporal Interpersonal Emotion Systems (TIES) framework [3, 4], with its computational form CompTIES [5], shows that the dynamic pattern of emotion predicts experiential quality. These are, however, post-hoc tools fitted to observed data; none compares trajectories

in real time inside a narrative. Reagan et al. [16] showed that stories' emotional arcs collapse onto six shapes, but that is a comparison *between works*, not between two people who experienced the *same* work.

This late-breaking paper reports a working system and its metrics, built to ask three questions.

R1. Can an interactive narrative operate on the participant's emotional trajectory alone, with no plot branching?
R2. Can the way a participant's trajectory departs from the author's be measured quantitatively and separated into distinct modes?
R3. Can a trajectory that reaches a particular affective relation to the author's be converted automatically into an interpretive fragment for the next participant?

We contribute (1) TEM, an interactive narrative system whose scene access is a function of emotional distance and in which transition patterns move the *centre* of the accessible region rather than its radius; (2) two metrics, *trajectory alignment* and a *contamination* vector with separable drift and fixation axes; and (3) a pilot validation: a 193-play persona simulation that shows internal discriminability and measures the instrument's own ceiling bias, and a 21-scene-play human pilot that exhibits the low tail the simulation lacked. We claim no theory of memory. We claim a measuring device, and an environment in which the measured quantity is what gets rendered.

2 Related Work

Drama management without a branching graph. The idea that a system rather than an authored graph chooses the next narrative unit is well established. Façade [13] selects beats toward an authored tension curve; search-based drama management [22] formalised this; PaSSAGE [19] added player modelling; and the lineage is now called experience management [17]. TEM shares the absence of a branching graph but departs on three points. First, the objective runs the other way: a drama manager optimises toward a target trajectory and treats deviation as error, whereas TEM steers toward nothing—the author's trajectory is a *baseline for measurement*, and divergence from it is the rendered content. Second, there is no latent player model; the engine computes a geometric relation between two sequences each turn and neither classifies nor recommends. Third, the selection space is a neighbourhood on an affective manifold whose centre shifts with the transition pattern. The most verifiable difference is at the schema level: even beat-based managers keep pre- and post-conditions that leave a partial plot graph, while TEM's choice records carry no next-scene column at all (Sect. 3.1).

Comparing emotional trajectories. Emotional convergence between people has been studied longitudinally [1], and CompTIES [5] fits coupled-oscillator models to rating-dial recordings after the fact. TEM's alignment metric (Sect. 4.1)

transplants the TIES principle—that the shape of change predicts similarity independently of its level—into a real-time engine inside an interactive narrative.

Reader traces passed forward. Mechanisms for leaving one reader's trace to the next include the anonymous messages of *Dark Souls* [7], anchored to spatial position; web annotation layers such as Hypothesis; and Genius-style commentary ranked by popularity. TEM's trajectory bridges (Sect. 3.3) are closest to the first but anchor to an *emotional* axis, and they refuse popularity ranking: exposure is conditioned on alignment with the current participant's state.

Memory as reconstruction. That recall reconstructs rather than retrieves [2, 12, 15, 10] is the background against which TEM was designed. This paper makes no cognitive claim; it isolates one facet—divergence of emotional trajectory—and makes it measurable inside a narrative.

3 The Etched Mutation

TEM is a browser-based interactive narrative with two modes. In *Record*, an author structures a personal memory into scenes through an AI-mediated conversation. In *Play*, a participant traverses another person's memory scene by scene, supplying an emotional response at every turn as a short continuation of the text or a choice. A third view, *strata*, lays every scene out as a three-dimensional terrain positioned by a valence–arousal projection of its emotion distribution, navigated in first person with spatialised audio; contour depth accumulates from past plays, so the terrain records collective traversal. The runtime is deterministic and covered by regression tests.

3.1 Data Model

Table 1 lists the core entities. The absence of a `next_scene_id` column is deliberate: a choice changes the participant's emotional state, and the next scene is a function of that state. All emotion comparisons are taken in a *memory-local frame*, the set of labels the author actually used in that memory (a 17-label default vocabulary serves as fallback), so that a memory written largely in *longing* is measured on that axis rather than on a fixed global basis.

3.2 Scene Access by Emotional Trajectory

Each turn, given the participant's current emotion distribution u_t and each scene's original distribution o_s, the system computes

$$d(s,t) = 1 - \cos(u_t, o_s), \tag{1}$$

takes the scenes with $d \leq \tau$ as candidates, weights them by recency of visit, and presents the top k as accessible pins. Crucially, the transition pattern reported

Table 1. Core entities of TEM.

Entity	Key fields	Meaning
memory	id, title, meta	one authored memory
scene	memory_id, scene_order, text, original_emotion, echo_words, text_stage_1/2/3	one scene; `original_emotion` is a distribution over emotion labels
choice	scene_id, emotion, intensity	an option inside a scene; records affective colour only; **no next_scene_id**
play	memory_id, trajectory_data	one participant's traversal
trajectory_bridge	memory_id, scene_id, source_run_id, entry_emotion, key_passed_scenes	automatic record of a contact run

by the engine (Sect. 4.1) shifts the *centre* of this region rather than its radius: *echo_follow* biases the centre toward the original, *contradiction* toward the opposite of the participant's current state, *avoidance* toward neutral ground. If patterns changed only the radius, the engine would degrade into a lookup table. The consequence is that two participants of the same work can see entirely different scene sequences; this is the concrete form of "difference" that we measure. The participant sees only a fogged local view of nearby accessible scenes; the author's tooling sees the whole map.

3.3 Contact and Trajectory Bridges

We call *contact* the rare event in which a participant's trajectory overlaps the author's beyond a threshold. Contact is neither an ending nor a reward; it is shown at most once per run. When it occurs, the run is converted automatically into a *trajectory bridge*: the emotion state at entry, the key scenes passed, and the sentence the participant left last. Bridges are exposed to later participants in the strata view and in scene rendering, anonymously, and conditioned on alignment with the later participant's state rather than on popularity. A bridge is thus one participant's memory-within-a-memory; it coexists with the author's own static interpretive fragments. Figure 1 summarises the runtime loop.

4 Metrics

4.1 Trajectory Alignment

The alignment engine scores the similarity between the participant's emotion sequence and the author's original sequence, every turn, as the product of three factors:

$$\text{alignment} = \text{clamp}_{[0,1]}\big(\text{level} \times \text{shape} \times \text{void_mod}\big). \tag{2}$$




Fig. 1. Runtime loop. Each turn the participant's input passes through alignment (Sect. 4.1), contamination (Sect. 4.2), and accessible-scene computation (Sect. 3.2) before rendering. A contact run is converted into a trajectory bridge and exposed to later participants.

Level is the mean, over visited scenes, of the per-scene cosine similarity between participant and original distributions. *Shape* compares the trajectories of *change*: with Δu and Δo the sequences of successive differences,

$$\text{shape} = \max\big(0,\ \cos(\text{flatten}\,\Delta u,\ \text{flatten}\,\Delta o)\big) \tag{3}$$

once three or more scenes have been visited, and 1.0 before that. The original sequence is re-ordered by the participant's visit order, because which scene one opens first is already an act of interpretation. *void_mod* is 0.7 when the participant withheld an emotion where the author expressed one, and 1.0 otherwise.

The factors are multiplied rather than added so that no factor can compensate for another: a level of zero yields zero alignment regardless of shape. That shape compares the *direction* of change rather than its magnitude is the transplanted TIES principle; two people whose emotional levels differ can still share a high shape score. The engine is deterministic (snapshot-tested against golden fixtures), runs in time linear in the number of visited scenes, and is non-monotonic by design. Alongside the score it reports a bucket (HIGH/MID/LOW/FIXATED), a mismatch type, and a transition pattern from {echo_follow, bridge, contradiction, displacement, avoidance, fixation}, which scene access consumes (Sect. 3.2). The engine does not judge; it observes and reports.

4.2 Contamination: Drift and Fixation

The contamination vector measures two *separate* modes of departure, each as an exponentially smoothed axis in $[0, 1]$ updated from the engine's per-turn output. *Drift* is directional departure: its per-turn signal is

$$\text{drift}_t = 0.45\,(1 - \text{level}) + 0.35\,(1 - \text{shape}) + 0.20\,b_{\text{mismatch}}, \tag{4}$$

where $b_{\text{mismatch}} \in [0, 1]$ weights the reported mismatch type (emotion mismatch 1.0, attribution mismatch 0.7, target displacement 0.6). *Fixation* is over-staying on one emotion or attribution:

$$\text{fix}_t = 0.55\,f_{\text{sim}} + 0.25\,b_{\text{align}} + 0.20\,b_{\text{pattern}}, \tag{5}$$

where f_{sim} is the mean pairwise cosine among the last three participant states, b_{align} rises linearly from alignment 0.55 to 1.0, and b_{pattern} is 1.0 for the *fixation* pattern and 0.5 for *echo_follow*. Each axis is updated as $\alpha\,\text{signal}_t + (1-\alpha)\,\text{axis}_{t-1}$. The dominant stage is declared *hypercompletion* when fixation ≥ 0.65 and exceeds drift, and *biased inclination* when drift ≥ 0.35. The full three-signal fixation specification (similarity, attribution repetition, exploration rate) is only partially implemented; the current runtime uses the similarity signal alone.

Two axes are needed because the same total departure can feel entirely different: drift-dominant play "wanders off onto another road", fixation-dominant play "gets stuck on one point and repeats". Rendering decisions—which biased stage of a scene's text is shown, when a character's monologue is triggered—reference the two axes independently.

4.3 Declared Limits

(1) Scene emotion distributions come from author self-report, alone or with AI assistance; convergent validity against independent raters is unmeasured. (2) Participant input is discrete text or choices, not a continuous physiological signal. (3) There is no ground truth for a "correct" trajectory; the metrics measure similarity and mode of departure, not accuracy.

5 Evaluation

5.1 Persona Simulation

Fifteen synthetic participants were driven by an LLM on top of Big Five backbones stratified from a public IPIP-NEO response corpus (N = 307,313) [9, 11]. On a single ten-scene memory they produced 193 plays (seed 42; two to four visits per persona). The measured quantity is the *per-scene alignment score*, the level component of Sect. 4.1: the cosine similarity between the persona's emotion distribution and the scene's original distribution. The LLM's own self-reported alignment was also logged, as a comparison signal only.

Table 2. Correlation between Big Five trait and mean per-scene alignment ($n = 15$ personas).

Trait	r	**Reading**
Openness	**0.634**	significant; strongest, unanticipated
Agreeableness	**0.590**	significant; as predicted
Extraversion	**0.549**	significant
Conscientiousness	0.192	not significant
Neuroticism	0.131	not significant

Distribution. Per-scene alignment had mean 0.809, SD 0.149, range 0.254–0.986. Mismatch was flagged on 97.4% of scene-plays, with *target_displacement* dominant (82.4%). Self-reported alignment collapsed onto three values (71.0% of cases), confirming that alignment must be computed from distributions rather than asked.

H1: personality discriminates alignment. Table 2 gives Pearson correlations between each Big Five trait and mean alignment across the 15 personas ($|r| \geq 0.51$ corresponds to $p < .05$). Openness, Agreeableness, and Extraversion predicted alignment; Conscientiousness and Neuroticism did not. Openness as the strongest predictor was not anticipated.

H2: extreme personas form the tails. The cynical persona (low Agreeableness, low Conscientiousness) ranked last (0.638) and produced the low tail. The extreme-optimist persona, designed to fail at empathising with the memory's shadow, ranked seventh (0.840): negative extremes are simulated, but *empathic failure is not*. This asymmetry is a property of the instrument.

H3: ceiling bias. All fifteen personas averaged above 0.64, and no scene-play fell below 0.25. LLM-simulated readers over-resonate: sampling personality from a real distribution does not remove the upward bias introduced at the response-generation step. The instrument is therefore valid for *relative* comparison but ceiling-biased in *absolute* distribution. We read this as a measured boundary rather than a failure.

5.2 Human Pilot

In a closed alpha (August 2026) three participants completed one run each of a second authored memory, yielding 21 scene-plays. The formula is identical to Sect. 5.1; values stored by the live system were recomputed offline and matched in all 21 cases. Human emotion distributions are extracted by an LLM from the participant's free-text continuation, whereas persona distributions are produced directly by the role-playing LLM; both pass through an LLM but from different input modalities.

Table 3. Per-scene alignment, human pilot versus persona simulation (same formula).

	Human pilot ($n = 21$)	**Persona sim.** ($n = 193$)
Mean	0.517	0.809
SD	0.211	0.149
Range	0.114–0.781	0.254–0.986
Share < 0.42	28.6%	3.1%
Share < 0.25	**14.3%**	**0.0%**




Fig. 2. Per-scene alignment distributions under the same formula. Top: persona simulation, no case below 0.25. Bottom: human pilot, 14.3% below 0.25. The low tail the simulation could not reproduce is present in human data.

Three things are observed (Table 3, Fig. 2). *First, the low tail is real.* Sect. 5.1 reported the absence of a tail below 0.25 as an assumption about human readers; 14.3% of human scene-plays fell below it (minimum 0.114), against none of 193 simulated. This is the first human signal consistent with the ceiling-bias boundary. *Second, dispersion is wider.* The human SD (0.211) is 1.4× the simulation's, and the three run means (0.633, 0.522, 0.456) sit at distinct heights. *Third, path divergence was observed in human trajectories* (Fig. 3). The three scene sequences share their first three visits and diverge at the fourth. We read the shared prefix as a consequence of design rather than a defect: the shape factor activates only from the third scene, so trajectory-based access has a warm-up interval. Whether the prefix length coincides with shape activation is testable once more runs accumulate.




Fig. 3. Scene sequences of the three pilot participants. The first three visits coincide; divergence begins at the fourth visit, with no authored branch in the data. Overlapping segments are offset vertically by a few pixels.

What this does not claim. The pilot was collected on a *different* memory from the simulation, so part of the 0.292 mean gap may be a work effect; until same-work human data exist the comparison is valid only for distribution shape (tail and dispersion). Mismatch types were excluded because the two populations used different classifiers. $n = 3$ is a convenience sample without ethics-board review; it is a directional signal, not a statistical claim.

6 Limitations and Future Work

Scene emotion distributions rest on author self-report and need cross-author or independent-rater validation. The fixation composite is partially implemented; results labelled FIXATED currently reflect the similarity signal alone. LLM personas import the LLM's affective biases, which multi-model comparison or human calibration must bound. The contact threshold is heuristic and has no sensitivity analysis. Finally, some authored turning points are hard to induce by emotional distance alone; an author-side "port" mechanism is being designed within a budget of roughly 15% of scenes so that the engine is not reduced to decoration.

Next steps are (i) a human study ($N = 30$–50) on the same memory as the simulation, testing the two pilot contrasts—the low tail and the 1.4× dispersion—while removing the work confound; (ii) tracking alignment, drift, and fixation *after* a participant is exposed to a trajectory bridge, to measure whether bridges alter later trajectories; and (iii) cross-work replication, to separate whether the 82.4% dominance of *target_displacement* is driven by the memory's topic or by classifier bias.

Emotional input is sensitive data. Authors consent at recording time to their fragments being exposed to later participants; a filter removes personally identifying content from exposed fragments; trigger-word handling escalates over turns rather than blocking outright; and bridges are traceable to a run identifier internally but never rendered with any author identity.

7 Conclusion

Interactive narrative has long promised a different experience to every participant; few tools say what that difference *is* in emotional terms. We presented a working system in which the participant's emotional trajectory, not a branching graph, determines scene access; a real-time alignment metric that compares the shape of emotional change; a contamination vector that separates drift from fixation; and a mechanism that turns contact runs into interpretive fragments for later participants. A 193-play simulation established internal discriminability and the instrument's ceiling bias; a 21-scene-play human pilot showed the tail and dispersion the simulation lacked, and three readers walking different scene sequences with no authored branch. What we offer is not a theory but a measuring device, and an environment in which what it measures is what is rendered.

References

1. Anderson, C., Keltner, D., John, O.P.: Emotional convergence between people over time. Journal of Personality and Social Psychology **84**(5), 1054–1068 (2003)
2. Bartlett, F.C.: Remembering: A Study in Experimental and Social Psychology. Cambridge University Press (1932)
3. Butler, E.A.: Temporal interpersonal emotion systems: The "TIES" that form relationships. Personality and Social Psychology Review **15**(4), 367–393 (2011)
4. Butler, E.A.: Emotions are temporal interpersonal systems. Current Opinion in Psychology **17**, 129–134 (2017)
5. Butler, E.A., Guan, J., Predoehl, A., Brau, E., Simek, K., Barnard, K.: Computational temporal interpersonal emotion systems. In: Vallacher, R.R., Read, S.J., Nowak, A. (eds.) Computational Social Psychology, chap. 7. Routledge (2017)
6. Evans, R., Short, E.: Versu—a simulationist storytelling system. IEEE Transactions on Computational Intelligence and AI in Games **6**(2), 113–130 (2014)
7. FromSoftware: Dark souls. Video game, Namco Bandai Games (2011)
8. Garbe, J., Kreminski, M., Samuel, B., Wardrip-Fruin, N., Mateas, M.: StoryAssembler: An engine for generating dynamic choice-driven narratives. In: Proceedings of the 14th International Conference on the Foundations of Digital Games (FDG 2019). pp. 24:1–24:10. ACM (2019)
9. Goldberg, L.R.: A broad-bandwidth, public domain, personality inventory measuring the lower-level facets of several five-factor models. In: Mervielde, I., Deary, I., De Fruyt, F., Ostendorf, F. (eds.) Personality Psychology in Europe, vol. 7, pp. 7–28. Tilburg University Press (1999)
10. Hirst, W., Echterhoff, G.: Remembering in conversations: The social sharing and reshaping of memories. Annual Review of Psychology **63**, 55–79 (2012)

11. Johnson, J.A.: Measuring thirty facets of the Five Factor Model with a 120-item public domain inventory: Development of the IPIP-NEO-120. Journal of Research in Personality **51**, 78–89 (2014)
12. Loftus, E.F., Palmer, J.C.: Reconstruction of automobile destruction: An example of the interaction between language and memory. Journal of Verbal Learning and Verbal Behavior **13**(5), 585–589 (1974)
13. Mateas, M., Stern, A.: Structuring content in the Façade interactive drama architecture. In: Proceedings of the First AAAI Conference on Artificial Intelligence and Interactive Digital Entertainment (AIIDE 2005). pp. 93–98 (2005)
14. Murray, J.H.: Hamlet on the Holodeck: The Future of Narrative in Cyberspace. Free Press, New York (1997)
15. Nader, K., Schafe, G.E., LeDoux, J.E.: Fear memories require protein synthesis in the amygdala for reconsolidation after retrieval. Nature **406**(6797), 722–726 (2000)
16. Reagan, A.J., Mitchell, L., Kiley, D., Danforth, C.M., Dodds, P.S.: The emotional arcs of stories are dominated by six basic shapes. EPJ Data Science **5**(1), 31 (2016)
17. Riedl, M.O., Bulitko, V.: Interactive narrative: An intelligent systems approach. AI Magazine **34**(1), 67–77 (2013)
18. Russell, J.A., Mehrabian, A.: Evidence for a three-factor theory of emotions. Journal of Research in Personality **11**(3), 273–294 (1977)
19. Thue, D., Bulitko, V., Spetch, M., Wasylishen, E.: Interactive storytelling: A player modelling approach. In: Proceedings of the Third AAAI Conference on Artificial Intelligence and Interactive Digital Entertainment (AIIDE 2007). pp. 43–48 (2007)
20. Warriner, A.B., Kuperman, V., Brysbaert, M.: Norms of valence, arousal, and dominance for 13,915 English lemmas. Behavior Research Methods **45**(4), 1191–1207 (2013)
21. Watson, D., Clark, L.A., Tellegen, A.: Development and validation of brief measures of positive and negative affect: The PANAS scales. Journal of Personality and Social Psychology **54**(6), 1063–1070 (1988)
22. Weyhrauch, P.: Guiding Interactive Drama. Ph.D. thesis, Carnegie Mellon University (1997)