ECE/CS 472/572:
Special Topics Part III:
GPU Architecture Introduction

Prof. Lizhong Chen

Spring 2019

GPU: System Organization

- Nvidia DGX-1 High-performance computing (HPC) sever

http://www.anandtech.com/show/10229/nvidia-announces-dgx1-server

GPU: System Organization

- Nvidia DGX-1 with panel open



http://www.anandtech.com/show/10229/nvidia-announces-dgx1-server

GPU: System Organization

- Inside Nvidia DGX-1



http://www.anandtech.com/show/10229/nvidia-announces-dgx1-server

GPU: System Organization

- Tesla P100 in Nvidia DGX-1



http://www.anandtech.com/show/10229/nvidia-announces-dgx1-server

NVIDIA Tesla GP100



- 6 GPCs
- 30 TPCs
- 60 SMs
- 3840 Cores
- 240 Tex
- 8 MCs
  - 4096-bit

NVIDIA Telsa GP100 SM

- 64 FP32 cores
  - Supports 16-bit FP
- 32 FP64 cores
- 2 32K 32-bit Registers
- Separate shared mem.
- Unified Texture/L1 $

GPUs Everywhere

- Many of the top-ranked supercomputers are based on GPU
  - The World #1 supercomputer is powered by NVIDIA GPU



GPU Computing: Past, Present and Future, David Luebke, NVIDIA

But Why are GPUs Everywhere?

- It is the performance/Watt metric
  - Mobile computers, Supercomputers, Laptops: Share power agony



GPU Computing: Past, Present and Future, David Luebke, NVIDIA

GPU: Initially for Graphics

- Take a scene and project on a screen
  - How does each polygon translate into a screen pixel



Image credit: Henrik Wann Jensen

http://www.cs.cmu.edu/afs/cs/academic/class/15869-f11/www/lectures/01_intro.pdf

Graphics-based GPU Pipeline (before 2006)



GPU Pipeline Functions

- Vector Shader : Takes as input vectors given in 3D format (X,Y,Z) and projects to a 2D space
- Pixel Shader: Takes each projected point in 2D space and puts texture, color and depth for each point
  - Texture mapping: Adding an image on top of a scene
  - Depth mapping: Shows which objects will obscure other objects



Example Image: Before and After Texture Mapping



Example Image: Z-Buffer Representation of Image

- Geometry Shaders: Operates directly on graphics primitives, such as lines, triangles (as opposed to pixels)

Doggett, M., "Texture Caches," *Micro, IEEE* , vol.32, no.3, pp.136,141, May-June 2012
http://www.felixgers.de/teaching/jogl/depthbufferALgo.html

Need for Unified Shader



GPU Architecture: Implications & Trends D. Luebke, Nvidia

Resource Balancing Unified Shader



GPU Pipeline evolution

Before 2006

- Processor per function



After 2006

- Unified Shader Model(GeForce 8 Series)
- Any work can be performed on any shader core → High performance computing



Unified Shader Model



Unified Shader Model



Multiple Contexts(Thread groups) can be interleavingly scheduled
→ Can hide stall times



GPU vs CPU

Complex OoO CPU



GPU (Nvidia FERMI)



512 CUDA cores

http://techreport.com/review/17670/nvidia-fermi-gpu-architecture-revealed

Basic idea of high performance GPU

- Many simple cores
  - No fancy Branch prediction
  - No Complex O-o-O control logic
  - No memory prefetcher
  - No cache coherence
  - . . .
- Unified shader cores
  - Sharing instruction stream across groups of fragments
- Stall latency hiding
  - When a group stalls, work on another group