

Supplementary Materials for: Predicting the long-term impact of AI assistants on collective intelligence

Jaeseung Kim¹ Sang Woo Park^{1,2,*}

¹ School of Biological Sciences, Seoul National University, Seoul, Korea

² Institute for Data Innovation in Science, Seoul National University, Seoul, Korea

*Corresponding author: sangwoopark@snu.ac.kr

Materials and Methods

Prediction target

Following previous models of CI, we model the prediction target as a linear combination of M independent causal factors (Hong et al., 2012; Mann and Helbing, 2017; Wang et al., 2025):

$$Y = \alpha_0 + \alpha_1 X_1 + \cdots + \alpha_M X_M, \quad (\text{S1})$$

where the coefficient α_i determines the magnitude and direction of the effect of factor i , and α_0 represents a global intercept. Each causal factor X_i is modeled as an independent Gaussian random variable with mean zero and standard deviation σ_i .

Players

We consider a well-mixed population $\mathcal{N}$ consisting of N players engaged in a prediction task (Wang et al., 2025). In the absence of AI assistance, the strategy of player A is characterized by two variables: interest e_A and belief c_A . Player A observes the causal factor X_{e_A} and makes a prediction by multiplying the observed factor value by their belief:

$$Y_A = c_A X_{e_A}, \quad (\text{S2})$$

where e_A can take an integer value from 0 to M . When $e_A = 0$, the player does not observe any causal factor and instead makes a constant prediction based solely on their belief. We refer to this as a stubborn strategy because the player's prediction does not respond to the realized values of the causal factors. For notational convenience, we assume that $X_0 = 1$.

When the group is assisted by AI, each player's strategy additionally includes reliance on AI, denoted by β_A . We assume that each player consults the AI independently and revises their prediction by taking a weighted average of their own prediction and the AI-generated prediction:

$$Y_A^{\text{re}} = \beta_A Y_A^{\text{AI}} + (1 - \beta_A) Y_A, \quad (\text{S3})$$

where β_A ranges from 0 to 1. A value of $\beta_A = 1$ indicates complete reliance on AI, whereas $\beta_A = 0$ indicates that the player does not use the AI prediction.

AI models

We assume that the AI model has been trained on similar tasks and is therefore capable of making predictions based on causal factors. However, because the model is imperfect, its outputs are subject to systematic additive bias and stochastic error. The additive bias associated with factor i is denoted by b_i , and the stochastic error is denoted by ϵ . The AI is neither trained nor updated during the simulation, and its biases therefore remain fixed throughout the simulation. For simplicity, we assume $b_i = b$ for the main analysis for all i . The model formulation nevertheless allows biases to differ among factors.

We assume that the stochastic error follows a Gaussian distribution with mean zero and standard deviation τ . Each time a player consults the AI, an independent error is generated. Errors are therefore independent across players and across repeated consultations by the same player. Consequently, stochastic AI errors can be attenuated when independently generated predictions are aggregated across players. We therefore hold τ constant and vary the magnitude of the additive bias to manipulate the level of AI accuracy during our analyses.

We consider two extreme types of AI that differ in the amount of information available for prediction. The first is termed the Omniscient AI, which can observe all M causal factors and incorporate them into its prediction regardless of the user's interest. The prediction generated by the Omniscient AI for player A is expressed as follows:

$$Y_A^{\text{AI}} = \alpha_0 + b_0 + \alpha_1 X_1 + b_1 + \cdots + \alpha_M X_M + b_M + \epsilon. \quad (\text{S4})$$

The second is termed the Chatbot AI, which can use only the single causal factor X_{e_A} associated with the player's interest. The prediction generated by the Chatbot AI for player A is expressed as follows:

$$Y_A^{\text{AI}} = \alpha_{e_A} X_{e_A} + b_{e_A} + \epsilon. \quad (\text{S5})$$

Aggregation rules

The revised individual predictions are aggregated to form a collective prediction. We use two aggregation rules proposed in previous work (Wang et al., 2025), depending on the type of AI used by the group. First, when the group is assisted by the Omniscient AI, the AI component of each revised prediction contains information about all M factors, even though the individual's own prediction is based on only one factor. Each revised prediction can therefore be treated as an estimate of the entire target. Accordingly, we calculate the collective prediction by taking the simple average of the revised individual predictions:

$$\hat{Y}^{\text{re}} = \frac{Y_1^{\text{re}} + Y_2^{\text{re}} + \cdots + Y_N^{\text{re}}}{N}. \quad (\text{S6})$$

Second, when the group is assisted by the Chatbot AI, both the player’s initial prediction and the AI’s prediction are based on the same causal factor. Each revised prediction therefore contains information about only one factor and can be treated as an estimate of that factor’s contribution to the target. We consequently use clustering aggregation.

Clustering aggregation is performed by grouping individuals according to their interests and calculating the mean prediction within each group. The collective prediction is then obtained by summing the mean predictions of all nonempty groups:

$$\hat{Y}^{\text{re}} = \sum_{i:n_i>0} \frac{1}{n_i} \sum_{A \in \mathcal{A}_i} Y_A^{\text{re}}, \quad (\text{S7})$$

where $\mathcal{A}_i$ represents the set of players interested in factor i , and $n_i = |\mathcal{A}_i|$ represents the number of players in that set.

When the group is not assisted by AI, collective predictions are computed from the unrevised individual predictions throughout the simulation. Both simple averaging and clustering can be used in the absence of AI. For fair comparison, we use the same aggregation rule as in the corresponding AI-assisted condition.

Incentive structures

Players receive payoffs based on the underlying incentive structure. We consider seven incentive structures: feedback structure, niche-expert structure, direct intervention on AI use of these two structures, and three different balanced structures.

The feedback structure does not directly reward individuals according to their own prediction accuracy. Instead, it rewards predictions that are aligned with the residual error of the collective prediction and therefore have the potential to move the collective prediction toward the true value. Given player A ’s revised prediction Y_A^{re} and the collective prediction $\hat{Y}^{\text{re}}$, the payoff is expressed as

$$\pi_A = Y_A^{\text{re}}(Y - \hat{Y}^{\text{re}}). \quad (\text{S8})$$

The niche-expert structure assigns higher payoffs to individuals who make accurate predictions while having an underrepresented interest. Specifically, the squared prediction error of player A is weighted by $\rho_{e_A} = n_{e_A}/N$, the proportion of players interested in the same factor:

$$\pi_A = -\rho_{e_A}(Y_A^{\text{re}} - Y)^2. \quad (\text{S9})$$

Previous research has shown that these two incentive structures can produce near perfect collective accuracy through social learning, except when the niche-expert incentive is combined with simple averaging (Wang et al., 2025). They are therefore used as baseline structures for examining how AI assistance affects the emergence of CI.

99 To examine the effects of directly encouraging or discouraging AI use, we mod-
 100 ify the feedback and niche-expert structures by adding a term proportional to the
 101 player’s reliance on AI:

$$\pi_A = Y_A^{\text{re}}(Y - \hat{Y}^{\text{re}}) + \lambda\beta_A \quad (\text{S10})$$

$$\pi_A = -\rho_{e_A}(Y_A^{\text{re}} - Y)^2 + \lambda\beta_A. \quad (\text{S11})$$

102 Here, λ represents the strength of the direct incentive or penalty applied to AI use. A
 103 positive value of λ rewards AI reliance, whereas a negative value penalizes it. When
 104 $\lambda = 0$, no direct incentive or penalty is applied, and the payoff functions reduce to
 105 the original feedback and niche-expert structures.

106 The balanced structure is defined as the weighted mean of the feedback and
 107 niche-expert payoff components, with balancing weight w :

$$\pi_A = (1 - w)Y_A^{\text{re}}(Y - \hat{Y}^{\text{re}}) - w\rho_{e_A}(Y_A^{\text{re}} - Y)^2, \quad (\text{S12})$$

108 where $w \in [0, 1]$ determines the relative contribution of the feedback and niche-expert
 109 components. We set $w = 0.5$ for all analyses unless otherwise specified, such that
 110 the two components contribute equally to the balanced structure. The sensitivity of
 111 the results to w is examined in Supplementary Fig. S7.

112 To examine whether incentives based on unrevised predictions (i.e., predictions
 113 made without incorporating AI predictions) could overcome the limitations of the
 114 other incentive structures, we defined an unrevised balanced structure. The unre-
 115 vised balanced structure is defined as the arithmetic mean of the feedback structure
 116 based on the unrevised collective prediction and the niche-expert structure based on
 117 unrevised individual predictions:

$$\pi_A = \frac{Y_A(Y - \hat{Y}) - \rho_{e_A}(Y_A - Y)^2}{2}, \quad (\text{S13})$$

118 where $\hat{Y}$ is the collective prediction based on unrevised individual predictions, and
 119 $Y_A(Y - \hat{Y})$ and $-\rho_{e_A}(Y_A - Y)^2$ represent the unrevised feedback and unrevised niche-
 120 expert components, respectively.

121 We further defined a combined balanced structure as the arithmetic mean of
 122 the balanced and unrevised balanced structures, with the balancing weight set to
 123 $w = 0.5$:

$$\pi_A = \frac{Y_A^{\text{re}}(Y - \hat{Y}^{\text{re}}) - \rho_{e_A}(Y_A^{\text{re}} - Y)^2 + Y_A(Y - \hat{Y}) - \rho_{e_A}(Y_A - Y)^2}{4}. \quad (\text{S14})$$

124 Simulations

125 All simulations are conducted using an agent-based model with 50 causal factors
 126 ($M = 50$) and 10,000 players ($N = 10,000$). The parameters defining the prediction
 127 target are sampled at the beginning of the simulations and subsequently held fixed.

Coefficients α_i are sampled from a uniform distribution on $[-5, 5]$, except in the simulation presented in Figure 4, in which α_i is set to $5 - 0.2i$ for visualization. Standard deviations σ_i are sampled from a uniform distribution on $[0, 3]$.

Players’ initial strategies are also sampled from predefined probability distributions. The distribution of individual belief c_A depends on the aggregation rule. Under simple averaging, each factor’s contribution is scaled by the proportion of players interested in that factor. We therefore sample beliefs from a Gaussian distribution with mean zero and standard deviation 100, following the scaling used in previous work (Wang et al., 2025). Under clustering aggregation, beliefs are sampled from a Gaussian distribution with mean zero and standard deviation 5. Because predictions are averaged separately within each interest group and then summed, no additional scaling of c_A is required. The initial interest of each player is sampled uniformly from the integers between 0 and 50, and reliance on AI is sampled from a uniform distribution on $[0, 1]$. To account for stochastic variation, we perform 30 independent simulation replicates with randomly initialized player populations for each condition presented in the main figures.

We assume that prediction events occur on a substantially faster timescale than social learning. In each generation, we therefore calculate the expected payoff $\mathbb{E}[\pi_A]$ of each player analytically rather than explicitly sampling prediction events. The expectation is taken over the distributions of the causal factors $X_1, \dots, X_M$ and the stochastic AI error ϵ , conditional on the current population strategies and the fixed target parameters. Closed form expression of expected payoffs are derived for all incentive structures and are presented in the Supplementary Text.

Each generation consists of an expected payoff calculation followed by one opportunity for pairwise social learning. Two distinct players, A and B , are randomly sampled, and player A imitated all three strategies of player B with probability

$$\frac{1}{1 + \exp(s(\mathbb{E}[\pi_A] - \mathbb{E}[\pi_B]))}, \quad (\text{S15})$$

where s represents the strength of social learning and was set to 50 in all simulations. We introduce a mutation rate μ , such that with probability μ , player A does not imitate player B but instead redraw all strategy components from the same distributions used to initialize the population. The mutation rate is set to zero in all simulations except those presented in Supplementary Fig. S4.

Unless otherwise specified, each simulation is run for 200,000 generations. When a result is represented by a single summary value rather than as a temporal trajectory, the metric was averaged over the final 10,000 generations.

To evaluate the dynamics of collective prediction, we define six summary metrics: collective accuracy, collective bias, collective variance, counterfactual collective accuracy, interest diversity, and median reliance on AI. At each population state, expectations and variances are evaluated analytically over the distributions of the causal factors and AI errors rather than estimated from sampled prediction events. Collective bias and collective variance constitute the bias–variance decomposition of the group level collective prediction error.

169 Collective accuracy is normalized relative to the baseline prediction α_0 . A nega-
170 tive value indicates that the collective prediction performs worse than the baseline.
171 Counterfactual collective accuracy is evaluated by setting $\beta_A = 0$ while retaining the
172 evolved interests and beliefs of the AI-assisted population. In calculating interest
173 diversity, we use the convention that $\rho_i \ln \rho_i = 0$ when $\rho_i = 0$ (Table S1).

Supplementary Text

Here, we derive the expected payoffs and collective accuracy used in the simulations. We consider Omniscient AI and Chatbot AI separately because they contain different amounts of information and therefore require different aggregation rules. We then analyze the corresponding evolutionary dynamics under a deterministic large-population approximation.

Omniscient AI

We first consider Omniscient AI, which incorporates all causal factors regardless of the player's interest. We derive individual and collective predictions before calculating the expected payoffs under each incentive structure.

Model

Because Omniscient AI observes all M causal factors, its prediction for player A is given by

$$Y_A^{AI} = \alpha_0 + b_0 + \alpha_1 X_1 + b_1 + \cdots + \alpha_M X_M + b_M + \epsilon, \quad (\text{S16})$$

where b_i represent factor-specific biases and ϵ represents stochastic error, following a Gaussian distribution with mean zero and standard deviation τ . A new stochastic error is generated independently for each player and prediction event.

Let $B = \sum_{i=0}^M b_i$ denote the total additive bias. Because the true prediction target is $Y = \alpha_0 + \sum_{i=1}^M \alpha_i X_i$, the AI prediction can be written as

$$Y^{AI} = Y + B + \epsilon. \quad (\text{S17})$$

In contrast to the AI prediction, player A 's initial prediction depends only on the causal factor associated with their interest. Their initial and revised predictions are therefore given by:

$$Y_A = c_A X_{e_A} \quad (\text{S18})$$

$$Y_A^{re} = \beta_A Y^{AI} + (1 - \beta_A) Y_A \quad (\text{S19})$$

represents player A 's interest, c_A represents their belief about the effect of the corresponding factor, and β_A represents their reliance on AI. As in the main text, we set $X_0 = 1$, such that a player with $e_A = 0$ makes a constant initial prediction.

198 Aggregation

199 Because the AI component of each revised prediction contains information about all
200 M causal factors, we use simple averaging to obtain the collective prediction:

$$\hat{Y}^{re} = \frac{1}{N} \sum_{j=1}^N Y_j^{re} \quad (\text{S20})$$

$$= \frac{1}{N} \sum_{j=1}^N \{\beta_j Y^{AI} + (1 - \beta_j) Y_j\} \quad (\text{S21})$$

$$= \frac{1}{N} \sum_{j=1}^N \{\beta_j (Y + B + \epsilon_j) + (1 - \beta_j) c_j X_{e_j}\} \quad (\text{S22})$$

201 To separate the contributions of AI and the players' initial predictions, we define the
202 population's mean reliance on AI, the stochastic AI error remaining after aggregation,
203 and the aggregate contribution of initial predictions associated with each factor:

$$\bar{\beta} = \frac{1}{N} \sum_{j=1}^N \beta_j \quad (\text{S23})$$

$$\bar{\eta} = \frac{1}{N} \sum_{j=1}^N \beta_j \epsilon_j \quad (\text{S24})$$

$$\gamma_i = \frac{1}{N} \sum_{A \in \mathcal{A}_i} (1 - \beta_A) c_A \quad (\text{S25})$$

204 Here, $\bar{\beta}$ represents the mean reliance on AI, $\bar{\eta}$ represents the stochastic AI error
205 remaining after averaging, and γ_i represents the contribution of players' initial pre-
206 dictions to factor i . Using these definitions, the revised collective prediction can be
207 written as follows:

$$\hat{Y}^{re} = \bar{\beta}(Y + B) + \sum_{i=0}^M \gamma_i X_i + \bar{\eta} \quad (\text{S26})$$

208 Thus, the collective prediction consists of an AI-derived component, the contributions
209 of the players' initial predictions, and the stochastic AI error that remains after
210 aggregation.

211 Expected payoffs

212 We next derive the expected payoff under each incentive structure. Expectations are
213 taken over the distributions of the causal factors and stochastic AI errors, conditional
214 on the current population strategies and the fixed parameters of the prediction target.

215 Feedback

216 Under the feedback structure, a player's payoff depends on the alignment between
 217 their revised prediction and the residual error of the collective prediction. To express
 218 this residual, we first define the remaining error in the intercept and in the coefficient
 219 of each causal factor:

$$\delta_0 = \alpha_0 - (\bar{\beta}(\alpha_0 + B) + \gamma_0), \quad (\text{S27})$$

$$\delta_i = \alpha_i - (\bar{\beta}\alpha_i + \gamma_i), \quad (i \neq 0), \quad (\text{S28})$$

$$Y - \hat{Y}^{re} = \delta_0 + \sum_{i=1}^M \delta_i X_i - \bar{\eta}, \quad (\text{S29})$$

220 where δ_0 represents the remaining error in the intercept, whereas δ_i represents the
 221 remaining error associated with factor i . Because the causal factors and stochastic AI
 222 errors are independent and have zero mean, cross terms vanish when the expectation
 223 is taken. Substituting the revised individual prediction and collective residual into
 224 the feedback payoff gives

$$\mathbb{E}[\pi_A] = \mathbb{E}[Y_A^{re}(Y - \hat{Y}^{re})] \quad (\text{S30})$$

$$= \mathbb{E} \left[\left\{ \beta_A \alpha_0 + \beta_A \sum_{i=1}^M \alpha_i X_i + \beta_A B + \beta_A \epsilon + (1 - \beta_A) c_A X_{e_A} \right\} \right] \quad (\text{S31})$$

$$\times \left\{ \delta_0 + \sum_{i=1}^M \delta_i X_i - \bar{\eta} \right\} \quad (\text{S32})$$

$$= \beta_A \alpha_0 \delta_0 + \beta_A \sum_{i=1}^M \delta_i \alpha_i \sigma_i^2 + \beta_A B \delta_0 - \frac{1}{N} \beta_A^2 \tau^2 + (1 - \beta_A) c_A \delta_{e_A} \sigma_{e_A}^2 \quad (\text{S33})$$

$$= \beta_A \left\{ (\alpha_0 + B) \delta_0 + \sum_{i=1}^M \alpha_i \delta_i \sigma_i^2 \right\} + (1 - \beta_A) c_A \delta_{e_A} \sigma_{e_A}^2 - \frac{\beta_A^2 \tau^2}{N} \quad (\text{S34})$$

225 The first term represents the alignment between the AI-derived prediction and the
 226 collective residual, whereas the second term represents the contribution of the player's
 227 initial prediction. The final term arises because the stochastic error in player A 's AI
 228 prediction also contributes to the collective prediction. This finite-population effect
 229 decreases as population size increases.

230 Niche-expert

231 Under the niche-expert structure, the payoff is the negative squared error of the
 232 revised individual prediction, weighted by the frequency of the player's interest.
 233 Because $X_0 = 1$, a player with $e_A = 0$ makes a constant initial prediction. In this

case, the expected payoff is:

$$\mathbb{E}[\pi_A] = -\mathbb{E}[\rho_0(Y_A^{\text{re}} - Y)^2] \quad (\text{S35})$$

$$= -\mathbb{E}[\rho_0\{(\beta_A - 1)Y + \beta_A B + \beta_A \epsilon + (1 - \beta_A)c_A\}^2] \quad (\text{S36})$$

$$= -\mathbb{E}\left[\rho_0\left\{(\beta_A - 1)(\alpha_0 - c_A) + \beta_A B + (\beta_A - 1)\sum_{i=1}^M \alpha_i X_i + \beta_A \epsilon\right\}^2\right] \quad (\text{S37})$$

$$= -\rho_0\left\{(1 - \beta_A)^2(\alpha_0 - c_A)^2 - 2\beta_A(1 - \beta_A)(\alpha_0 - c_A)B + \beta_A^2 B^2\right. \quad (\text{S38})$$

$$\left. + (1 - \beta_A)^2 \sum_{i \neq 0} \alpha_i^2 \sigma_i^2 + \beta_A^2 \tau^2\right\} \quad (\text{S39})$$

For a player with $e_A \neq 0$, the initial prediction instead depends on the observed value of factor X_{e_A} . The expected payoff is therefore:

$$\mathbb{E}[\pi_A] = -\mathbb{E}[\rho_{e_A}(Y_A^{\text{re}} - Y)^2] \quad (\text{S40})$$

$$= -\mathbb{E}[\rho_{e_A}\{(\beta_A - 1)Y + \beta_A B + \beta_A \epsilon + (1 - \beta_A)c_A X_{e_A}\}^2] \quad (\text{S41})$$

$$= -\mathbb{E}\left[\rho_{e_A}\left\{(\beta_A - 1)\alpha_0 + \beta_A B\right. \quad (\text{S42})$$

$$\left. + (\beta_A - 1)(\alpha_{e_A} - c_A)X_{e_A} + (\beta_A - 1)\sum_{i \neq e_A, 0} \alpha_i X_i + \beta_A \epsilon\right\}^2\right] \quad (\text{S43})$$

$$= -\rho_{e_A}\left\{(1 - \beta_A)^2 \alpha_0^2 - 2\beta_A(1 - \beta_A)\alpha_0 B\right. \quad (\text{S44})$$

$$+ \beta_A^2 B^2 + (1 - \beta_A)^2(\alpha_{e_A} - c_A)^2 \sigma_{e_A}^2 \quad (\text{S45})$$

$$\left. + (1 - \beta_A)^2 \sum_{i \neq e_A, 0} \alpha_i^2 \sigma_i^2 + \beta_A^2 \tau^2\right\} \quad (\text{S46})$$

These expressions separate the contributions of the player's belief, the unobserved causal factors, systematic AI bias, and stochastic AI error. Increasing reliance on AI reduces the contribution of errors in the player's initial prediction but increases their exposure to AI bias and stochastic error.

Incentivizing or penalizing AI use

Direct incentives add the term $\lambda\beta_A$ to either the feedback or niche-expert payoff. Because this term is fixed conditional on the player's strategy, its expectation is simply $\lambda\beta_A$. The expected payoffs therefore become

$$\mathbb{E}[\pi_{A, \text{Feedback}}] = \mathbb{E}\left[Y_A^{\text{re}}(Y - \hat{Y}^{\text{re}}) + \lambda\beta_A\right] = \mathbb{E}\left[Y_A^{\text{re}}(Y - \hat{Y}^{\text{re}})\right] + \lambda\beta_A, \quad (\text{S47})$$

$$\mathbb{E}[\pi_{A, \text{Niche-expert}}] = \mathbb{E}\left[-\rho_{e_A}(Y_A^{\text{re}} - Y)^2 + \lambda\beta_A\right] = -\mathbb{E}\left[\rho_{e_A}(Y_A^{\text{re}} - Y)^2\right] + \lambda\beta_A. \quad (\text{S48})$$

Thus, a positive value of λ increases the payoff of strategies with greater reliance on AI, whereas a negative value favors strategies with lower reliance.

247 Expected accuracy

248 Using the residual defined above, the mean squared error of the revised collective
249 prediction is:

$$\mathbb{E}[(Y - \alpha_0)^2] = \mathbb{E} \left[\left(\alpha_0 + \sum_{i=1}^M \alpha_i X_i - \alpha_0 \right)^2 \right] = \sum_{i=1}^M \alpha_i^2 \sigma_i^2 \quad (\text{S49})$$

$$\mathbb{E}[(Y - \hat{Y}^{re})^2] = \mathbb{E} \left[\left(\delta_0 + \sum_{i=1}^M \delta_i X_i - \bar{\eta} \right)^2 \right] = \delta_0^2 + \sum_{i=1}^M \delta_i^2 \sigma_i^2 + \frac{\tau^2}{N^2} \sum_{j=1}^N \beta_j^2 \quad (\text{S50})$$

250 The expected collective accuracy is therefore

$$R = 1 - \frac{\mathbb{E}[(Y - \hat{Y}^{re})^2]}{\mathbb{E}[(Y - \alpha_0)^2]} \quad (\text{S51})$$

$$= 1 - \frac{\delta_0^2 + \sum_{i=1}^M \delta_i^2 \sigma_i^2 + \frac{\tau^2}{N^2} \sum_{j=1}^N \beta_j^2}{\sum_{i=1}^M \alpha_i^2 \sigma_i^2} \quad (\text{S52})$$

251 The collective prediction error consists of the squared error in the intercept, the re-
252 maining error associated with each causal factor, and the stochastic AI error remain-
253 ing after averaging across players. Counterfactual collective accuracy is obtained
254 from the same expression by setting $\beta_A = 0$ for all players while retaining their
255 evolved interests and beliefs.

256 Chatbot AI

257 Unlike Omniscient AI, Chatbot AI use only the causal factor associated with each
258 player's interest. This causes the information contained in AI predictions to depend
259 directly on the distribution of interests in the population. Here, we derive the collec-
260 tive prediction, expected payoffs, and expected collective accuracy under this form
261 of AI assistance.

262 Model

263 The prediction generated by Chatbot AI for player A depends on the causal factor
264 associated with the player's interest:

$$Y_A^{AI} = \alpha_{e_A} X_{e_A} + b_{e_A} + \epsilon, \quad (\text{S53})$$

265 where b_{e_A} represents factor-specific additive bias, and ϵ represents stochastic error.
266 The stochastic error follows a Gaussian distribution with mean zero and standard

267 deviation τ and is generated independently across players and prediction events.
 268 Player A's initial and revised predictions can be then written as follows:

$$Y_A = c_A X_{e_A} \quad (\text{S54})$$

$$Y_A^{re} = \beta_A Y_A^{AI} + (1 - \beta_A) Y_A \quad (\text{S55})$$

269 Here, c_A represents player A's belief about the effect of their focal factor, e_A repre-
 270 sents their interest, and β_A represents their reliance on AI. Thus, the revised predic-
 271 tion remains specific to the single factor associated with the player's interest.

272 Aggregation

273 Because both the player's initial prediction and the Chatbot AI prediction contain
 274 information about the same causal factor, we use clustering aggregation. Revised
 275 predictions are first averaged among players interested in the same factor and then
 276 summed across represented interests:

$$\hat{Y}^{re} = \sum_{i=0}^M \frac{1}{n_i} \sum_{A \in \mathcal{A}_i} Y_A^{re} \quad (\text{S56})$$

$$= \sum_{i=0}^M \frac{1}{n_i} \sum_{A \in \mathcal{A}_i} \{ \beta_A Y_A^{AI} + (1 - \beta_A) Y_A \} \quad (\text{S57})$$

$$= \sum_{i=0}^M \frac{1}{n_i} \sum_{A \in \mathcal{A}_i} [\{ \beta_A \alpha_{e_A} + (1 - \beta_A) c_A \} X_{e_A} + \beta_A b_{e_A} + \beta_A \epsilon_A], \quad (\text{S58})$$

277 where $\mathcal{A}_i$ is the set of players interested in factor i , and $n_i = |\mathcal{A}_i|$ is the number of
 278 players in that set.

279 To simplify the collective prediction, we define the effective coefficient, weighted
 280 AI bias, and stochastic error associated with each interest group:

$$\tilde{c}_i = \frac{1}{n_i} \sum_{A \in \mathcal{A}_i} \{ \beta_A \alpha_{e_A} + (1 - \beta_A) c_A \}, \quad (\text{S59})$$

$$\tilde{B}_i = \frac{1}{n_i} \sum_{A \in \mathcal{A}_i} \beta_A b_{e_A}, \quad (\text{S60})$$

$$\bar{B} = \sum_{i=0}^M \tilde{B}_i, \quad (\text{S61})$$

$$\tilde{\eta}_i = \frac{1}{n_i} \sum_{A \in \mathcal{A}_i} \beta_A \epsilon_A, \quad (\text{S62})$$

$$\bar{\eta} = \sum_{i=0}^M \tilde{\eta}_i, \quad (\text{S63})$$

where $\tilde{c}_i$ represents the mean effective coefficient for factor i after AI assistance, whereas $\tilde{B}_i$ and $\tilde{\eta}_i$ represent its systematic and stochastic error components. Thus, the collective prediction can be written as:

$$\hat{Y}^{re} = \sum_{i \in \mathcal{I}} \tilde{c}_i X_i + \bar{B} + \bar{\eta}, \quad (\text{S64})$$

where $\mathcal{I} = \{i \in \{0, \dots, M\} | n_i > 0\}$ denotes the set of represented interests.

Expected payoffs

We next derive the expected payoff under each incentive structure. Expectations are taken over the causal factors and stochastic AI errors, conditional on the current population strategies and the fixed parameters of the prediction target.

Feedback

Under the feedback structure, players are rewarded according to whether their revised predictions reduce the error in the collective prediction. We therefore define the remaining errors in the intercept and factor-specific coefficients as

$$\delta_0 = \alpha_0 - \tilde{c}_0 - \bar{B}, \quad (\text{S65})$$

$$\delta_i = \alpha_i - \tilde{c}_i, \quad (i \neq 0), \quad (\text{S66})$$

$$Y - \hat{Y}^{re} = \delta_0 + \sum_{i=1}^M \delta_i X_i - \bar{\eta}, \quad (\text{S67})$$

where δ_0 includes the remaining error in the intercept and the total additive AI bias, whereas δ_i measures the remaining error in the coefficient of factor i . Because the causal factors and stochastic errors are independent and have zero mean, substituting the revised individual prediction into the feedback payoff gives

$$\mathbb{E}[\pi_A] = \mathbb{E}[Y_A^{re}(Y - \hat{Y}^{re})] \quad (\text{S68})$$

$$= \mathbb{E}[\{(\beta_A \alpha_{e_A} + (1 - \beta_A) c_A) X_{e_A} + \beta_A b_{e_A} + \beta_A \epsilon\} \quad (\text{S69})$$

$$\times \left\{ \delta_0 + \sum_{i=1}^M \delta_i X_i - \bar{\eta} \right\}] \quad (\text{S70})$$

$$= \{\beta_A \alpha_{e_A} + (1 - \beta_A) c_A\} \delta_{e_A} \sigma_{e_A}^2 + \beta_A b_{e_A} \delta_0 - \frac{1}{n_{e_A}} \beta_A^2 \tau^2 \quad (\text{S71})$$

Thus, the expected feedback payoff depends on the remaining collective error associated with the player's interest, the contribution of factor-specific AI bias to the intercept error, and the player's contribution to the stochastic error of their interest group.

301 Niche-expert

302 Under the niche-expert structure, the negative squared error of each revised indi-
 303 vidual prediction is weighted by the frequency of the player's interest. We consider
 304 $e_A = 0$ separately because these players make constant predictions rather than factor-
 305 dependent predictions. When $e_A = 0$, the expected payoff is

$$\mathbb{E}[\pi_A] = -\mathbb{E}[\rho_0(Y_A^{re} - Y)^2] \quad (\text{S72})$$

$$= -\mathbb{E} \left[\rho_0 \left[\left\{ \beta_A \alpha_0 + (1 - \beta_A) c_A \right\} + \beta_A b_0 + \beta_A \epsilon - \alpha_0 - \sum_{i=1}^M \alpha_i X_i \right]^2 \right] \quad (\text{S73})$$

$$= -\rho_0 \left\{ (1 - \beta_A)^2 (c_A - \alpha_0)^2 + 2(1 - \beta_A)(c_A - \alpha_0) \beta_A b_0 + \beta_A^2 b_0^2 \right. \quad (\text{S74})$$

$$\left. + \sum_{i \neq 0} \alpha_i^2 \sigma_i^2 + \beta_A^2 \tau^2 \right\} \quad (\text{S75})$$

306 When $e_A \neq 0$, the player's prediction varies with their focal causal factor. The
 307 expected payoff is then

$$\mathbb{E}[\pi_A] = -\mathbb{E}[\rho_{e_A}(Y_A^{re} - Y)^2] \quad (\text{S76})$$

$$= -\mathbb{E}[\rho_{e_A} [\left\{ \beta_A \alpha_{e_A} + (1 - \beta_A) c_A \right\} X_{e_A} \quad (\text{S77})$$

$$+ \beta_A b_{e_A} + \beta_A \epsilon - \alpha_0 - \sum_{i=1}^M \alpha_i X_i]^2] \quad (\text{S78})$$

$$= -\rho_{e_A} \left\{ (1 - \beta_A)^2 (c_A - \alpha_{e_A})^2 \sigma_{e_A}^2 + \sum_{i \neq e_A, 0} \alpha_i^2 \sigma_i^2 \right. \quad (\text{S79})$$

$$\left. + \alpha_0^2 + \beta_A^2 b_{e_A}^2 - 2\alpha_0 \beta_A b_{e_A} + \beta_A^2 \tau^2 \right\} \quad (\text{S80})$$

308 In both cases, the expected squared error consists of the mismatch between the
 309 player's belief and the true coefficient, contributions from causal factors omitted
 310 from the individual prediction, factor-specific AI bias, and stochastic AI error. The
 311 niche-expert weight ρ_{e_A} scales these errors according to the frequency of the player's
 312 interest.

313 Incentivizing or penalizing AI use

314 Directly incentivizing or penalizing AI use adds the term $\lambda \beta_A$ to the player's payoff.
 315 Because this term is fixed conditional on the player's strategy, it can be taken outside

the expectation. The expected payoffs are therefore

$$\mathbb{E}[\pi_{A,Feedback}] = \mathbb{E} \left[Y_A^{\text{re}}(Y - \hat{Y}^{\text{re}}) + \lambda\beta_A \right] \quad (\text{S81})$$

$$= \mathbb{E} \left[Y_A^{\text{re}}(Y - \hat{Y}^{\text{re}}) \right] + \lambda\beta_A, \quad (\text{S82})$$

$$\mathbb{E}[\pi_{A,Niche-expert}] = \mathbb{E} \left[-\rho_{e_A}(Y_A^{\text{re}} - Y)^2 + \lambda\beta_A \right] \quad (\text{S83})$$

$$= -\mathbb{E} \left[\rho_{e_A}(Y_A^{\text{re}} - Y)^2 \right] + \lambda\beta_A. \quad (\text{S84})$$

Balanced

Under the balanced structure, the payoff corresponds to the weighted mean of the feedback and niche-expert payoff components, with balancing weight w :

$$\mathbb{E}[\pi_A] = \mathbb{E} \left[(1 - w)Y_A^{\text{re}}(Y - \hat{Y}^{\text{re}}) - w\rho_{e_A}(Y_A^{\text{re}} - Y)^2 \right] \quad (\text{S85})$$

$$= (1 - w)\mathbb{E} \left[Y_A^{\text{re}}(Y - \hat{Y}^{\text{re}}) \right] - w\mathbb{E} \left[\rho_{e_A}(Y_A^{\text{re}} - Y)^2 \right] \quad (\text{S86})$$

The expected payoff under the balanced structure can therefore be calculated directly from the feedback and niche-expert payoffs derived above.

Unrevised balanced

The unrevised feedback and niche-expert components are identical to those in the model without AI assistance (Wang et al., 2025). We therefore calculate their expected payoffs following the derivations in the original model and take their arithmetic mean:

$$\mathbb{E}[\pi_A] = \frac{1}{2}\mathbb{E} \left[Y_A(Y - \hat{Y}) - \rho_{e_A}(Y_A - Y)^2 \right]. \quad (\text{S87})$$

Combined balanced

Under the combined balanced structure, the payoff is the arithmetic mean of the balanced and unrevised balanced payoffs, with $w = 0.5$ for both balanced components. Its expected payoff is therefore

$$\mathbb{E}[\pi_A] = \frac{1}{4}\mathbb{E} \left[Y_A^{\text{re}}(Y - \hat{Y}^{\text{re}}) - \rho_{e_A}(Y_A^{\text{re}} - Y)^2 \right. \quad (\text{S88})$$

$$\left. + Y_A(Y - \hat{Y}) - \rho_{e_A}(Y_A - Y)^2 \right]. \quad (\text{S89})$$

The expected payoff under the combined balanced structure can therefore be calculated directly from the revised and unrevised feedback and niche-expert payoffs derived above.

334 Expected accuracy

335 Finally, we derive the expected collective accuracy under clustering aggregation.
 336 The intercept α_0 serves as the baseline prediction. Because the causal factors are
 337 independent and have mean zero, its expected squared error is

$$\mathbb{E}[(Y - \alpha_0)^2] = \mathbb{E} \left[\left(\alpha_0 + \sum_{i=1}^M \alpha_i X_i - \alpha_0 \right)^2 \right] = \sum_{i=1}^M \alpha_i^2 \sigma_i^2 \quad (\text{S90})$$

338 Using the expression for the collective residual above, the expected squared error of
 339 the revised collective prediction is

$$\mathbb{E}[(Y - \hat{Y}^{\text{re}})^2] = \mathbb{E} \left[\left(\delta_0 + \sum_{i=1}^M \delta_i X_i - \bar{\eta} \right)^2 \right] = \delta_0^2 + \sum_{i=1}^M \delta_i^2 \sigma_i^2 + \sum_{i=0}^M \frac{\tau^2}{n_i^2} \sum_{A \in \mathcal{A}_i} \beta_A^2 \quad (\text{S91})$$

340 The first two terms represent squared errors in the intercept and factor-specific coef-
 341 ficients. The final term represents the stochastic AI error remaining after predictions
 342 are averaged within each interest group. Thus, stochastic error has a larger effect
 343 when an interest is represented by fewer individuals. Normalizing this error relative
 344 to the baseline gives:

$$R = 1 - \frac{\mathbb{E}[(Y - \hat{Y}^{\text{re}})^2]}{\mathbb{E}[(Y - \alpha_0)^2]} \quad (\text{S92})$$

$$= 1 - \frac{\delta_0^2 + \sum_{i=1}^M \delta_i^2 \sigma_i^2 + \sum_{i=0}^M \frac{\tau^2}{n_i^2} \sum_{A \in \mathcal{A}_i} \beta_A^2}{\sum_{i=1}^M \alpha_i^2 \sigma_i^2} \quad (\text{S93})$$

345 Here, $R = 1$ represents perfect collective prediction, $R = 0$ represents performance
 346 equal to the baseline, and $R < 0$ represents performance worse than the baseline.

347 Evolutionary dynamics

348 Following previous work (Wang et al., 2025; Taylor and Jonker, 1978; Traulsen et al.,
 349 2005), we use replicator dynamics as a deterministic large-population approximation
 350 to characterize equilibrium states and their local stability. The agent-based sim-
 351 ulations themselves follow the Fermi imitation rule defined above. At equal-payoff
 352 stationary states, the replicator and Fermi formulations imply the same local invasion
 353 directions for any finite selection strength $s > 0$, although their transient dynamics
 354 need not coincide. We focus on the feedback and niche-expert structures, for which
 355 the long-term dynamics can be characterized analytically. The direct interventions
 356 on AI use and the balanced structure are examined through simulations.

Let λ denote a strategy, p_λ its frequency, and $u_\lambda = \mathbb{E}(\pi_\lambda)$ its expected payoff. Then, the corresponding replicator equation can be written as:

$$\frac{dp_\lambda}{dt} = p_\lambda(u_\lambda - \bar{u}), \quad (\text{S94})$$

where $\bar{u} = \sum_\lambda p_\lambda u_\lambda$ represents the mean expected payoff of the population. At an internal stationary state, all strategies with positive frequency must have the same expected payoff. A boundary state can also be stationary because a strategy with zero frequency cannot increase unless it is introduced into the population. We therefore assess the stability of boundary states by asking whether they can be invaded by a rare alternative strategy.

Omniscient AI

With Omniscient AI, every AI prediction contains information about the full prediction target, and revised predictions are combined through averaging. As population size increases, independent AI errors vanish from the collective prediction. However, these errors remain in individual prediction errors and can therefore continue to affect niche-expert payoffs. We consider the two incentive structures separately.

Feedback

Under the feedback structure, both the stochastic error in the collective prediction, $\bar{\eta}$, and its contribution to expected payoff vanish as $N \rightarrow \infty$. Following previous work (Wang et al., 2025), we define the Lyapunov function as the expected error of collective prediction:

$$V = \mathbb{E} \left[(Y - \hat{Y}^{re})^2 \right]. \quad (\text{S95})$$

The function V is non-negative and equals zero when the collective prediction is identical to the target. To determine how V changes over time, we take its time derivative:

$$\frac{dV}{dt} = -2\mathbb{E} \left[(Y - \hat{Y}^{re}) \frac{d\hat{Y}^{re}}{dt} \right] \quad (\text{S96})$$

$$= -2\mathbb{E} \left[\left(\delta_0 + \sum_{i=1}^M \delta_i X_i \right) \left\{ \frac{d\bar{\beta}}{dt} (Y + B) + \sum_{i=0}^M \frac{d\gamma_i}{dt} X_i \right\} \right] \quad (\text{S97})$$

$$= -2 \left[\left\{ (\alpha_0 + B)\delta_0 + \sum_{i=1}^M \alpha_i \delta_i \sigma_i^2 \right\} \frac{d\bar{\beta}}{dt} + \delta_0 \frac{d\gamma_0}{dt} + \sum_{i=1}^M \delta_i \sigma_i^2 \frac{d\gamma_i}{dt} \right]. \quad (\text{S98})$$

For notational convenience, we define

$$K = (\alpha_0 + B)\delta_0 + \sum_{i=1}^M \alpha_i \delta_i \sigma_i^2. \quad (\text{S99})$$

Although K changes with the population state, it is common to all strategies at a given state and can therefore be treated as a constant with respect to the strategy index λ . We also define:

$$G_e = \begin{cases} \delta_0, & e = 0, \\ \delta_e \sigma_e^2, & e \neq 0. \end{cases} \quad (\text{S100})$$

Under the replicator equation, the rate of change in the population mean of a strategy component is given by its covariance with expected payoff.

$$\frac{d\bar{\beta}}{dt} = \sum_{\lambda} p_{\lambda} (u_{\lambda} - \bar{u}) \beta_{\lambda} = \text{Cov}(\beta, u). \quad (\text{S101})$$

Similarly, the terms involving γ_i can be combined as

$$\delta_0 \frac{d\gamma_0}{dt} + \sum_{i=1}^M \delta_i \sigma_i^2 \frac{d\gamma_i}{dt} = \text{Cov}((1 - \beta)cG_e, u). \quad (\text{S102})$$

Therefore,

$$\frac{dV}{dt} = -2 \{ K \text{Cov}(\beta, u) + \text{Cov}((1 - \beta)cG_e, u) \} \quad (\text{S103})$$

$$= -2 \text{Cov}(K\beta + (1 - \beta)cG_e, u). \quad (\text{S104})$$

For the feedback structure in the limit $N \rightarrow \infty$, the expected payoff of strategy λ is

$$u_{\lambda} = K\beta_{\lambda} + (1 - \beta_{\lambda})c_{\lambda}G_{e_{\lambda}}. \quad (\text{S105})$$

This expected payoff is identical to the quantity inside the covariance above. Therefore,

$$\frac{dV}{dt} = -2 \text{Cov}(u, u) = -2 \text{Var}(u) \leq 0. \quad (\text{S106})$$

Therefore, the expected error of collective prediction cannot increase during the evolutionary process and decreases whenever strategies differ in their expected payoffs. The derivative becomes zero when the variance of expected payoffs is zero, $\text{Var}(u) = 0$. This condition arises when all represented strategies receive the same expected payoff. However, this condition does not necessarily imply that $V = 0$, because a population can lack strategies that would improve its collective prediction.

If $V > 0$, at least one component of the collective residual remains nonzero. A rare strategy whose prediction is aligned with this residual can obtain a higher expected payoff than the resident strategies and invade the population. Thus, provided that novel strategies can be introduced, an evolutionarily stable state must satisfy $V = 0$. At such a state, $\hat{Y}^{\text{re}} = Y$, and collective accuracy reaches $R = 1$.

402 Niche-expert

403 Unlike feedback payoffs, niche-expert payoffs depend on the prediction error of each
 404 individual. Stochastic AI error therefore remains in the expected payoff even when
 405 $N \rightarrow \infty$, and we retain $\tau > 0$ throughout this analysis.

406 We first consider strategies having the same interest by optimizing the expected
 407 payoff with respect to c and β . For a nonzero interest e , the expected payoff is strictly
 408 concave with respect to c for $\beta < 1$ and $\sigma_e > 0$, and is maximized at

$$c_e^* = \alpha_e. \quad (\text{S107})$$

409 After substituting $c_e^* = \alpha_e$, the payoff is strictly concave with respect to β . Its
 410 unconstrained stationary point is then:

$$\tilde{\beta}_e = \frac{\alpha_0^2 + \alpha_0 B + \sum_{j \neq e, 0} \alpha_j^2 \sigma_j^2}{(\alpha_0 + B)^2 + \sum_{j \neq e, 0} \alpha_j^2 \sigma_j^2 + \tau^2}. \quad (\text{S108})$$

411 Because β is constrained between 0 and 1, the optimal β_e^* is $\tilde{\beta}_e$ when $0 < \tilde{\beta}_e < 1$,
 412 and otherwise lies at the corresponding boundary, $\beta_e^* = 0$ or $\beta_e^* = 1$. Thus, the
 413 boundary cases do not require a separate evolutionary argument; they only change
 414 the optimal prediction and its minimum expected squared error. When $\beta_e^* = 1$, the
 415 revised prediction is independent of c_e , so different values of c_e are selectively neutral
 416 and can be treated as a single payoff-equivalent strategy class.

417 To compare the optimized strategies across interests, let L_e denote the minimum
 418 expected individual squared error within interest e , $\mathbb{E}[(Y_A^{re} - Y)^2]$. For an internal
 419 optimum,

$$L_e = \frac{B^2 \sum_{j \neq e, 0} \alpha_j^2 \sigma_j^2 + \tau^2 \left(\alpha_0^2 + \sum_{j \neq e, 0} \alpha_j^2 \sigma_j^2 \right)}{(\alpha_0 + B)^2 + \sum_{j \neq e, 0} \alpha_j^2 \sigma_j^2 + \tau^2}. \quad (\text{S109})$$

420 If the optimum is located at $\beta_e^* = 0$ or $\beta_e^* = 1$, L_e is instead obtained by evaluating
 421 the expected squared prediction error at the corresponding boundary.

422 Interest 0 must be considered separately because $X_0 = 1$ and the player's belief
 423 determines a constant prediction. Optimizing with respect to c gives

$$c_0^*(\beta) = \alpha_0 - \frac{\beta}{1 - \beta} B. \quad (\text{S110})$$

424 Substituting this into the expected payoff gives a strictly concave function of β , with
 425 the unique optimum:

$$\beta_0^* = \frac{\sum_{j=1}^M \alpha_j^2 \sigma_j^2}{\sum_{j=1}^M \alpha_j^2 \sigma_j^2 + \tau^2}. \quad (\text{S111})$$

426 Therefore,

$$c_0^* = \alpha_0 - \frac{B}{\tau^2} \sum_{j=1}^M \alpha_j^2 \sigma_j^2, \quad (\text{S112})$$

427 and

$$L_0 = \frac{\tau^2 \sum_{j=1}^M \alpha_j^2 \sigma_j^2}{\sum_{j=1}^M \alpha_j^2 \sigma_j^2 + \tau^2}. \quad (\text{S113})$$

428 At this optimum, the player adjusts their belief to offset the systematic AI bias. The
 429 stochastic component of AI error cannot be removed in the same way and therefore
 430 limits the benefit of AI reliance.

431 We denote the optimal strategy within interest e by S_e . When $\beta_e^* = 1$, different
 432 values of c_e are selectively neutral and can be treated as a single payoff-equivalent
 433 strategy class. A stable state can contain only the optimal strategy class within each
 434 represented interest because a suboptimal strategy can be invaded by S_e .

435 We next consider the frequencies of the $M + 1$ optimal strategies. Let ρ_e denote
 436 the frequency of S_e . Its expected payoff is

$$u_e = -\rho_e L_e. \quad (\text{S114})$$

437 Assuming $L_e > 0$ for all interests, the equal-payoff condition of the replicator equa-
 438 tion at an internal stationary state gives

$$\rho_0^* L_0 = \rho_1^* L_1 = \dots = \rho_M^* L_M. \quad (\text{S115})$$

439 Together with $\sum_{e=0}^M \rho_e^* = 1$, this uniquely determines

$$\rho_e^* = \frac{D}{L_e}, \quad D = \left(\sum_{j=0}^M \frac{1}{L_j} \right)^{-1}. \quad (\text{S116})$$

440 This internal stationary state is locally stable. At equilibrium, all represented in-
 441 terests have the same expected payoff, with $\rho_e^* L_e = D$. If the frequency of one
 442 interest increases slightly above its equilibrium value, its payoff decreases because
 443 the niche-expert payoff is proportional to $-\rho_e L_e$. Conversely, if the frequency of an
 444 interest decreases below its equilibrium value, its payoff increases. The replicator dy-
 445 namics therefore generate a restoring force that reduces small deviations in interest
 446 frequencies and drives the population back toward the internal stationary state.

447 If one or more interests are absent, the resulting boundary state can be stationary
 448 under the replicator equation, but it is unstable against invasion. The payoff of a rare
 449 absent interest approaches zero as $\rho_e \rightarrow 0$, whereas the mean payoff of the resident
 450 population is negative when $L_e > 0$, so the rare interest increases when introduced
 451 at sufficiently small frequency.

452 Thus, there exists a unique stable full-support equilibrium in terms of the optimal
 453 prediction strategies and their frequencies. Whether the constrained optimum has
 454 $\beta_e^* = 0$, $0 < \beta_e^* < 1$, or $\beta_e^* = 1$ does not change the frequency argument, because
 455 these cases differ only through the resulting value of L_e . When $\beta_e^* = 1$, the strategy
 456 is selectively neutral with respect to c_e , but its prediction, payoff, and equilibrium
 457 interest frequency remain uniquely determined.

458 Having characterized this equilibrium, we next compare its collective prediction
 459 with a prediction made entirely by AI. In particular, the expected squared error of
 460 an Omniscient AI prediction is

$$\mathbb{E}[(Y - Y^{\text{AI}})^2] = B^2 + \tau^2. \quad (\text{S117})$$

461 For every interest, complete reliance on AI, $\beta = 1$, is a feasible strategy. There-
 462 fore, because L_e is the minimum individual expected squared prediction error within
 463 interest e ,

$$L_e \leq B^2 + \tau^2. \quad (\text{S118})$$

464 Moreover, for interest 0,

$$L_0 = \frac{\tau^2 \sum_{j=1}^M \alpha_j^2 \sigma_j^2}{\sum_{j=1}^M \alpha_j^2 \sigma_j^2 + \tau^2} < \tau^2 \leq B^2 + \tau^2. \quad (\text{S119})$$

465 Because the stable equilibrium has $\rho_0^* > 0$,

$$\sum_{e=0}^M \rho_e^* L_e < B^2 + \tau^2. \quad (\text{S120})$$

466 The collective prediction is the average of individual revised predictions. By convex-
 467 ity of the squared error,

$$\mathbb{E}[(Y - \hat{Y}^{re})^2] \leq \sum_{e=0}^M \rho_e^* L_e. \quad (\text{S121})$$

468 Therefore,

$$\mathbb{E}[(Y - \hat{Y}^{re})^2] < \mathbb{E}[(Y - Y^{\text{AI}})^2]. \quad (\text{S122})$$

469 Thus, the diversity of optimized predictions allows the population to outperform an
 470 individual AI prediction at equilibrium.

471 However, outperforming AI does not imply perfect collective accuracy. Under
 472 averaging, the non-AI contribution associated with a particular factor is provided
 473 only by individuals interested in that factor. The predictions of individuals with
 474 other interests therefore attenuate that factor's coefficient in the collective prediction.
 475 For a nonzero factor i , the residual coefficient of the stationary collective prediction
 476 can be written as

$$\delta_i^* = \alpha_i \{1 - \bar{\beta}^* - \rho_i^*(1 - \beta_i^*)\} = \alpha_i \sum_{e \neq i} \rho_e^*(1 - \beta_e^*). \quad (\text{S123})$$

477 At the stable equilibrium, $\rho_0^* > 0$. In addition, $\tau > 0$ implies $\beta_0^* < 1$. Therefore, for
 478 every factor with $\alpha_i \neq 0$,

$$\delta_i^* \neq 0. \quad (\text{S124})$$

479 Because $\sum_{i=1}^M \alpha_i^2 \sigma_i^2 > 0$, at least one factor contributes positive prediction error.
 480 Hence,

$$\mathbb{E} \left[(Y - \hat{Y}^{re})^2 \right] > 0, \quad (\text{S125})$$

481 and consequently the stationary collective accuracy satisfies $R^* < 1$. Thus, the niche-
 482 expert structure preserves interest diversity and allows the population to outperform
 483 AI, but averaging prevents the population from reaching perfect collective accuracy.

484 AI models under alternative aggregation rules

485 In the main analysis, we assume that collective predictions under the omniscient AI
 486 and chatbot AI models are generated using averaging and clustering aggregation,
 487 respectively. However, the aggregation rules can, in principle, be swapped between
 488 the two AI models. To examine the consequences of these alternative combinations,
 489 we investigate their behavior through mathematical derivation and simulation.

490 Omniscient AI with clustering aggregation

491 Under clustering aggregation, the collective prediction based on individual predic-
 492 tions revised by the omniscient AI can be written as

$$\hat{Y}^{re} = \sum_{i \in \mathcal{I}} \frac{1}{n_i} \sum_{A \in \mathcal{A}_i} Y_A^{re} \quad (\text{S126})$$

$$= \sum_{i \in \mathcal{I}} \frac{1}{n_i} \sum_{A \in \mathcal{A}_i} \{ \beta_A Y_A^{AI} + (1 - \beta_A) Y_A \} \quad (\text{S127})$$

$$= \sum_{i \in \mathcal{I}} \frac{1}{n_i} \sum_{A \in \mathcal{A}_i} [\beta_A (Y + B + \epsilon_A) + (1 - \beta_A) c_A X_{e_A}], \quad (\text{S128})$$

493 where $\mathcal{A}_i$ is the set of players interested in factor i , $n_i = |\mathcal{A}_i|$ is the number of players
 494 in that set, and $\mathcal{I} = \{i \in \{0, \dots, M\} : n_i > 0\}$ is the set of represented interests.

495 To simplify the collective prediction, we define:

$$c_i^{agg} = \frac{1}{n_i} \sum_{A \in \mathcal{A}_i} (1 - \beta_A) c_A, \quad (\text{S129})$$

$$\bar{\beta}_i = \frac{1}{n_i} \sum_{A \in \mathcal{A}_i} \beta_A, \quad (\text{S130})$$

$$\beta^{agg} = \sum_{i \in \mathcal{I}} \bar{\beta}_i, \quad (\text{S131})$$

$$\tilde{\eta}_i = \frac{1}{n_i} \sum_{A \in \mathcal{A}_i} \beta_A \epsilon_A, \quad (\text{S132})$$

$$\bar{\eta} = \sum_{i \in \mathcal{I}} \tilde{\eta}_i. \quad (\text{S133})$$

496 Thus, the collective prediction can be written as

$$\hat{Y}^{re} = \sum_{i \in \mathcal{I}} c_i^{agg} X_i + \beta^{agg}(Y + B) + \bar{\eta}. \quad (\text{S134})$$

497 Because individual reliance on AI, β_A , is initialized independently from $U(0, 1)$,
 498 the expected initial value of β^{agg} is $|\mathcal{I}|/2$. When all $M + 1$ interests are represented,
 499 this becomes $(M + 1)/2$. Thus, clustering aggregation incorporates the omniscient AI
 500 prediction repeatedly across interest groups, scaling its contribution to the collective
 501 prediction by a factor of approximately $(M + 1)/2$ at initialization. For a large number
 502 of factors, such as $M = 50$, this produces an unrealistically large contribution of the
 503 AI prediction to the collective prediction. Therefore, clustering aggregation does not
 504 provide a reasonable aggregation rule for the omniscient AI model in the context
 505 of our study, as it repeatedly incorporates predictions of the entire outcome across
 506 interest groups.

507 Chatbot AI with averaging aggregation

508 Each prediction generated by Chatbot AI contains information about only one fac-
 509 tor. Averaging these predictions does not repeatedly incorporate the full prediction
 510 target, but instead weights the contribution of each factor by the proportion of
 511 individuals interested in that factor. Under averaging aggregation, the collective
 512 prediction can be written as

$$\hat{Y}^{re} = \frac{1}{N} \sum_{A=1}^N Y_A^{re} \quad (\text{S135})$$

$$= \frac{1}{N} \sum_{A=1}^N [\{\beta_A \alpha_{e_A} + (1 - \beta_A) c_A\} X_{e_A} + \beta_A b_{e_A} + \beta_A \epsilon_A]. \quad (\text{S136})$$

513 We define the aggregate revised coefficient associated with each factor, the ag-
 514 gregate AI bias, and the stochastic error as

$$c_i^{av} = \frac{1}{N} \sum_{A \in \mathcal{A}_i} \{\beta_A \alpha_i + (1 - \beta_A) c_A\}, \quad (\text{S137})$$

$$B^{av} = \frac{1}{N} \sum_{A=1}^N \beta_A b_{e_A}, \quad (\text{S138})$$

$$\bar{\eta} = \frac{1}{N} \sum_{A=1}^N \beta_A \epsilon_A. \quad (\text{S139})$$

515 Thus, the collective prediction becomes

$$\hat{Y}^{re} = \sum_{i=0}^M c_i^{av} X_i + B^{av} + \bar{\eta}. \quad (\text{S140})$$

516 We define the remaining errors in the intercept and factor-specific coefficients as

$$\delta_0 = \alpha_0 - c_0^{av} - B^{av}, \quad (\text{S141})$$

$$\delta_i = \alpha_i - c_i^{av}, \quad (i \neq 0). \quad (\text{S142})$$

517 Expected payoffs

518 Under the feedback structure, the expected payoff is

$$\mathbb{E}[\pi_A] = \{\beta_A \alpha_{e_A} + (1 - \beta_A) c_A\} \delta_{e_A} \sigma_{e_A}^2 + \beta_A b_{e_A} \delta_0 - \frac{\beta_A^2 \tau^2}{N}, \quad (\text{S143})$$

519 where $\sigma_0^2 = 1$. Because the niche-expert payoff depends only on individual prediction
 520 error and the frequency of the player's interest, its expected payoff is unaffected by
 521 the aggregation rule. It is therefore identical to the expected payoff derived for
 522 Chatbot AI with clustering aggregation.

523 Expected accuracy

524 The expected squared error of the collective prediction is

$$\mathbb{E}[(Y - \hat{Y}^{re})^2] = \delta_0^2 + \sum_{i=1}^M \delta_i^2 \sigma_i^2 + \frac{\tau^2}{N^2} \sum_{A=1}^N \beta_A^2. \quad (\text{S144})$$

525 Therefore, the expected collective accuracy is

$$R = 1 - \frac{\delta_0^2 + \sum_{i=1}^M \delta_i^2 \sigma_i^2 + \frac{\tau^2}{N^2} \sum_{A=1}^N \beta_A^2}{\sum_{i=1}^M \alpha_i^2 \sigma_i^2}. \quad (\text{S145})$$

526 Simulation results

527 The effect of averaging depends on the incentive structure (Fig. S10). Under the
 528 feedback structure, social learning can compensate for the attenuation introduced
 529 by averaging by favoring factor-specific predictions that reduce the remaining collec-
 530 tive error. In particular, the mean revised coefficient among individuals interested in
 531 factor i can approach α_i / ρ_i , such that its aggregate contribution approaches α_i . Con-
 532 sistent with this mechanism, collective accuracy reaches a near-perfect level across
 533 AI bias values. Collective bias and variance also remain near zero, although coun-
 534 terfactual human CI remains below one.

535 In contrast, the niche-expert structure rewards individual predictive accuracy
 536 rather than contributions to the collective prediction. Revised factor-specific co-
 537 efficients therefore remain close to their corresponding true coefficients, such that
 538 $\bar{c}_i^{re} \approx \alpha_i$. Averaging then reduces their aggregate contribution to $c_i^{av} \approx \rho_i \alpha_i$. When
 539 interests are approximately uniformly distributed, $\rho_i \approx 1/(M+1)$. The attenuation
 540 of the nonzero factor coefficients alone then gives $R \approx 1 - M/(M+1)^2 = 0.039$

541 when $M = 50$, before accounting for the remaining intercept and stochastic errors.
542 Accordingly, collective accuracy remains near zero even though interest diversity re-
543 mains high and reliance on AI can be substantial. Chatbot AI does not resolve this
544 problem because its predictions are also restricted to the user’s factor of interest.

545 These results show that the aggregation rule must reflect the information con-
546 tained in individual and AI predictions. Clustering aggregation repeatedly counts
547 the full prediction target when paired with Omniscient AI, whereas averaging aggre-
548 gation attenuates factor-specific predictions when paired with Chatbot AI.

Supplementary Figure




Figure S1: **Niche-expert structure with averaging aggregation cannot promote CI without AI.** Trajectories of the mean absolute error from true coefficients and collective accuracy under the niche-expert structure with averaging aggregation in the absence of AI. The mean absolute error from true coefficients is calculated by first taking, for each interest, the absolute difference between the true coefficient and the mean belief of individuals sharing that interest, and then averaging these differences across all $M + 1$ interests. The mean absolute error decreases across generations, indicating that the mean beliefs move closer to their corresponding true coefficients. However, collective accuracy remains near zero, indicating that simply averaging individual predictions does not yield accurate collective predictions. Prediction target parameters: $M = 50$, $s = 50$, $\mu = 0$, $\alpha_i \sim U(-5, 5)$, and $\sigma_i \sim U(0, 3)$. Population parameters: $N = 10,000$, $c_A \sim \mathcal{N}(0, 100^2)$.



Figure S2: **Evaluation metrics across various levels of AI bias.** Evaluation metrics across varying levels of AI bias under different assumptions about AI types (Omniscient AI, and Chatbot AI) and incentive structures (feedback, niche-expert). Larger absolute AI bias indicates a less accurate AI model. Dashed horizontal lines represent the values of the evaluation metrics when the group is not assisted by AI. Collective accuracy represents the predictive performance of the group, and counterfactual human CI represents the group’s predictive accuracy if AI assistance were unavailable at the given generation. Interest diversity is defined as Hill-Shannon diversity of interest within the population, median reliance on AI represents the median value of reliance on AI (β). Collective bias represents systematic deviation of the collective prediction from the true target, collective variance represents variability of the collective prediction error across prediction events. All the evaluation metrics are averaged over generations 190,001–200,000. Prediction target parameters: $M = 50$, $s = 50$, $\mu = 0$, $\alpha_i \sim U(-5, 5)$, and $\sigma_i \sim U(0, 3)$. Population parameters: $N = 10,000$, $c_A \sim \mathcal{N}(0, 100^2)$ for (A, B), $c_A \sim \mathcal{N}(0, 5^2)$ for (C, D), and $\beta_A \sim U(0, 1)$. AI parameters: $\tau = 0.3$.




Figure S3: **Comparison of evaluation metrics with and without AI.** Trajectories of evaluation metrics when the group is assisted by the Omniscient AI and Chatbot AI. Here, feedback and niche-expert incentive structures are considered. Blue lines represent trajectories of evaluation metrics without AI assistance. Orange lines represent trajectories of evaluation metrics with AI assistance. Interest diversity is define as Hill-Shannon diversity of interest within population, median reliance on AI represent population median of reliance on AI (β), collective bias represent systematic deviation of the collective prediction from the true target, collective variance represent variability of the collective prediction error across prediction events. Prediction target parameters: $M = 50$, $s = 50$, $\mu = 0$, $\alpha_i \sim U(-5, 5)$, and $\sigma_i \sim U(0, 3)$. Population parameters: $N = 10,000$, $c_A \sim \mathcal{N}(0, 100^2)$ for (A, B), $c_A \sim \mathcal{N}(0, 5^2)$ for (C, D), and $\beta_A \sim U(0, 1)$. AI parameters: $b_i = 0.4$ and $\tau = 0.3$.





Figure S4: **Feedback structure becomes more prone to interest diversity loss with AI** Trajectories of interest diversity with and without AI under the feedback structure (A). Heatmaps of interest diversity across varying levels of mutation rate (B, C) and the standard deviation of the initial belief distribution (D, E), with and without AI. Interest diversity declines toward zero even without AI over long timescales when there is no mutation and the initial belief distribution is narrow. However, with AI, interest diversity declines more strongly, even under moderate mutation rates and wider initial belief distributions. Interest diversity in the heatmaps is averaged over generations 190,001–200,000. Prediction target parameters: $M = 50$, $s = 50$, $\mu = 0$ for (D, E), $\alpha_i \sim U(-5, 5)$, and $\sigma_i \sim U(0, 3)$. Population parameters: $N = 10,000$, $c_A \sim \mathcal{N}(0, 5^2)$ for (A, B, C), and $\beta_A \sim U(0, 1)$. AI parameters: $b_i = 0.4$ and $\tau = 0.3$, Chatbot AI is used.




Figure S5: **Niche-expert structure may reduce reliance on AI, delaying the emergence of CI.** Trajectories of collective accuracy and median reliance on AI when the niche-expert structure causes reliance on AI to decline over time. Red lines represent trajectories with AI across varying levels of AI bias (-0.2, -0.4, and -0.6). Green lines represent trajectories without AI; reliance on AI is set to zero in the absence of AI. This reduction in reliance on AI occurs when the α_0 and AI bias have opposite signs, and is associated with the eventual emergence of CI, although CI emerges substantially later than in the condition without AI. Prediction target parameters: $M = 50$, $s = 50$, $\mu = 0$, $\alpha_i \sim U(-5, 5)$, and $\sigma_i \sim U(0, 3)$. Population parameters: $N = 10,000$, $c_A \sim \mathcal{N}(0, 5^2)$, and $\beta_A \sim U(0, 1)$. AI parameters: $\tau = 0.3$, Chatbot AI is used.




Figure S6: **Comparison of evaluation metrics between incentive structures across various levels of AI bias.** Evaluation metrics under feedback, niche-expert and balanced structures across varying levels of AI bias. Larger absolute AI bias indicates a less accurate AI model. All the evaluation metrics are averaged over generations 190,001–200,000. The balanced structure maintains near-perfect collective accuracy across bias levels and higher counterfactual human CI than the other incentive structures. These patterns are driven by well-calibrated reliance on AI, which increases as AI becomes more accurate, and by well-preserved interest diversity, which together lead to low collective variance and collective bias. Prediction target parameters: $M = 50$, $s = 50$, $\mu = 0$, $\alpha_i \sim U(-5, 5)$, and $\sigma_i \sim U(0, 3)$. Population parameters: $N = 10,000$, $c_A \sim \mathcal{N}(0, 5^2)$, and $\beta_A \sim U(0, 1)$. AI parameters: $\tau = 0.3$, Chatbot AI is used.




Figure S7: **Balanced structure is robust across varying balancing weights.** Evaluation metrics across varying levels of the balancing weight (0.1 – 0.9). The balancing weight represents the weight assigned to the niche-expert structure when constructing the balanced structure by combining the niche-expert and feedback structures. A balancing weight of 0.5 represents equal weighting of the niche-expert and feedback structures, whereas 0 corresponds to the feedback structure and 1 corresponds to the niche-expert structure. Although the evaluation metrics vary as the balancing weight changes from 0.1 to 0.9, the absolute magnitude of these deviations remains limited. Prediction target parameters: $M = 50$, $s = 50$, $\mu = 0$, $\alpha_i \sim U(-5, 5)$, and $\sigma_i \sim U(0, 3)$. Population parameters: $N = 10,000$, $c_A \sim \mathcal{N}(0, 5^2)$, and $\beta_A \sim U(0, 1)$. AI parameters: $b_i = 0.4$, $\tau = 0.3$, Chatbot AI is used.




Figure S8: **Balanced structure shows well-calibrated reliance on AI.** Median reliance on AI across varying levels of AI bias. Thirty randomly initialized simulations were performed for each bias level. Each dot represents a single simulation, and the box plots show the median and interquartile range (IQR) for each bias level. The balanced structure shows well-calibrated reliance on AI, with reliance increasing as absolute magnitude of AI bias decreases. Prediction target parameters: $M = 50$, $s = 50$, $\mu = 0$, $\alpha_i \sim U(-5, 5)$, and $\sigma_i \sim U(0, 3)$. Population parameters: $N = 10,000$, $c_A \sim \mathcal{N}(0, 5^2)$, and $\beta_A \sim U(0, 1)$. AI parameters: $\tau = 0.3$, Chatbot AI is used.




Figure S9: **Incentive structures incorporating unrevised prediction accuracy can promote better counterfactual human CI.** Evaluation metrics under the balanced, unrevised balanced, and combined balanced structures across varying levels of AI bias. The unrevised balanced structure is defined as the arithmetic mean of the feedback and niche-expert structures based on unrevised predictions, whereas the combined balanced structure is defined as the arithmetic mean of the balanced and unrevised balanced structures. All evaluation metrics are averaged over generations 190,001–200,000. The unrevised balanced structure achieves near-perfect counterfactual human CI; however, median reliance on AI remains near 0.5 because the unrevised balanced incentive does not account for AI predictions and therefore imposes no selection on β_A . Consequently, collective accuracy directly inherits AI bias and decreases as the magnitude of AI bias increases. The combined balanced structure, which leverages both the balanced and unrevised balanced structures, achieves near-perfect counterfactual human CI without compromising collective accuracy. Prediction target parameters: $M = 50$, $s = 50$, $\mu = 0$, $\alpha_i \sim U(-5, 5)$, and $\sigma_i \sim U(0, 3)$. Population parameters: $N = 10,000$, $c_A \sim \mathcal{N}(0, 5^2)$, and $\beta_A \sim U(0, 1)$. AI parameters: $\tau = 0.3$; Chatbot AI is used.




Figure S10: **Chatbot AI with averaging aggregation has a limited influence on CI.** Evaluation metrics across varying levels of AI bias under Chatbot AI with averaging aggregation. Two incentive structures, feedback and niche-expert, are considered. A larger absolute AI bias indicates a less accurate AI model. Dashed horizontal lines represent the values of the evaluation metrics when the group is not assisted by AI. Collective accuracy represents the predictive performance of the group, whereas counterfactual human CI represents the group’s predictive accuracy if AI assistance were unavailable at the given generation. Interest diversity is defined as the Hill–Shannon diversity of interests within the population, and median reliance on AI represents the median reliance on AI (β) across individuals. Collective bias represents the systematic deviation of the collective prediction from the true target, whereas collective variance represents the variability of collective prediction errors across prediction events. All evaluation metrics are averaged over generations 190,001–200,000. Prediction target parameters: $M = 50$, $s = 50$, $\mu = 0$, $\alpha_i \sim U(-5, 5)$, and $\sigma_i \sim U(0, 3)$. Population parameters: $N = 10,000$, $c_A \sim \mathcal{N}(0, 100^2)$, and $\beta_A \sim U(0, 1)$. AI parameters: $\tau = 0.3$.

Table S1: Evaluation metrics used to analyze collective prediction dynamics.

Metric	Definition	Interpretation
Collective accuracy	$1 - \frac{\mathbb{E}[(Y - \hat{Y}^{\text{re}})^2]}{\mathbb{E}[(Y - \alpha_0)^2]}$	Accuracy of the revised collective prediction relative to the baseline prediction α_0 .
Collective bias	$\left(\mathbb{E}[Y - \hat{Y}^{\text{re}}]\right)^2$	Squared expected deviation of the revised collective prediction from the true target.
Collective variance	$\text{Var}(Y - \hat{Y}^{\text{re}})$	Variability of the revised collective prediction error across prediction events.
Counterfactual collective accuracy	$1 - \frac{\mathbb{E}[(Y - \hat{Y})^2]}{\mathbb{E}[(Y - \alpha_0)^2]}$	Accuracy obtained after removing AI use from the current population while retaining its evolved interests and beliefs.
Interest diversity	$\exp\left(-\sum_{i=0}^M \rho_i \ln \rho_i\right)$	Effective number of interests represented in the population.
Median reliance on AI	$\text{median}_{A \in N}(\beta_A)$	Median reliance on AI in the population.

550 References

- 551 Hong, L., S. E. Page, and M. Riolo (2012). Incentives, information, and emergent
552 collective accuracy. *Managerial and Decision Economics* 33(5-6), 323–334.
- 553 Mann, R. P. and D. Helbing (2017). Optimal incentives for collective intelligence.
554 *Proceedings of the National Academy of Sciences* 114(20), 5077–5082.
- 555 Taylor, P. D. and L. B. Jonker (1978). Evolutionary stable strategies and game
556 dynamics. *Mathematical biosciences* 40(1-2), 145–156.
- 557 Traulsen, A., J. C. Claussen, and C. Hauert (2005). Coevolutionary dynamics: from
558 finite to infinite populations. *Physical review letters* 95(23), 238701.
- 559 Wang, G., Q. Su, L. Wang, and J. B. Plotkin (2025). Individual incentives that
560 promote collective intelligence. *Proceedings of the National Academy of Sci-*
561 *ences* 122(51), e2516535122.