

Supplementary Materials for: Predicting the long-term impact of AI assistants on collective intelligence

Jaeseung Kim¹ Sang Woo Park^{1,2,*}

¹ School of Biological Sciences, Seoul National University, Seoul, Korea

² Institute for Data Innovation in Science, Seoul National University, Seoul, Korea

*Corresponding author: sangwoopark@snu.ac.kr

Materials and Methods

Prediction target

Following previous models of CI, we model the prediction target as a linear combination of M independent causal factors (Hong et al., 2012; Mann and Helbing, 2017; Wang et al., 2025):

$$Y = \alpha_0 + \alpha_1 X_1 + \cdots + \alpha_M X_M, \quad (\text{S1})$$

where the coefficient α_i determines the magnitude and direction of the effect of factor i , and α_0 represents a global intercept. Each causal factor X_i is modeled as an independent Gaussian random variable with mean zero and standard deviation σ_i .

Players

We consider a well-mixed population $\mathcal{N}$ consisting of N players engaged in a novel prediction task. In the absence of AI assistance, the strategy of player A is characterized by two variables: interest e_A and belief c_A . Player A observes the causal factor X_{e_A} and makes a prediction by multiplying the observed factor value by their belief:

$$Y_A = c_A X_{e_A}, \quad (\text{S2})$$

where e_A can take an integer value from 0 to M . When $e_A = 0$, the player does not observe any causal factor and instead makes a constant prediction based solely on their belief. We refer to this as a stubborn strategy because the player's prediction does not respond to the realized values of the causal factors. For notational convenience, we assume that $X_0 = 1$.

When the group is assisted by AI, each player's strategy additionally includes reliance on AI, denoted by β_A . We assume that each player consults the AI independently and revises their prediction by taking a weighted average of their own prediction and the AI-generated prediction:

$$Y_A^{\text{re}} = \beta_A Y_A^{\text{AI}} + (1 - \beta_A) Y_A, \quad (\text{S3})$$

where β_A ranges from 0 to 1. A value of $\beta_A = 1$ indicates complete reliance on AI, whereas $\beta_A = 0$ indicates that the player does not use the AI prediction.

AI models

We assume that the AI model has been trained on similar tasks and is therefore capable of making predictions based on causal factors. However, because the model is imperfect, its outputs are subject to systematic additive bias and stochastic error. The additive bias associated with factor i is denoted by b_i , and the stochastic error is denoted by ϵ . The AI is neither trained nor updated during the simulation, and its biases therefore remain fixed throughout the simulation. For simplicity, we assume $b_i = b$ for the main analysis for all i . The model formulation nevertheless allows biases to differ among factors.

We assume that the stochastic error follows a Gaussian distribution with mean zero and standard deviation τ . Each time a player consults the AI, an independent error is generated. Errors are therefore independent across players and across repeated consultations by the same player. Consequently, stochastic AI errors can be attenuated when independently generated predictions are aggregated across players. We therefore hold τ constant and vary the magnitude of the additive bias to manipulate the level of AI accuracy during our analyses.

We consider two extreme types of AI that differ in the amount of information available for prediction. The first is termed the Omniscient AI, which can observe all M causal factors and incorporate them into its prediction regardless of the user's interest. The prediction generated by the Omniscient AI for player A is expressed as follows:

$$Y_A^{\text{AI}} = \alpha_0 + b_0 + \alpha_1 X_1 + b_1 + \cdots + \alpha_M X_M + b_M + \epsilon. \quad (\text{S4})$$

The second is termed the Chatbot AI, which can use only the single causal factor X_{e_A} associated with the player's interest. The prediction generated by the Chatbot AI for player A is expressed as follows:

$$Y_A^{\text{AI}} = \alpha_{e_A} X_{e_A} + b_{e_A} + \epsilon. \quad (\text{S5})$$

Aggregation rules

The revised individual predictions are aggregated to form a collective prediction. We use two aggregation rules proposed in previous research (Wang et al., 2025), depending on the type of AI used by the group. First, when the group is assisted by the Omniscient AI, the AI component of each revised prediction contains information about all M factors, even though the individual's own prediction is based on only one factor. Each revised prediction can therefore be treated as an estimate of the entire target. Accordingly, we calculate the collective prediction by taking the simple average of the revised individual predictions:

$$\hat{Y}^{\text{re}} = \frac{Y_1^{\text{re}} + Y_2^{\text{re}} + \cdots + Y_n^{\text{re}}}{N}. \quad (\text{S6})$$

Second, when the group is assisted by the Chatbot AI, both the player’s initial prediction and the AI’s prediction are based on the same causal factor. Each revised prediction therefore contains information about only one factor and can be treated as an estimate of that factor’s contribution to the target. We consequently use clustering aggregation.

Clustering aggregation is performed by grouping individuals according to their interests and calculating the mean prediction within each group. The collective prediction is then obtained by summing the mean predictions of all nonempty groups:

$$\hat{Y}^{\text{re}} = \sum_{i:n_i>0} \frac{1}{n_i} \sum_{A \in \mathcal{A}_i} Y_A^{\text{re}}, \quad (\text{S7})$$

where $\mathcal{A}_i$ represents the set of players interested in factor i , and $n_i = |\mathcal{A}_i|$ represents the number of players in that set.

When the group is not assisted by AI, collective predictions are computed from the unrevised individual predictions throughout the simulation. Both simple averaging and clustering can be used in the absence of AI. For fair comparison, we use the same aggregation rule as in the corresponding AI-assisted condition.

Incentive structures

Players receive payoffs based on the underlying incentive structure. We consider five incentive structures: feedback structure, niche-expert structure, direct intervention on AI use of these two structures, and a balanced structure.

The feedback structure does not directly reward individuals according to their own prediction accuracy. Instead, it rewards predictions that are aligned with the residual error of the collective prediction and therefore have the potential to move the collective prediction toward the true value. Given player A ’s revised prediction Y_A^{re} and the collective prediction $\hat{Y}^{\text{re}}$, the payoff is expressed as

$$\pi_A = Y_A^{\text{re}}(Y - \hat{Y}^{\text{re}}). \quad (\text{S8})$$

The niche-expert structure assigns higher payoffs to individuals who make accurate predictions while having an underrepresented interest. Specifically, the squared prediction error of player A is weighted by $\rho_{e_A} = n_{e_A}/n$, the proportion of players interested in the same factor:

$$\pi_A = -\rho_{e_A}(Y_A^{\text{re}} - Y)^2. \quad (\text{S9})$$

Previous research has shown that these two incentive structures can produce near perfect collective accuracy through social learning, except when the niche-expert incentive is combined with simple averaging (Wang et al., 2025). They are therefore used as baseline structures for examining how AI assistance affects the emergence of CI.

99 To examine the effects of directly encouraging or discouraging AI use, we mod-
 100 ify the feedback and niche-expert structures by adding a term proportional to the
 101 player’s reliance on AI:

$$\pi_A = Y_A^{\text{re}}(Y - \hat{Y}^{\text{re}}) + \lambda\beta_A \quad (\text{S10})$$

$$\pi_A = -\rho_{e_A}(Y_A^{\text{re}} - Y)^2 + \lambda\beta_A. \quad (\text{S11})$$

102 Here, λ represents the strength of the direct incentive or penalty applied to AI use. A
 103 positive value of λ rewards AI reliance, whereas a negative value penalizes it. When
 104 $\lambda = 0$, no direct incentive or penalty is applied, and the payoff functions reduce to
 105 the original feedback and niche-expert structures.

106 The balanced structure is defined as the arithmetic mean of the feedback and
 107 niche-expert payoff components:

$$\pi_A = \frac{Y_A^{\text{re}}(Y - \hat{Y}^{\text{re}}) - \rho_{e_A}(Y_A^{\text{re}} - Y)^2}{2}. \quad (\text{S12})$$

108 Simulations

109 All simulations are conducted using an agent-based model with 50 causal factors
 110 ($M = 50$) and 10,000 players ($n = 10,000$). The parameters defining the prediction
 111 target are sampled at the beginning of the simulations and subsequently held fixed.

112 Coefficients α_i are sampled from a uniform distribution on $[-5, 5]$, except in the
 113 simulation presented in Figure 4, in which α_i is set to $5 - 0.2i$ for visualization.
 114 Standard deviations σ_i are sampled from a uniform distribution on $[0, 3]$.

115 Players’ initial strategies are also sampled from predefined probability distribu-
 116 tions. The distribution of individual belief c_A depends on the aggregation rule. Under
 117 simple averaging, each factor’s contribution is scaled by the proportion of players in-
 118 terested in that factor. We therefore sample beliefs from a Gaussian distribution
 119 with mean zero and standard deviation 100, following the scaling used in previous
 120 work (Wang et al., 2025). Under clustering aggregation, beliefs are sampled from a
 121 Gaussian distribution with mean zero and standard deviation 5. Because predictions
 122 are averaged separately within each interest group and then summed, no additional
 123 scaling of c_A is required. The initial interest of each player is sampled uniformly
 124 from the integers between 0 and 50, and reliance on AI was sampled from a uniform
 125 distribution on $[0, 1]$.

126 We assume that prediction events occur on a substantially faster timescale than
 127 social learning. In each generation, we therefore calculate the expected payoff $\mathbb{E}[\pi_A]$
 128 of each player analytically rather than explicitly sampling prediction events. The
 129 expectation is taken over the distributions of the causal factors $X_1, \dots, X_M$ and the
 130 stochastic AI error ϵ , conditional on the current population strategies and the fixed
 131 target parameters. Closed form expression of expected payoffs are derived for all
 132 incentive structures and are presented in the Supplementary Text.

Each generation consists of an expected payoff calculation followed by one opportunity for pairwise social learning. Two distinct players, A and B , are randomly sampled, and player A imitated all three strategies of player B with probability

$$\frac{1}{1 + \exp(s(\mathbb{E}[\pi_A] - \mathbb{E}[\pi_B]))}, \quad (\text{S13})$$

where s represents the strength of social learning and was set to 50 in all simulations. We introduce a mutation rate μ , such that with probability μ , player A does not imitate player B but instead redraw all strategy components from the same distributions used to initialize the population. The mutation rate is set to zero in all simulations except those presented in Supplementary Fig. S4.

Unless otherwise specified, each simulation is run for 200,000 generations. When a result is represented by a single summary value rather than as a temporal trajectory, the metric was averaged over the final 10,000 generations.

To evaluate the dynamics of collective prediction, we define six summary metrics: collective accuracy, collective bias, collective variance, counterfactual collective accuracy, interest diversity, and median reliance on AI. At each population state, expectations and variances are evaluated analytically over the distributions of the causal factors and AI errors rather than estimated from sampled prediction events. Collective bias and collective variance constitute the bias–variance decomposition of the group level collective prediction error.

Collective accuracy is normalized relative to the baseline prediction α_0 . A negative value indicates that the collective prediction performs worse than the baseline. Counterfactual collective accuracy is evaluated by setting $\beta_A = 0$ while retaining the evolved interests and beliefs of the AI-assisted population. In calculating interest diversity, we use the convention that $\rho_i \ln \rho_i = 0$ when $\rho_i = 0$ (Table S1).

Supplementary Text

Here, we derive the expected payoffs and collective accuracy used in the simulations. We consider Omniscient AI and Chatbot AI separately because they contain different amounts of information and therefore require different aggregation rules. We then analyze the corresponding evolutionary dynamics under a deterministic large-population approximation.

Omniscient AI

We first consider Omniscient AI, which incorporates all causal factors regardless of the player’s interest. We derive individual and collective predictions before calculating the expected payoffs under each incentive structure.

166 Model

167 Because Omniscient AI observes all M causal factors, its prediction for player A is
 168 given by

$$Y_A^{AI} = \alpha_0 + b_0 + \alpha_1 X_1 + b_1 + \cdots + \alpha_M X_M + b_M + \epsilon, \quad (\text{S14})$$

169 where b_i represent factor-specific biases and ϵ represents stochastic error, following
 170 a Gaussian distribution with mean zero and standard deviation τ . A new stochastic
 171 error is generated independently for each player and prediction event.

172 Let $B = \sum_{i=0}^M b_i$ denote the total additive bias. Because the true prediction
 173 target is $Y = \alpha_0 + \sum_{i=1}^M \alpha_i X_i$, the AI prediction can be written as

$$Y^{AI} = Y + B + \epsilon. \quad (\text{S15})$$

174 In contrast to the AI prediction, player A 's initial prediction depends only on the
 175 causal factor associated with their interest. Their initial and revised predictions are
 176 therefore given by:

$$Y_A = c_A X_{e_A} \quad (\text{S16})$$

$$Y_A^{re} = \beta_A Y^{AI} + (1 - \beta_A) Y_A \quad (\text{S17})$$

177 represents player A 's interest, c_A represents their belief about the effect of the corre-
 178 sponding factor, and β_A represents their reliance on AI. As in the main text, we set
 179 $X_0 = 1$, such that a player with $e_A = 0$ makes a constant initial prediction.

180 Aggregation

181 Because the AI component of each revised prediction contains information about all
 182 M causal factors, we use simple averaging to obtain the collective prediction:

$$\hat{Y}^{re} = \frac{1}{N} \sum_{j=1}^N Y_j^{re} \quad (\text{S18})$$

$$= \frac{1}{N} \sum_{j=1}^N \{ \beta_j Y^{AI} + (1 - \beta_j) Y_j \} \quad (\text{S19})$$

$$= \frac{1}{N} \sum_{j=1}^N \{ \beta_j (Y + B + \epsilon) + (1 - \beta_j) c_j X_{e_j} \} \quad (\text{S20})$$

183 To separate the contributions of AI and the players' initial predictions, we define the
 184 population's mean reliance on AI, the stochastic AI error remaining after aggregation,

185 and the aggregate contribution of initial predictions associated with each factor:

$$\bar{\beta} = \frac{1}{N} \sum_{j=1}^N \beta_j \quad (\text{S21})$$

$$\bar{\eta} = \frac{1}{N} \sum_{j=1}^N \beta_j \epsilon_j \quad (\text{S22})$$

$$\gamma_i = \frac{1}{N} \sum_{A \in \mathcal{A}_i} (1 - \beta_A) c_A \quad (\text{S23})$$

186 Here, $\bar{\beta}$ represents the mean reliance on AI, $\bar{\eta}$ represents the stochastic AI error
 187 remaining after averaging, and γ_i represents the contribution of players' initial pre-
 188 dictions to factor i . Using these definitions, the revised collective prediction can be
 189 written as follows:

$$\hat{Y}^{re} = \bar{\beta}(Y + B) + \sum_{i=0}^M \gamma_i X_i + \bar{\eta} \quad (\text{S24})$$

190 Thus, the collective prediction consists of an AI-derived component, the contributions
 191 of the players' initial predictions, and the stochastic AI error that remains after
 192 aggregation.

193 Expected payoffs

194 We next derive the expected payoff under each incentive structure. Expectations are
 195 taken over the distributions of the causal factors and stochastic AI errors, conditional
 196 on the current population strategies and the fixed parameters of the prediction target.

197 Feedback

198 Under the feedback structure, a player's payoff depends on the alignment between
 199 their revised prediction and the residual error of the collective prediction. To express
 200 this residual, we first define the remaining error in the intercept and in the coefficient
 201 of each causal factor:

$$\delta_0 = \alpha_0 - (\bar{\beta}(\alpha_0 + B) + \gamma_0), \quad (\text{S25})$$

$$\delta_i = \alpha_i - (\bar{\beta}\alpha_i + \gamma_i), \quad (i \neq 0), \quad (\text{S26})$$

$$Y - \hat{Y}^{re} = \delta_0 + \sum_{i=1}^M \delta_i X_i - \bar{\eta}, \quad (\text{S27})$$

202 where δ_0 represents the remaining error in the intercept, whereas δ_i represents the
 203 remaining error associated with factor i . Because the causal factors and stochastic AI
 204 errors are independent and have zero mean, cross terms vanish when the expectation

is taken. Substituting the revised individual prediction and collective residual into the feedback payoff gives

$$\mathbb{E}(\pi_A) = \mathbb{E}[Y_A^{re}(Y - \hat{Y}^{re})] \quad (\text{S28})$$

$$= \mathbb{E} \left[\left\{ \beta_A \alpha_0 + \beta_A \sum_{i=1}^M \alpha_i X_i + \beta_A B + \beta_A \epsilon + (1 - \beta_A) c_A X_{e_A} \right\} \right] \quad (\text{S29})$$

$$\times \left\{ \delta_0 + \sum_{i=1}^m \delta_i X_i - \bar{\eta} \right\} \quad (\text{S30})$$

$$= \beta_A \alpha_0 \delta_0 + \beta_A \sum_{i=1}^M \delta_i \alpha_i \sigma_i^2 + \beta_A B \delta_0 - \frac{1}{N} \beta_A^2 \tau^2 + (1 - \beta_A) c_A \delta_{e_A} \sigma_{e_A}^2 \quad (\text{S31})$$

$$= \beta_A \left\{ (\alpha_0 + B) \delta_0 + \sum_{i=1}^M \alpha_i \delta_i \sigma_i^2 \right\} + (1 - \beta_A) c_A \delta_{e_A} \sigma_{e_A}^2 - \frac{\beta_A^2 \tau^2}{N} \quad (\text{S32})$$

The first term represents the alignment between the AI-derived prediction and the collective residual, whereas the second term represents the contribution of the player's initial prediction. The final term arises because the stochastic error in player A 's AI prediction also contributes to the collective prediction. This finite-population effect decreases as population size increases.

Niche-expert

Under the niche-expert structure, the payoff is the negative squared error of the revised individual prediction, weighted by the frequency of the player's interest. Because $X_0 = 1$, a player with $e_A = 0$ makes a constant initial prediction. In this case, the expected payoff is:

$$\mathbb{E}(\pi_A) = -\mathbb{E}[\rho_0 (Y_A^{re} - Y)^2] \quad (\text{S33})$$

$$= -\mathbb{E} [\rho_0 \{(\beta_A - 1)Y + \beta_A B + \beta_A \epsilon + (1 - \beta_A) c_A\}^2] \quad (\text{S34})$$

$$= -\mathbb{E} \left[\rho_0 \left\{ (\beta_A - 1)(\alpha_0 - c_A) + \beta_A B + (\beta_A - 1) \sum_{i=1}^M \alpha_i X_i + \beta_A \epsilon \right\}^2 \right] \quad (\text{S35})$$

$$= -\rho_0 \left\{ (1 - \beta_A)^2 (\alpha_0 - c_A)^2 - 2\beta_A (1 - \beta_A) (\alpha_0 - c_A) B + \beta_A^2 B^2 \right. \quad (\text{S36})$$

$$\left. + (1 - \beta_A)^2 \sum_{i \neq 0} \alpha_i^2 \sigma_i^2 + \beta_A^2 \tau^2 \right\} \quad (\text{S37})$$

217 For a player with $e_A \neq 0$, the initial prediction instead depends on the observed value
 218 of factor X_{e_A} . The expected payoff is therefore:

$$\mathbb{E}(\pi_A) = -\mathbb{E}[\rho_{e_A}(Y_A^{re} - Y)^2] \quad (\text{S38})$$

$$= -\mathbb{E}[\rho_{e_A} \{(\beta_A - 1)Y + \beta_A B + \beta_A \epsilon + (1 - \beta_A)c_A X_{e_A}\}^2] \quad (\text{S39})$$

$$= -\mathbb{E}[\rho_{e_A} \{(\beta_A - 1)\alpha_0 + \beta_A B$$

$$+ (\beta_A - 1)(\alpha_{e_A} - c_A)X_{e_A} + (\beta_A - 1) \sum_{i \neq e_A, 0} \alpha_i X_i + \beta_A \epsilon \}^2] \quad (\text{S41})$$

$$= -\rho_{e_A} \left\{ (1 - \beta_A)^2 \alpha_0^2 - 2\beta_A(1 - \beta_A)\alpha_0 B \right. \quad (\text{S42})$$

$$+ \beta_A^2 B^2 + (1 - \beta_A)^2 (\alpha_{e_A} - c_A)^2 \sigma_{e_A}^2 \quad (\text{S43})$$

$$\left. + (1 - \beta_A)^2 \sum_{i \neq e_A, 0} \alpha_i^2 \sigma_i^2 + \beta_A^2 \tau^2 \right\} \quad (\text{S44})$$

219 These expressions separate the contributions of the player's belief, the unobserved
 220 causal factors, systematic AI bias, and stochastic AI error. Increasing reliance on
 221 AI reduces the contribution of errors in the player's initial prediction but increases
 222 their exposure to AI bias and stochastic error.

223 Incentivizing or penalizing AI use

224 Direct incentives add the term $\lambda\beta_A$ to either the feedback or niche-expert payoff.
 225 Because this term is fixed conditional on the player's strategy, its expectation is
 226 simply $\lambda\beta_A$. The expected payoffs therefore become

$$\mathbb{E}(\pi_{A, \text{Feedback}}) = \mathbb{E}[Y_A^{re}(Y - \hat{Y}^{re}) + \lambda\beta_A] = \mathbb{E}[Y_A^{re}(Y - \hat{Y}^{re})] + \lambda\beta_A, \quad (\text{S45})$$

$$\mathbb{E}(\pi_{A, \text{Niche-expert}}) = -\mathbb{E}[\rho_{e_A}(Y_A^{re} - Y)^2 + \lambda\beta_A] = -\mathbb{E}[\rho_{e_A}(Y_A^{re} - Y)^2] + \lambda\beta_A. \quad (\text{S46})$$

227 Thus, a positive value of λ increases the payoff of strategies with greater reliance on
 228 AI, whereas a negative value favors strategies with lower reliance.

229 Expected accuracy

230 Using the residual defined above, the mean squared error of the revised collective
 231 prediction is:

$$\mathbb{E}[(Y - \alpha_0)^2] = \mathbb{E} \left[\left(\alpha_0 + \sum_{i=1}^M \alpha_i X_i - \alpha_0 \right)^2 \right] = \sum_{i=1}^M \alpha_i^2 \sigma_i^2 \quad (\text{S47})$$

$$\mathbb{E}[(Y - \hat{Y}^{re})^2] = \mathbb{E} \left[\left(\delta_0 + \sum_{i=1}^M \delta_i X_i - \hat{\eta} \right)^2 \right] = \delta_0^2 + \sum_{i=1}^M \delta_i^2 \sigma_i^2 + \frac{\tau^2}{N^2} \sum_{j=1}^N \beta_j^2 \quad (\text{S48})$$

232 The expected collective accuracy is therefore

$$R = 1 - \frac{\mathbb{E}[(Y - \hat{Y})^2]}{\mathbb{E}[(Y - \alpha_0)^2]} \quad (\text{S49})$$

$$= 1 - \frac{\delta_0^2 + \sum_{i=1}^M \delta_i^2 \sigma_i^2 + \frac{\tau^2}{N^2} \sum_{j=1}^N \beta_j^2}{\sum_{i=1}^M \alpha_i^2 \sigma_i^2} \quad (\text{S50})$$

233 The collective prediction error consists of the squared error in the intercept, the re-
 234 maining error associated with each causal factor, and the stochastic AI error remain-
 235 ing after averaging across players. Counterfactual collective accuracy is obtained
 236 from the same expression by setting $\beta_A = 0$ for all players while retaining their
 237 evolved interests and beliefs.

238 Chatbot AI

239 Unlike Omniscient AI, Chatbot AI use only the causal factor associated with each
 240 player's interest. This causes the information contained in AI predictions to depend
 241 directly on the distribution of interests in the population. Here, we derive the collec-
 242 tive prediction, expected payoffs, and expected collective accuracy under this form
 243 of AI assistance.

244 Model

245 The prediction generated by Chatbot AI for player A depends on the causal factor
 246 associated with the player's interest:

$$Y_A^{AI} = \alpha_{e_A} X_{e_A} + b_{e_A} + \epsilon, \quad (\text{S51})$$

247 where b_{e_A} represents factor-specific additive bias, and ϵ represents stochastic error.
 248 The stochastic error follows a Gaussian distribution with mean zero and standard
 249 deviation τ and is generated independently across players and prediction events. The
 250 player's initial and revised predictions are given by Player A 's initial and revised
 251 predictions can be then written as follows:

$$Y_A = c_A X_{e_A} \quad (\text{S52})$$

$$Y_A^{re} = \beta_A Y_A^{AI} + (1 - \beta_A) Y_A \quad (\text{S53})$$

252 Here, c_A represents player A 's belief about the effect of their focal factor, e_A repre-
 253 sents their interest, and β_A represents their reliance on AI. Thus, the revised predic-
 254 tion remains specific to the single factor associated with the player's interest.

255 Aggregation

256 Because both the player's initial prediction and the Chatbot AI prediction contain
 257 information about the same causal factor, we use clustering aggregation. Revised
 258 predictions are first averaged among players interested in the same factor and then
 259 summed across represented interests:

$$\hat{Y}^{re} = \sum_{i=0}^M \frac{1}{n_i} \sum_{A \in \mathcal{A}_i} Y_A^{re} \quad (\text{S54})$$

$$= \sum_{i=0}^M \frac{1}{n_i} \sum_{A \in \mathcal{A}_i} \{ \beta_A Y_A^{AI} + (1 - \beta_A) Y_A \} \quad (\text{S55})$$

$$= \sum_{i=0}^M \frac{1}{n_i} \sum_{A \in \mathcal{A}_i} [\{ \beta_A \alpha_{e_A} + (1 - \beta_A) c_A \} X_{e_A} + \beta_A b_{e_A} + \beta_A \epsilon], \quad (\text{S56})$$

260 where $\mathcal{A}_i$ is the set of players interested in factor i , and $n_i = |\mathcal{A}_i|$ is the number of
 261 players in that set.

262 To simplify the collective prediction, we define the effective coefficient, weighted
 263 AI bias, and stochastic error associated with each interest group:

$$\tilde{c}_i = \frac{1}{n_i} \sum_{A \in \mathcal{A}_i} \{ \beta_A \alpha_{e_A} + (1 - \beta_A) c_A \}, \quad (\text{S57})$$

$$\tilde{B}_i = \frac{1}{n_i} \sum_{A \in \mathcal{A}_i} \beta_A b_{e_A}, \quad (\text{S58})$$

$$\bar{B} = \sum_{i=0}^M \tilde{B}_i, \quad (\text{S59})$$

$$\tilde{\eta}_i = \frac{1}{n_i} \sum_{A \in \mathcal{A}_i} \beta_A \epsilon, \quad (\text{S60})$$

$$\bar{\eta} = \sum_{i=0}^M \tilde{\eta}_i, \quad (\text{S61})$$

264 where $\tilde{c}_i$ represents the mean effective coefficient for factor i after AI assistance,
 265 whereas $\tilde{B}_i$ and $\tilde{\eta}_i$ represent its systematic and stochastic error components. Thus,
 266 the collective prediction can be written as:

$$\hat{Y}^{re} = \sum_{i \in \mathcal{I}} \tilde{c}_i X_i + \bar{B} + \bar{\eta}, \quad (\text{S62})$$

267 where $\mathcal{I} = \{i \in \{0, \dots, M\} > 0\}$ denotes the set of represented interests.

268 Expected payoffs

269 We next derive the expected payoff under each incentive structure. Expectations are
 270 taken over the causal factors and stochastic AI errors, conditional on the current
 271 population strategies and the fixed parameters of the prediction target.

272 Feedback

273 Under the feedback structure, players are rewarded according to whether their revised
 274 predictions reduce the error in the collective prediction. We therefore define the
 275 remaining errors in the intercept and factor-specific coefficients as

$$\delta_0 = \alpha_0 - \tilde{c}_0 - \bar{B}, \quad (\text{S63})$$

$$\delta_i = \alpha_i - \tilde{c}_i, \quad (i \neq 0), \quad (\text{S64})$$

$$Y - \hat{Y}^{re} = \delta_0 + \sum_{i=1}^M \delta_i X_i - \bar{\eta}, \quad (\text{S65})$$

276 where δ_0 includes the remaining error in the intercept and the total additive AI bias,
 277 whereas δ_i measures the remaining error in the coefficient of factor i . Because the
 278 causal factors and stochastic errors are independent and have zero mean, substituting
 279 the revised individual prediction into the feedback payoff gives

$$\mathbb{E}(\pi_A) = \mathbb{E}[Y_A^{re}(Y - \hat{Y}^{re})] \quad (\text{S66})$$

$$= \mathbb{E}[\{(\beta_A \alpha_{e_A} + (1 - \beta_A) c_A) X_{e_A} + \beta_A b_{e_A} + \beta_A \epsilon\} \quad (\text{S67})$$

$$\times \left\{ \delta_0 + \sum_{i=1}^M \delta_i X_i - \bar{\eta} \right\}] \quad (\text{S68})$$

$$= \{\beta_A \alpha_{e_A} + (1 - \beta_A) c_A\} \delta_{e_A} \sigma_{e_A}^2 + \beta_A b_{e_A} \delta_0 - \frac{1}{n_{e_A}} \beta_A^2 \tau^2 \quad (\text{S69})$$

280 Thus, the expected feedback payoff depends on the remaining collective error asso-
 281 ciated with the player's interest, the contribution of factor-specific AI bias to the
 282 intercept error, and the player's contribution to the stochastic error of their interest
 283 group.

284 Niche-expert

285 Under the niche-expert structure, the negative squared error of each revised indi-
 286 vidual prediction is weighted by the frequency of the player's interest. We consider
 287 $e_A = 0$ separately because these players make constant predictions rather than factor-

288 dependent predictions. When $e_A = 0$, the expected payoff is

$$\mathbb{E}(\pi_A) = -\mathbb{E}[\rho_0(Y_A^{re} - Y)^2] \quad (S70)$$

$$= -\mathbb{E} \left[\rho_0 \left[\{\beta_A \alpha_0 + (1 - \beta_A)c_A\} + \beta_A b_0 + \beta_A \epsilon - \alpha_0 - \sum_{i=1}^M \alpha_i X_i \right]^2 \right] \quad (S71)$$

$$= -\rho_0 \left\{ (1 - \beta_A)^2 (c_A - \alpha_0)^2 + 2(1 - \beta_A)(c_A - \alpha_0)\beta_A b_0 + \beta_A^2 b_0^2 \right. \quad (S72)$$

$$\left. + \sum_{i \neq 0} \alpha_i^2 \sigma_i^2 + \beta_A^2 \tau^2 \right\} \quad (S73)$$

289 When $e_A \neq 0$, the player's prediction varies with their focal causal factor. The
290 expected payoff is then

$$\mathbb{E}(\pi_A) = -\mathbb{E}[\rho_{e_A}(Y_A^{re} - Y)^2] \quad (S74)$$

$$= -\mathbb{E} [\rho_{e_A} [\{\beta_A \alpha_{e_A} + (1 - \beta_A)c_A\} X_{e_A} \quad (S75)$$

$$+ \beta_A b_{e_A} + \beta_A \epsilon - \alpha_0 - \sum_{i=1}^M \alpha_i X_i]^2] \quad (S76)$$

$$= -\rho_{e_A} \left\{ (1 - \beta_A)^2 (c_A - \alpha_{e_A})^2 \sigma_{e_A}^2 + \sum_{i \neq e_A, 0} \alpha_i^2 \sigma_i^2 \right. \quad (S77)$$

$$\left. + \alpha_0^2 + \beta_A^2 b_{e_A}^2 - 2\alpha_0 \beta_A b_{e_A} + \beta_A^2 \tau^2 \right\} \quad (S78)$$

291 In both cases, the expected squared error consists of the mismatch between the
292 player's belief and the true coefficient, contributions from causal factors omitted
293 from the individual prediction, factor-specific AI bias, and stochastic AI error. The
294 niche-expert weight ρ_{e_A} scales these errors according to the frequency of the player's
295 interest.

296 Incentivizing or penalizing AI use

297 Directly incentivizing or penalizing AI use adds the term $\lambda \beta_A$ to the player's payoff.
298 Because this term is fixed conditional on the player's strategy, it can be taken outside
299 the expectation. The expected payoffs are therefore

$$\mathbb{E}(\pi_{A, Feedback}) = \mathbb{E} \left[Y_A^{re} (Y - \hat{Y}^{re}) + \lambda \beta_A \right] \quad (S79)$$

$$= \mathbb{E} \left[Y_A^{re} (Y - \hat{Y}^{re}) \right] + \lambda \beta_A, \quad (S80)$$

$$\mathbb{E}(\pi_{A, Niche-expert}) = -\mathbb{E} [\rho_{e_A} (Y_A^{re} - Y)^2 + \lambda \beta_A] \quad (S81)$$

$$= -\mathbb{E} [\rho_{e_A} (Y_A^{re} - Y)^2] + \lambda \beta_A. \quad (S82)$$

300 **Balanced**

301 Under the balanced structure, the payoff corresponds to the arithmetic mean of the
302 feedback and niche-expert payoff components:

$$\mathbb{E}(\pi_A) = \mathbb{E} \left[\frac{Y_A^{\text{re}}(Y - \hat{Y}^{\text{re}}) - \rho_{e_A}(Y_A^{\text{re}} - Y)^2}{2} \right] \quad (\text{S83})$$

$$= \frac{\mathbb{E} \left[Y_A^{\text{re}}(Y - \hat{Y}^{\text{re}}) \right] - \mathbb{E} [\rho_{e_A}(Y_A^{\text{re}} - Y)^2]}{2} \quad (\text{S84})$$

303 The expected payoff under the balanced structure can therefore be calculated directly
304 from the feedback and niche-expert payoffs derived above.

305 **Expected accuracy**

306 Finally, we derive the expected collective accuracy under clustering aggregation.
307 The intercept α_0 serves as the baseline prediction. Because the causal factors are
308 independent and have mean zero, its expected squared error is

$$\mathbb{E}[(Y - \alpha_0)^2] = \mathbb{E} \left[\left(\alpha_0 + \sum_{i=1}^M \alpha_i X_i - \alpha_0 \right)^2 \right] = \sum_{i=1}^M \alpha_i^2 \sigma_i^2 \quad (\text{S85})$$

309 Using the expression for the collective residual above, the expected squared error of
310 the revised collective prediction is

$$\mathbb{E}[(Y - \hat{Y})^2] = \mathbb{E} \left[\left(\delta_0 + \sum_{i=1}^M \delta_i X_i - \hat{\eta} \right)^2 \right] = \delta_0^2 + \sum_{i=1}^M \delta_i^2 \sigma_i^2 + \sum_{i=0}^M \frac{\tau^2}{n_i^2} \sum_{A \in \mathcal{A}_i} \beta_A^2 \quad (\text{S86})$$

311 The first two terms represent squared errors in the intercept and factor-specific coef-
312 ficients. The final term represents the stochastic AI error remaining after predictions
313 are averaged within each interest group. Thus, stochastic error has a larger effect
314 when an interest is represented by fewer individuals. Normalizing this error relative
315 to the baseline gives:

$$R = 1 - \frac{\mathbb{E}[(Y - \hat{Y})^2]}{\mathbb{E}[(Y - \alpha_0)^2]} \quad (\text{S87})$$

$$= 1 - \frac{\delta_0^2 + \sum_{i=1}^M \delta_i^2 \sigma_i^2 + \sum_{i=0}^M \frac{\tau^2}{n_i^2} \sum_{A \in \mathcal{A}_i} \beta_A^2}{\sum_{i=1}^M \alpha_i^2 \sigma_i^2} \quad (\text{S88})$$

316 Here, $R = 1$ represents perfect collective prediction, $R = 0$ represents performance
317 equal to the baseline, and $R < 0$ represents performance worse than the baseline.

318 Evolutionary dynamics

319 Following previous work (Wang et al., 2025; Taylor and Jonker, 1978; Traulsen et al.,
 320 2005), we use replicator dynamics as a deterministic large-population approximation
 321 to characterize equilibrium states and their local stability. The agent-based sim-
 322 ulations themselves follow the Fermi imitation rule defined above. At equal-payoff
 323 stationary states, the replicator and Fermi formulations imply the same local invasion
 324 directions for any finite selection strength $s > 0$, although their transient dynamics
 325 need not coincide. We focus on the feedback and niche-expert structures, for which
 326 the long-term dynamics can be characterized analytically. The direct interventions
 327 on AI use and the balanced structure are examined through simulations.

328 Let λ denote a strategy, p_λ its frequency, and $u_\lambda = \mathbb{E}(\pi_\lambda)$ its expected payoff.
 329 Then, the corresponding replicator equation can be written as:

$$\frac{dp_\lambda}{dt} = p_\lambda(u_\lambda - \bar{u}), \quad (\text{S89})$$

330 where $\bar{u} = \sum_\lambda p_\lambda u_\lambda$ represents the mean expected payoff of the population. At an
 331 internal stationary state, all strategies with positive frequency must have the same
 332 expected payoff. A boundary state can also be stationary because a strategy with zero
 333 frequency cannot increase unless it is introduced into the population. We therefore
 334 assess the stability of boundary states by asking whether they can be invaded by a
 335 rare alternative strategy.

336 Omniscient AI

337 With Omniscient AI, every AI prediction contains information about the full predic-
 338 tion target, and revised predictions are combined through averaging. As population
 339 size increases, independent AI errors vanish from the collective prediction. How-
 340 ever, these errors remain in individual prediction errors and can therefore continue
 341 to affect niche-expert payoffs. We consider the two incentive structures separately.

342 Feedback

343 Under the feedback structure, both the stochastic error in the collective prediction,
 344 $\bar{\eta}$, and its contribution to expected payoff vanish as $N \rightarrow \infty$. Following previous
 345 work (Wang et al., 2025), we define the Lyapunov function as the expected error of
 346 collective prediction:

$$V = \mathbb{E} \left[(Y - \hat{Y}^{re})^2 \right]. \quad (\text{S90})$$

347 The function V is non-negative and equals zero when the collective prediction is
 348 identical to the target. To determine how V changes over time, we take its time

349 derivative:

$$\frac{dV}{dt} = -2\mathbb{E} \left[(Y - \hat{Y}^{re}) \frac{d\hat{Y}^{re}}{dt} \right] \quad (\text{S91})$$

$$= -2\mathbb{E} \left[\left(\delta_0 + \sum_{i=1}^M \delta_i X_i \right) \left\{ \frac{d\bar{\beta}}{dt} (Y + B) + \sum_{i=0}^M \frac{d\gamma_i}{dt} X_i \right\} \right] \quad (\text{S92})$$

$$= -2 \left[\left\{ (\alpha_0 + B)\delta_0 + \sum_{i=1}^M \alpha_i \delta_i \sigma_i^2 \right\} \frac{d\bar{\beta}}{dt} + \delta_0 \frac{d\gamma_0}{dt} + \sum_{i=1}^M \delta_i \sigma_i^2 \frac{d\gamma_i}{dt} \right]. \quad (\text{S93})$$

350 For notational convenience, we define

$$K = (\alpha_0 + B)\delta_0 + \sum_{i=1}^M \alpha_i \delta_i \sigma_i^2. \quad (\text{S94})$$

351 Although K changes with the population state, it is common to all strategies at a
 352 given state and can therefore be treated as a constant with respect to the strategy
 353 index λ . We also define:

$$G_e = \begin{cases} \delta_0, & e = 0, \\ \delta_e \sigma_e^2, & e \neq 0. \end{cases} \quad (\text{S95})$$

354 Under the replicator equation, the rate of change in the population mean of a
 355 strategy component is given by its covariance with expected payoff.

$$\frac{d\bar{\beta}}{dt} = \sum_{\lambda} p_{\lambda} (u_{\lambda} - \bar{u}) \beta_{\lambda} = \text{Cov}(\beta, u). \quad (\text{S96})$$

356 Similarly, the terms involving γ_i can be combined as

$$\delta_0 \frac{d\gamma_0}{dt} + \sum_{i=1}^M \delta_i \sigma_i^2 \frac{d\gamma_i}{dt} = \text{Cov}((1 - \beta)cG_e, u). \quad (\text{S97})$$

357 Therefore,

$$\frac{dV}{dt} = -2 \{ K \text{Cov}(\beta, u) + \text{Cov}((1 - \beta)cG_e, u) \} \quad (\text{S98})$$

$$= -2 \text{Cov}(K\beta + (1 - \beta)cG_e, u). \quad (\text{S99})$$

358 For the feedback structure in the limit $N \rightarrow \infty$, the expected payoff of strategy
 359 λ is

$$u_{\lambda} = K\beta_{\lambda} + (1 - \beta_{\lambda})c_{\lambda}G_{e_{\lambda}}. \quad (\text{S100})$$

360 This expected payoff is identical to the quantity inside the covariance above. There-
 361 fore,

$$\frac{dV}{dt} = -2 \text{Cov}(u, u) = -2 \text{Var}(u) \leq 0. \quad (\text{S101})$$

Because payoff variance is non-negative, the expected collective prediction error cannot increase and decreases whenever the strategies currently represented in the population differ in their expected payoffs. The derivative becomes zero when all represented strategies receive the same expected payoff. However, this condition does not necessarily imply that $V = 0$, because a population can lack strategies that would improve its collective prediction.

If $V > 0$, at least one component of the collective residual remains nonzero. A rare strategy whose prediction is aligned with this residual can obtain a higher expected payoff than the resident strategies and invade the population. Thus, provided that novel strategies can be introduced, an evolutionarily stable state must satisfy $V = 0$. At such a state, $\hat{Y}^{\text{re}} = Y$, and collective accuracy reaches $R = 1$.

Therefore, the expected error of collective prediction cannot increase during the evolutionary process and decreases whenever strategies differ in their expected payoffs. The derivative becomes zero when the variance of expected payoffs is zero, $\text{Var}(u) = 0$. This condition arises when all represented strategies receive the same expected payoff. However, this condition does not necessarily imply that $V = 0$, because a population can lack strategies that would improve its collective prediction.

If $V > 0$, at least one component of the collective residual remains nonzero. A rare strategy whose prediction is aligned with this residual can obtain a higher expected payoff than the resident strategies and invade the population. Thus, provided that novel strategies can be introduced, an evolutionarily stable state must satisfy $V = 0$. At such a state, $\hat{Y}^{\text{re}} = Y$, and collective accuracy reaches $R = 1$.

Niche-expert

Unlike feedback payoffs, niche-expert payoffs depend on the prediction error of each individual. Stochastic AI error therefore remains in the expected payoff even when $N \rightarrow \infty$, and we retain $\tau > 0$ throughout this analysis.

We first consider strategies having the same interest by optimizing the expected payoff with respect to c and β . For a nonzero interest e , the expected payoff is strictly concave with respect to c for $\beta < 1$ and $\sigma_e > 0$, and is maximized at

$$c_e^* = \alpha_e. \quad (\text{S102})$$

After substituting $c_e^* = \alpha_e$, the payoff is strictly concave with respect to β . Its unconstrained stationary point is then:

$$\tilde{\beta}_e = \frac{\alpha_0^2 + \alpha_0 B + \sum_{j \neq e, 0} \alpha_j^2 \sigma_j^2}{(\alpha_0 + B)^2 + \sum_{j \neq e, 0} \alpha_j^2 \sigma_j^2 + \tau^2}. \quad (\text{S103})$$

Because β is constrained between 0 and 1, the optimal β_e^* is $\tilde{\beta}_e$ when $0 < \tilde{\beta}_e < 1$, and otherwise lies at the corresponding boundary, $\beta_e^* = 0$ or $\beta_e^* = 1$. Thus, the boundary cases do not require a separate evolutionary argument; they only change the optimal prediction and its minimum expected squared error. When $\beta_e^* = 1$, the

revised prediction is independent of c_e , so different values of c_e are selectively neutral and can be treated as a single payoff-equivalent strategy class.

To compare the optimized strategies across interests, let L_e denote the minimum expected individual squared error within interest e , $\mathbb{E}[(Y_A^{re} - Y)^2]$. For an internal optimum,

$$L_e = \frac{B^2 \sum_{j \neq e, 0} \alpha_j^2 \sigma_j^2 + \tau^2 \left(\alpha_0^2 + \sum_{j \neq e, 0} \alpha_j^2 \sigma_j^2 \right)}{(\alpha_0 + B)^2 + \sum_{j \neq e, 0} \alpha_j^2 \sigma_j^2 + \tau^2}. \quad (\text{S104})$$

If the optimum is located at $\beta_e^* = 0$ or $\beta_e^* = 1$, L_e is instead obtained by evaluating the expected squared prediction error at the corresponding boundary.

Interest 0 must be considered separately because $X_0 = 1$ and the player's belief determines a constant prediction. Optimizing with respect to c gives

$$c_0^*(\beta) = \alpha_0 - \frac{\beta}{1 - \beta} B. \quad (\text{S105})$$

Substituting this into the expected payoff gives a strictly concave function of β , with the unique optimum:

$$\beta_0^* = \frac{\sum_{j=1}^M \alpha_j^2 \sigma_j^2}{\sum_{j=1}^M \alpha_j^2 \sigma_j^2 + \tau^2}. \quad (\text{S106})$$

Therefore,

$$c_0^* = \alpha_0 - \frac{B}{\tau^2} \sum_{j=1}^M \alpha_j^2 \sigma_j^2, \quad (\text{S107})$$

and

$$L_0 = \frac{\tau^2 \sum_{j=1}^M \alpha_j^2 \sigma_j^2}{\sum_{j=1}^M \alpha_j^2 \sigma_j^2 + \tau^2}. \quad (\text{S108})$$

At this optimum, the player adjusts their belief to offset the systematic AI bias. The stochastic component of AI error cannot be removed in the same way and therefore limits the benefit of AI reliance.

We denote the optimal strategy within interest e by S_e . When $\beta_e^* = 1$, different values of c_e are selectively neutral and can be treated as a single payoff-equivalent strategy class. A stable state can contain only the optimal strategy class within each represented interest because a suboptimal strategy can be invaded by S_e .

We next consider the frequencies of the $M + 1$ optimal strategies. Let ρ_e denote the frequency of S_e . Its expected payoff is

$$u_e = -\rho_e L_e. \quad (\text{S109})$$

Assuming $L_e > 0$ for all interests, the equal-payoff condition of the replicator equation at an internal stationary state gives

$$\rho_0^* L_0 = \rho_1^* L_1 = \cdots = \rho_M^* L_M. \quad (\text{S110})$$

421 Together with $\sum_{e=0}^M \rho_e^* = 1$, this uniquely determines

$$\rho_e^* = \frac{D}{L_e}, \quad D = \left(\sum_{j=0}^M \frac{1}{L_j} \right)^{-1}. \quad (\text{S111})$$

422 This internal stationary state is locally stable. At equilibrium, all represented in-
 423 terests have the same expected payoff, with $\rho_e^* L_e = D$. If the frequency of one
 424 interest increases slightly above its equilibrium value, its payoff decreases because
 425 the niche-expert payoff is proportional to $-\rho_e L_e$. Conversely, if the frequency of an
 426 interest decreases below its equilibrium value, its payoff increases. The replicator dy-
 427 namics therefore generate a restoring force that reduces small deviations in interest
 428 frequencies and drives the population back toward the internal stationary state.

429 If one or more interests are absent, the resulting boundary state can be stationary
 430 under the replicator equation, but it is unstable against invasion. The payoff of a rare
 431 absent interest approaches zero as $\rho_e \rightarrow 0$, whereas the mean payoff of the resident
 432 population is negative when $L_e > 0$, so the rare interest increases when introduced
 433 at sufficiently small frequency.

434 Thus, there exists a unique stable full-support equilibrium in terms of the optimal
 435 prediction strategies and their frequencies. Whether the constrained optimum has
 436 $\beta_e^* = 0$, $0 < \beta_e^* < 1$, or $\beta_e^* = 1$ does not change the frequency argument, because
 437 these cases differ only through the resulting value of L_e . When $\beta_e^* = 1$, the strategy
 438 is selectively neutral with respect to c_e , but its prediction, payoff, and equilibrium
 439 interest frequency remain uniquely determined.

440 Having characterized this equilibrium, we next compare its collective prediction
 441 with a prediction made entirely by AI. In particular, the expected squared error of
 442 an Omniscient AI prediction is

$$\mathbb{E} [(Y - Y^{\text{AI}})^2] = B^2 + \tau^2. \quad (\text{S112})$$

443 For every interest, complete reliance on AI, $\beta = 1$, is a feasible strategy. There-
 444 fore, because L_e is the minimum individual expected squared prediction error within
 445 interest e ,

$$L_e \leq B^2 + \tau^2. \quad (\text{S113})$$

446 Moreover, for interest 0,

$$L_0 = \frac{\tau^2 \sum_{j=1}^M \alpha_j^2 \sigma_j^2}{\sum_{j=1}^M \alpha_j^2 \sigma_j^2 + \tau^2} < \tau^2 \leq B^2 + \tau^2. \quad (\text{S114})$$

447 Because the stable equilibrium has $\rho_0^* > 0$,

$$\sum_{e=0}^M \rho_e^* L_e < B^2 + \tau^2. \quad (\text{S115})$$

448 The collective prediction is the average of individual revised predictions. By convex-
 449 ity of the squared error,

$$\mathbb{E} \left[(Y - \hat{Y}^{re})^2 \right] \leq \sum_{e=0}^M \rho_e^* L_e. \quad (\text{S116})$$

450 Therefore,

$$\mathbb{E} \left[(Y - \hat{Y}^{re})^2 \right] < \mathbb{E} \left[(Y - Y^{\text{AI}})^2 \right]. \quad (\text{S117})$$

451 Thus, the diversity of optimized predictions allows the population to outperform an
 452 individual AI prediction at equilibrium.

453 However, outperforming AI does not imply perfect collective accuracy. Under
 454 averaging, the non-AI contribution associated with a particular factor is provided
 455 only by individuals interested in that factor. The predictions of individuals with
 456 other interests therefore attenuate that factor's coefficient in the collective prediction.
 457 For a nonzero factor i , the residual coefficient of the stationary collective prediction
 458 can be written as

$$\delta_i^* = \alpha_i \left\{ 1 - \bar{\beta}^* - \rho_i^* (1 - \beta_i^*) \right\} = \alpha_i \sum_{e \neq i} \rho_e^* (1 - \beta_e^*). \quad (\text{S118})$$

459 At the stable equilibrium, $\rho_0^* > 0$. In addition, $\tau > 0$ implies $\beta_0^* < 1$. Therefore, for
 460 every factor with $\alpha_i \neq 0$,

$$\delta_i^* \neq 0. \quad (\text{S119})$$

461 Because $\sum_{i=1}^M \alpha_i^2 \sigma_i^2 > 0$, at least one factor contributes positive prediction error.
 462 Hence,

$$\mathbb{E} \left[(Y - \hat{Y}^{re})^2 \right] > 0, \quad (\text{S120})$$

463 and consequently the stationary collective accuracy satisfies $R^* < 1$. Thus, the niche-
 464 expert structure preserves interest diversity and allows the population to outperform
 465 AI, but averaging prevents the population from reaching perfect collective accuracy.

Supplementary Figure




Figure S1: **Niche-expert structure with averaging aggregation cannot promote CI without AI.** Trajectories of the mean absolute error from true coefficients and collective accuracy under the niche-expert structure with averaging aggregation in the absence of AI. The mean absolute error from true coefficients is calculated by first taking, for each interest, the absolute difference between the true coefficient and the mean belief of individuals sharing that interest, and then averaging these differences across all $m + 1$ interests. The mean absolute error decreases across generations, indicating that the mean beliefs converge toward their corresponding true coefficients. However, collective accuracy remains near zero, indicating that simply averaging individual predictions does not yield accurate collective predictions. Prediction target parameters: $m = 50$, $s = 50$, $\mu = 0$, $\alpha_i \sim U(-5, 5)$, and $\sigma_i \sim U(0, 3)$. Population parameters: $N = 10,000$, $c_A \sim \mathcal{N}(0, 100^2)$.




Figure S2: **Evaluation metrics across various levels of AI bias.** Evaluation metrics across varying levels of AI bias under different assumptions about AI types (Omniscient AI, and Chatbot AI) and incentive structures (feedback, niche-expert). Larger absolute AI bias indicates a less accurate AI model. Across the range of AI bias considered, AI accuracy varies from approximately 0.24 to nearly 1 when the AI predicts the target independently. Dashed horizontal lines represent the values of the evaluation metrics when the group is not assisted by AI. Collective accuracy represents the predictive performance of the group, and counterfactual human CI represents the group’s predictive accuracy if AI assistance were unavailable at the given generation. Interest diversity is defined as Hill-Shannon diversity of interest within the population, median reliance on AI represents the median value of reliance on AI (β). Collective bias represents systematic deviation of the collective prediction from the true target, collective variance represents variability of the collective prediction error across prediction events. All the evaluation metrics are averaged over generations 190,000–200,000. Prediction target parameters: $m = 50$, $s = 50$, $\mu = 0$, $\alpha_i \sim U(-5, 5)$, and $\sigma_i \sim U(0, 3)$. Population parameters: $N = 10,000$, $c_A \sim \mathcal{N}(0, 100^2)$ for (A, B), $c_A \sim \mathcal{N}(0, 5^2)$ for (C, D), and $\beta_A \sim U(0, 1)$. AI parameters: $\tau = 0.3$.




Figure S3: **Comparison of evaluation metrics with and without AI.** Trajectories of evaluation metrics when the group is assisted by the Omniscient AI and Chatbot AI. Here, feedback and niche-expert incentive structures are considered. Blue lines represent trajectories of evaluation metrics without AI assistance. Orange lines represent trajectories of evaluation metrics with AI assistance. Interest diversity is define as Hill-Shannon diversity of interest within population, median reliance on AI represent population median of reliance on AI (β), collective bias represent systematic deviation of the collective prediction from the true target, collective variance represent variability of the collective prediction error across prediction events. Prediction target parameters: $m = 50$, $s = 50$, $\mu = 0$, $\alpha_i \sim U(-5, 5)$, and $\sigma_i \sim U(0, 3)$. Population parameters: $N = 10,000$, $c_A \sim \mathcal{N}(0, 100^2)$ for (A, B), $c_A \sim \mathcal{N}(0, 5^2)$ for (C, D), and $\beta_A \sim U(0, 1)$. AI parameters: $b_i = 0.36$ and $\tau = 0.3$.





Figure S4: **Feedback structure becomes more prone to interest diversity loss with AI** Trajectories of interest diversity with and without AI under the feedback structure (A). Heatmaps of interest diversity across varying levels of mutation rate (B, C) and the standard deviation of the initial belief distribution (D, E), with and without AI. Interest diversity declines toward zero even without AI over long timescales when there is no mutation and the initial belief distribution is narrow. However, with AI, interest diversity declines more strongly, even under moderate mutation rates and wider initial belief distributions. Interest diversity in the heatmaps is averaged over generations 190,000–200,000. Prediction target parameters: $m = 50$, $s = 50$, $\mu = 0$ for (D, E), $\alpha_i \sim U(-5, 5)$, and $\sigma_i \sim U(0, 3)$. Population parameters: $N = 10,000$, $c_A \sim \mathcal{N}(0, 5^2)$ for (A, B, C), and $\beta_A \sim U(0, 1)$. AI parameters: $b_i = 0.4$ and $\tau = 0.3$, Chatbot AI is used.




Figure S5: **Niche-expert structure may reduce reliance on AI, delaying the emergence of CI.** Trajectories of collective accuracy and median reliance on AI when the niche-expert structure causes reliance on AI to decline over time. Red lines represent trajectories with AI across varying levels of AI bias (-0.2, -0.4, and -0.6). Green lines represent trajectories without AI; reliance on AI is set to zero in the absence of AI. This reduction in reliance on AI occurs when the α_0 and AI bias have opposite signs, and is associated with the eventual emergence of CI, although CI emerges substantially later than in the condition without AI. Prediction target parameters: $m = 50$, $s = 50$, $\mu = 0$, $\alpha_i \sim U(-5, 5)$, and $\sigma_i \sim U(0, 3)$. Population parameters: $N = 10,000$, $c_A \sim \mathcal{N}(0, 5^2)$, and $\beta_A \sim U(0, 1)$. AI parameters: $\tau = 0.3$, Chatbot AI is used.




Figure S6: **Comparison of evaluation metrics between incentive structures across various levels of AI bias.** Evaluation metrics under feedback, niche-expert and balanced structures across varying levels of AI bias. Larger absolute AI bias indicates a less accurate AI model. Across the range of AI bias considered, AI accuracy varies from approximately 0.24 to nearly 1 when the AI predicts the target independently. All the evaluation metrics are averaged over generations 190,000–200,000. The balanced structure maintains near-perfect collective accuracy across bias levels and higher counterfactual human CI than the other incentive structures. These patterns are driven by well-calibrated reliance on AI, which increases as AI becomes more accurate, and by well-preserved interest diversity, which together lead to low collective variance and collective bias. Prediction target parameters: $m = 50$, $s = 50$, $\mu = 0$, $\alpha_i \sim U(-5, 5)$, and $\sigma_i \sim U(0, 3)$. Population parameters: $N = 10,000$, $c_A \sim \mathcal{N}(0, 5^2)$, and $\beta_A \sim U(0, 1)$. AI parameters: $\tau = 0.3$, Chatbot AI is used.




Figure S7: **Balanced structure is robust across varying balancing weights.** Evaluation metrics across varying levels of the balancing weight (0.1 – 0.9). The balancing weight represents the weight assigned to the niche-expert structure when constructing the balanced structure by combining the niche-expert and feedback structures. A balancing weight of 0.5 represents equal weighting of the niche-expert and feedback structures, whereas 0 corresponds to the feedback structure and 1 corresponds to the niche-expert structure. Although the evaluation metrics vary as the balancing weight changes from 0.1 to 0.9, the absolute magnitude of these deviations remains limited. Prediction target parameters: $m = 50$, $s = 50$, $\mu = 0$, $\alpha_i \sim U(-5, 5)$, and $\sigma_i \sim U(0, 3)$. Population parameters: $N = 10,000$, $c_A \sim \mathcal{N}(0, 5^2)$, and $\beta_A \sim U(0, 1)$. AI parameters: $b_i = 0.4$, $\tau = 0.3$, Chatbot AI is used.




Figure S8: **Balanced structure shows well-calibrated reliance on AI.** Median reliance on AI across varying levels of AI bias. Thirty randomly initialized simulations were performed for each bias level. Each dot represents a single simulation, and the box plots show the median and interquartile range (IQR) for each bias level. The balanced structure shows well-calibrated reliance on AI, with reliance increasing as AI bias decreases. Prediction target parameters: $m = 50$, $s = 50$, $\mu = 0$, $\alpha_i \sim U(-5, 5)$, and $\sigma_i \sim U(0, 3)$. Population parameters: $N = 10,000$, $c_A \sim \mathcal{N}(0, 5^2)$, and $\beta_A \sim U(0, 1)$. AI parameters: $\tau = 0.3$, Chatbot AI is used.

Table S1: Evaluation metrics used to analyze collective prediction dynamics.

Metric	Definition	Interpretation
Collective accuracy	$1 - \frac{\mathbb{E}[(Y - \hat{Y}^{\text{re}})^2]}{\mathbb{E}[(Y - \alpha_0)^2]}$	Accuracy of the revised collective prediction relative to the baseline prediction α_0 .
Collective bias	$\left(\mathbb{E}[Y - \hat{Y}^{\text{re}}]\right)^2$	Squared expected deviation of the revised collective prediction from the true target.
Collective variance	$\text{Var}(Y - \hat{Y}^{\text{re}})$	Variability of the revised collective prediction error across prediction events.
Counterfactual collective accuracy	$1 - \frac{\mathbb{E}[(Y - \hat{Y})^2]}{\mathbb{E}[(Y - \alpha_0)^2]}$	Accuracy obtained after removing AI use from the current population while retaining its evolved interests and beliefs.
Interest diversity	$\exp\left(-\sum_{i=0}^M \rho_i \ln \rho_i\right)$	Effective number of interests represented in the population.
Median reliance on AI	$\text{median}_{A \in N}(\beta_A)$	Median reliance on AI in the population.

467 **References**

- 468 Hong, L., S. E. Page, and M. Riolo (2012). Incentives, information, and emergent
469 collective accuracy. *Managerial and Decision Economics* 33(5-6), 323–334.
- 470 Mann, R. P. and D. Helbing (2017). Optimal incentives for collective intelligence.
471 *Proceedings of the National Academy of Sciences* 114(20), 5077–5082.
- 472 Taylor, P. D. and L. B. Jonker (1978). Evolutionary stable strategies and game
473 dynamics. *Mathematical biosciences* 40(1-2), 145–156.
- 474 Traulsen, A., J. C. Claussen, and C. Hauert (2005). Coevolutionary dynamics: from
475 finite to infinite populations. *Physical review letters* 95(23), 238701.
- 476 Wang, G., Q. Su, L. Wang, and J. B. Plotkin (2025). Individual incentives that
477 promote collective intelligence. *Proceedings of the National Academy of Sci-*
478 *ences* 122(51), e2516535122.