

Personalized AI assistants could either promote or hinder the emergence of collective intelligence

Jaeseung Kim¹ Sang Woo Park^{1,2,3,*}

¹ School of Biological Sciences, Seoul National University, Seoul, Korea

*Corresponding author: sangwoopark@snu.ac.kr

Abstract

Advances in artificial intelligence (AI) have enabled the wide use of personalized assistance for cognitive tasks, which enhanced individual performance on various fields. However, the impact of AI assistance on collective intelligence remains poorly understood. AI assistance may undermine the emergence of collective intelligence by reducing the individual diversity or introducing structured biases into a population. Here, we develop a human-AI collective prediction model mediated by social learning based on incentive structure by extending the existing works on collective intelligence. Our model uncovers that emergence of collective intelligence is depend on how human and AI interact. When AI works as if it is omniscient and gives assistance regardless of users' interests, collective intelligence will be promoted. However, when AI works as a chat-bot and gives assistance only based on users' interests, collective intelligence could be hindered due to diversity loss and overconfidence on AI. We showed that, to promote collective intelligence, penalizing or incentivizing AI usage is not reliable. Instead, elaborating more diversity-aware incentives could be the key to promote and maintain the collective intelligence.

24 Introduction

25 Collective intelligence (CI) describes a phenomenon in which a group’s ability to solve
26 problems, make decisions, or adapt to changing environments exceeds each member’s
27 ability [1, 2, 3, 4, 5]. This phenomenon, also referred to as wisdom of crowds, has
28 thus served as a central mechanism underlying the success of diverse organizations,
29 ranging from animal groups [6, 7, 8] and human societies [2, 9] to machine-learning
30 systems [10, 11]. Understanding the conditions that promote and maintain CI there-
31 fore remains a fundamental question across social sciences [12], evolutionary biology
32 [13], and computer science [14]. Addressing this question has become particularly
33 timely as artificial intelligence (AI) has begun to reshape how individuals acquire
34 information, make decisions, and contribute to collective outcomes [15].

35 The recent emergence of generative AIs and large language models (LLMs) has
36 changed the way individuals engage in various cognitive tasks, ranging from simple
37 everyday tasks to more complex tasks, including scientific discovery [16] and creative
38 writing [17]. In particular, while the use of personal AI models, such as ChatGPT, has
39 been rapidly increasing [18], the potential long-term impact of personal AI services
40 on human society, especially the CI, remains uncertain. Some argue that AI can
41 promote CI by enhancing individual expertise [19], and opinion aggregation [20].
42 Conversely, empirical evidence indicate that the use of AIs can limit the diversity of
43 opinions [17, 21, 22], a key requirement for the emergence of CI [23, 24, 25].

44 Our ability to predict the long-term impact of personal AI services on human CI is
45 hampered by the apparent discrepancy in the incentives that shape AI uses. On one
46 hand, many industrial sectors are pushing towards increased AI usages, where the
47 number of “tokens” used is often perceived as a proxy for productivity [26, 27]. On
48 the other hand, many academic institutions appear to discourage, and even penalize,
49 AI use, reflecting concerns about plagiarism, misinformation, and limited independ-
50 ence [28, 29]. Such discrepancy raises a question about whether directly incentivizing
51 or penalizing AI usage will benefit or harm human CI. These observations further
52 highlight the importance of indentifying a robust incentive structure that can pro-
53 mote CI in the presence of AI, which can retain the benefits of AIs while preventing
54 potential risk such as preserving the diversity of individual opinions.

55 To address these questions, we extend previous approaches for modeling CI, where
56 each individual makes independent predictions for the outcome from partial obser-
57 vations of underlying causal factors [12, 13, 30]. We allow each individual to inde-
58 pendently consult with personal AIs and revise their predictions accordingly. Across
59 different assumptions about the AI model’s ability and underlying incentive struc-
60 tures, we investigate the robustness of human CIs.

Main

Model

[SWP: unclear what is meant by decentralized manner.] [SWP: how about something like this: We begin by extending previously established models of CI in which a group of players participates in a prediction task from partial/independent observations of underlying causal factors and aggregates their predictions...] We begin by extending previously established models of CI in which a group of players makes collective predictions by gathering information and aggregating individual predictions in a decentralized manner [30, 12, 13]. [SWP: I would first describe Y and then each individual's prediction. I think we can also leave out "in the previous approach".] In the previous approach, among M different factors (x_i) that affect the outcome (Y), an individual (A) makes a prediction based on their factor of interest (x_{e_A}) and their own belief (c_A): $Y_A = c_A x_{e_A}$. Here, we assume each individual can independently consult AI and revise their prediction based on their reliance on AI (β_A): $Y_A^{re} = \beta_A Y_A^{AI} + (1 - \beta_A) Y_A$. [SWP: We need to say that this revised prediction now contributes to the collective outcome.]

[SWP: I would first describe what AI does biologically. Noise and bias are secondary information and can be added towards the end. For example: To model AI prediction, we consider a scenario where AI has already been trained on this prediction task and therefore has information about the effect of each causal factor. Every time a player consults with AI, it will make predictions based on the known information, which can include factor-specific bias and stochastic error.] To specify how individuals consult AI, we model the AI prediction (Y_A^{AI}) as a noisy and biased estimate of the target outcome. Specifically, AI predictions include factor-specific bias (b_i) and stochastic error (ϵ). We then consider two extreme modes of AI response, which differ in the amount of information AI uses when consulting an individual user [SWP: when making prediction?]. The first is the "AI knows all" model, in which AI predicts the outcome based on all factors regardless of the user's interest: $Y_A^{AI} = \sum_{i=0}^M (\alpha_i x_i + b_i) + \epsilon$, where α_i represents the true coefficient of the factor. The second is the "AI answers question" model, in which AI predicts the outcome based only on the user's interest: $Y_A^{AI} = \alpha_{e_A} x_{e_A} + b_{e_A} + \epsilon$.

[SWP: After every round of prediction task?] After the prediction, each individual receives payoff under the assumed incentive structure. We consider two incentive structures, "feedback" and "niche expert" [13], which have been shown to promote near-perfect collective accuracy in the absence of AI (except averaging aggregation with niche expert incentive). The feedback structure gives higher payoff to individuals who can push the collective prediction toward the true outcome, regardless of their individual predictive accuracy. In contrast, the niche expert structure gives higher payoff to individuals who have both better predictive accuracy and a minority interest.

[SWP: Need to say something about each round vs each generation... I think

102 *one generation consists of several rounds but we're making some kind of equilibrium*
 103 *assumption?]* Through time, the group evolves by imitating the peers who got better
 104 payoff. Specifically, for each generation, two individuals are randomly sampled, and
 105 one imitates all three strategies (factor of interest, belief, reliance on AI) of the
 106 other with a probability determined by the difference in expected payoff. Individual
 107 predictions are aggregated into a collective prediction by simple averaging in the AI
 108 knows all model, or by clustering in the AI answers question model, depending on
 109 the mode of AI.

110 *[SWP: I think we need a brief paragraph about what our goals are to make the*
 111 *next sections flow better. For example: this model now allows us to explore the*
 112 *impact of AI on]*

113 **AI can either promote or prevent the emergence of CI**

114 To understand how AI could affect the emergence of CI, we first compare collective
 115 dynamics with and without AI assistance. We find that AI affects CI in qualitatively
 116 different ways depending on the mode of AI.

117 In the AI knows all model, AI promotes CI by increasing either the speed at
 118 which CI emerges or the resulting collective accuracy (Fig. 2A). When the group can
 119 achieve near-perfect CI without AI (feedback incentive), AI accelerates its emergence
 120 by raising the initial collective accuracy to the level of AI accuracy. By contrast,
 121 when the group cannot achieve CI without AI (niche expert incentive), AI enables
 122 moderately accurate CI that exceeds the accuracy achievable by either AI or the
 123 human group alone. These trends are robust across different levels of AI accuracy
 124 and can be shown mathematically by assuming a sufficiently large group of players
 125 (see SI).

126 In contrast, In the AI answers question model, AI prevents the emergence and
 127 maintenance of CI (Fig. 2B). Under the feedback incentive, the group initially
 128 achieves near-perfect CI. However, as interest diversity rapidly decreases, the group
 129 fails to capture variation in some factors, leading to increased collective variance
 130 and a breakdown of collective accuracy. Under the niche expert incentive, collective
 131 accuracy initially increases but peaks before near-perfect CI is achieved, and then
 132 plateaus with a slight decline. This trend is mediated by increased reliance on AI:
 133 individuals with higher reliance on AI obtain higher payoffs, causing the group to
 134 become increasingly reliant on AI and the collective prediction to inherit AI bias.
 135 However, the niche expert incentive can also drive reliance on AI toward zero, de-
 136 pending on the relationship between the true coefficient and AI bias. In this case,
 137 the group excludes AI assistance and builds CI on its own, which largely delays the
 138 emergence of CI (see SI).

139 Directly incentivizing or penalizing AI use can harm CI

140 Given the strong influence of AI use on collective outcomes, a straightforward inter-
141 vention is to directly incentivize or penalize AI use itself. To investigate whether such
142 direct incentives or penalties improve CI, we modify the two incentive structures by
143 adding a payoff term proportional to individual reliance on AI:

$$\text{Feedback/Niche expert} + \lambda\beta_A \quad (1)$$

144 where λ represent the strength of incentive ($\lambda > 0$) or penalty ($\lambda < 0$). Except in the
145 AI knows all model under the feedback incentive, directly incentivizing or penalizing
146 AI use fails to promote near-perfect CI. Moreover, in most cases, directly incen-
147 tivizing or penalizing leads to lower collective accuracy than the original incentive
148 structures (Fig. 3).

149 When AI use is directly incentivized, reliance on AI evolves toward full reliance
150 ($\beta_A = 1$), reducing collective accuracy as the collective prediction inherits AI bias.
151 By contrast, when AI use is directly penalized, group evolves toward no reliance on
152 AI ($\beta_A = 0$), where collective accuracy decreases with the strength of the penalty. In
153 some cases, when AI bias is relatively large and the penalty is weak, penalizing AI use
154 can achieve higher collective accuracy than the original incentive structure. However,
155 in most cases, penalizing AI use imposes strong selection against AI reliance, pushing
156 the group toward lower stationary collective accuracy. Although the AI answers
157 question model under the feedback incentive already shows stochastic breakdown of
158 CI due to the loss of interest diversity, incentivizing or penalizing AI use further
159 strengthens the breakdown.

160 Balanced incentives mitigate AI-induced failures of CI

161 Focusing on the AI answers question model, in which both incentive structures fail
162 to promote accurate CI, we investigate whether a better incentive structure can over-
163 come the risks introduced by AI. Here, we propose a “balanced” incentive, defined
164 as the simple average of the feedback and niche expert incentives.

165 The core idea of the balanced incentive is to maintain both prediction diversity
166 and interest diversity. The feedback incentive can strongly maintain prediction di-
167 versity, defined as diversity in revised predictions among players, by incentivizing
168 players whose predictions lie opposite to the collective prediction. However, inter-
169 est diversity can be hindered when AI assistance is present. This occurs because
170 revising individual predictions with AI predictions reduces the dispersion of revised
171 predictions in the group. Although the initial distribution of revised predictions is
172 shifted toward the true value because of the AI’s help, this reduced dispersion makes
173 it harder for the group to achieve near-perfect predictions through social learning for
174 factors with large absolute coefficients. This eventually leads to a strong flow of play-
175 ers from factors with relatively small coefficients to factors with larger coefficients,
176 causing a loss of interest diversity.

177 By contrast, the niche expert incentive can maintain interest diversity because
 178 it directly incentivizes minority interests. However, it cannot maintain prediction
 179 diversity because, within the same factor of interest, individuals are rewarded only
 180 according to their individual predictive performance, which homogenize the predic-
 181 tions. This leads to strong selection for either high or low reliance on AI, which in
 182 turn results in lower collective accuracy.

183 The balanced incentive can promote near-perfect CI by maintaining both predic-
 184 tion and interest diversity, regardless of AI accuracy. Reliance on AI decreases as
 185 AI accuracy decreases, reflecting the effective use of AI assistance. However, human
 186 accuracy, defined as collective accuracy without AI, remains largely stochastic, and
 187 only moderate accuracy can be achieved. This suggests that, although an appropriate
 188 incentive structure can promote robust CI under AI assistance, the group may need
 189 to rebuild CI through further adaptation when AI assistance become inaccessible.

190 Discussion

191 We present an epidemiological analysis of RSV outbreaks in Japan combining spa-
 192 tiotemporal observations with dynamical disease modeling. Our analysis revealed
 193 semiannual cycles in seasonal RSV transmission in four major islands (Honshu,
 194 Shikoku, Kyushu, and Ryukyu), which correlate with specific humidity and tem-
 195 perature. We found that these semiannual cycles allowed a sudden shift in the
 196 seasonality of RSV outbreaks in response to an increase in RSV transmission—this
 197 increase could be captured by either through changes in susceptibility or transmissi-
 198 bility. We hypothesize that an increase in childcare capacity through Comprehensive
 199 Support System for Children and Childcare may have contributed to the increase in
 200 RSV transmission [?].

201 Our analysis revealed considerable heterogeneity in epidemic dynamics across
 202 major islands in Japan. We showed that these differences could be explained by
 203 the differences in underlying seasonal transmission. Notably, we found a robust,
 204 quadratic relationship between the estimated transmission rates against mean spe-
 205 cific humidity and mean temperature across four major islands (Honshu, Shikoku,
 206 Kyushu, and Ryukyu), indicating low transmission at intermediate levels of specific
 207 humidity. These findings echo earlier studies that demonstrated similar relationships
 208 for RSV [?] and influenza [? ? ? ? ?]. However, given strong correlation between
 209 specific humidity and temperature, we were unable to identify the primary environ-
 210 mental driver from the current study. Their relative contributions may be separated
 211 from data spanning a wider geographical region with more climate variability as well
 212 as epidemiological variability [?].

213 The robustness of this quadratic relationship across islands exhibiting different
 214 climate conditions also suggests a possibility that climate-driven transmission may
 215 be, in part, facilitated by human behavior: for example, an increase in time spent
 216 indoors during low and high humidity seasons can contribute to increased transmis-

217 sion. Further investigation is needed to establish the underlying mechanism behind
 218 how climate conditions affect the transmission of respiratory pathogens, especially
 219 across different environmental contexts (e.g., indoor vs outdoor). We note that this
 220 relationship is correlational, rather than causal, and therefore any other climate vari-
 221 ables (e.g., rainfall) or seasonal variation in human behavior (e.g., school terms) that
 222 correlate with seasonal variation in specific humidity and temperature will be implic-
 223 itly captured by this relationship. Understanding why the relationship between RSV
 224 transmission and humidity in Hokkaido island differs from other locations remains
 225 to be answered.

226 We hypothesized that the Comprehensive Support System for Children and Child-
 227 care may have contributed to the increase in RSV transmission, but other mecha-
 228 nisms may have also contributed. For example, an increase in inbound overseas trav-
 229 elers may have led to an increased exposure to RSV among adults thereby increasing
 230 the total amount of transmission [?]. However, RSV typically infects young chil-
 231 dren [?] and contact rates among young children and adolescents (5–19) are much
 232 higher than among older adults in Japan [?], suggesting that an increase in
 233 inbound overseas travelers may have smaller effects than an increase in childcare at-
 234 tendance on overall RSV dynamics. Another competing hypothesis that could lead
 235 to an increase in transmission would be strain evolution: for example, one study
 236 noted that L172Q/S173L mutant strains of RSV B that became dominant around
 237 2016 had reduced susceptibility against monoclonal antibodies [?]. However, it is
 238 not yet clear how this mutation translates to susceptibility against infection-derived
 239 antibodies. While our findings are consistent with those by [?], who also pointed
 240 out the association between an increase in childcare attendance and a large change
 241 in the seasonality of Kawasaki disease in Japan, we cannot rule out the possibility
 242 that other factors, such as increase in air travel [?] or strain evolution [?], could
 243 have contributed to the increase in overall transmission.

244 Our sensitivity analysis revealed that an increase in transmissibility, rather than
 245 an increase in susceptibility, can also explain a sudden shift in seasonality in RSV
 246 outbreaks. In fact, both models provide evidence for increased contact rates. Specif-
 247 ically, the total rate of RSV transmission can be written as $\hat{\beta}cSI/N$, where $\hat{\beta}$ repre-
 248 sents the rate of transmission per contact, c represents the contact rate, S represents
 249 the number of susceptible individuals, I represents the number of infected individu-
 250 als, and N represents the total population size. Then, an increase in contact rate c
 251 can be captured by either increase in S (the original model) and $\hat{\beta}$ (the sensitivity
 252 analysis). Therefore, conclusions from both models are consistent with our hypoth-
 253 esis that an increase in contact rates, especially among children, contributed to the
 254 sudden change in RSV seasonality. Detailed age structured surveillance data, along-
 255 side age structured model, will be needed to properly assess the relative contribution
 256 of potential mechanisms, such as increase in childhood mixing patterns or increase
 257 in inbound overseas travelers.

258 Our model-based estimate of the initial susceptible fraction range between 8%–
 259 11%. However this estimate must be interpreted with care as it represents effective

260 changes in population-level susceptibility, which can depend on many factors such
 261 as immunological and behavioral changes, rather than an actual susceptible fraction.
 262 Therefore, these estimates are not directly comparable to serological estimates of
 263 proportion seronegative. For example, [?] recently estimated that 90% of individ-
 264 uals above 3 years of age have been infected at least once by analyzing anti-pre-F
 265 protein antibody concentration data from the Netherlands [? ?], but individuals
 266 with RSV antibodies can still permit reinfection. A cross-section serological assay
 267 from healthcare and non-healthcare workers at a pediatric medical facility in Japan
 268 found that 95% of the participants were seropositive but only 63.5% had greater
 269 than 8 fold neutralizing antibody titers [?], suggesting challenges in translating
 270 serological data to susceptible fraction. While our estimates are not inconsistent
 271 with these data, detailed age structured serological data and model are needed to
 272 accurately estimate changes in population-level susceptibility against RSV.

273 Interventions to slow the transmission of COVID-19 have disrupted the circu-
 274 lation of many pathogens [? ? ? ?], including RSV epidemics in Japan. This
 275 disruption has added major challenges to predicting future outbreaks, which pre-
 276 vented us from making long-term predictions. Continued analysis of RSV dynamics
 277 in the post-COVID period, particularly with regard to whether RSV outbreaks in
 278 Japan return to fall or winter outbreaks, may help further validate our models.

279 Our analysis relied on several simplifying assumptions. For example, our model
 280 assumed that the waning of immunity can render previously infected individual to
 281 become fully susceptible to reinfections; this approximation allowed us to reconstruct
 282 the dynamics of susceptible hosts more easily. In practice, immunity is likely more
 283 complex with secondary infections being less susceptible and transmissible than pri-
 284 mary infections [?]. Other studies have also suggested the importance of interaction
 285 between RSV A and B [? ?] as well as competition between RSV and human
 286 metapneumovirus [?]; our model did not account for such strain dynamics. We
 287 also did not account for explicit spatial structure or underlying stochasticity of the
 288 system. Therefore, our estimates of transmission rates must be interpreted with cau-
 289 tion as they may implicitly capture factors that we did not account for explicitly,
 290 including strain dynamics, spatial structure, and exogenous transmission. Our anal-
 291 yses also primarily focused on three major islands (Honshu, Shikoku, and Kyushu),
 292 necessitating a better understanding of RSV dynamics in Hokkaido and Ryukyu is-
 293 lands; however, we note that these three islands make up $> 95\%$ of the population
 294 in Japan, meaning that our analyses capture the majority of RSV transmission in
 295 Japan. Despite these limitations, our model likely represents a parsimonious ap-
 296 proximation of the complex host-pathogen interactions, allowing us to draw general
 297 conclusions about how interactions between endogenous (contact rates) and exoge-
 298 nous (climate-driven factors) factors can give rise to a sudden dynamical transition.

299 Understanding how endogenous and exogenous factors shape epidemic dynamics
 300 is critical to predicting future outbreaks and making public health decisions. Our
 301 analysis shows that the interplay between climate-driven transmission and subtle
 302 changes in contact rates can cause a sudden transition in epidemic dynamics. More

303 broadly, our analysis demonstrates that detailed epidemiological time series data can
 304 allow us to tease apart endogenous and exogenous factors in explaining dynamical
 305 transitions, offering unique insights into a long-standing ecological question.

306 Methods

307 To model CI, we start with an abstract model that assumes the prediction target
 308 is the result of multiple causal factors [13]. Specifically, the prediction target Y is
 309 modeled as a linear combination of M independent factors $(x_1, x_2, \dots, x_m)$ and $M + 1$
 310 coefficients $(\alpha_0, \alpha_1, \dots, \alpha_m)$, where α_0 denotes the global offset (Fig. 1A). The M
 311 factors are randomly drawn from normal distributions with mean X_i and standard
 312 deviation σ_i in each generation.

313 Among a population of N individuals, each individual can observe a single factor
 314 and make a prediction based on the observed value and their own belief. In particular,
 315 individual A 's prediction is modeled as:

$$Y_A = c_A x_{e_A} \quad (2)$$

316 where c_A represents individual A 's personal belief, e_A represents the factor that A
 317 observes (interest), and x_{e_A} represents the realized value of A 's interest. Individuals
 318 can also choose not to observe any factor, which represents stubborn individuals
 319 who make predictions only based on their own belief. For notational convenience,
 320 we assume that stubborn individuals have interest 0, and let x_0 always be 1.

321 Next, we model AI as a prediction system that has learned the true coefficients
 322 with bias and error (Fig. 1B). For each factor $i \in [0, M]$, AI knows the exact
 323 coefficient α_i and has a fixed bias b_i , resulting in a prediction of $\alpha_i x_i + b_i$. In terms
 324 of human-AI interaction, we model two contrasting modes of AI: the "AI knows all"
 325 model and the "AI answers question" model. In the AI knows all model, AI acts
 326 as an omniscient system and gives an answer regardless of the individual's interest,
 327 accounting for all factors related to the task. Thus, AI predicts as follows:

$$Y_A^{AI} = \sum_{i=0}^M (\alpha_i x_i + b_i) + \epsilon \quad (3)$$

328 In contrast, the AI answers question model acts as a chatbot and gives an answer
 329 only based on the individual's interest. Thus, given the individual's interest, e_A , AI
 330 predicts as follows:

$$Y_A^{AI} = \alpha_{e_A} x_{e_A} + b_{e_A} + \epsilon \quad (4)$$

331 In both models, $\epsilon \sim N(0, \sigma_e^2)$ represents random error arising from the stochastic
 332 generative process of the AI model.

333 AI works as a personalized assistant for each individual, such that each individual
 334 receives assistance by incorporating the AI's prediction. However, even with the same

335 opportunity to receive AI assistance, reliance on AI can vary substantially across
 336 individuals. To model this, we assume that the revised prediction is a weighted sum
 337 of the individual’s own prediction and the AI’s prediction by introducing AI belief
 338 β_A as a weighting coefficient. The revised prediction of individual A can be written
 339 as:

$$Y_A^{revised} = \beta_A Y_A^{AI} + (1 - \beta_A) Y_A \quad (5)$$

340 The revised predictions of individuals are aggregated by two different mechanisms,
 341 depending on the mode of AI. In the AI knows all model, even if an individual can
 342 observe only a single factor, their revised prediction contains information about all
 343 factors through interaction with AI. Therefore, we use simple averaging of revised
 344 predictions as the collective prediction. In contrast, in the AI answers question
 345 model, each individual gives a prediction based only on a single factor even after
 346 revising their prediction with AI assistance. Therefore, we use clustering aggregation
 347 to obtain the collective prediction, which is performed by clustering individuals based
 348 on interest and summing the average values of each cluster.

349 For each generation, each individual is rewarded with a payoff based on the given
 350 incentive structure (Fig. 1C). We adopt two incentive structures, “feedback” and
 351 “niche expert,” which were proposed by Wang et al. [13] and promote collective
 352 intelligence when prediction is performed without AI. The feedback incentive gives
 353 higher payoff to individuals who can push the collective prediction toward the true
 354 value, regardless of their individual performance. Given individual A ’s revised pre-
 355 diction $Y_A^{revised}$ and the collective prediction $\hat{Y}^{revised}$, it can be expressed as:

$$\pi_A = Y_A^{revised} (Y - \hat{Y}^{revised}) \quad (6)$$

356 The niche expert incentive gives higher payoff to individuals who have both better
 357 individual performance and a minority interest. Specifically, the niche expert payoff
 358 is expressed as the product of the proportion of individuals who observe the same
 359 factor as individual A , ρ_{e_A} , and individual accuracy. Given individual A ’s revised
 360 prediction $Y_A^{revised}$, it can be expressed as:

$$\pi_A = -\rho_{e_A} (Y_A^{revised} - Y)^2 \quad (7)$$

361 These two incentive structures were shown to achieve nearly perfect collective in-
 362 telligence through social learning (except for the niche expert incentive with simple
 363 averaging aggregation) by promoting individual expertise while maintaining collec-
 364 tive diversity. Therefore, we use these incentive structures as a baseline to under-
 365 stand how AI affects the emergence of collective intelligence. Moreover, we modify
 366 the two baseline incentives in a later section to understand the consequences of direct
 367 incentives and penalties for AI usage.

368 Throughout the simulation, individuals engage in social learning by imitating
 369 other individuals who receive higher payoffs. We assume that prediction events
 370 occur more frequently than social learning events within the population, such that

individual payoff can be computed as an expected payoff. The imitation process is performed for at most one pair in each generation. By sampling two random individuals, A and B , imitation is performed with probability:

$$\frac{1}{1 + \exp(s(\mathbb{E}[\pi_A] - \mathbb{E}[\pi_B]))} \quad (8)$$

where s denotes the strength of social learning. When imitation occurs, A imitates all three strategies of B : interest, belief, and AI belief.

To evaluate and analyze the dynamics of collective prediction, we define six summary metrics: collective accuracy, collective bias, collective variance, human accuracy, interest diversity, and median AI belief. These metrics capture the accuracy of the revised collective prediction, its bias-variance decomposition, the predictive performance without AI, the diversity of individual interests, and median AI belief in the population (Table 1).

Table 1: Evaluation metrics used to analyze collective prediction dynamics.

Metric	Definition	Interpretation
Collective accuracy	$1 - \frac{\mathbb{E}[(Y - \hat{Y}^{\text{revised}})^2]}{\mathbb{E}[(Y - \alpha_0)^2]}$	Accuracy of the revised collective prediction relative to the baseline prediction α_0 .
Collective bias	$\left(\mathbb{E}[Y - \hat{Y}^{\text{revised}}]\right)^2$	Squared systematic deviation of the revised collective prediction from the true value.
Collective variance	$\text{Var}(Y - \hat{Y}^{\text{revised}})$	Variability of the revised collective prediction error across prediction events.
Human accuracy	$1 - \frac{\mathbb{E}[(Y - \hat{Y})^2]}{\mathbb{E}[(Y - \alpha_0)^2]}$	Accuracy of the human-only collective prediction relative to the baseline prediction α_0 .
Interest diversity	$\exp\left(-\sum_{i=0}^M \rho_i \ln \rho_i\right)$	Effective number of interests represented in the population.
Median AI belief	$\text{median}_{A \in N}(\beta_A)$	Median value of AI belief β_A in the population.

382 Data and code availability

383 All data are stored in a publicly available GitHub repository ([https://github.com/](https://github.com/parklab-snu/collective-intelligence-with-AI)
384 `parklab-snu/collective-intelligence-with-AI`).

385 References

- 386 [1] Francis Galton. Vox populi, 1907.
- 387 [2] Anita Williams Woolley, Christopher F Chabris, Alex Pentland, Nada Hashmi,
388 and Thomas W Malone. Evidence for a collective intelligence factor in the
389 performance of human groups. *science*, 330(6004):686–688, 2010.
- 390 [3] Ilan Yaniv and Maxim Milyavsky. Using advice from multiple sources to revise
391 and improve judgments. *Organizational Behavior and Human Decision Pro-*
392 *cesses*, 103(1):104–120, 2007.
- 393 [4] Cars Hommes, Joep Sonnemans, Jan Tuinstra, and Henk Van de Velden. Coord-
394 ination of expectations in asset pricing experiments. *The Review of Financial*
395 *Studies*, 18(3):955–980, 2005.
- 396 [5] Irving Lorge, David Fox, Joel Davitz, and Marlin Brenner. A survey of studies
397 contrasting the quality of group performance and individual performance, 1920-
398 1957. *Psychological bulletin*, 55(6):337, 1958.
- 399 [6] Tabea Dreyer, Amir Haluts, Amos Korman, Nir Gov, Ehud Fonio, and Ofer
400 Feinerman. Comparing cooperative geometric puzzle solving in ants versus hu-
401 mans. *Proceedings of the National Academy of Sciences*, 122(1):e2414274121,
402 2025.
- 403 [7] Andrew M Simons. Many wrongs: the advantage of group navigation. *Trends*
404 *in ecology & evolution*, 19(9):453–455, 2004.
- 405 [8] Andrew Berdahl, Colin J Torney, Christos C Ioannou, Jolyon J Faria, and Iain D
406 Couzin. Emergent sensing of complex environments by mobile animal groups.
407 *Science*, 339(6119):574–576, 2013.
- 408 [9] Christoph Riedl, Young Ji Kim, Pranav Gupta, Thomas W Malone, and
409 Anita Williams Woolley. Quantifying collective intelligence in human groups.
410 *Proceedings of the National Academy of Sciences*, 118(21):e2005737118, 2021.
- 411 [10] Leo Breiman. Bagging predictors. *Machine learning*, 24(2):123–140, 1996.
- 412 [11] Leo Breiman. Random forests. *Machine learning*, 45(1):5–32, 2001.
- 413 [12] Richard P Mann and Dirk Helbing. Optimal incentives for collective intelligence.
414 *Proceedings of the National Academy of Sciences*, 114(20):5077–5082, 2017.

- [13] Guocheng Wang, Qi Su, Long Wang, and Joshua B Plotkin. Individual incentives that promote collective intelligence. *Proceedings of the National Academy of Sciences*, 122(51):e2516535122, 2025.
- [14] Justin Werfel. Fluid thinking about collective intelligence. *Nature Machine Intelligence*, 8(4):506–516, 2026.
- [15] Hao Cui and Taha Yasseri. AI-enhanced collective intelligence. *Patterns*, 5(11):101074, 2024.
- [16] Chris Lu, Cong Lu, Robert Tjarko Lange, Yutaro Yamada, Shengran Hu, Jakob Foerster, David Ha, and Jeff Clune. Towards end-to-end automation of AI research. *Nature*, 651(8107):914–919, 2026.
- [17] Anil R Doshi and Oliver P Hauser. Generative AI enhances individual creativity but reduces the collective diversity of novel content. *Science advances*, 10(28):eadn5290, 2024.
- [18] Sha Sajadieh, Loredana Fattorini, Raymond Perrault, Yolanda Gil, Vanessa Parli, Lapo Santarasci, Juan Pava, Nestor Maslej, Russ Altman, Erik Brynjolfsson, et al. Artificial intelligence index report 2026. *arXiv preprint arXiv:2606.15708*, 2026.
- [19] Michelle Vaccaro, Abdullah Almaatouq, and Thomas Malone. When combinations of humans and AI are useful: A systematic review and meta-analysis. *Nature Human Behaviour*, 8(12):2293–2303, 2024.
- [20] Jason W Burton, Ezequiel Lopez-Lopez, Shahar Hechtlinger, Zoe Rahwan, Samuel Aeschbach, Michiel A Bakker, Joshua A Becker, Aleks Berditchevskaia, Julian Berger, Levin Brinkmann, et al. How large language models can reshape collective intelligence. *Nature human behaviour*, 8(9):1643–1655, 2024.
- [21] Lennart Meincke, Gideon Nave, and Christian Terwiesch. ChatGPT decreases idea diversity in brainstorming. *Nature human behaviour*, 9(6):1107–1109, 2025.
- [22] Andreas Fügener, Jörn Grahl, Alok Gupta, and Wolfgang Ketter. Will humans-in-the-loop become borgs? merits and pitfalls of working with AI. *MIS quarterly*, 45(3):1527–1556, 2021.
- [23] Jan Lorenz, Heiko Rauhut, Frank Schweitzer, and Dirk Helbing. How social influence can undermine the wisdom of crowd effect. *Proceedings of the national academy of sciences*, 108(22):9020–9025, 2011.
- [24] Lucy M Aplin, Damien R Farine, Richard P Mann, and Ben C Sheldon. Individual-level personality influences social foraging and collective behaviour in wild birds. *Proceedings of the Royal Society B: Biological Sciences*, 281(1789):20141016, 2014.

- 451 [25] Lu Hong and Scott E Page. Groups of diverse problem solvers can outperform
452 groups of high-ability problem solvers. *Proceedings of the National Academy of*
453 *Sciences*, 101(46):16385–16389, 2004.
- 454 [26] Isabelle Bousquette. Why some companies say AI ‘token-
455 maxx’ is key to survival. [https://www.wsj.com/cio-journal/](https://www.wsj.com/cio-journal/why-some-companies-say-ai-tokenmaxxing-is-key-to-survival-e699a128)
456 [why-some-companies-say-ai-tokenmaxxing-is-key-to-survival-e699a128](https://www.wsj.com/cio-journal/why-some-companies-say-ai-tokenmaxxing-is-key-to-survival-e699a128),
457 April 2026. The Wall Street Journal. Accessed: 2026-07-07.
- 458 [27] Tim Keary. Is the cult of ‘tokenmaxxing’ just another fad or the
459 new normal? [https://www.forbes.com/sites/timkeary/2026/04/13/](https://www.forbes.com/sites/timkeary/2026/04/13/is-the-cult-of-tokenmaxxingjust-another-fad-or-the-new-normal/)
460 [is-the-cult-of-tokenmaxxingjust-another-fad-or-the-new-normal/](https://www.forbes.com/sites/timkeary/2026/04/13/is-the-cult-of-tokenmaxxingjust-another-fad-or-the-new-normal/),
461 April 2026. Forbes. Accessed: 2026-07-07.
- 462 [28] Dalmeet Singh Chawla. Researchers who use hallucinated references to face
463 arXiv ban. *Nature*, 653(8116):988–989, 2026.
- 464 [29] H Holden Thorp. Chatgpt is fun, but not an author. *Science*, 379(6630):313–313,
465 2023.
- 466 [30] Lu Hong, Scott E Page, and Maria Riolo. Incentives, information, and emergent
467 collective accuracy. *Managerial and Decision Economics*, 33(5-6):323–334, 2012.

468 Acknowledgements

469 S.W.P. was supported by the New Faculty Startup Fund from Seoul National Univer-
470 sity, and the Global-LAMP Program of the National Research Foundation of Korea
471 (NRF) grant funded by the Ministry of Education (No. RS-2023-00301976).

472 Contributions

473 Jaeseung Kim: Conceptualization, Formal Analysis, Investigation, Methodology,
474 Software, Visualization, Writing - Original Draft Preparation, Writing - Review
475 Editing. Sang Woo Park: Conceptualization, Investigation, Methodology, Super-
476 vision, Writing - Original Draft Preparation, Writing - Review Editing.

477 Competing Interests

478 The authors declare no competing interests.

479 Figures

Figure 1: **Observed changes in RSV outbreak dynamics in Japan.** (A) Relative RSV cases across 47 prefectures in Japan between 2013 and 2024. Relative cases, representing the relative magnitude of RSV outbreaks in each prefecture compared to RSV outbreak sizes before the COVID-19 pandemic, are calculated by dividing the raw cases by the maximum value before the COVID-19 pandemic. The red arrow indicates when the shift in seasonality occurred. (B) Estimates of center of gravity (i.e., the mean timing of an epidemic) across 46 prefectures, excluding Okinawa. (C) Estimates of the epidemic trough (i.e., the minimum number of cases in a season divided by the population size) across 47 prefectures. In panels B and C, the center (horizontal line), lower bounds, and upper bounds of the box plot correspond to median, lower quartile (25th percentile), and upper quartile (75th percentile), respectively. The whiskers indicate the range of values that extend up to 1.5 times the interquartile range beyond the lower and upper quartiles. Outliers, which fall outside this range, are plotted individually. (D) Time series of RSV cases across 5 major islands.

Figure 2: **Summary of SIRS model fits to RSV outbreaks across major islands in Japan.** (A) Comparisons of observed cases (points) across the five major islands and fitted epidemic trajectories (red lines). (B) Estimated periodic seasonal transmission rates. (C) Relationship between the estimated periodic seasonal transmission rates and mean specific humidity. Points represent seasonal transmission rate estimates across 52 weeks versus average humidity across 2013–2020. Blue lines and regions represent the corresponding locally estimated scatterplot smoothing (LOESS) estimates and corresponding 95% confidence intervals ($n=52$). Red lines and regions represent the corresponding quadratic regression fits and corresponding 95% confidence intervals ($n=52$). (D) Estimated relative changes in transmission, capturing the impact of NPI measures. (E) Estimated proportion of the susceptible pool. In panels B, D, and E, lines represent the estimated median of the posterior distribution ($n=8000$ posterior samples). In panels B, D, and E, shaded regions represent the 95% credible intervals from the posterior distribution ($n=8000$ posterior samples).

Figure 3: **An increase in the susceptible pool explains sudden changes in seasonality.** (A) Predicted effects of the proportion of infected $i(0)$ and susceptible $S(0)$ at the beginning of season on center of gravity. Points represent the estimated values for $i(0)$ and $s(0)$ between 2013 and 2019, showing the last two digits of a given year. The white vertical dashed line represents the $i(0)$ value used for simulating epidemic dynamics in panel B. (B) Changes in epidemic trajectories caused by an increase in the susceptible proportion at the beginning of season for a fixed value of $i(0)$. (C–F) Comparisons of interpolated transmission rates used for simulating the SIRS model, corresponding to each corner in Panel G. Black lines represent the transmission rates used for simulations. Gray lines represent the estimated transmission rates the Honshu island as a visual reference. (C) The estimated transmission rates for the Honshu island. (D) The resulting transmission rates for the Honshu island with equal amplitude as the Kyushu island. (E) The resulting transmission rates for the Kyushu island with equal amplitude as the Honshu island. (F) The estimated transmission rates for the Kyushu island. (G) Differences in peak epidemic timing when we increase the the susceptible proportion at the beginning of season from 7.8% to 10.5% using transmission patterns that interpolate the estimates for Honshu and Kyushu islands.

Figure 4: **Increase in the susceptible pool following the launch of the Comprehensive Support System for Children and Childcare in Japan.** (A) Direct comparisons between the estimates of susceptible proportion at the beginning of each season in each island (black) and the number of children attending childcare facilities in Japan (red). Points represent median from $n=8000$ posterior samples. Shaded regions represent the 95% credible interval in our estimates ($n=8000$ posterior samples). (B) Correlations between the estimates of susceptible proportion at the beginning of each season in each island and the number of children attending childcare facilities in Japan. Points represent median from $n=8000$ posterior samples. Error bars represent the 95% credible interval in our estimates ($n=8000$ posterior samples). Red lines and shaded regions represent the best fitting linear regression and the corresponding 95% confidence intervals.