

1  
2 Personalized AI assistants could either promote or hinder the  
3 emergence of collective intelligence [SWP: *The potential*  
4 *impact of personalized AI assistants on collective*  
5 *intelligence?*]

6  
7 Jaeseung Kim<sup>1</sup> Sang Woo Park<sup>1,2,\*</sup>

8 **1** School of Biological Sciences, Seoul National University, Seoul, Korea

9 **2** Institute for Data Innovation in Science, Seoul National University, Seoul, Korea

10 \*Corresponding author: sangwoopark@snu.ac.kr

## 11 Abstract

12 Recent advances in artificial intelligence (AI) have enabled widespread use of per-  
13 sonal AI assistants for various cognitive tasks, ranging from simple everyday tasks  
14 to scientific discovery and creative writing. While AI assistance can improve the  
15 performance of each individual, it can weaken their subsequent performance with-  
16 out AI and further limit the diversity of interests and opinions. These risks raise  
17 the question of whether human collective intelligence can persist as our society be-  
18 comes increasingly reliant on AI assistants. To address this question, we develop an  
19 evolutionary model of collective intelligence, where each individual participate in a  
20 prediction task, consult AI, and imitate each other’s prediction strategy. We find  
21 that “Chatbot” AI, which depends on users’ interests, can prevent the emergence  
22 of collective intelligence by either limiting diversity or propagating systematic bias  
23 through overreliance. Directly incentivizing or penalizing AI use generally worsens  
24 these outcomes. Instead, a balanced incentive structure that preserve minority ex-  
25 pertise and reward contributions to collective outcome can promote the emergence of  
26 collective intelligence. However, the inherent ability of the population’s to make pre-  
27 diction in the absence of AI remains suboptimal even under this balanced incentive  
28 structure, raising concerns for continued AI reliance. [SWP: *conclusion?*]

## 29 Introduction

30 Collective intelligence (CI) describes a phenomenon in which a group’s ability to  
31 solve problems, make decisions, or adapt to changing environments exceeds each  
32 member’s ability (Galton, 1907; Woolley et al., 2010; Yaniv and Milyavsky, 2007;  
33 Hommes et al., 2005; Lorge et al., 1958). This phenomenon, also referred to as  
34 wisdom of crowds, has thus served as a central mechanism underlying the success of  
35 diverse organizations, ranging from animal groups (Dreyer et al., 2025; Simons, 2004;  
36 Berdahl et al., 2013) and human societies (Woolley et al., 2010; Riedl et al., 2021) to  
37 machine-learning systems (Breiman, 1996, 2001). Understanding the conditions that  
38 promote and maintain CI therefore remains a fundamental question across social  
39 sciences (Mann and Helbing, 2017), evolutionary biology (Wang et al., 2025), and  
40 computer science (Werfel, 2026). Addressing this question has become particularly  
41 timely as artificial intelligence (AI) has begun to reshape how individuals acquire  
42 information, make decisions, and contribute to collective outcomes (Cui and Yasseri,  
43 2024).

44 The recent emergence of generative AIs and large language models (LLMs) has  
45 changed the way individuals engage in various cognitive tasks, ranging from simple  
46 everyday tasks to more complex tasks (Noy and Zhang, 2023; Brynjolfsson et al.,  
47 2025), including scientific discovery (Lu et al., 2026) and creative writing (Doshi  
48 and Hauser, 2024). In particular, while the use of generative AI models, such as  
49 ChatGPT, has been rapidly increasing (Bick et al., 2026; Sajadieh et al., 2026), the  
50 potential long-term impact of personal AI assistants on human society, especially the  
51 CI, remains uncertain. Some argue that AI can promote CI by enhancing individual  
52 expertise (Vaccaro et al., 2024), and opinion aggregation (Burton et al., 2024; Tessler  
53 et al., 2024). Conversely, empirical evidence indicate that the use of AIs can limit the  
54 diversity of opinions (Fügener et al., 2021; Doshi and Hauser, 2024; Lee and Chung,  
55 2024; Meincke et al., 2025), a key requirement for the emergence of CI (Hong and  
56 Page, 2004; Lorenz et al., 2011; Aplin et al., 2014; Becker et al., 2017).

57 Our ability to predict the long-term impact of personal AI assistants on human  
58 CI is further hampered by the apparent discrepancy in the incentives that shape AI  
59 uses. On one hand, many industrial sectors are pushing towards increased AI usages,  
60 where the number of “tokens” used is often perceived as a proxy for productivity  
61 (Bousquette, 2026; Keary, 2026). On the other hand, many academic institutions  
62 appear to discourage, and even penalize, AI uses, reflecting concerns about plagia-  
63 rism, misinformation, and limited independence (Thorp, 2023; Chawla, 2026). Such  
64 discrepancy raises a question about whether directly incentivizing or penalizing AI  
65 usage will benefit or harm human CI. These observations further highlight the im-  
66 portance of indentifying a robust incentive structure that can promote CI in the  
67 presence of personal AI assistants. Such incentive structure should seek to retain  
68 the benefits of AIs and prevent potential risk, such as preserving the diversity of  
69 individual opinions.

70 To address these questions, we extend previous approaches for modeling CI, where

each individual participates in a prediction task from partial observations of underlying causal factors (Mann and Helbing, 2017; Wang et al., 2025; Hong et al., 2012). In particular, we allow each individual to independently consult with personal AI assistants and revise their predictions accordingly. The resulting model allows us to investigate the robustness of human CIs under different assumptions about the AI model’s ability to make predictions as well as incentive structures that are associated with the prediction task. In doing so, we assess the impact of directly incentivizing or penalizing AI uses on CI and further suggest a balanced incentive structure that can maintain CI in the presence of AI.

## Mathematical model




Figure 1: **A schematic diagram of the model for individual and collective prediction in the presence of personal AI assistants.** (A) The prediction target is modeled as a linear combination of causal factors. (B) Each player is characterized by three strategies: interest, belief, and reliance on AI. Players make predictions based on their interests and beliefs and subsequently revise them with AI assistance. We consider two types of AI, Chatbot AI and Omniscient AI, which differ in the amount of information available for generating predictions. (C) Players receive payoffs according to the incentive structure, and the population evolves through imitation of peers with higher payoffs.

We begin by extending previously established models of CI, in which a group of players participates in a prediction task (Figure 1): each player makes an individual prediction based on partial observations of the underlying causal factors, and the group forms a collective prediction by aggregating these individual predictions (Hong et al., 2012; Mann and Helbing, 2017; Wang et al., 2025). Specifically, the prediction target,  $Y$ , is modeled as a linear combination of  $M$  causal factors  $x_i$ , with fixed coefficients  $\alpha_i$ :  $Y = \sum_{i=1}^M \alpha_i x_i + \alpha_0$ , where each factor is drawn from independent normal distribution (Figure 1A). Then, each individual  $A$  observes a single factor of their interest  $x_{e_A}$  and makes a prediction based on their own belief,  $c_A$ :  $Y_A = c_A x_{e_A}$  (Figure 1B). We assume each individual can then independently consult their AI assistants and revise their prediction based on their reliance on AI,  $\beta_A$ :

92  $Y_A^{\text{re}} = \beta_A Y_A^{\text{AI}} + (1 - \beta_A) Y_A$  (Figure 1B). The revised predictions are then aggregated  
 93 using two alternative aggregation rules, averaging and clustering, to form collective  
 94 prediction.

95 To model AI, we assume that AI has already been trained on similar tasks and is  
 96 able to make predictions based on partial or full observations of causal factors (Figure  
 97 1B). Every time a player consults AI, it will make a new prediction  $Y_A^{\text{AI}}$  based on  
 98 its internal parameters, which can include factor-specific bias ( $b_i$ ) and stochastic  
 99 error  $\epsilon$ . Here, we consider two extreme types of AI response, which differ in the  
 100 amount of information AI uses when making predictions. In one extreme, the AI  
 101 can observe all causal factors and use all information to make predictions, regardless  
 102 of the user’s interest:  $Y_A^{\text{AI}} = \sum_{i=0}^M (\alpha_i x_i + b_i) + \epsilon$ . In the other extreme, AI works  
 103 like a chatbot, where the AI predicts the outcome based only on the user’s interest:  
 104  $Y_A^{\text{AI}} = \alpha_{e_A} x_{e_A} + b_{e_A} + \epsilon$ . Hereafter, we refer to these two types as ‘Omniscient AI’  
 105 and ‘Chatbot AI’, respectively.

106 We assume that appropriate aggregation rule for collective prediction depends  
 107 on the type of AI. When Chatbot AI is used, each revised prediction depends on a  
 108 single factor. Thus, we use clustering aggregation, under which revised predictions  
 109 are first averaged among individuals who are interested in the same factor, and  
 110 then summed across factors. When Omniscient AI is used, however, each revised  
 111 prediction contains information about all causal factors, in which case clustering  
 112 these predictions by interest would be inappropriate. Instead, we use averaging  
 113 aggregation, under which revised individual predictions are averaged directly to form  
 114 the collective prediction.

115 Each generation consists of multiple round of predictions, and each player is re-  
 116 warded a payoff according to the incentive structure (Figure 1C). For simplicity,  
 117 we assume that a sufficiently large number of prediction rounds occurs within each  
 118 generation, allowing us to use the expected payoff value rather than computing the  
 119 payoffs for every round. We consider two incentive structures from previous work,  
 120 “feedback” and “niche-expert”, which have been shown to promote near-perfect col-  
 121 lective accuracy in the absence of AI (Wang et al., 2025). The feedback structure  
 122 gives higher payoff to individuals who can push the collective prediction toward the  
 123 true target, regardless of their individual predictive accuracy:  $\pi_A = Y_A^{\text{re}}(Y - \hat{Y}^{\text{re}})$ . In  
 124 contrast, the niche-expert structure gives higher payoff to individuals who have both  
 125 better predictive accuracy and a minority interest:  $\pi_A = -\rho_{e_A}(Y_A^{\text{re}} - Y)^2$ . Here,  $\rho_{e_A}$   
 126 denotes the proportion of players interested in the same factor, thereby allowing the  
 127 niche-expert structure to preserve interest diversity. We note collective intelligence  
 128 fails to emerge under the combination of averaging aggregation with niche-expert  
 129 structure in the absence of AI (Wang et al., 2025).

130 Through time, the group evolves by allowing each individual to imitate peers  
 131 who received higher payoffs (Figure 1C). Specifically, after each generation, two  
 132 individuals are randomly sampled, and one imitates all three strategies (the factor of  
 133 interest, factor belief, and reliance on AI) of the other with a probability determined  
 134 by the difference in their expected payoffs (Materials and Methods). Individual

135 predictions are aggregated into a collective prediction  $\hat{Y}$  based on the aggregation  
 136 rules. Collective accuracy is defined as the reduction in prediction error achieved  
 137 by the collective prediction relative to a baseline prediction  $\alpha_0$  (Wang et al., 2025):  
 138  $1 - \mathbb{E}[(Y - \hat{Y}^{\text{re}})^2] / \mathbb{E}[(Y - \alpha_0)^2]$ . Hereafter, we say that CI emerges when the collective  
 139 accuracy reaches a near perfect level.

140 This model now allows us to explore the impact of AI on CI depending on the  
 141 type of AI and the incentive structure. Here, we begin by comparing the emergence  
 142 of CI with and without AI and subsequently investigate a how different incentive  
 143 structures affect the emergence of CI in the presence of AI.

## 144 AI can either promote or prevent the emergence of 145 CI

146 To understand the impact of AI, we first compare collective dynamics with and  
 147 without AI. First, consistent with Wang et al. (2025), simple imitation rules and  
 148 incentive structures allow collective intelligence to emerge in the absence of AI (Fig.  
 149 2A,C,D). One exception is the use of simple averaging with niche-expert incentive  
 150 structures, under which the collective accuracy of the population remains near zero.  
 151 This is because enhancing individual accuracy causes individuals to predict close to  
 152 the true coefficient of their interest, but simply averaging these predictions does not  
 153 necessarily produce an accurate estimate of the full prediction target (Fig. S1).

154 We find that AI usage can have heterogeneous outcomes depending on its type.  
 155 For example, the use of Omniscient AI can either preserve CI under the feedback  
 156 incentive structure (Fig. 2A) or promote higher collective accuracy under the niche-  
 157 expert incentive structure (Fig. 2B). These results are robust across different levels  
 158 of AI accuracy and can be shown analytically by assuming a sufficiently large group  
 159 of players (Fig. S2; see SI Evolutionary dynamics section). **[SWP: need to get**  
 160 **back.]**

161 In contrast, the use of Chatbot AI prevents the emergence of CI, thereby resulting  
 162 in lower levels of collective accuracy (Fig. 2C, D). Under the feedback incentive  
 163 structure, the use of Chatbot AI leads to a loss of diversity in the population's  
 164 interest, making it impossible to account for effect of some causal factors (Fig. S2,  
 165 S3). This causes an increase in collective variance and stochastic decrease in collective  
 166 accuracy (Fig. 2C; Fig. S3). We note that the loss of interest diversity may arise  
 167 even in the absence of AI in finite populations (Fig. S3), but the use of Chatbot  
 168 AI makes the group more vulnerable to such loss (Fig. S4). Under the niche-  
 169 expert incentive structure, the population becomes overly reliant on AI, causing the  
 170 collective prediction to inherit the AI's bias (Fig. S3). This leads to an increase in  
 171 collective bias and a decrease in collective accuracy (Fig. 2; Fig. S3). Interestingly,  
 172 we find that the niche-expert structure can prevent the use of AI under specific  
 173 assumptions about the relationship between the true coefficient and AI bias (Fig.  
 174 S2). In this case, the population reduces **[JS: I think it is difficult to say that it**




Figure 2: **Comparison of collective accuracy with and without AI.** Trajectories of collective accuracy when the group is assisted by the Omniscient AI (A,B) and Chatbot AI (C,D). Here, feedback (A,C) and niche-expert (B,D) incentive structures are considered. Blue lines represent trajectories of collective accuracy without AI assistance. Orange lines represent trajectories of collective accuracy with AI assistance. Gray lines represent trajectories of counterfactual collective accuracy, computed from players’ unrevised predictions, indicating the group’s predictive accuracy if AI assistance were unavailable at the given generation. Prediction target parameters:  $m = 50$ ,  $s = 50$ ,  $\mu = 0$ ,  $\alpha_i \sim U(-5, 5)$ , and  $\sigma_i \sim U(0, 3)$ . Population parameters:  $N = 10,000$ ,  $c_A \sim \mathcal{N}(0, 100^2)$  for (A, B),  $c_A \sim \mathcal{N}(0, 5^2)$  for (C, D), and  $\beta_A \sim U(0, 1)$ . AI parameters:  $b_i = 0.36$  and  $\tau = 0.3$ .


completely excludes AI, because reliance on AI does not approach zero. This may be due to the limited population size.] the reliance on AI assistance, allowing the CI to emerge eventually. However, this phenomenon can substantially delay the emergence of CI (Fig. S5).

To investigate whether the group can retain its predictive ability when AI assistance suddenly becomes unavailable at any given time, we quantify counterfactual collective accuracy based on unrevised predictions. Across all scenarios, we find that

the counterfactual collective accuracy is lower than the collective accuracy of the corresponding population (Fig. 2).

In summary, an omniscient AI can promote CI, but AI operating with limited information may prevent the emergence of CI. Moreover, reliance on AI can limit inherent ability of the population to make accurate predictions on their own, raising concerns about future AI usage. These findings further underscore the need for incentive structures that can mitigate the potential risks associated with AI assistance.

## Directly incentivizing or penalizing AI use can additionally harm CI



**Figure 3: Collective accuracy under the influence of direct intervention on AI use.** Collective accuracy and median reliance on AI under varying strengths of intervention ( $\lambda$ ) across different assumptions about AI types (omniscient AI, A–D and chatbot AI, E–H) and incentive structures (Feedback, A,B,E,F, and Niche expert, C,D,G,H). Positive  $\lambda$  represents an incentive for AI use, whereas negative  $\lambda$  represents a penalty for AI use. In each panel, the vertical dashed line indicates the original incentive structure ( $\lambda = 0$ ). Four AI bias levels are shown:  $b_i = \pm 0.2$ , representing higher-accuracy AI, and  $b_i = \pm 0.4$ , representing lower-accuracy AI. Collective accuracy (A,C,E,G) and median reliance on AI (B,D,F,H) are averaged over generations 190,000–200,000. Prediction target parameters:  $m = 50$ ,  $s = 50$ ,  $\mu = 0$ ,  $\alpha_i \sim U(-5, 5)$ , and  $\sigma_i \sim U(0, 3)$ . Population parameters:  $N = 10,000$ ,  $c_A \sim \mathcal{N}(0, 100^2)$  for (A–D),  $c_A \sim \mathcal{N}(0, 5^2)$  for (E–H), and  $\beta_A \sim U(0, 1)$ . AI parameter:  $\tau = 0.3$ .

Given the strong influence of AI on collective outcomes, a straightforward inter-

vention is to directly incentivize or penalize the use of AI. To investigate whether such direct incentives or penalties can help the emergence of CI, we modify the two incentive structures by adding a payoff term proportional to individual reliance on AI:

$$\text{Feedback/Niche-expert} + \lambda\beta_A \quad (1)$$

where  $\lambda$  represent the strength of intervention ( $\lambda > 0$ ) or penalty ( $\lambda < 0$ ), and  $\beta_A$  represent individual reliance on AI. [SWP: maybe we need to call incentive pi earlier on...] [SWP: also good to define beta again here as a reminder.]


Directly incentivizing or penalizing AI use can further reduce the collective accuracy (Fig. 3C, E, G), except when Omniscient AI is used under the feedback structure; in the latter case, the population retains collective intelligence regardless of the intervention strength (Fig. 3A). The reduction in collective accuracy arises because incentivizing or penalizing AI usage causes individuals to imitate others based on their AI usage rather than their predictive accuracy. Thus, stronger interventions can push the group to always [JS: wholly?] ( $\beta = 1$ ) or never ( $\beta = 0$ ) rely on AI (Fig. 3B, D, F, H) but these scenarios do not necessarily lead to better outcomes (Fig. 3D, F, H). When AI bias is relatively large, a weak penalty can lead to higher collective accuracy, but this represents a narrow parameter regime (Figure 3G).

Overall, these results indicate that simply incentivizing or penalizing the AI, independent of individuals' performance, use may exacerbate rather than resolve the risk of AI on CI. Thus, we also considered an incentive structure where interventions for AI usage affects the payoffs multiplicatively, thus giving higher payoffs to individuals who rely more (or less) AI and makes better prediction. [SWP: Supp.] [JS: Should I add the multiplicative intervention to the SI? I remember that we didn't reach a clear conclusion during our last meeting about whether to include it.]

## Balanced incentives mitigate AI-induced failures of CI

Neither the original incentive structures nor simple interventions targeting AI use are sufficient to promote CI. What incentive structure, then, would work in the presence of AI? Here, we propose a "balanced" incentive structure, modeled as the average of the feedback and niche expert incentives.

The core idea behind the balanced structure is to maintain interest diversity and prevent collective bias. On one hand, the feedback incentive structure is prone to the loss of interest diversity but can prevent collective bias by incentivizing players whose predictions lie opposite to the collective prediction. On the other hand, the niche-expert structure can maintain interest diversity because it directly incentivizes minority interests. However the niche-expert structure cannot prevent collective bias because, within the same factor of interest, individuals are rewarded only according to their individual predictive performance, which in turn homogenize the predictions.



**Figure 4: Balanced structure can promote collective intelligence** Trajectories of collective accuracy (A) and counterfactual human CI (B) under three incentive structures (feedback, niche-expert, and balanced) with Chatbot AI. Distributions of individual interest and belief (C-E) and of interest and reliance on AI (F-H) after 200,000 generations. Each point represents an individual. Dashed lines in panels C-E represent the true coefficients ( $\alpha_i$ ) of the prediction target. Dashed horizontal lines in panels F-H indicate the median reliance on AI. Prediction target parameters:  $m = 50$ ,  $s = 50$ ,  $\mu = 0$ ,  $\alpha_i = 5 - 0.2i$ , and  $\sigma_i \sim U(0, 3)$ . Population parameters:  $N = 10,000$ ,  $c_A \sim \mathcal{N}(0, 5^2)$ , and  $\beta_A \sim U(0, 1)$ . AI parameters:  $b_i = 0.4$  and  $\tau = 0.3$ .

Therefore, when the two incentive structures are combined, the population achieves CI by maintaining interest diversity while limiting collective bias (Fig. 4A, S6). Un-

der the balanced structure, individuals remain more evenly distributed across causal factors, and their beliefs lie closer to the true coefficients than under either incentive structure alone (Fig. 4C–E). The balanced structure also produces higher counterfactual collective accuracy than the feedback or niche-expert structure (Fig. 4B, S6). These patterns are robust to how the two incentive structures are weighted when combined (Fig. S7), and are driven by the emergent property of the balanced structure, under which the population increases its reliance on AI as AI becomes more accurate (Fig S8).

[SWP: *may need some robustness check rather than a case study...*]

## Discussion

The ongoing race towards the development of “better” AIs continues to pose questions about the societal benefits and risks of AI uses (Bender et al., 2021; Burton et al., 2024; Cui and Yasseri, 2024). Here, we used mathematical models of evolutionary dynamics to investigate how AI uses and incentive structures jointly affect the emergence of CI, which is defined as the population’s ability to make accurate predictions. We find that an “omniscient” AI model, which incorporates information about all relevant causal factors, can improve collective accuracy, whereas a “chatbot” AI model, whose outcome depends on the user’s interest, can impair it. These contrasting outcomes arise because AI assistance affects not only individual predictions, but also the population’s interest diversity, beliefs, and reliance on AI. We also show that directly incentivizing or penalizing AI uses, independent of individual’s performances, can further limit the collective accuracy of the population. Instead, a balanced incentive structure can maintain CI by promoting diversity and limiting bias.

Our analysis reveals that AI can prevent the emergence of CI through two different mechanisms. First, AI use can cause individuals to concentrate on a subset of the factors that determine the prediction target, thereby reducing diversity in their interests. This result is broadly consistent with recent empirical studies showing that AI assistance can improve individual performance but limit the diversity of outputs, in domains ranging from scientific research (Hao et al., 2026) to creative writing (Doshi and Hauser, 2024). Second, over-reliance on AI can cause the population to inherit inherent biases in AI’s predictions (Fügener et al., 2021; Vicente and Matute, 2023), causing the prediction accuracy to decrease eventually. This mechanism can prevent the emergence of CI even when the interest diversity is maintained because biases in AI predictions can be amplified when individual predictions are aggregated. Thus, preserving the diversity of ideas will not be sufficient to promote CI. Instead, AI uses need to be calibrated to prevent systematic AI biases from becoming collective biases (Buçinca et al., 2021).

Our analyses of counterfactual collective accuracy also raises an important concern for future AI uses: while AI uses may improve the apparent performance of

272 individuals and, in some cases, the population as a whole, it can simultaneously re-  
 273 duce the population’s ability to make accurate predictions without AI. These results  
 274 echo findings from a recent field experiment, which demonstrated that students,  
 275 who seemingly performed better in solving mathematics problems under AI assis-  
 276 tance, performed worse on their own than those who did not have access (Bastani  
 277 et al., 2025). These findings highlight the need to evaluate AI tools not only by  
 278 the performance gains they provide during use, but also by whether individuals and  
 279 populations retain the ability to perform without them (Melumad and Yun, 2025;  
 280 Ke et al., 2026). Making this distinction clear will be particularly important for  
 281 education, where AI may help students complete a task without helping them learn  
 282 how to do it on their own (Bastani et al., 2025; Melumad and Yun, 2025).

283 As generative AIs and large language models are already generating substantial  
 284 benefits, many organizations, both industrial and academic, are increasingly seek-  
 285 ing to improve their collective performance by regulating AI uses (Thorp, 2023;  
 286 Bousquette, 2026; Chawla, 2026; Keary, 2026). Such regulations may take direct  
 287 forms, including AI-use policies or token-based leaderboards, or may operate indi-  
 288 rectly through other incentives, such as productivity rewards or the social stigma  
 289 associated with AI use (Reif et al., 2025). Our model suggests that directly incen-  
 290 tivizing or penalizing AI use is unlikely to induce appropriately calibrated reliance on  
 291 AI or to promote CI. Incentivizing AI use could lead to overreliance, causing groups  
 292 to propagate AI biases, whereas penalizing AI use could lead to underreliance, pre-  
 293 venting groups from using AI even when it performs well in the relevant domain.  
 294 Our result instead shows that appropriate AI use and accurate CI can be promoted  
 295 by focusing on the traditional properties of groups that have been emphasized for  
 296 decades: maintaining diversity and preventing collective bias, rather than on AI use  
 297 itself (Hong and Page, 2004; Lorenz et al., 2011; Mann and Helbing, 2017).

298 There are several limitations to our analyses. First, our model allows for social  
 299 learning among humans, but AI’s inherent ability remains fixed throughout the evo-  
 300 lutionary process. In reality, AI systems can also learn from human-generated data  
 301 (Ouyang et al., 2022). Such bidirectional learning increase the similarity between  
 302 human and AI errors and therefore further reduce the group performance (?). Sec-  
 303 ond, we model AI errors using fixed, factor-specific additive biases and independent  
 304 random errors. This assumption allows random errors to be reduced through ag-  
 305 gregation, while systematic biases can still persist in the collective prediction. In  
 306 reality, AI errors may have more complex structures, including biased estimates of  
 307 factor effects and correlated errors across individuals, factors, or repeated interac-  
 308 tions. Further empirical and theoretical work is therefore needed to understand how  
 309 these error structures affect the emergence of CI. Finally, following established mod-  
 310 els of CI, we assume that the prediction target is a linear combination of independent  
 311 causal factors. This assumption does not hold for many real-world tasks, where causal  
 312 factors may be correlated or interact nonlinearly. Future studies should therefore in-  
 313 vestigate how nonlinear relationships between causal factors and prediction targets  
 314 affect the interaction between AI assistance and the emergence of CI.

315 The rapid adoption of personalized AI assistants is changing how individuals  
 316 learn, work, and make decisions (Tessler et al., 2024; Glickman and Sharot, 2025;  
 317 Sajadieh et al., 2026; Bick et al., 2026; Ke et al., 2026). While the immediate ben-  
 318 efits and risks of these systems have been evaluated at the individual level Noy and  
 319 Zhang (2023); Bastani et al. (2025), our study raises a broader concern that their  
 320 widespread AI use may reshape collective intelligence of human society. Our results  
 321 further underline the importance of designing reward structures that preserve minor-  
 322 ity expertise and prevent AI biases from persisting across the population. A detailed  
 323 empirical understanding of how AI assistance reshapes diversity, expertise, and re-  
 324 liance at the population level will therefore be critical for predicting the dynamics of  
 325 future of human collective intelligence.

## 326 Methods

### 327 Prediction target

328 Following previous models of CI, we model the prediction target as a linear combi-  
 329 nation of  $M$  independent causal factors (Hong et al., 2012; Mann and Helbing, 2017;  
 330 Wang et al., 2025):

$$Y = \alpha_0 + \alpha_1 X_1 + \cdots + \alpha_M X_M, \quad (2)$$

331 where the coefficient  $\alpha_i$  determines the magnitude and direction of the effect of  
 332 factor  $i$ , and  $\alpha_0$  represents a global intercept. Each causal factor  $X_i$  is modeled as an  
 333 independent Gaussian random variable with mean zero and standard deviation  $\sigma_i$ .

### 334 Players

335 We consider a well-mixed population  $\mathcal{N}$  consisting of  $N$  players engaged in a novel  
 336 prediction task. In the absence of AI assistance, the strategy of player  $A$  is char-  
 337 acterized by two variables: interest  $e_A$  and belief  $c_A$ . Player  $A$  observes the causal  
 338 factor  $X_{e_A}$  and makes a prediction by multiplying the observed factor value by their  
 339 belief:

$$Y_A = c_A X_{e_A}, \quad (3)$$

340 where  $e_A$  can take an integer value from 0 to  $M$ . When  $e_A = 0$ , the player does  
 341 not observe any causal factor and instead makes a constant prediction based solely  
 342 on their belief. We refer to this as a stubborn strategy because the player’s predic-  
 343 tion does not respond to the realized values of the causal factors. For notational  
 344 convenience, we assume that  $X_0 = 1$ .

345 When the group is assisted by AI, each player’s strategy additionally includes  
 346 reliance on AI, denoted by  $\beta_A$ . We assume that each player consults the AI inde-  
 347 pendently and revises their prediction by taking a weighted average of their own  
 348 prediction and the AI-generated prediction:

$$Y_A^{\text{re}} = \beta_A Y_A^{\text{AI}} + (1 - \beta_A) Y_A, \quad (4)$$

where  $\beta_A$  ranges from 0 to 1. A value of  $\beta_A = 1$  indicates complete reliance on AI, whereas  $\beta_A = 0$  indicates that the player does not use the AI prediction.

## AI models

We assume that the AI model has been trained on similar tasks and is therefore capable of making predictions based on causal factors. However, because the model is imperfect, its outputs are subject to systematic additive bias and stochastic error. The additive bias associated with factor  $i$  is denoted by  $b_i$ , and the stochastic error is denoted by  $\epsilon$ . The AI is neither trained nor updated during the simulation, and its biases therefore remain fixed throughout the simulation. For simplicity, we assume  $b_i = b$  for the main analysis for all  $i$ . The model formulation nevertheless allows biases to differ among factors.

We assume that the stochastic error follows a Gaussian distribution with mean zero and standard deviation  $\tau$ . Each time a player consults the AI, an independent error is generated. Errors are therefore independent across players and across repeated consultations by the same player. Consequently, stochastic AI errors can be attenuated when independently generated predictions are aggregated across players. We therefore hold  $\tau$  constant and vary the magnitude of the additive bias to manipulate the level of AI accuracy during our analyses.

We consider two extreme types of AI that differ in the amount of information available for prediction. The first is termed the Omniscient AI, which can observe all  $M$  causal factors and incorporate them into its prediction regardless of the user's interest. The prediction generated by the Omniscient AI for player  $A$  is expressed as follows:

$$Y_A^{\text{AI}} = \alpha_0 + b_0 + \alpha_1 X_1 + b_1 + \cdots + \alpha_M X_M + b_M + \epsilon. \quad (5)$$

The second is termed the Chatbot AI, which can use only the single causal factor  $X_{e_A}$  associated with the player's interest. The prediction generated by the Chatbot AI for player  $A$  is expressed as follows:

$$Y_A^{\text{AI}} = \alpha_{e_A} X_{e_A} + b_{e_A} + \epsilon. \quad (6)$$

## Aggregation rules

The revised individual predictions are aggregated to form a collective prediction. We use two aggregation rules proposed in previous research (Wang et al., 2025), depending on the type of AI used by the group. First, when the group is assisted by the Omniscient AI, the AI component of each revised prediction contains information about all  $M$  factors, even though the individual's own prediction is based on only one factor. Each revised prediction can therefore be treated as an estimate of the entire target. Accordingly, we calculate the collective prediction by taking the simple average of the revised individual predictions:

$$\hat{Y}^{\text{re}} = \frac{Y_1^{\text{re}} + Y_2^{\text{re}} + \cdots + Y_n^{\text{re}}}{N}. \quad (7)$$

384 Second, when the group is assisted by the Chatbot AI, both the player’s initial  
 385 prediction and the AI’s prediction are based on the same causal factor. Each revised  
 386 prediction therefore contains information about only one factor and can be treated  
 387 as an estimate of that factor’s contribution to the target. We consequently use  
 388 clustering aggregation.

389 Clustering aggregation is performed by grouping individuals according to their  
 390 interests and calculating the mean prediction within each group. The collective  
 391 prediction is then obtained by summing the mean predictions of all nonempty groups:

$$\hat{Y}^{\text{re}} = \sum_{i:n_i>0} \frac{1}{n_i} \sum_{A \in \mathcal{A}_i} Y_A^{\text{re}}, \quad (8)$$

392 where  $\mathcal{A}_i$  represents the set of players interested in factor  $i$ , and  $n_i = |\mathcal{A}_i|$  represents  
 393 the number of players in that set.

394 When the group is not assisted by AI, collective predictions are computed from the  
 395 unrevised individual predictions throughout the simulation. Both simple averaging  
 396 and clustering can be used in the absence of AI. For fair comparison, we use the  
 397 same aggregation rule as in the corresponding AI-assisted condition.

## 398 Incentive structures

399 Players receive payoffs based on the underlying incentive structure. We consider five  
 400 incentive structures: feedback structure, niche-expert structure, direct intervention  
 401 on AI use of these two structures, and a balanced structure.

402 The feedback structure does not directly reward individuals according to their  
 403 own prediction accuracy. Instead, it rewards predictions that are aligned with the  
 404 residual error of the collective prediction and therefore have the potential to move  
 405 the collective prediction toward the true value. Given player  $A$ ’s revised prediction  
 406  $Y_A^{\text{re}}$  and the collective prediction  $\hat{Y}^{\text{re}}$ , the payoff is expressed as

$$\pi_A = Y_A^{\text{re}}(Y - \hat{Y}^{\text{re}}). \quad (9)$$

407 The niche-expert structure assigns higher payoffs to individuals who make accu-  
 408 rate predictions while having an underrepresented interest. Specifically, the squared  
 409 prediction error of player  $A$  is weighted by  $\rho_{e_A} = n_{e_A}/n$ , the proportion of players  
 410 interested in the same factor:

$$\pi_A = -\rho_{e_A}(Y_A^{\text{re}} - Y)^2. \quad (10)$$

411 Previous research has shown that these two incentive structures can produce near  
 412 perfect collective accuracy through social learning, except when the niche-expert  
 413 incentive is combined with simple averaging (Wang et al., 2025). They are therefore  
 414 used as baseline structures for examining how AI assistance affects the emergence of  
 415 CI.

416 To examine the effects of directly encouraging or discouraging AI use, we mod-  
 417 ify the feedback and niche-expert structures by adding a term proportional to the  
 418 player’s reliance on AI:

$$\pi_A = Y_A^{\text{re}}(Y - \hat{Y}^{\text{re}}) + \lambda\beta_A \quad (11)$$

$$\pi_A = -\rho_{e_A}(Y_A^{\text{re}} - Y)^2 + \lambda\beta_A. \quad (12)$$

419 Here,  $\lambda$  represents the strength of the direct incentive or penalty applied to AI use. A  
 420 positive value of  $\lambda$  rewards AI reliance, whereas a negative value penalizes it. When  
 421  $\lambda = 0$ , no direct incentive or penalty is applied, and the payoff functions reduce to  
 422 the original feedback and niche-expert structures.

423 The balanced structure is defined as the arithmetic mean of the feedback and  
 424 niche-expert payoff components:

$$\pi_A = \frac{Y_A^{\text{re}}(Y - \hat{Y}^{\text{re}}) - \rho_{e_A}(Y_A^{\text{re}} - Y)^2}{2}. \quad (13)$$

## 425 Simulations

426 All simulations are conducted using an agent-based model with 50 causal factors  
 427 ( $M = 50$ ) and 10,000 players ( $n = 10,000$ ). The parameters defining the prediction  
 428 target are sampled at the beginning of the simulations and subsequently held fixed.

429 Coefficients  $\alpha_i$  are sampled from a uniform distribution on  $[-5, 5]$ , except in the  
 430 simulation presented in Figure 4, in which  $\alpha_i$  is set to  $5 - 0.2i$  for visualization.  
 431 Standard deviations  $\sigma_i$  are sampled from a uniform distribution on  $[0, 3]$ .

432 Players’ initial strategies are also sampled from predefined probability distribu-  
 433 tions. The distribution of individual belief  $c_A$  depends on the aggregation rule. Under  
 434 simple averaging, each factor’s contribution is scaled by the proportion of players in-  
 435 terested in that factor. We therefore sample beliefs from a Gaussian distribution  
 436 with mean zero and standard deviation 100, following the scaling used in previous  
 437 work (Wang et al., 2025). Under clustering aggregation, beliefs are sampled from a  
 438 Gaussian distribution with mean zero and standard deviation 5. Because predictions  
 439 are averaged separately within each interest group and then summed, no additional  
 440 scaling of  $c_A$  is required. The initial interest of each player is sampled uniformly  
 441 from the integers between 0 and 50, and reliance on AI was sampled from a uniform  
 442 distribution on  $[0, 1]$ .

443 We assume that prediction events occur on a substantially faster timescale than  
 444 social learning. In each generation, we therefore calculate the expected payoff  $\mathbb{E}[\pi_A]$   
 445 of each player analytically rather than explicitly sampling prediction events. The  
 446 expectation is taken over the distributions of the causal factors  $X_1, \dots, X_M$  and the  
 447 stochastic AI error  $\epsilon$ , conditional on the current population strategies and the fixed  
 448 target parameters. Closed form expression of expected payoffs are derived for all  
 449 incentive structures and are presented in the Supplementary Methods.

Each generation consists of an expected payoff calculation followed by one opportunity for pairwise social learning. Two distinct players,  $A$  and  $B$ , are randomly sampled, and player  $A$  imitated all three strategies of player  $B$  with probability

$$\frac{1}{1 + \exp(s(\mathbb{E}[\pi_A] - \mathbb{E}[\pi_B]))}, \quad (14)$$

where  $s$  represents the strength of social learning and was set to 50 in all simulations. We introduce a mutation rate  $\mu$ , such that with probability  $\mu$ , player  $A$  does not imitate player  $B$  but instead redrew all strategy components from the same distributions used to initialize the population. The mutation rate is set to zero in all simulations except those presented in Supplementary Fig. S4 [SWP: *need to check*].

Unless otherwise specified, each simulation is run for 200,000 generations. When a result is represented by a single summary value rather than as a temporal trajectory, the metric was averaged over the final 10,000 generations.

To evaluate the dynamics of collective prediction, we define six summary metrics: collective accuracy, collective bias, collective variance, counterfactual collective accuracy, interest diversity, and median reliance on AI. At each population state, expectations and variances are evaluated analytically over the distributions of the causal factors and AI errors rather than estimated from sampled prediction events. Collective bias and collective variance constitute the bias–variance decomposition of the group level collective prediction error.

Collective accuracy is normalized relative to the baseline prediction  $\alpha_0$ . A negative value indicates that the collective prediction performs worse than the baseline. Counterfactual collective accuracy is evaluated by setting  $\beta_A = 0$  while retaining the evolved interests and beliefs of the AI-assisted population. In calculating interest diversity, we use the convention that  $\rho_i \ln \rho_i = 0$  when  $\rho_i = 0$  (Table 1).

## Data and code availability

All data are stored in a publicly available GitHub repository (<https://github.com/parklab-snu/collective-intelligence-with-AI>).

## Acknowledgements

S.W.P. was supported by the New Faculty Startup Fund from Seoul National University, and the Global-LAMP Program of the National Research Foundation of Korea (NRF) grant funded by the Ministry of Education (No. RS-2023-00301976).

## Contributions

Jaeseung Kim: Conceptualization, Formal Analysis, Investigation, Methodology, Software, Visualization, Writing - Original Draft Preparation, Writing - Review &

Table 1: Evaluation metrics used to analyze collective prediction dynamics.

| Metric                             | Definition                                                                         | Interpretation                                                                                                         |
|------------------------------------|------------------------------------------------------------------------------------|------------------------------------------------------------------------------------------------------------------------|
| Collective accuracy                | $1 - \frac{\mathbb{E}[(Y - \hat{Y}^{\text{re}})^2]}{\mathbb{E}[(Y - \alpha_0)^2]}$ | Accuracy of the revised collective prediction relative to the baseline prediction $\alpha_0$ .                         |
| Collective bias                    | $\left(\mathbb{E}[Y - \hat{Y}^{\text{re}}]\right)^2$                               | Squared expected deviation of the revised collective prediction from the true target.                                  |
| Collective variance                | $\text{Var}(Y - \hat{Y}^{\text{re}})$                                              | Variability of the revised collective prediction error across prediction events.                                       |
| Counterfactual collective accuracy | $1 - \frac{\mathbb{E}[(Y - \hat{Y})^2]}{\mathbb{E}[(Y - \alpha_0)^2]}$             | Accuracy obtained after removing AI use from the current population while retaining its evolved interests and beliefs. |
| Interest diversity                 | $\exp\left(-\sum_{i=0}^M \rho_i \ln \rho_i\right)$                                 | Effective number of interests represented in the population.                                                           |
| Median reliance on AI              | $\text{median}_{A \in N}(\beta_A)$                                                 | Median reliance on AI in the population.                                                                               |

483 Editing. Sang Woo Park: Conceptualization, Investigation, Methodology, Supervi-  
484 sion, Writing - Original Draft Preparation, Writing - Review & Editing.

## 485 **Competing Interests**

486 The authors declare no competing interests.

## Supplementary Text

### 1 Omniscient AI

Omniscient AI assumes that AI can incorporate all causal factors regardless of the player's interest.

#### 1.1 Model

$$Y_A^{AI} = \alpha_0 + b_0 + \alpha_1 X_1 + b_1 + \cdots + \alpha_M X_M + b_M + \epsilon. \quad (S1)$$

For simplicity, prediction of Omniscient AI can be written as:

$$Y^{AI} = Y + B + \epsilon \quad (S2)$$

where  $Y$  stands for true prediction target ( $Y = \alpha_0 + \alpha_1 X_1 + \cdots + \alpha_M X_M$ ) and  $B$  is sum of all fixed biases ( $B = b_0 + b_1 + \cdots + b_M$ ),  $\epsilon$  follows normal distribution with zero mean,  $\tau$  standard deviation with no correlation within or between players. Player A's prediction and revised prediction can be written as follows:

$$Y_A = c_A X_{e_A} \quad (S3)$$

$$Y_A^{re} = \beta_A Y^{AI} + (1 - \beta_A) Y_A \quad (S4)$$

where  $c_A$  stands for player A's belief on the factor,  $e_A$  stands for the interest, and  $\beta_A$  stands for reliance on AI.

#### 1.2 Aggregation

Because  $Y_A^{AI}$  is subject to all  $M$  factors, we use simple averaging aggregation for collective prediction.

$$\begin{aligned} \hat{Y}^{re} &= \frac{1}{N} \sum_{j=1}^N Y_j^{re} \\ &= \frac{1}{N} \sum_{j=1}^N \{ \beta_j Y^{AI} + (1 - \beta_j) Y_j \} \\ &= \frac{1}{N} \sum_{j=1}^N \{ \beta_j (Y + B + \epsilon) + (1 - \beta_j) c_j X_{e_j} \} \end{aligned}$$

Reparameterization for simple derivation and interpretability.

$$\bar{\beta} := \frac{1}{N} \sum_{j=1}^N \beta_j \quad (S5)$$

504

$$\bar{\eta} := \frac{1}{N} \sum_{j=1}^N \beta_j \epsilon \quad (\text{S6})$$

505

$$\gamma_i := \frac{1}{N} \sum_{A \in \mathcal{A}_i} (1 - \beta_A) c_A \quad (\text{S7})$$

506  $\bar{\beta}$  can be interpreted as mean reliance on AI,  $\gamma$  stands for the coefficient for the factor  
 507  $i$  which is solely based on players' belief.

508 By this reparameterization, we can write  $\hat{Y}^{re}$  as follows.

$$\hat{Y}^{re} = \bar{\beta}(Y + B) + \sum_{i=0}^M \gamma_i X_i + \bar{\eta} \quad (\text{S8})$$

### 509 1.3 Expected payoffs

#### 510 Feedback

$$\delta_0 := \alpha_0 - (\bar{\beta}(\alpha_0 + B) + \gamma_0) \quad (\text{S9})$$

511

$$\delta_i := \alpha_i - (\bar{\beta}\alpha_i + \gamma_i), \quad (i \neq 0) \quad (\text{S10})$$

512

$$Y - \hat{Y}^{re} = \delta_0 + \sum_{i=1}^M \delta_i X_i - \bar{\eta} \quad (\text{S11})$$

513 See equation Eq. (S6) for the  $\bar{\eta}$ .

514  $\delta_0$  is constant term and  $\delta_i$  is independent of  $\alpha_k$  ( $k \neq i$ ),  $\epsilon$ , and  $\bar{\eta}$ .

$$\begin{aligned} \mathbb{E}(\pi_A) &= \mathbb{E}[Y_A^{re}(Y - \hat{Y}^{re})] \\ &= \mathbb{E} \left[ \left\{ \beta_A \alpha_0 + \beta_A \sum_{i=1}^M \alpha_i X_i + \beta_A B + \beta_A \epsilon + (1 - \beta_A) c_A X_{e_A} \right\} \left\{ \delta_0 + \sum_{i=1}^M \delta_i X_i - \bar{\eta} \right\} \right] \\ &= \beta_A \alpha_0 \delta_0 + \beta_A \sum_{i=1}^M \delta_i \alpha_i \sigma_i^2 + \beta_A B \delta_0 - \frac{1}{N} \beta_A^2 \tau^2 + (1 - \beta_A) c_A \delta_{e_A} \sigma_{e_A}^2 \\ &= \beta_A \left\{ (\alpha_0 + B) \delta_0 + \sum_{i=1}^M \alpha_i \delta_i \sigma_i^2 \right\} + (1 - \beta_A) c_A \delta_{e_A} \sigma_{e_A}^2 - \frac{\beta_A^2 \tau^2}{N} \end{aligned}$$

515 **Niche-expert**

516 If  $e_A = 0$ , player does not observe causal factor and their unrevised prediction is same  
 517 with their belief  $c_A$ . Such that, the expected payoff is

$$\begin{aligned}
 \mathbb{E}(\pi_A) &= -\mathbb{E}[\rho_0(Y_A^{re} - Y)^2] \\
 &= -\mathbb{E}[\rho_0\{(\beta_A - 1)Y + \beta_A B + \beta_A \epsilon + (1 - \beta_A)c_A\}^2] \\
 &= -\mathbb{E}\left[\rho_0\left\{(\beta_A - 1)(\alpha_0 - c_A) + \beta_A B + (\beta_A - 1)\sum_{i=1}^M \alpha_i X_i + \beta_A \epsilon\right\}^2\right] \\
 &= -\rho_0\left\{(1 - \beta_A)^2(\alpha_0 - c_A)^2 - 2\beta_A(1 - \beta_A)(\alpha_0 - c_A)B + \beta_A^2 B^2\right. \\
 &\quad \left.+ (1 - \beta_A)^2 \sum_{i \neq 0} \alpha_i^2 \sigma_i^2 + \beta_A^2 \tau^2\right\}
 \end{aligned}$$

518 Else,

$$\begin{aligned}
 \mathbb{E}(\pi_A) &= -\mathbb{E}[\rho_{e_A}(Y_A^{re} - Y)^2] \\
 &= -\mathbb{E}[\rho_{e_A}\{(\beta_A - 1)Y + \beta_A B + \beta_A \epsilon + (1 - \beta_A)c_A X_{e_A}\}^2] \\
 &= -\mathbb{E}\left[\rho_{e_A}\left\{(\beta_A - 1)\alpha_0 + \beta_A B + (\beta_A - 1)(\alpha_{e_A} - c_A)X_{e_A} + (\beta_A - 1)\sum_{i \neq e_A, 0} \alpha_i X_i + \beta_A \epsilon\right\}^2\right] \\
 &= -\rho_{e_A}\left\{(1 - \beta_A)^2 \alpha_0^2 - 2\beta_A(1 - \beta_A)\alpha_0 B + \beta_A^2 B^2 + (1 - \beta_A)^2(\alpha_{e_A} - c_A)^2 \sigma_{e_A}^2\right. \\
 &\quad \left.+ (1 - \beta_A)^2 \sum_{i \neq e_A, 0} \alpha_i^2 \sigma_i^2 + \beta_A^2 \tau^2\right\}
 \end{aligned}$$

519 **Incentivizing or penalizing AI use**

520 Because additive term  $\lambda\beta$  is not a random variable, we can simply derive the expected  
 521 payoff as

$$\mathbb{E}(\pi_{A, Feedback}) = \mathbb{E}[Y_A^{re}(Y - \hat{Y}^{re}) + \lambda\beta_A] = \mathbb{E}[Y_A^{re}(Y - \hat{Y}^{re})] + \lambda\beta_A. \quad (S12)$$

$$\mathbb{E}(\pi_{A, Niche-expert}) = -\mathbb{E}[\rho_{e_A}(Y_A^{re} - Y)^2 + \lambda\beta_A] = -\mathbb{E}[\rho_{e_A}(Y_A^{re} - Y)^2] + \lambda\beta_A. \quad (S13)$$

522 **1.4 Expected accuracy**

$$\mathbb{E}[(Y - \alpha_0)^2] = \mathbb{E}\left[\left(\alpha_0 + \sum_{i=1}^M \alpha_i X_i - \alpha_0\right)^2\right] = \sum_{i=1}^M \alpha_i^2 \sigma_i^2 \quad (S14)$$

523

$$\mathbb{E}[(Y - \hat{Y}^{re})^2] = \mathbb{E}\left[\left(\delta_0 + \sum_{i=1}^M \delta_i X_i - \hat{\eta}\right)^2\right] = \delta_0^2 + \sum_{i=1}^M \delta_i^2 \sigma_i^2 + \frac{\tau^2}{N^2} \sum_{j=1}^N \beta_j^2 \quad (\text{S15})$$

524

$$\begin{aligned} R &= 1 - \frac{\mathbb{E}[(Y - \hat{Y})^2]}{\mathbb{E}[(Y - \alpha_0)^2]} \\ &= 1 - \frac{\delta_0^2 + \sum_{i=1}^M \delta_i^2 \sigma_i^2 + \frac{\tau^2}{N^2} \sum_{j=1}^N \beta_j^2}{\sum_{i=1}^M \alpha_i^2 \sigma_i^2} \end{aligned}$$

## 525 2 Chatbot AI

### 526 2.1 Model

$$Y_A^{AI} = \alpha_{e_A} X_{e_A} + b_{e_A} + \epsilon \quad (\text{S16})$$

527  $b_{e_A}$  stands for factor specific additive bias,  $\epsilon$  follows normal distribution with zero  
 528 mean,  $\tau$  standard deviation with no correlation within or between players. Player  
 529 A's prediction and revised prediction can be written as follows:

$$Y_A = c_A X_{e_A} \quad (\text{S17})$$

530

$$Y_A^{re} = \beta_A Y_A^{AI} + (1 - \beta_A) Y_A \quad (\text{S18})$$

531 where  $c_A$  stands for player A's belief on the factor,  $e_A$  stands for the interest, and  
 532  $\beta_A$  stands for reliance on AI.

### 533 2.2 Aggregation

534 For Chatbot AI, clustering aggregation is used for collective prediction.

$$\begin{aligned} \hat{Y}^{re} &= \sum_{i=0}^M \frac{1}{n_i} \sum_{A \in \mathcal{A}_i} Y_A^{re} \\ &= \sum_{i=0}^M \frac{1}{n_i} \sum_{A \in \mathcal{A}_i} \{\beta_A Y_A^{AI} + (1 - \beta_A) Y_A\} \\ &= \sum_{i=0}^M \frac{1}{n_i} \sum_{A \in \mathcal{A}_i} [\{\beta_A \alpha_{e_A} + (1 - \beta_A) c_A\} X_{e_A} + \beta_A b_{e_A} + \beta_A \epsilon] \end{aligned}$$

535 Reparameterize for the simplicity.

$$\tilde{c}_i := \frac{1}{n_i} \sum_{A \in \mathcal{A}_i} \{\beta_A \alpha_{e_A} + (1 - \beta_A) c_A\} \quad (\text{S19})$$

536

$$\tilde{B}_i := \frac{1}{n_i} \sum_{A \in \mathcal{A}_i} \beta_A b_{e_A} \quad (\text{S20})$$

537

$$\bar{B} := \sum_{i=0}^M \tilde{B}_i \quad (\text{S21})$$

538

$$\tilde{\eta}_i := \frac{1}{n_i} \sum_{A \in \mathcal{A}_i} \beta_A \epsilon \quad (\text{S22})$$

539

$$\bar{\eta} := \sum_{i=0}^M \tilde{\eta}_i \quad (\text{S23})$$

## 540 2.3 Expected payoffs

### 541 Feedback

542

$$\delta_0 := \alpha_0 - \tilde{c}_0 - \bar{B} \quad (\text{S24})$$

543

$$\delta_i := \alpha_i - \tilde{c}_i, \quad (i \neq 0) \quad (\text{S25})$$

$$Y - \hat{Y}^{re} = \delta_0 + \sum_{i=1}^M \delta_i X_i - \bar{\eta} \quad (\text{S26})$$

544  $\delta_0$  is constant term and  $\delta_i$  is independent of  $\alpha_k$  ( $k \neq i$ ),  $\epsilon$ , and  $\bar{\eta}$ .

$$\begin{aligned} \mathbb{E}(\pi_A) &= \mathbb{E}[Y_A^{re}(Y - \hat{Y}^{re})] \\ &= \mathbb{E} \left[ \{(\beta_A \alpha_{e_A} + (1 - \beta_A) c_A) X_{e_A} + \beta_A b_{e_A} + \beta_A \epsilon\} \left\{ \delta_0 + \sum_{i=1}^M \delta_i X_i - \bar{\eta} \right\} \right] \\ &= \{\beta_A \alpha_{e_A} + (1 - \beta_A) c_A\} \delta_{e_A} \sigma_{e_A}^2 + \beta_A b_{e_A} \delta_0 - \frac{1}{n_{e_A}} \beta_A^2 \tau^2 \end{aligned}$$

### 545 Niche-expert

546 If  $e_A = 0$ ,

$$\begin{aligned} \mathbb{E}(\pi_A) &= -\mathbb{E}[\rho_0(Y_A^{re} - Y)^2] \\ &= -\mathbb{E} \left[ \rho_0 \left[ \{\beta_A \alpha_0 + (1 - \beta_A) c_A\} + \beta_A b_0 + \beta_A \epsilon - \alpha_0 - \sum_{i=1}^M \alpha_i X_i \right]^2 \right] \\ &= -\rho_0 \left\{ (1 - \beta_A)^2 (c_A - \alpha_0)^2 + 2(1 - \beta_A)(c_A - \alpha_0) \beta_A b_0 + \beta_A^2 b_0^2 \right. \\ &\quad \left. + \sum_{i \neq 0} \alpha_i^2 \sigma_i^2 + \beta_A^2 \tau^2 \right\} \end{aligned}$$

547 Else,

$$\begin{aligned}
\mathbb{E}(\pi_A) &= -\mathbb{E}[\rho_{e_A}(Y_A^{\text{re}} - Y)^2] \\
&= -\mathbb{E}\left[\rho_{e_A}\left[\{\beta_A\alpha_{e_A} + (1 - \beta_A)c_A\}X_{e_A} + \beta_A b_{e_A} + \beta_A\epsilon - \alpha_0 - \sum_{i=1}^M \alpha_i X_i\right]^2\right] \\
&= -\rho_{e_A}\left\{(1 - \beta_A)^2(c_A - \alpha_{e_A})^2\sigma_{e_A}^2 + \sum_{i \neq e_A, 0} \alpha_i^2 \sigma_i^2\right. \\
&\quad \left.+ \alpha_0^2 + \beta_A^2 b_{e_A}^2 - 2\alpha_0\beta_A b_{e_A} + \beta_A^2 \tau^2\right\}
\end{aligned}$$

## 548 Incentivizing or penalizing AI use

549 Because additive term  $\lambda\beta$  is not a random variable, we can simply derive the expected  
550 payoff as

$$\mathbb{E}(\pi_{A, \text{Feedback}}) = \mathbb{E}\left[Y_A^{\text{re}}(Y - \hat{Y}^{\text{re}}) + \lambda\beta_A\right] = \mathbb{E}\left[Y_A^{\text{re}}(Y - \hat{Y}^{\text{re}})\right] + \lambda\beta_A. \quad (\text{S27})$$

$$\mathbb{E}(\pi_{A, \text{Niche-expert}}) = -\mathbb{E}\left[\rho_{e_A}(Y_A^{\text{re}} - Y)^2 + \lambda\beta_A\right] = -\mathbb{E}\left[\rho_{e_A}(Y_A^{\text{re}} - Y)^2\right] + \lambda\beta_A. \quad (\text{S28})$$

## 551 Balanced

552 Expected payoff of the balanced structure can also be driven by arithmetic mean of  
553 expected payoff of feedback and niche-expert.

$$\mathbb{E}(\pi_A) = \mathbb{E}\left[\frac{Y_A^{\text{re}}(Y - \hat{Y}^{\text{re}}) - \rho_{e_A}(Y_A^{\text{re}} - Y)^2}{2}\right] = \frac{\mathbb{E}\left[Y_A^{\text{re}}(Y - \hat{Y}^{\text{re}})\right] - \mathbb{E}\left[\rho_{e_A}(Y_A^{\text{re}} - Y)^2\right]}{2} \quad (\text{S29})$$

## 554 2.4 Expected accuracy

$$\mathbb{E}[(Y - \alpha_0)^2] = \mathbb{E}\left[\left(\alpha_0 + \sum_{i=1}^M \alpha_i X_i - \alpha_0\right)^2\right] = \sum_{i=1}^M \alpha_i^2 \sigma_i^2 \quad (\text{S30})$$

$$\mathbb{E}[(Y - \hat{Y})^2] = \mathbb{E}\left[\left(\delta_0 + \sum_{i=1}^M \delta_i X_i - \hat{\eta}\right)^2\right] = \delta_0^2 + \sum_{i=1}^M \delta_i^2 \sigma_i^2 + \sum_{i=0}^M \frac{\tau^2}{n_i^2} \sum_{A \in \mathcal{A}_i} \beta_A^2 \quad (\text{S31})$$

$$\begin{aligned}
R &= 1 - \frac{\mathbb{E}[(Y - \hat{Y})^2]}{\mathbb{E}[(Y - \alpha_0)^2]} \\
&= 1 - \frac{\delta_0^2 + \sum_{i=1}^M \delta_i^2 \sigma_i^2 + \sum_{i=0}^M \frac{\tau^2}{n_i^2} \sum_{A \in \mathcal{A}_i} \beta_A^2}{\sum_{i=1}^M \alpha_i^2 \sigma_i^2}
\end{aligned}$$

### 557 3 Evolutionary dynamics

558 For sufficiently large population ( $N \rightarrow \infty$ ), we can approximate the deterministic  
559 evolutionary dynamics using the replicator equation. Let  $\lambda$  denote a strategy,  $p_\lambda$  its  
560 frequency, and  $u_\lambda = \mathbb{E}(\pi_\lambda)$  its expected payoff. The replicator equation is

$$\frac{dp_\lambda}{dt} = p_\lambda(u_\lambda - \bar{u}), \quad (\text{S32})$$

561 where  $\bar{u} = \sum_\lambda p_\lambda u_\lambda$ . Therefore, at an internal stationary state, all strategies  
562 with positive frequency have the same expected payoff. A boundary state can also  
563 be stationary because a strategy with exactly zero frequency cannot increase under  
564 the replicator equation. Thus, stability of a boundary state needs to be considered  
565 separately by examining invasion by a rare strategy.

## 566 3.1 Omniscient AI

### 567 3.1.1 Feedback

568 When the population size approaches infinity, the effect of stochastic error on the  
569 collective prediction vanishes ( $\bar{\eta} \rightarrow 0$ ) and the effect of stochastic error in the ex-  
570 pected payoff,  $-\beta^2 \tau^2 / N$ , also vanishes. Following prior research (Wang et al., 2025),  
571 we define the Lyapunov function as the expected error of collective prediction

$$V = \mathbb{E} \left[ (Y - \hat{Y}^{re})^2 \right]. \quad (\text{S33})$$

572 The function  $V$  is non-negative and equals zero when the collective prediction is  
573 identical to the target. To examine how  $V$  changes under the evolutionary dynamics,  
574 we take its time derivative:

$$\begin{aligned}
\frac{dV}{dt} &= -2\mathbb{E} \left[ (Y - \hat{Y}^{re}) \frac{d\hat{Y}^{re}}{dt} \right] \\
&= -2\mathbb{E} \left[ \left( \delta_0 + \sum_{i=1}^M \delta_i X_i \right) \left\{ \frac{d\bar{\beta}}{dt} (Y + B) + \sum_{i=0}^M \frac{d\gamma_i}{dt} X_i \right\} \right] \\
&= -2 \left[ \left\{ (\alpha_0 + B) \delta_0 + \sum_{i=1}^M \alpha_i \delta_i \sigma_i^2 \right\} \frac{d\bar{\beta}}{dt} + \delta_0 \frac{d\gamma_0}{dt} + \sum_{i=1}^M \delta_i \sigma_i^2 \frac{d\gamma_i}{dt} \right].
\end{aligned}$$

575 For notational convenience, we define

$$K = (\alpha_0 + B) \delta_0 + \sum_{i=1}^M \alpha_i \delta_i \sigma_i^2. \quad (\text{S34})$$

576 Although  $K$  changes with the population state, it is common to all strategies at a  
577 given state and can therefore be treated as a constant with respect to the strategy  
578 index  $\lambda$ . We also define

$$G_e = \begin{cases} \delta_0, & e = 0, \\ \delta_e \sigma_e^2, & e \neq 0. \end{cases} \quad (\text{S35})$$

579 By the definitions of  $\bar{\beta}$  and  $\gamma_i$  and the replicator equation,

$$\frac{d\bar{\beta}}{dt} = \sum_{\lambda} p_{\lambda} (u_{\lambda} - \bar{u}) \beta_{\lambda} = \text{Cov}(\beta, u). \quad (\text{S36})$$

580 Similarly, the terms involving  $\gamma_i$  can be combined as

$$\delta_0 \frac{d\gamma_0}{dt} + \sum_{i=1}^M \delta_i \sigma_i^2 \frac{d\gamma_i}{dt} = \text{Cov}((1 - \beta) c G_e, u). \quad (\text{S37})$$

581 Therefore,

$$\begin{aligned}
\frac{dV}{dt} &= -2 \{ K \text{Cov}(\beta, u) + \text{Cov}((1 - \beta) c G_e, u) \} \\
&= -2 \text{Cov}(K\beta + (1 - \beta) c G_e, u).
\end{aligned}$$

582 For the feedback structure in the limit  $N \rightarrow \infty$ , the expected payoff of strategy  
583  $\lambda$  is

$$u_{\lambda} = K \beta_{\lambda} + (1 - \beta_{\lambda}) c_{\lambda} G_{e_{\lambda}}. \quad (\text{S38})$$

584 Which is same with Thus,

$$\frac{dV}{dt} = -2 \text{Cov}(u, u) = -2 \text{Var}(u) \leq 0. \quad (\text{S39})$$

Therefore, the expected error of collective prediction cannot increase during the evolutionary process and decreases whenever strategies differ in their expected payoffs. The derivative becomes zero when the variance of expected payoffs is zero,  $\text{Var}(u) = 0$ . This condition corresponds to equal expected payoffs among the strategies present in the population. A boundary state in which the entire population consists of a single strategy can also satisfy  $\text{Var}(u) = 0$  even when  $V > 0$ . However, such a state is not evolutionarily stable under the feedback structure. If the collective prediction differs from the target  $Y$ , a nonzero residual remains. By the definition of the feedback payoff, a novel strategy whose prediction aligns with the direction of this residual obtains a higher expected payoff than the resident strategy and can therefore invade the population. Thus, an imperfect boundary equilibrium with  $V > 0$  is unstable to the introduction of novel predictions.

Consequently, the evolutionary dynamics continue to reduce the collective prediction error until the population reaches the stable state with zero residual,  $V = 0$ . At this state, the collective prediction equals the target,  $\hat{Y}^{re} = Y$ , and the collective accuracy reaches  $R = 1$ .

### 3.1.2 Niche-expert

Unlike the stochastic error in the collective prediction, stochastic error in the niche-expert payoff is evaluated at the individual level and does not vanish as population size increases. Therefore, we retain  $\tau > 0$  in the following derivation.

We first consider strategies having the same interest by optimizing the expected payoff with respect to  $c$  and  $\beta$ . For a nonzero interest  $e$ , the expected payoff is strictly concave with respect to  $c$  for  $\beta < 1$  and  $\sigma_e > 0$ , and is maximized at

$$c_e^* = \alpha_e. \quad (\text{S40})$$

After substituting  $c_e^* = \alpha_e$ , the payoff is strictly concave with respect to  $\beta$ . Its unconstrained stationary point is

$$\tilde{\beta}_e = \frac{\alpha_0^2 + \alpha_0 B + \sum_{j \neq e, 0} \alpha_j^2 \sigma_j^2}{(\alpha_0 + B)^2 + \sum_{j \neq e, 0} \alpha_j^2 \sigma_j^2 + \tau^2}. \quad (\text{S41})$$

Because  $\beta$  is constrained between 0 and 1, the optimal  $\beta_e^*$  is  $\tilde{\beta}_e$  when  $0 < \tilde{\beta}_e < 1$ , and otherwise lies at the corresponding boundary,  $\beta_e^* = 0$  or  $\beta_e^* = 1$ . Thus, the boundary cases do not require a separate evolutionary argument; they only change the optimal prediction and its minimum expected squared error. When  $\beta_e^* = 1$ , the revised prediction is independent of  $c_e$ , so different values of  $c_e$  are selectively neutral and can be treated as a single payoff-equivalent strategy class.

Let  $L_e$  denote the minimum expected individual error,  $\mathbb{E}[(Y_A^{re} - Y)^2]$ , within interest  $e$ . For an internal optimum,

$$L_e = \frac{B^2 \sum_{j \neq e, 0} \alpha_j^2 \sigma_j^2 + \tau^2 \left( \alpha_0^2 + \sum_{j \neq e, 0} \alpha_j^2 \sigma_j^2 \right)}{(\alpha_0 + B)^2 + \sum_{j \neq e, 0} \alpha_j^2 \sigma_j^2 + \tau^2}. \quad (\text{S42})$$

618 If the optimum is located at  $\beta_e^* = 0$  or  $\beta_e^* = 1$ ,  $L_e$  is instead obtained by evaluating  
 619 the expected squared prediction error at the corresponding boundary.

620 For interest 0, optimization with respect to  $c$  gives

$$c_0^*(\beta) = \alpha_0 - \frac{\beta}{1 - \beta} B. \quad (\text{S43})$$

621 Substituting this into the expected payoff gives a strictly concave function of  $\beta$ ,  
 622 with the unique optimum

$$\beta_0^* = \frac{\sum_{j=1}^M \alpha_j^2 \sigma_j^2}{\sum_{j=1}^M \alpha_j^2 \sigma_j^2 + \tau^2}. \quad (\text{S44})$$

623 Therefore,

$$c_0^* = \alpha_0 - \frac{B}{\tau^2} \sum_{j=1}^M \alpha_j^2 \sigma_j^2, \quad (\text{S45})$$

624 and

$$L_0 = \frac{\tau^2 \sum_{j=1}^M \alpha_j^2 \sigma_j^2}{\sum_{j=1}^M \alpha_j^2 \sigma_j^2 + \tau^2}. \quad (\text{S46})$$

625 We denote the optimal strategy, or the payoff-equivalent strategy class when  
 626  $\beta_e^* = 1$ , by  $S_e$ . A state containing a suboptimal strategy within an interest can  
 627 be stationary if the optimal strategy is absent, but it is unstable against invasion  
 628 because the optimal strategy has a strictly higher payoff at the same  $\rho_e$ . Therefore,  
 629 a stable state can contain only  $S_e$  within each represented interest.

630 We next consider the frequencies of the  $M + 1$  optimal strategies. Let  $\rho_e$  denote  
 631 the frequency of  $S_e$ . Its expected payoff is

$$u_e = -\rho_e L_e. \quad (\text{S47})$$

632 Assuming  $L_e > 0$  for all interests, the equal-payoff condition of the replicator  
 633 equation at an internal stationary state gives

$$\rho_0^* L_0 = \rho_1^* L_1 = \cdots = \rho_M^* L_M. \quad (\text{S48})$$

634 Together with  $\sum_{e=0}^M \rho_e^* = 1$ , this uniquely determines

$$\rho_e^* = \frac{D}{L_e}, \quad D = \left( \sum_{j=0}^M \frac{1}{L_j} \right)^{-1}. \quad (\text{S49})$$

635 This internal stationary state is locally stable. At equilibrium, all represented  
 636 interests have the same expected payoff, with  $\rho_e^* L_e = D$ . If the frequency of one  
 637 interest increases slightly above its equilibrium value, its payoff decreases because  
 638 the niche-expert payoff is proportional to  $-\rho_e L_e$ . Conversely, if the frequency of  
 639 an interest decreases below its equilibrium value, its payoff increases. The replicator  
 640 dynamics therefore generate a restoring force that reduces small deviations in interest  
 641 frequencies and drives the population back toward the internal stationary state.

642 If one or more interests are absent, the resulting boundary state can be stationary  
 643 under the replicator equation, but it is unstable against invasion. The payoff of a rare  
 644 absent interest approaches zero as  $\rho_e \rightarrow 0$ , whereas the mean payoff of the resident  
 645 population is negative when  $L_e > 0$ , so the rare interest increases when introduced  
 646 at sufficiently small frequency.

647 Thus, there exists a unique stable full-support equilibrium in terms of the optimal  
 648 prediction strategies and their frequencies. Whether the constrained optimum has  
 649  $\beta_e^* = 0$ ,  $0 < \beta_e^* < 1$ , or  $\beta_e^* = 1$  does not change the frequency argument, because  
 650 these cases differ only through the resulting value of  $L_e$ . When  $\beta_e^* = 1$ , the strategy  
 651 is selectively neutral with respect to  $c_e$ , but its prediction, payoff, and equilibrium  
 652 interest frequency remain uniquely determined.

653 This equilibrium also allows a direct comparison with the expected accuracy of  
 654 the AI. Using  $Y^{\text{AI}}$  itself without aggregation as the prediction gives

$$\mathbb{E} [(Y - Y^{\text{AI}})^2] = B^2 + \tau^2. \quad (\text{S50})$$

655 For every interest, complete reliance on AI,  $\beta = 1$ , is a feasible strategy. There-  
 656 fore, because  $L_e$  is the minimum individual expected squared prediction error within  
 657 interest  $e$ ,

$$L_e \leq B^2 + \tau^2. \quad (\text{S51})$$

658 Moreover, for interest 0,

$$L_0 = \frac{\tau^2 \sum_{j=1}^M \alpha_j^2 \sigma_j^2}{\sum_{j=1}^M \alpha_j^2 \sigma_j^2 + \tau^2} < \tau^2 \leq B^2 + \tau^2. \quad (\text{S52})$$

659 Because the stable equilibrium has  $\rho_0^* > 0$ ,

$$\sum_{e=0}^M \rho_e^* L_e < B^2 + \tau^2. \quad (\text{S53})$$

660 The collective prediction is the average of individual revised predictions. By  
 661 convexity of the squared error,

$$\mathbb{E} [(Y - \hat{Y}^{re})^2] \leq \sum_{e=0}^M \rho_e^* L_e. \quad (\text{S54})$$

662 Therefore,

$$\mathbb{E} \left[ (Y - \hat{Y}^{re})^2 \right] < \mathbb{E} \left[ (Y - Y^{AI})^2 \right]. \quad (\text{S55})$$

663 Because the collective accuracy and AI accuracy use the same normalization by  
 664  $\mathbb{E}[(Y - \alpha_0)^2]$ , the stationary collective accuracy under the niche-expert structure is  
 665 strictly greater than the expected accuracy of the AI prediction.

666 Although the niche-expert structure improves collective prediction relative to the  
 667 AI, the stationary collective accuracy does not reach one when  $\tau > 0$ . For a nonzero  
 668 factor  $i$ , the residual coefficient of the stationary collective prediction can be written  
 669 as

$$\delta_i^* = \alpha_i \left\{ 1 - \bar{\beta}^* - \rho_i^* (1 - \beta_i^*) \right\} = \alpha_i \sum_{e \neq i} \rho_e^* (1 - \beta_e^*). \quad (\text{S56})$$

670 At the stable equilibrium,  $\rho_0^* > 0$ . In addition,  $\tau > 0$  implies  $\beta_0^* < 1$ . Therefore,  
 671 for every factor with  $\alpha_i \neq 0$ ,

$$\delta_i^* \neq 0. \quad (\text{S57})$$

672 Because  $\sum_{i=1}^M \alpha_i^2 \sigma_i^2 > 0$ , at least one factor contributes positive prediction error.  
 673 Hence,

$$\mathbb{E} \left[ (Y - \hat{Y}^{re})^2 \right] > 0, \quad (\text{S58})$$

674 and consequently the stationary collective accuracy satisfies  $R^* < 1$ .

## Supplementary Figure




Figure S1: **Niche-expert structure with averaging aggregation cannot promote CI without AI.** Trajectories of the mean absolute error from true coefficients and collective accuracy under the niche-expert structure with averaging aggregation in the absence of AI. The mean absolute error from true coefficients is calculated by first taking, for each interest, the absolute difference between the true coefficient and the mean belief of individuals sharing that interest, and then averaging these differences across all  $m + 1$  interests. The mean absolute error decreases across generations, indicating that the mean beliefs converge toward their corresponding true coefficients. However, collective accuracy remains near zero, indicating that simply averaging individual predictions does not yield accurate collective predictions. Prediction target parameters:  $m = 50$ ,  $s = 50$ ,  $\mu = 0$ ,  $\alpha_i \sim U(-5, 5)$ , and  $\sigma_i \sim U(0, 3)$ . Population parameters:  $N = 10,000$ ,  $c_A \sim \mathcal{N}(0, 100^2)$ .




Figure S2: **Evaluation metrics across various levels of AI bias.** Evaluation metrics across varying levels of AI bias under different assumptions about AI types (omniscient AI, and chatbot AI) and incentive structures (feedback, niche-expert). Larger absolute AI bias indicates a less accurate AI model. Across the range of AI bias considered, AI accuracy varies from approximately 0.24 to nearly 1 when the AI predicts the target independently. Dashed horizontal lines represent the values of the evaluation metrics when the group is not assisted by AI. Collective accuracy represents the predictive performance of the group, and counterfactual human CI represents the group’s predictive accuracy if AI assistance were unavailable at the given generation. Interest diversity is defined as Hill-Shannon diversity of interest within the population, median reliance on AI represents the median value of reliance on AI ( $\beta$ ). Collective bias represents systematic deviation of the collective prediction from the true target, collective variance represents variability of the collective prediction error across prediction events. All the evaluation metrics are averaged over generations 190,000–200,000. Prediction target parameters:  $m = 50$ ,  $s = 50$ ,  $\mu = 0$ ,  $\alpha_i \sim U(-5, 5)$ , and  $\sigma_i \sim U(0, 3)$ . Population parameters:  $N = 10,000$ ,  $c_A \sim \mathcal{N}(0, 100^2)$  for (A, B),  $c_A \sim \mathcal{N}(0, 5^2)$  for (C, D), and  $\beta_A \sim U(0, 1)$ . AI parameters:  $\tau = 0.3$ .




Figure S3: **Comparison of evaluation metrics with and without AI.** Trajectories of evaluation metrics when the group is assisted by the Omniscient AI and Chatbot AI. Here, feedback and niche-expert incentive structures are considered. Blue lines represent trajectories of evaluation metrics without AI assistance. Orange lines represent trajectories of evaluation metrics with AI assistance. Interest diversity is define as hill-shannon diversity of interest within population, median reliance on AI represent population median of reliance on AI ( $\beta$ ), collective bias represent systematic deviation of the collective prediction from the true target, collective variance repressent variability of the collective prediction error across prediction events. Prediction target parameters:  $m = 50$ ,  $s = 50$ ,  $\mu = 0$ ,  $\alpha_i \sim U(-5, 5)$ , and  $\sigma_i \sim U(0, 3)$ . Population parameters:  $N = 10,000$ ,  $c_A \sim \mathcal{N}(0, 100^2)$  for (A, B),  $c_A \sim \mathcal{N}(0, 5^2)$  for (C, D), and  $\beta_A \sim U(0, 1)$ . AI parameters:  $b_i = 0.36$  and  $\tau = 0.3$ .





Figure S4: **Feedback structure becomes more prone to interest diversity loss with AI** Trajectories of interest diversity with and without AI under the feedback structure (A). Heatmaps of interest diversity across varying levels of mutation rate (B, C) and the standard deviation of the initial belief distribution (D, E), with and without AI. Interest diversity declines toward zero even without AI over long timescales when there is no mutation and the initial belief distribution is narrow. However, with AI, interest diversity declines more strongly, even under moderate mutation rates and wider initial belief distributions. Interest diversity in the heatmaps is averaged over generations 190,000–200,000. Prediction target parameters:  $m = 50$ ,  $s = 50$ ,  $\mu = 0$  for (D, E),  $\alpha_i \sim U(-5, 5)$ , and  $\sigma_i \sim U(0, 3)$ . Population parameters:  $N = 10,000$ ,  $c_A \sim \mathcal{N}(0, 5^2)$  for (A, B, C), and  $\beta_A \sim U(0, 1)$ . AI parameters:  $b_i = 0.4$  and  $\tau = 0.3$ , chatbot AI is used.




Figure S5: **Niche-expert structure may reduce reliance on AI, delaying the emergence of CI.** Trajectories of collective accuracy and median reliance on AI when the niche-expert structure causes reliance on AI to decline over time. Red lines represent trajectories with AI across varying levels of AI bias (-0.2, -0.4, and -0.6). Green lines represent trajectories without AI; reliance on AI is set to zero in the absence of AI. This reduction in reliance on AI occurs when the  $\alpha_0$  and AI bias have opposite signs, and is associated with the eventual emergence of CI, although CI emerges substantially later than in the condition without AI. Prediction target parameters:  $m = 50$ ,  $s = 50$ ,  $\mu = 0$ ,  $\alpha_i \sim U(-5, 5)$ , and  $\sigma_i \sim U(0, 3)$ . Population parameters:  $N = 10,000$ ,  $c_A \sim \mathcal{N}(0, 5^2)$ , and  $\beta_A \sim U(0, 1)$ . AI parameters:  $\tau = 0.3$ , chatbot AI is used.




Figure S6: **Comparison of evaluation metrics between incentive structures across various levels of AI bias.** Evaluation metrics under feedback, niche-expert and balanced structures across varying levels of AI bias. Larger absolute AI bias indicates a less accurate AI model. Across the range of AI bias considered, AI accuracy varies from approximately 0.24 to nearly 1 when the AI predicts the target independently. All the evaluation metrics are averaged over generations 190,000–200,000. The balanced structure maintains near-perfect collective accuracy across bias levels and higher counterfactual human CI than the other incentive structures. These patterns are driven by well-calibrated reliance on AI, which increases as AI becomes more accurate, and by well-preserved interest diversity, which together lead to low collective variance and collective bias. Prediction target parameters:  $m = 50$ ,  $s = 50$ ,  $\mu = 0$ ,  $\alpha_i \sim U(-5, 5)$ , and  $\sigma_i \sim U(0, 3)$ . Population parameters:  $N = 10,000$ ,  $c_A \sim \mathcal{N}(0, 5^2)$ , and  $\beta_A \sim U(0, 1)$ . AI parameters:  $\tau = 0.3$ , chatbot AI is used.




Figure S7: **Balanced structure is robust across varying balancing weights.** Evaluation metrics across varying levels of the balancing weight (0.1 – 0.9). The balancing weight represents the weight assigned to the niche-expert structure when constructing the balanced structure by combining the niche-expert and feedback structures. A balancing weight of 0.5 represents equal weighting of the niche-expert and feedback structures, whereas 0 corresponds to the feedback structure and 1 corresponds to the niche-expert structure. Although the evaluation metrics vary as the balancing weight changes from 0.1 to 0.9, the absolute magnitude of these deviations remains limited. Prediction target parameters:  $m = 50$ ,  $s = 50$ ,  $\mu = 0$ ,  $\alpha_i \sim U(-5, 5)$ , and  $\sigma_i \sim U(0, 3)$ . Population parameters:  $N = 10,000$ ,  $c_A \sim \mathcal{N}(0, 5^2)$ , and  $\beta_A \sim U(0, 1)$ . AI parameters:  $b_i = 0.4$ ,  $\tau = 0.3$ , chatbot AI is used.




Figure S8: **Balanced structure shows well-calibrated reliance on AI.** Median reliance on AI across varying levels of AI bias. Thirty randomly initialized simulations were performed for each bias level. Each dot represents a single simulation, and the box plots show the median and interquartile range (IQR) for each bias level. The balanced structure shows well-calibrated reliance on AI, with reliance increasing as AI bias decreases. Prediction target parameters:  $m = 50$ ,  $s = 50$ ,  $\mu = 0$ ,  $\alpha_i \sim U(-5, 5)$ , and  $\sigma_i \sim U(0, 3)$ . Population parameters:  $N = 10,000$ ,  $c_A \sim \mathcal{N}(0, 5^2)$ , and  $\beta_A \sim U(0, 1)$ . AI parameters:  $\tau = 0.3$ , chatbot AI is used.

## References

- Aplin, L. M., D. R. Farine, R. P. Mann, and B. C. Sheldon (2014). Individual-level personality influences social foraging and collective behaviour in wild birds. *Proceedings of the Royal Society B: Biological Sciences* 281(1789), 20141016.
- Bastani, H., O. Bastani, A. Sungu, H. Ge, Ö. Kabakcı, and R. Mariman (2025). Generative AI without guardrails can harm learning: Evidence from high school mathematics. *Proceedings of the National Academy of Sciences* 122(26), e2422633122.
- Becker, J., D. Brackbill, and D. Centola (2017). Network dynamics of social influence in the wisdom of crowds. *Proceedings of the national academy of sciences* 114(26), E5070–E5076.
- Bender, E. M., T. Gebru, A. McMillan-Major, and S. Shmitchell (2021). On the dangers of stochastic parrots: Can language models be too big? In *Proceedings of the 2021 ACM conference on fairness, accountability, and transparency*, pp. 610–623.
- Berdahl, A., C. J. Torney, C. C. Ioannou, J. J. Faria, and I. D. Couzin (2013). Emergent sensing of complex environments by mobile animal groups. *Science* 339(6119), 574–576.
- Bick, A., A. Blandin, and D. J. Deming (2026). The rapid adoption of generative ai. *Management Science*.
- Bousquette, I. (2026, April). Why some companies say AI ‘tokenmaxxing’ is key to survival. <https://www.wsj.com/cio-journal/why-some-companies-say-ai-tokenmaxxing-is-key-to-survival-e699a128>. The Wall Street Journal. Accessed: 2026-07-07.
- Breiman, L. (1996). Bagging predictors. *Machine learning* 24(2), 123–140.
- Breiman, L. (2001). Random forests. *Machine learning* 45(1), 5–32.
- Brynjolfsson, E., D. Li, and L. Raymond (2025). Generative AI at work. *The Quarterly Journal of Economics* 140(2), 889–942.
- Buçinca, Z., M. B. Malaya, and K. Z. Gajos (2021). To trust or to think: cognitive forcing functions can reduce overreliance on AI in AI-assisted decision-making. *Proceedings of the ACM on Human-computer Interaction* 5(CSCW1), 1–21.
- Burton, J. W., E. Lopez-Lopez, S. Hechtlinger, Z. Rahwan, S. Aeschbach, M. A. Bakker, J. A. Becker, A. Berditchevskaia, J. Berger, L. Brinkmann, et al. (2024). How large language models can reshape collective intelligence. *Nature human behaviour* 8(9), 1643–1655.

710 Chawla, D. S. (2026). Researchers who use hallucinated references to face arXiv ban.  
711 *Nature* 653(8116), 988–989.

712 Cui, H. and T. Yasseri (2024). AI-enhanced collective intelligence. *Patterns* 5(11),  
713 101074.

714 Doshi, A. R. and O. P. Hauser (2024). Generative AI enhances individual creativity  
715 but reduces the collective diversity of novel content. *Science advances* 10(28),  
716 eadn5290.

717 Dreyer, T., A. Haluts, A. Korman, N. Gov, E. Fonio, and O. Feinerman (2025). Com-  
718 paring cooperative geometric puzzle solving in ants versus humans. *Proceedings of*  
719 *the National Academy of Sciences* 122(1), e2414274121.

720 Fügener, A., J. Grahl, A. Gupta, and W. Ketter (2021). Will humans-in-the-loop  
721 become borgs? merits and pitfalls of working with AI. *MIS quarterly* 45(3),  
722 1527–1556.

723 Galton, F. (1907). Vox populi.

724 Glickman, M. and T. Sharot (2025). How human–AI feedback loops alter human  
725 perceptual, emotional and social judgements. *Nature Human Behaviour* 9(2),  
726 345–359.

727 Hao, Q., F. Xu, Y. Li, and J. Evans (2026). Artificial intelligence tools expand  
728 scientists’ impact but contract science’s focus. *Nature* 649(8099), 1237–1243.

729 Hommes, C., J. Sonnemans, J. Tuinstra, and H. Van de Velden (2005). Coordi-  
730 nation of expectations in asset pricing experiments. *The Review of Financial*  
731 *Studies* 18(3), 955–980.

732 Hong, L. and S. E. Page (2004). Groups of diverse problem solvers can outperform  
733 groups of high-ability problem solvers. *Proceedings of the National Academy of*  
734 *Sciences* 101(46), 16385–16389.

735 Hong, L., S. E. Page, and M. Riolo (2012). Incentives, information, and emergent  
736 collective accuracy. *Managerial and Decision Economics* 33(5-6), 323–334.

737 Ke, Y., L. Jin, J. C. L. Ong, A. J. Thirunavukarasu, J. Car, C. Y. Cheung, Y. C.  
738 Tham, D. S. W. Ting, M. E. H. Ong, S. Compton, et al. (2026). AI-induced  
739 never-skilling in medical education. *Nature medicine*, 1–10.

740 Keary, T. (2026, April). Is the cult of ‘tokenmaxxing’ just another fad or  
741 the new normal? [https://www.forbes.com/sites/timkeary/2026/04/13/  
742 is-the-cult-of-tokenmaxxingjust-another-fad-or-the-new-normal/](https://www.forbes.com/sites/timkeary/2026/04/13/is-the-cult-of-tokenmaxxingjust-another-fad-or-the-new-normal/).  
743 Forbes. Accessed: 2026-07-07.

744 Lee, B. C. and J. Chung (2024). An empirical investigation of the impact of ChatGPT  
745 on creativity. *Nature Human Behaviour* 8(10), 1906–1914.

746 Lorenz, J., H. Rauhut, F. Schweitzer, and D. Helbing (2011). How social influence  
747 can undermine the wisdom of crowd effect. *Proceedings of the national academy  
748 of sciences* 108(22), 9020–9025.

749 Lorge, I., D. Fox, J. Davitz, and M. Brenner (1958). A survey of studies contrasting  
750 the quality of group performance and individual performance, 1920-1957. *Psycho-  
751 logical bulletin* 55(6), 337.

752 Lu, C., C. Lu, R. T. Lange, Y. Yamada, S. Hu, J. Foerster, D. Ha, and J. Clune  
753 (2026). Towards end-to-end automation of AI research. *Nature* 651(8107), 914–  
754 919.

755 Mann, R. P. and D. Helbing (2017). Optimal incentives for collective intelligence.  
756 *Proceedings of the National Academy of Sciences* 114(20), 5077–5082.

757 Meincke, L., G. Nave, and C. Terwiesch (2025). ChatGPT decreases idea diversity  
758 in brainstorming. *Nature human behaviour* 9(6), 1107–1109.

759 Melumad, S. and J. H. Yun (2025). Experimental evidence of the effects of large  
760 language models versus web search on depth of learning. *PNAS nexus* 4(10),  
761 pgaf316.

762 Noy, S. and W. Zhang (2023). Experimental evidence on the productivity effects of  
763 generative artificial intelligence. *Science* 381(6654), 187–192.

764 Ouyang, L., J. Wu, X. Jiang, D. Almeida, C. Wainwright, P. Mishkin, C. Zhang,  
765 S. Agarwal, K. Slama, A. Ray, et al. (2022). Training language models to follow  
766 instructions with human feedback. *Advances in neural information processing  
767 systems* 35, 27730–27744.

768 Reif, J. A., R. P. Larrick, and J. B. Soll (2025). Evidence of a social evaluation  
769 penalty for using AI. *Proceedings of the National Academy of Sciences* 122(19),  
770 e2426766122.

771 Riedl, C., Y. J. Kim, P. Gupta, T. W. Malone, and A. W. Woolley (2021). Quantify-  
772 ing collective intelligence in human groups. *Proceedings of the National Academy  
773 of Sciences* 118(21), e2005737118.

774 Sajadieh, S., L. Fattorini, R. Perrault, Y. Gil, V. Parli, L. Santarlasci, J. Pava,  
775 N. Maslej, R. Altman, E. Brynjolfsson, et al. (2026). Artificial intelligence index  
776 report 2026. *arXiv preprint arXiv:2606.15708*.

777 Simons, A. M. (2004). Many wrongs: the advantage of group navigation. *Trends in  
778 ecology & evolution* 19(9), 453–455.

- 779 Tessler, M. H., M. A. Bakker, D. Jarrett, H. Sheahan, M. J. Chadwick, R. Koster,  
780 G. Evans, L. Campbell-Gillingham, T. Collins, D. C. Parkes, et al. (2024). AI can  
781 help humans find common ground in democratic deliberation. *Science* 386(6719),  
782 eadq2852.
- 783 Thorp, H. H. (2023). Chatgpt is fun, but not an author. *Science* 379(6630), 313–313.
- 784 Vaccaro, M., A. Almaatouq, and T. Malone (2024). When combinations of humans  
785 and AI are useful: A systematic review and meta-analysis. *Nature Human Be-*  
786 *haviour* 8(12), 2293–2303.
- 787 Vicente, L. and H. Matute (2023). Humans inherit artificial intelligence biases.  
788 *Scientific reports* 13(1), 15737.
- 789 Wang, G., Q. Su, L. Wang, and J. B. Plotkin (2025). Individual incentives that  
790 promote collective intelligence. *Proceedings of the National Academy of Sci-*  
791 *ences* 122(51), e2516535122.
- 792 Werfel, J. (2026). Fluid thinking about collective intelligence. *Nature Machine*  
793 *Intelligence* 8(4), 506–516.
- 794 Woolley, A. W., C. F. Chabris, A. Pentland, N. Hashmi, and T. W. Malone (2010).  
795 Evidence for a collective intelligence factor in the performance of human groups.  
796 *science* 330(6004), 686–688.
- 797 Yaniv, I. and M. Milyavsky (2007). Using advice from multiple sources to re-  
798 vise and improve judgments. *Organizational Behavior and Human Decision Pro-*  
799 *cesses* 103(1), 104–120.