

Sampling and reconstruction

CS 4620 Lecture 13

Outline

- Review signal processing
 - Sampling
 - Reconstruction
 - Filtering
 - Convolution
- Closely related to computer graphics topics such as
 - Image processing
 - Anti-aliasing
 - Curve and surfaces

Sampling

- Image: A function defined on a two-dimensional plane


$$I : \mathbb{R}^2 \rightarrow \dots$$

- Sampled image: pixels




Sampled representations

- How to store and compute with continuous functions?
- Common scheme for representation: samples
write down the function's values at many points





Reconstruction

- Making samples back into a continuous function for output (need realizable method)
for analysis or processing (need mathematical method)
amounts to “guessing” what the function did in between



Filtering

- Processing done on a function can be executed in continuous form (e.g. analog circuit) but can also be executed using sampled representation
- Simple example: smoothing by averaging



Roots of sampling

- Nyquist 1928; Shannon 1949

famous results in information theory

- 1940s: first practical uses in telecommunications
- 1960s: first digital audio systems
- 1970s: commercialization of digital audio
- 1982: introduction of the Compact Disc


the first high-profile consumer application

- This is why all the terminology has a communications or audio “flavor”

early applications are 1D; for us 2D (images) is important


Sampling in digital audio

- Recording: sound to analog to samples to disc
 - Playback: disc to samples to analog to sound again
- how can we be sure we are filling in the gaps correctly?




Undersampling

- What if we “missed” things between the samples?
- Simple example: undersampling a sine wave




Undersampling

- What if we “missed” things between the samples?
- Simple example: undersampling a sine wave




Undersampling

- What if we “missed” things between the samples?
- Simple example: undersampling a sine wave



Undersampling

- What if we “missed” things between the samples?
 - Simple example: undersampling a sine wave
- unsurprising result: information is lost




Undersampling

- What if we “missed” things between the samples?
- Simple example: undersampling a sine wave

unsurprising result: information is lost

surprising result: indistinguishable from lower frequency



Undersampling


- What if we “missed” things between the samples?
- Simple example: undersampling a sine wave

unsurprising result: information is lost


surprising result: indistinguishable from lower frequency

also was always indistinguishable from higher frequencies

aliasing: signals “traveling in disguise” as other frequencies




Aliasing in line-drawings




Preventing aliasing

- Introduce lowpass filters:
remove high frequencies leaving only safe, low frequencies
choose lowest frequency in reconstruction (disambiguate)



Preventing aliasing

- Introduce lowpass filters:
remove high frequencies leaving only safe, low frequencies
choose lowest frequency in reconstruction (disambiguate)




Linear filtering: a key idea

- Transformations on signals; e.g.:
bass/treble controls on stereo
blurring/sharpening operations in image editing
smoothing/noise reduction in tracking
- Can be modeled mathematically by *convolution*


Convolution warm-up

- basic idea: define a new function by averaging over a sliding window
- a simple example to start off: smoothing




Convolution warm-up

- basic idea: define a new function by averaging over a sliding window
- a simple example to start off: smoothing




Convolution warm-up

- basic idea: define a new function by averaging over a sliding window
- a simple example to start off: smoothing




Convolution warm-up

- basic idea: define a new function by averaging over a sliding window
- a simple example to start off: smoothing



Convolution warm-up


- basic idea: define a new function by averaging over a sliding window
- a simple example to start off: smoothing



Convolution warm-up

- Same moving average operation, expressed mathematically:

$$b_{\text{smooth}}[i] = \frac{1}{2r + 1} \sum_{j=i-r}^{i+r} b[j]$$



Discrete convolution

- Simple averaging:

$$b_{\text{smooth}}[i] = \frac{1}{2r + 1} \sum_{j=i-r}^{i+r} b[j]$$

every sample gets the same weight

- Convolution: same idea but with *weighted* average


$$(a \star b)[i] = \sum_j a[j] b[i - j]$$

each sample gets its own weight (normally zero far away)

- This is all convolution is: it is a **moving weighted average**


Filters

- Sequence of weights $a[j]$ is called a *filter*
- Filter is nonzero over its *region of support*
usually centered on zero: support radius r
- Filter is *normalized* so that it sums to 1.0
this makes for a weighted average, not just any
old weighted sum
- Most filters are symmetric about 0
since for images we usually want to treat
left and right the same




Convolution and filtering

- Can express sliding average as convolution with a *box filter*
- $a_{\text{box}} = [\dots, 0, 1, 1, 1, 1, 1, 0, \dots]$




Example: box and step




Convolution and filtering

- Convolution applies with any sequence of weights
- Example: bell curve (gaussian-like) [..., 1, 4, 6, 4, 1, ...]/16



Convolution and filtering

- Convolution applies with any sequence of weights
- Example: bell curve (gaussian-like) [..., 1, 4, 6, 4, 1, ...]/16



And in pseudocode...

```
function convolve(sequence  $a$ , sequence  $b$ , int  $r$ , int  $i$  )  
     $s = 0$   
    for  $j = -r$  to  $r$   
         $s = s + a[j]b[i - j]$   
    return  $s$ 
```

Discrete convolution

- Notation $b = c \star a$

- Convolution is a multiplication-like operation

commutative $a \star b = b \star a$

associative $a \star (b \star c) = (a \star b) \star c$

distributes over addition $a \star (b + c) = a \star b + a \star c$

scalars factor out $\alpha a \star b = a \star \alpha b = \alpha(a \star b)$

identity: unit impulse

$$e = [\dots, 0, 0, 1, 0, 0, \dots]$$

$$a \star e = a$$

- Conceptually no distinction between filter and signal

Discrete filtering in 2D

- Same equation, one more index

$$(a \star b)[i, j] = \sum_{i', j'} a[i', j'] b[i - i', j - j']$$

now the filter is a rectangle you slide around over a grid of numbers

- Commonly applied to images

blurring (using box, using gaussian, ...)

sharpening (impulse minus blur)


- Usefulness of associativity

often apply several filters one after another: $((a \star b_1) \star b_2) \star b_3$

this is equivalent to applying one filter: $a \star (b_1 \star b_2 \star b_3)$


And in pseudocode...

```
function convolve2d(filter2d  $a$ , filter2d  $b$ , int  $i$ , int  $j$ )  
   $s = 0$   
   $r = a.\text{radius}$   
  for  $i' = -r$  to  $r$  do  
    for  $j' = -r$  to  $r$  do  
       $s = s + a[i'][j']b[i - i'][j - j']$   
  return  $s$ 
```




Philip Greenspun]

original ▲ | ▼ box blur



sharpened ▲ | ▼ gaussian blur






Philip Greenspun]

original ▲|▼ box blur

sharpened ▲|▼ gaussian blur



Optimization: separable filters

- basic alg. is $O(r^2)$: large filters get expensive fast!
- definition: $a_2(x,y)$ is *separable* if it can be written as:

$$a_2[i, j] = a_1[i]a_1[j]$$

this is a useful property for filters because it allows factoring:

$$\begin{aligned}(a_2 \star b)[i, j] &= \sum_{i'} \sum_{j'} a_2[i', j'] b[i - i', j - j'] \\&= \sum_{i'} \sum_{j'} a_1[i'] a_1[j'] b[i - i', j - j'] \\&= \sum_{i'} a_1[i'] \left(\sum_{j'} a_1[j'] b[i - i', j - j'] \right)\end{aligned}$$

Separable filtering

$$a_2[i, j] = a_1[i]a_1[j]$$

1	4	6	4	1
4	16	24	16	4
6	24	36	24	6
4	16	24	16	4
1	4	6	4	1

0	0	0	0	0
0	0	0	0	0
1	4	6	4	1
0	0	0	0	0
0	0	0	0	0

0	0	1	0	0
0	0	4	0	0
0	0	6	0	0
0	0	4	0	0
0	0	1	0	0

first, convolve with this

$$\sum_{i'} a_1[i'] \left(\sum_{j'} a_1[j'] b[i - i', j - j'] \right)$$

Separable filtering

$$a_2[i, j] = a_1[i]a_1[j]$$

1	4	6	4	1
4	16	24	16	4
6	24	36	24	6
4	16	24	16	4
1	4	6	4	1

0	0	0	0	0
0	0	0	0	0
1	4	6	4	1
0	0	0	0	0
0	0	0	0	0

0	0	1	0	0
0	0	4	0	0
0	0	6	0	0
0	0	4	0	0
0	0	1	0	0

second, convolve with this

first, convolve with this


$$\sum_{i'} a_1[i'] \left(\sum_{j'} a_1[j'] b[i - i', j - j'] \right)$$

Continuous convolution: warm-up

- Can apply sliding-window average to a continuous function just as well

output is continuous

integration replaces summation




Continuous convolution: warm-up

- Can apply sliding-window average to a continuous function just as well

output is continuous

integration replaces summation




Continuous convolution: warm-up

- Can apply sliding-window average to a continuous function just as well

output is continuous

integration replaces summation




Continuous convolution: warm-up

- Can apply sliding-window average to a continuous function just as well

output is continuous

integration replaces summation



Continuous convolution: warm-up

- Can apply sliding-window average to a continuous function just as well

output is continuous

integration replaces summation



Continuous convolution

- Sliding average expressed mathematically:

$$g_{\text{smooth}}(x) = \frac{1}{2r} \int_{x-r}^{x+r} g(t) dt$$

note difference in normalization (only for box)


- Convolution just adds weights

$$(f \star g)(x) = \int_{-\infty}^{\infty} f(t)g(x-t)dt$$

weighting is now by a function

weighted integral is like weighted average

again bounds are set by support of $f(x)$



One more convolution


- Continuous-discrete convolution

$$(a \star f)(x) = \sum_i a[i] f(x - i)$$


$$(a \star f)(x, y) = \sum_{i,j} a[i, j] f(x - i, y - j)$$

used for reconstruction and resampling


Continuous-discrete convolution




Continuous-discrete convolution




Continuous-discrete convolution



Continuous-discrete convolution



Continuous-discrete convolution





Resampling

- Changing the sample rate
in images, this is enlarging and reducing
- Creating more samples:
increasing the sample rate
“upsampling”
“enlarging”
- Ending up with fewer samples:
decreasing the sample rate
“downsampling”
“reducing”



Resampling

- Reconstruction creates a continuous function
forget its origins, go ahead and sample it





Resampling

- Reconstruction creates a continuous function
forget its origins, go ahead and sample it





Resampling

- Reconstruction creates a continuous function
forget its origins, go ahead and sample it




Resampling


- Reconstruction creates a continuous function
forget its origins, go ahead and sample it



Resampling

- Reconstruction creates a continuous function
forget its origins, go ahead and sample it





And in pseudocode...

```
function reconstruct(sequence  $a$ , filter  $f$ , real  $x$ )  
   $s = 0$   
   $r = f.\text{radius}$   
  for  $i = \lceil x - r \rceil$  to  $\lfloor x + r \rfloor$  do  
     $s = s + a[i]f(x - i)$   
  return  $s$ 
```

Cont.-disc. convolution in 2D


- same convolution—just two variables now

$$(a \star f)(x, y) = \sum_{i, j} a[i, j] f(x - i, y - j)$$

loop over nearby pixels,
average using filter weight

looks like discrete filter,
but offsets are not integers
and filter is continuous

remember placement of filter
relative to grid is variable



Separable filters for resampling

- just as in filtering, separable filters are useful
- separability in this context is a statement about a continuous filter, rather than a discrete one:

$$f_2(x, y) = f_1(x)f_1(y)$$

- resample in two passes, one resampling each row and one resampling each column
- intermediate storage required: product of one dimension of src. and the other dimension of dest.
- same yucky details about boundary conditions



two-stage resampling using a
separable filter

A gallery of filters

- Box filter

Simple and cheap

- Tent filter

Linear interpolation

- Gaussian filter

Very smooth antialiasing filter

- B-spline cubic

Very smooth

- Catmull-rom cubic

Interpolating

- Mitchell-Netravali cubic

Good for image upsampling

Box filter




Figure 9.19. The discrete and continuous box filters.

Tent filter






Figure 9.20. The tent filter and two scaled versions.

Gaussian filter




$$f_g(x) = \frac{1}{\sqrt{2\pi}} e^{-x^2/2}.$$

B-Spline cubic



$$f_B(x) = \frac{1}{6} \begin{cases} -3(1 - |x|)^3 + 3(1 - |x|)^2 + 3(1 - |x|) + 1 & -1 \leq x \leq 1, \\ (2 - |x|)^3 & 1 \leq |x| \leq 2, \\ 0 & \text{otherwise.} \end{cases}$$

Catmull-Rom cubic



$$f_C(x) = \frac{1}{2} \begin{cases} -3(1 - |x|)^3 + 4(1 - |x|)^2 + (1 - |x|) & -1 \leq x \leq 1, \\ (2 - |x|)^3 - (2 - |x|)^2 & 1 \leq |x| \leq 2, \\ 0 & \text{otherwise.} \end{cases}$$

Mitchell-Netravali cubic




Figure 9.24. The Mitchell-Netravali filter.

$$\begin{aligned} f_M(x) &= \frac{1}{3}f_B(x) + \frac{2}{3}f_C(x) \\ &= \frac{1}{18} \begin{cases} -21(1 - |x|)^3 + 27(1 - |x|)^2 + 9(1 - |x|) + 1 & -1 \leq x \leq 1, \\ 7(2 - |x|)^3 - 6(2 - |x|)^2 & 1 \leq |x| \leq 2, \\ 0 & \text{otherwise.} \end{cases} \end{aligned}$$

Effects of reconstruction filters

- For some filters, the reconstruction process winds up implementing a simple algorithm

- Box filter (radius 0.5): nearest neighbor sampling

box always catches exactly one input point

it is the input point nearest the output point

so $\text{output}[i, j] = \text{input}[\text{round}(x(i)), \text{round}(y(j))]$

$x(i)$ computes the position of the output coordinate i on the input grid

- Tent filter (radius 1): linear interpolation

tent catches exactly 2 input points

weights are a and $(1 - a)$

result is straight-line interpolation from one point to the next

Properties of filters

- Degree of continuity
- Impulse response
- Interpolating or no
- Ringing, or overshoot




Figure 9.25. An interpolating filter reconstructs the sample points exactly because it has the value zero at all non-zero integer offsets from the center.

Ring, overshoot, ripples

- Overshoot caused by negative filter values





Figure 9.26. A filter with negative lobes will always produce some overshoot when filtering or reconstructing a sharp discontinuity.

Ringing, overshoot, ripples

- Overshoot
caused by
negative filter
values

- Ripples
constant in,
non-const. out
ripple free when:



Yucky details

- What about near the edge?

the filter window falls off the edge of the image

need to extrapolate

methods:

- clip filter (black)



[Philip Greenspun]

Yucky details

- What about near the edge?

the filter window falls off the edge of the image

need to extrapolate

methods:

- clip filter (black)



[Philip Greenspun]

Yucky details


- What about near the edge?

the filter window falls off the edge of the image

need to extrapolate

methods:

- clip filter (black)



[Philip Greenspun]

Yucky details

- What about near the edge?

the filter window falls off the edge of the image

need to extrapolate

methods:

- clip filter (black)
- wrap around



[Philip Greenspun]

Yucky details


- What about near the edge?

the filter window falls off the edge of the image

need to extrapolate

methods:

- clip filter (black)
- wrap around



[Philip Greenspun]

Yucky details

- What about near the edge?

the filter window falls off the edge of the image

need to extrapolate

methods:

- clip filter (black)
- wrap around
- copy edge



[Philip Greenspun]

Yucky details


- What about near the edge?

the filter window falls off the edge of the image

need to extrapolate

methods:

- clip filter (black)
- wrap around
- copy edge



[Philip Greenspun]

Yucky details

- What about near the edge?

the filter window falls off the edge of the image

need to extrapolate

methods:

- clip filter (black)
- wrap around
- copy edge
- reflect across edge



[Philip Greenspun]

Yucky details


- What about near the edge?

the filter window falls off the edge of the image

need to extrapolate

methods:

- clip filter (black)
- wrap around
- copy edge
- reflect across edge



[Philip Greenspun]

Yucky details

- What about near the edge?

the filter window falls off the edge of the image

need to extrapolate

methods:

- clip filter (black)
- wrap around
- copy edge
- reflect across edge
- vary filter near edge



[Philip Greenspun]

Yucky details


- What about near the edge?

the filter window falls off the edge of the image

need to extrapolate

methods:

- clip filter (black)
- wrap around
- copy edge
- reflect across edge
- vary filter near edge




[Philip Greenspun]


Reducing and enlarging

- Very common operation
- devices have differing resolutions
applications have different memory/quality tradeoffs
- Also very commonly done poorly
 - Simple approach: drop/replicate pixels
 - Correct approach: use resampling


Resampling example




Resampling example




Resampling example




Resampling example




Resampling example




Resampling example




Resampling example




Resampling example



Resampling example



Resampling example




Reducing and enlarging

- Very common operation
- devices have differing resolutions
applications have different memory/quality tradeoffs
- Also very commonly done poorly
 - Simple approach: drop/replicate pixels
 - Correct approach: use resampling



1000 pixel width


[Philip Greenspun]



[Philip Greenspun]



by dropping
pixels



gaussian filter

250 pixel width

Reducing






Figure 9.38. Resampling involves filtering for reconstruction and for sampling. Since two convolution filters applied in sequence can be replaced with a single filter, we only need one resampling filter, which serves the roles of reconstruction and sampling.



box reconstruction filter



bicubic reconstruction filter

4000 pixel width

[Philip Greenspun]


Types of artifacts

- Garden variety

what we saw in this natural image


fine features become jagged or sparkle

- Moiré patterns




[Hearn & Baker cover]

600ppi scan of a color halftone image



by dropping pixels



gaussian filter

downsampling a high resolution scan

[Hearn & Baker cover]

Types of artifacts

- Garden variety

what we saw in this natural image

fine features become jagged or sparkle

- Moiré patterns

caused by repetitive patterns in input

produce large-scale artifacts; highly visible

- These artifacts are *aliasing* just like in the audio example earlier

- How do I know what filter is best at preventing aliasing?

practical answer: experience

theoretical answer: there is another layer of cool math behind all this

- based on Fourier transforms
- provides much insight into aliasing, filtering, sampling, and reconstruction