

**SECURING OUR  
DIGITAL TOMORROW**

**MALWARE  
AND  
MACHINE LEARNING**



**QUEEN'S  
UNIVERSITY  
BELFAST**

**Dr. BooJoong Kang**  
Research Fellow , CSIT  
23 Sept. 2020





# Who am I?

- BooJoong Kang (강부중)
- Research Fellow
- Centre of Secure Information Technologies
- Queen's University Belfast, UK
- BS, MS, PhD from Hanyang University
- Cybersecurity
  - Network Security and Malware Analysis




# Outline

- Malware
- Malware Analysis
- Malware Detection
- ML-driven Malware Detection
- Adversarial Examples



# Malware

- Malware (a portmanteau for malicious software) is any software intentionally designed to cause damage to a computer, server, client, or computer network




# The first of many: Creeper

- Bob Thomas at BBN Technologies in 1971
- As a demonstration of mobile applications
  - Software that could automatically hop between computers on a network
- Find a computer, hop over to it and display “I’M THE CREEPER : CATCH ME IF YOU CAN.”
  
- Later, Thomas’s colleague Ray Tomlinson
- An update to the Creeper
  - Leave a copy of itself before moving onto the next one (self-replication)
- Invented another virus called the Reaper
  - Find infected computers and delete the Creeper
  
- Creeper: Worm
- Updated Creeper: Virus
- Reaper: Anti-Virus



# The first Trojan: ANIMAL

- John Walker, 1975
- "20 questions" program that guess the animal
- Become popular and start to occupy a lot of his time to copy it
- Subroutine, called PERVADE, saves copies of ANIMAL to any user-accessible directories that would, while the user was answering the questions
- Many of these directories were shared between offices
  - so the Trojan spread via that vector as well



# The first PC virus: Brain

- Basit Farooq Alvi and Amjad Farooq Alvi, two brothers, in 1986
- Infect IBM PC, slow down floppy disks and take up a good chunk of memory
- Designed to protect their medical software from piracy
- A message in the code that included their address and phone numbers

PC Tools Deluxe 34.22 Disk View/Edit Service  
Path=A: Absolute sector 00000000, System BOOT

Displacement	Hex codes	ASCII value
0000(0000)	FA E9 4A 01 34 12 00 07 14 00 01 00 00 00 00 20	-0J04; # 0
0016(0010)	20 20 20 20 20 20 57 65 6C 63 6F 6D 65 20 74 6F	Welcome to
0032(0020)	20 74 68 65 20 44 75 6E 67 65 6F 6E 20 20 20 20	the Dungeon
0048(0030)	20 20 20 20 20 20 20 20 20 20 20 20 20 20 20 20	
0064(0040)	20 20 20 20 20 20 20 20 20 20 20 20 20 20 20 20	
0080(0050)	20 20 63 29 20 31 39 38 36 20 42 61 73 69 74 20	(c) 1986 Basit
0096(0060)	26 20 41 6D 6A 61 64 20 20 70 76 74 29 20 4C 74	& Amjad (pvt) Lt
0112(0070)	64 2E 20 20 20 20 20 20 20 20 20 20 20 20 20 20	d.
0128(0080)	20 42 52 41 49 4E 20 43 4F 4D 50 55 54 45 52 20	BRAIN COMPUTER
0144(0090)	53 45 52 56 49 43 45 53 2E 2E 37 33 30 20 4E 49	SERVICES..730 NI
0160(00A0)	5A 41 4D 20 42 4C 4F 43 48 20 41 4C 4C 41 4D 41	2AM BLOCK ALLAMA
0176(00B0)	20 49 51 42 41 4C 20 54 4F 57 4E 20 20 20 20 20	IGBAL TOWN
0192(00C0)	20 20 20 20 20 20 20 20 20 20 20 4C 41 48 4F 52	LAHORE
0208(00D0)	45 2D 50 41 4B 49 53 54 41 4E 2E 2E 50 48 4F 4E	E-PAKISTAN..PHON
0224(00E0)	45 20 3A 34 33 30 37 39 31 2C 34 34 33 32 34 38	E :430791,443248
0240(00F0)	2C 32 38 30 35 33 30 2E 20 20 20 20 20 20 20 20	,280530.

Home=begin of file/disk End=end of file/disk  
ESC=Exit PgDn=forward PgUp=back F2=chg sector num F3=edit F4=get name



# The first ransomware: AIDS Trojan

- Joseph Popp in 1989
- Once installed, it counts all the times you booted up the computer
- Once you'd restarted 90 times
  - hide all files, rendering them inaccessible
  - demand you send a letter to an address with \$189 to "renew your license."
- He was eventually caught but let off the hook after being declared mentally unfit and agreeing to donate the profits to AIDS research

Dear Customer:

It is time to pay for your software lease from PC Cyborg Corporation. Complete the INVOICE and attach payment for the lease option of your choice. If you don't use the printed INVOICE, then be sure to refer to the important reference numbers below in all correspondence. In return you will receive:

- a renewal software package with easy-to-follow, complete instructions;
- an automatic, self-installing diskette that anyone can apply in minutes.

Important reference numbers: A5599796-2695577-

The price of 365 user applications is US\$189. The price of a lease for the lifetime of your hard disk is US\$378. You must enclose a bankers draft, cashier's check or international money order payable to PC CYBORG CORPORATION for the full amount of \$189 or \$378 with your order. Include your name, company, address, city, state, country, zip or postal code. Mail your order to PC Cyborg Corporation, P.O. Box 87-17-44, Panama 7, Panama.

Press ENTER to continue





# The first social engineering attack: Melissa

- In 1999, the first email-based viruses and the first to ever use social engineering
- Spread by sending emails to email contacts
  - The headline: "Important Message From ABC"
  - The body text: "Here is that document you asked for ... don't show anyone else ;-)"
- Infected DOC file includes a list of 80 pornographic websites as well as usernames and passwords
- Also other DOC files found on the computer, which have also been infected
  - classified or private files would be shared with friends, family, or work associates
- ILOVEYOU (Love Letter Worm) in 2000
- An email disguised as a love letter
- The attached text file overwrite files, steal user data such, then send itself to everyone on your email contact list
- Compromised an estimated 45 million computers around the world (about 10% of all connected computers) and caused over 8 billion dollars in damages




# Malware in the 21st Century

- Between 2000 and 2010, malware grew significantly, both in number and in how fast infections spread
  - A dramatic increase in malware toolkits, including the now infamous Sony rootkit and Crimeware kits
  - SQL injection attacks became a leading threat, claiming popular victims
    - SQL Slammer (2003) infected nearly 75,000 computers in ten minutes
  - Conficker Worm (2008) caused some of the worst damage seen since Slammer appeared in 2003
- Between 2010 and the present time, significant evolution in the sophistication of malware
  - Organized crime and state sponsors upped the game dramatically with large, well-funded development teams
  - Developing advanced malware with evasion tactics that outsmart conventional anti-malware systems
  - Infiltrating factories and military systems became a common reality, and the monetization of malware grew rapidly with dramatic growth in ransomware and other illegal schemes
  - Stuxnet Worm (2010) was designed with the express purpose of attacking Iran's nuclear program and included the ability to impact hardware as well as software
    - one of the most resource-intensive bits of malware created to date
  - Zeus Trojan (2011) is one of the most successful pieces of botnet software in the world, impacting millions of machines
  - WannaCry Ransomware (2017) locked people out of their data and demanded they pay a ransom or lose everything
    - Affected at least 150 countries, including hospitals, banks, telecommunications companies, warehouses, and many other industries



# Malware Analysis

- To understand
  - How it works
  - How to identify it
  - How to defeat or eliminate it



# Static Analysis

- Static Analysis examines the file itself
- Reverse-engineering with a disassembler or a decompiler

**simple.exe**

**header**

technical details about the executable

**sections**

contents of the executable

**code**

what is executed

**imports**

link between the executable and (Windows) libraries

**data**

information used by the code

**x86 assembly**

```

push 0
push 0x403000
push 0x403017
push 0
call [0x402070]
push 0
call [0x402068]
  
```

**Equivalent C code**

```

MessageBox(0, "Hello world!", "a simple PE executable", 0);
ExitProcess(0);
  
```

**Imports structures**

descriptors	Imports structures	Consequences
0x203c	0x204c, 0 <sup>INT</sup>	after loading, 0x402068 will point to kernel32.dll's ExitProcess 0x402070 will point to user32.dll's MessageBoxA
0x2078	kerne132.dll	
0x2068	0x204c, 0 <sup>INT</sup>	
0x2044	0x205a, 0 <sup>INT</sup>	
0x2085	user32.dll	
0x2070	0x205a, 0 <sup>INT</sup>	

**Strings**

```

a.simple.PE.executable.Hello.world!
Hello world!\0
  
```




# Features from Static Analysis

- Strings
- Byte-patterns
- Code
  - Functions
    - Function Call Graph
  - Instructions
    - Opcode
    - Control Flow Graph
  - APIs
- Combinations of Features can characterise programs

# Dynamic Analysis

- Examine the runtime behaviour of programs
  - the execution and effects of programs with VMs or Debuggers



# Features from Dynamic Analysis

- Executed Code
  - Function Calls
    - Called FCG
  - Executed Instructions
    - Executed CFG
  - API Calls
- Memory/Register Usages
- Network Traffic
- Any other behaviours

# Malware Detection

- Identify Unique Properties of Malware from Static/Dynamic Analysis
- Confusion Matrix in Malware Detection
  - Low False Positive is more important in Malware Detection

	Malware	Benign
Detected as Malware	True Positive	False Positive
Detected as Benign	False Negative	True Negative





# Malware Signatures

- Unique Properties of Malware
  - Hash
  - Strings
  - Byte-patterns
- Fast & Low False Positives
- Easy to Evade
  - a padding yields a different hash
  - variants, zero-day malware
    - continuous signature updates


```
rule Enfal_Malware_Backdoor {
meta:
description = "Generic Rule to detect the Enfal Malware"
author = "Florian Roth"
date = "2015/02/10"
super_rule = 1
hash0 = "6d484daba3927fc0744b1bbd7981a56ebef95790"
hash1 = "d4071272cc1bf944e3867db299b3f5dce126f82b"
hash2 = "6c7c8b804cc76e2c208c6e3b6453cb134d01fa41"
strings:
$sz = { 4d 5a }
$s1 = "Micorsoft Corportation" fullword wide
$s2 = "IM Monnitor Service" fullword wide
$x1 = "imemonsvc.dll" fullword wide
$x2 = "iphlpvc.tmp" fullword
$x3 = "{53A4988C-F91F-4054-9076-220AC5EC03F3}" fullword
$z1 = "urlmon" fullword
$z2 = "Registered trademarks and service marks are the property of their" wide
$z3 = "XpsUnregisterServer" fullword
$z4 = "XpsRegisterServer" fullword
condition:
( $sz at 0 ) and
(
( 1 of ($s*) ) or
( 2 of ($x*) and all of ($z*) )
)
and filesize < 40000
}
```




# Why ML?

- Manual analysis for signatures can't cope with the number of new malware


New Mobile Malware




New IoT Malware



New Coin Miner Malware



# ML-driven Malware Detection




# ML with Sequence Data

- N-grams

- unigram of “COLD”
  - C, O, L, D
- bigram of “COLD”
  - CO, OL, LD
- n-gram (n=4) of “COLD”
  - COLD

- Word2vec


- n-grams into a numerical vector
- existence or frequency





# Deep Learning in Malware Detection


- Feature Extraction and Selection by DL
- No need to enumerate n-grams of Opcode sequences



# Malware Visualisation

- Malware's binary content as a gray-scale image
  - every byte as one pixel in an image
  - reused samples
- Some Drawbacks
  - need to select an image width
  - non-existing spatial correlations between pixels in different rows
  - suffer from code obfuscation techniques
    - encryption/compression will change the bytes

Rammnit





Lollipop




# Adversarial Examples

- Attempt to fool models



# Adversarial Examples in Malware Detection

- Append Random, Benign, FGM bytes
  - might exceed the model's maximum size
- Slack FGM
  - unused space between sections
    - misalignments between the virtual addresses and the multipliers over the block sizes on disk





# Summary

- Malware
- Static/Dynamic Analysis
- Malware Detection
- ML-driven Malware Detection
- Adversarial Examples

# References

- A Brief History of Computer Viruses
  - <https://www.avg.com/en/signal/history-of-viruses>
- A Brief History of Malware — Its Evolution and Impact
  - <https://www.lastline.com/blog/history-of-malware-its-evolution-and-impact/>
- #11: Machine Learning and Security
  - <https://www.oreilly.com/library/view/machine-learning-and/9781491979891/ch04.html>
- #12: PE101
  - <http://pe101.corkami.com/>
- #14: Dynamic Malware Analysis in the Modern Era
  - <https://dl.acm.org/doi/10.1145/3329786>
- #17: Yara: the pattern matching swiss knife
  - <https://virustotal.github.io/yara/>
- #18 McAfee Labs COVID-19 Threats Report
  - <https://www.mcafee.com/enterprise/en-us/assets/reports/rp-quarterly-threats-july-2020.pdf>

# References

- #20: Machine Learning Aided Static Malware Analysis: A Survey and Tutorial
  - <https://arxiv.org/abs/1808.01201>
- #21: Deep Android Malware Detection
  - <https://dl.acm.org/doi/abs/10.1145/3029806.3029823>
- #22: The rise of machine learning for detection and classification of malware: Research developments, trends and challenges
  - <https://doi.org/10.1016/j.jnca.2019.102526>
- #23: Robust Physical-World Attacks on Deep Learning Visual Classification
  - <https://doi.org/10.1109/CVPR.2018.00175>
- #23: Fooling automated surveillance cameras: adversarial patches to attack person detection
  - <https://arxiv.org/pdf/1904.08653.pdf>
  - <https://www.youtube.com/watch?v=MIbFvK2S9g8>
- #24: Exploring Adversarial Examples in Malware Detection
  - <https://ieeexplore.ieee.org/stamp/stamp.jsp?tp=&arnumber=8844597>

**B.KANG@QUB.AC.UK**



**QUEEN'S  
UNIVERSITY  
BELFAST**

**CSIT**

**CENTRE  
FOR SECURE  
INFORMATION  
TECHNOLOGIES**

