

DC-D1414WEG

4MP Active Deterrence Turret Camera

NDAA & TAA Compliant



KEY FEATURES

- 1/1.8" STARVIS™ CMOS
- Max. 4MP(2688×1520) @25/30fps resolution
- Intelligent analysis: Smart Motion detection(Human and Vehicle)
- True WDR, 3D DNR, ROI, HLC, BLC, Defog
- Built-in warm lights, illumination distance up to 25m
- Built-in red and blue warning light, support sound-light warning
- 1/1 alarm in/out, 1/1 audio in/out, built-in mic and speaker
- Built-in micro SD card slot (up to 1 TB)

DC-D1414WEG | Datasheet

VIDEO

Image Sensor	1/1.8" CMOS
Max. Resolution	4MP (2688×1520)
Scanning Mode	Progressive Scan
Lens Type	Fixed focal
Focal Length	2.8 mm
Aperture	F1.0
Iris Control	Fixed Iris
Angular Field of View	H: 112.4°, V: 61.2°
Min. Illumination	Color: 0.0001 Lux @ (F1.0, AGC ON), 0 Lux with warm-light ON
Dynamic Range	True WDR
Electronic Shutter Speed	Auto/Manual, 1/5 to 1/50,000s
Day and Night	Fixed filter
Illuminator Type	Warm Light 25m / 82.02ft (4ea)
Image Setting	Image Adjustment: Brightness, Sharpness, Contrast, Saturation adjustable; Aisle Mode: Support; Mirror: Support; White Balance: Auto/Manual; Day/Night Setting: Auto, Day, Night, Time; Noise Reduction: 2D/3D DNR; Image Enhancement; HLC, BLC, Defog, WDR; Privacy masking: 4 areas
Backlight Compensation	BLC
Mirroring / Pivot	Support
Image Stabilizer	-
De-fog	Yes
Privacy Masking	4 areas
Intelligent Video	Intelligent analysis: Smart Motion detection (Human and Vehicle)
Video Out	-

PAN/TILT/ROTATE

Pan Range	Pan: 0° to 355°
Tilt Range	Tilt: 0° to 80°
Rotate Range	Rotation: 0° to 360°

NETWORK

Video Compression	H.265, H.264 (MP), M-JPEG
Intelligent Codec	-
Bitrate Control	CBR/VBR

Audio Compression	G.711 A-law, G.711 μ -law, RAM PCM
Two-way Audio	Yes
IP Camera Protocol	ONVIF (profile S/T/G/M)
Max. Frame Rate	Max. 4MP(2688×1520) @25/30fps resolution
Supported Resolution	4MP (2688×1520)
Multi-video Streaming	3 Streams
Network Protocols	IPv4/IPv6, HTTP/HTTPS, DNS, DDNS, DHCP, PPPoE, RTSP/ RTCP/RTP, TCP/UDP, NTP, ARP, UPnP, FTP, SMTP, QoS, ICMP, IGMP, SMTP, 802.1x, SNMP, Multicast
Security	IP address filter, encrypted HTTPS, Illegal login lock, IEEE 802.1x
Ethernet	1 Ethernet (10/100 Base-T) RJ-45 Connector
Recording Session Buffer (NLTSrec)	-
Edge Storage	Built-in micro SD card slot (up to 1 TB)

ALARM AND EVENT

Trigger Event	Motion detection, Smart Motion, Alarm input
Event Notification	Alarm record, Alarm output, FTP upload, SMTP upload, Audible alarm output, Red and blue light alarm
Audio Alarm	Yes
Audio In / Out	1/1 Audio in/out (Built-in Mic / Speaker)
Alarm In / Out	1/1 alarm in/out

ENVIRONMENTAL

Vandal Proof Casing	IK10
Outdoor Ready	IP66
Operating Temperature	-40°C to 60°C (-40°F to 140°F)
Operating Humidity	Less than 90% RH

ELECTRICAL

Power Source	12 VDC (-15% to +25%)/PoE (802.3af)
Power Consumption	Max. 9.5W
Approval	CE-EMC (EN 55032:2015+A1:2020, EN IEC 61000-6-3:2021, EN IEC 61000-3-2:2019+A12021, EN 61000-3-3:2013+A2:2021, EN 55035:2017+A11:2020, EN 50130-4:2011+A1:2014) FCC (FCC 47 CFR 15, Subpart B, ANSI C63.4-2014)

MECHANICAL

Dimensions	$\phi 140 \times 119.2$ mm (5.51 $\times$ 4.69 inch)
------------	--

Weight

0.9 kg (1.98 lb)

DIMENSIONS

Unit: mm

