

DC-T1434WG

4MP Active Deterrence Bullet Camera

NDAA & TAA Compliant



KEY FEATURES

- 1/1.8" progressive scan CMOS
- Max. 4MP(2688×1520) @25/30fps resolution
- Intelligent analytics: Smart Motion detection(Human and Vehicle)
- True WDR, 3D DNR, ROI, HLC, BLC, Defog
- Built-in warm lights, illumination distance up to 40m or 60m
- Built-in Red and Blue Warning Light, Support Sound-Light Warning
- 1/1 Alarm in/out, 1/1 Audio in/out, Built-in Mic and Speaker
- Built-in micro SD card slot (up to 512GB)

DC-T1434WG | Datasheet

VIDEO

Image Sensor	1/1.8" Progressive Scan CMOS
Max. Resolution	4MP (2688×1520)
Scanning Mode	Progressive scan
Lens Type	Motorized focus
Focal Length	4.5 to 8 mm
Aperture	F1.0
Iris Control	P-Iris
Angular Field of View	4.5 to 8 mm, H: 101°to 57.5°, V: 52.7°to 32° 8 to 32 mm, H: 39.7°to 16°, V: 22.6°to 9.2°
Min. Illumination	Color: 0.0001 Lux @ (F1.0, AGC ON), 0 Lux with warm-light ON
Dynamic Range	True WDR
Electronic Shutter Speed	Auto/Manual, 1/5 to 1/50,000s
Day and Night	Fixed filter
Illuminator Type	Warm Light 40m / 131.2ft (4ea)
Image Setting	Image Adjustment: Brightness, Sharpness, Contrast, Saturation adjustable; Aisle Mode: Support; Mirror: Support; White Balance: Auto/Manual; Day/Night Setting: Auto, Day, Night, Time; Noise Reduction: 2D/3D DNR; Image Enhancement; HLC, BLC, Defog, True WDR; S/N Ratio 55db; Privacy masking: 4 areas
Backlight Compensation	BLC
Mirroring / Pivot	Support
Image Stabilizer	-
De-fog	YES
Privacy Masking	4 areas
Intelligent Video	Intelligent analysis: Smart Motion detection (Human and Vehicle)
Video Out	-

PAN/TILT/ROTATE

Pan Range	Pan: 0° to 360°
Tilt Range	Tilt: 0° to 90°
Rotate Range	Rotation: 0° to 360°

NETWORK

Video Compression	H.265, H.264 (MP), M-JPEG
Intelligent Codec	-
Bitrate Control	CBR/VBR

Audio Compression	G.711, RAW_PCM
Two-way Audio	Yes
IP Camera Protocol	ONVIF (profile S/T/G/M)
Max. Frame Rate	Max. 4MP(2688×1520) @25/30fps resolution
Supported Resolution	4MP(2688×1520)
Multi-video Streaming	3 streams
Network Protocols	IPv4/IPv6, RTSP/RTCP/RTP, TCP/UDP, HTTPS, DHCP, DNS, DDNS, PPPoE, UPnP, ICMP, IGMP, FTP, NTP, SMTP, 802.1x, SNMP;
Security	IP address filter, encrypted HTTPS, Illegal login lock, IEEE 802.1x
Ethernet	1 Ethernet (10/100 Base-T) RJ-45 Connector
Recording Session Buffer (NLTSrec)	-
Edge Storage	SD Card Slot Built-in, up to 512 GB

ALARM AND EVENT

Trigger Event	Motion detection, Smart Motion, Alarm input
Event Notification	Alarm record, Alarm output, FTP upload, SMTP upload, Audible alarm output, Red and blue light alarm
Audio Alarm	Yes
Audio In / Out	1/1 Audio in/out (Built-in Mic / Speaker)
Alarm In / Out	1ch Input, 1ch Output

ENVIRONMENTAL

Vandal Proof Casing	IK10
Outdoor Ready	IP66
Operating Temperature	-40°C to 55°C (-40°F to 131°F)
Operating Humidity	Less than 90% RH

ELECTRICAL

Power Source	DC12V (-15% to +25%)/PoE (802.3af)
Power Consumption	Max. 11W
Approval	CE/FCC

MECHANICAL

Dimensions	303 × 100 × 107 mm (11.9 × 3.94 × 4.21 inch)
Weight	1.25 Kg (2.76 lb)

DIMENSIONS